

Document Identifier: DSP0239	2
Date: 2016-12-30	3
Version: 1.4.0	4

Management Component Transport Protocol (MCTP) IDs and Codes

7 Supersedes: 1.3.0

- 8 Document Type: Specification
- 9 Document Class: Normative
- 10 Document Status: Published
- 11 Document Language: en-US

13	Copyright Notice
14 15	Copyright © 2009, 2012, 2015, 2017 Distributed Management Task Force, Inc. (DMTF). All rights reserved.
16 17 18 19	DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability. Members and non-members may reproduce DMTF specifications and documents, provided that correct attribution is given. As DMTF specifications may be revised from time to time, the particular version and release date should always be noted.
20 21 22 23 24 25 26 27 28 29 30 31 32	Implementation of certain elements of this standard or proposed standard may be subject to third party patent rights, including provisional patent rights (herein "patent rights"). DMTF makes no representations to users of the standard as to the existence of such rights, and is not responsible to recognize, disclose, or identify any or all such third party patent right, owners or claimants, nor for any incomplete or inaccurate identification or disclosure of such rights, owners or claimants. DMTF shall have no liability to any party, in any manner or circumstance, under any legal theory whatsoever, for failure to recognize, disclose, or identify any such third party patent rights, or for such party's reliance on the standard or incorporation thereof in its product, protocols or testing procedures. DMTF shall have no liability to any party implementing such standard, whether such implementation is foreseeable or not, nor to any patent owner or claimant, and shall have no liability or responsibility for costs or losses incurred if a standard is withdrawn or modified after publication, and shall be indemnified and held harmless by any party implementing the standard from any and all claims of infringement by a patent owner for such implementations.
33 34 35	For information about patents held by third-parties which have notified the DMTF that, in their opinion, such patent may relate to or impact implementations of DMTF standards, visit http://www.dmtf.org/about/policies/disclosures.php .
36 37	PCI-SIG, PCIe, and the PCI HOT PLUG design mark are registered trademarks or service marks of PCI-SIG.

- 38 All other marks and brands are the property of their respective owners.

CONTENTS

41	Fore	eword	4
42	Intro	oduction	5
43	1	Scope	
44	2	Normative references	7
45	3	Terms and definitions	8
46	4	Symbols and abbreviated terms	8
47	5	Conventions	8
48		5.1 Reserved and unassigned values	
49		5.2 Byte ordering	
50	6	MCTP Message Type codes	9
51	7	MCTP physical medium identifiers1	0
52	8	MCTP physical transport binding identifiers1	1
53	9	MCTP host interface type identifiers1	
54	10	Host interface protocol identifiers1	2
55	ANN	NEX A (informative) Notation and conventions1	3
56	ANN	NEX B (informative) Change log1	4
57			

58 **Tables**

59	Table 1 – MCTP Message Types	9
	Table 2 – MCTP physical medium identifiers	
	Table 3 – MCTP physical transport binding identifiers	
62	Table 4 – MCTP host interface type identifiers	12
63		

Foreword

- 65 The *Management Component Transport Protocol (MCTP) IDs and Codes* (DSP0239) was prepared by 66 the PMCI Working Group.
- 67 DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems 68 management and interoperability.

69 Acknowledgments

70 The DMTF acknowledges the following individuals for their contributions to this document:

71 Editors:

- Hemal Shah Broadcom Corporation
- Tom Slaight Intel Corporation
- Philip Chidester Dell Inc.
- Edward Newman Hewlett Packard Enterprise

76 Contributors:

- Alan Berenbaum SMSC
- Patrick Caporale Lenovo
- Kelly Couch Intel Corporation
- Ed Klodnicki IBM
- Patrick Kutch Intel Corporation
- Yuval Itkin Mellanox Technologies
- Eliel Louzoun Intel Corporation
- Zvika Perry QLogic
- Bob Stevens Dell Inc.

Introduction

- 87 This document presents a collection of IDs and codes that are used across the Management Component
- 88 Transport Protocol (MCTP) and transport binding specifications.
- 89 The MCTP defines a communication model intended to facilitate communication between:
- 90 Management controllers and other management controllers
- Management controllers and management devices
- The communication model includes a message format, transport description, message exchange
 patterns, and configuration and initialization messages.
- 94 The *MCTP Base Protocol Specification* (<u>DSP0236</u>) describes the protocol and commands used for
- 95 communication within and initialization of an MCTP network. Associated with the Base Protocol
- 96 Specification are transport binding specifications that define how the MCTP base protocol and MCTP
- 97 control commands are implemented on a particular physical transport type and medium.

- 98
- 99

Management Component Transport Protocol (MCTP) IDs and Codes

100 **1 Scope**

The Management Component Transport Protocol (MCTP) IDs and Codes document provides a
 consolidated list of major IDs and codes used across the MCTP protocol and transport binding
 specifications. Only IDs and codes that are required by a particular specification should be included in
 that specification. IDs and codes values for other specifications should not be repeated for reference.
 Instead, a reference to this specification should be provided.

- 106 The following is an overview of the different sets of codes and identifiers (enumeration values) that are 107 specified in this document:
- 108 MCTP message type codes
- 109 Collection of the message type codes used for MCTP messages
- MCTP physical medium identifiers
- 111 Collection of identifiers for the different types of physical media that have been defined
- 112 MCTP physical transport binding identifiers
- 113 Collection of identifiers for the specifications that define the operation, formatting, addressing, 114 and encapsulation of MCTP packets over different physical media
- MCTP host interface type identifiers
 Collection of identifiers for the different physical interfaces used to transfer MCTP packets
 between the host and the management controller

118 **2** Normative references

The following referenced documents are indispensable for the application of this document. For dated or
 versioned references, only the edition cited (including any corrigenda or DMTF update versions) applies.
 For references without a date or version, the latest published edition of the referenced document
 (including any corrigenda or DMTF update versions) applies.

- 123 DMTF specifications are available at http://www.dmtf.org/standards/published_documents. Unless
- 124 otherwise specified, values defined in this document apply to all published DMTF Standard versions of 125 the particular referenced DMTF specification.
- 126 DMTF DSP0134, SMBIOS Reference Specification
- 127 DMTF DSP0222, Network Controller Sideband Interface (NC-SI) Specification
- 128 DMTF DSP0235, NVMe (NVM Express) Management Messages over MCTP Binding Specification
- 129 DMTF DSP0236, Management Component Transport Protocol (MCTP) Base Specification
- DMTF DSP0237, Management Component Transport Protocol (MCTP) SMBusl²C Transporting Binding
 Specification
- DMTF DSP0238, Management Component Transport Protocol (MCTP) PCIe VDM Transport Binding
 Specification
- 134 DMTF DSP0241, PLDM Over MCTP Binding Specification

Management Component Transport Protocol (MCTP) IDs and Codes

- 135 DMTF DSP0253, MCTP Serial Transport Binding Specification
- 136 DMTF DSP0254, MCTP KCS Transport Binding Specification
- 137 DMTF DSP0261, NC-SI Over MCTP Binding Specification
- 138 IPMI Consortium, Intelligent Platform Management Interface Specification 1.5 Revision 1.1, February 20,
 2002, <u>http://download.intel.com/design/servers/ipmi/IPMIv1_5rev1_1.pdf</u>
- ISO/IEC Directives, Part 2, *Rules for the structure and drafting of International Standards,* http://isotc.iso.org/livelink/livelink?func=ll&obild=4230456&objAction=browse&sort=subtype
- 142 PCI-SIG, PCI Express Base Specification 1.1, PCIeV1.1, March 28, 2005
- 143 PCI-SIG, *PCI Express Base Specification 2.0*, PCIeV2.1, March 4, 2009
- 144 PCI-SIG, PCI Express Base Specification 3.0, PCIeV3.0, November 10, 2010
- 145 Philips Semiconductors, *The l^2C-Bus Specification v2.0*, I2C, December 1998
- 146 RMII Consortium, Reduced Media Independent Interface (RMII) Specification v1.2, RMII, 1997
- 147 SMBus, System Management Bus (SMBus) Specification v2.0, SMBus, 2000,
- 148 <u>http://www.smbus.org/specs/smbus20.pdf</u>

149 **3 Terms and definitions**

150 Refer to <u>DSP0236</u> for terms and definitions that are used in the MCTP specifications.

151 **4** Symbols and abbreviated terms

152 Refer to <u>DSP0236</u> for symbols and abbreviated terms that are used in the MCTP specifications.

153 **5 Conventions**

154 The conventions described in the following clauses apply to this specification.

155 5.1 Reserved and unassigned values

- Unless otherwise specified, any reserved, unspecified, or unassigned values in enumerations or othernumeric ranges are reserved for future definition by the DMTF.
- Unless otherwise specified, numeric or bit fields that are designated as reserved shall be written as 0(zero) and ignored when read.

160 5.2 Byte ordering

161 Unless otherwise specified, byte ordering of multi-byte numeric fields or bit fields is "Big Endian" (that is, 162 the lower byte offset holds the most significant byte, and higher offsets hold lesser significant bytes).

163 6 MCTP Message Type codes

Table 1 defines the values for the Message Type field for different message types transported throughMCTP.

166 NOTE A device that supports a given message type may not support that message type equally across all busses
 167 that connect to the device.

Table '	I —	MCTP	Message	Types
---------	-----	------	---------	-------

Message Type	Message Type Code	Description
MCTP Control	0x00	Messages used to support initialization and configuration of MCTP communication within an MCTP network, as specified in <u>DSP0236</u>
Platform Level Data Model (PLDM)	0x01	Messages used to convey Platform Level Data Model (PLDM) traffic over MCTP, as specified in <u>DSP0241.</u>
NC-SI over MCTP	0x02	Messages used to convey NC-SI Control traffic over MCTP, as specified in <u>DSP0261</u> .
Ethernet over MCTP	0x03	Messages used to convey Ethernet traffic over MCTP. See <u>DSP0261</u> . This message type can also be used separately by other specifications.
NVM Express Management Messages over MCTP	0x04	Messages used to convey NVMe (NVM Express) Management Messages over MCTP, as specified in <u>DSP0235</u> .
Vendor Defined – PCI	0x7E	Message type used to support VDMs where the vendor is identifed using a PCI-based vendor ID. The specification of the initial Message Header bytes for this message type is provided within this specification. The specification of the format of this message is given in <u>DSP0236</u> . Otherwise, the message body content is specified by the vendor, company, or organization identified by the given vendor ID.
Vendor Defined – IANA	0x7F	Message type used to support VDMs where the vendor is identifed using an IANA-based vendor ID. This format uses an "Enterprise Number" that is assigned and maintained by the Internet Assigned Numbers Authority (IANA), <u>www.iana.org</u> , as the means of identifying a particular vendor, company, or organization. The specification of the format of this message is given in <u>DSP0236</u> . Otherwise, the message body content is specified by the vendor, company, or organization identified by the given vendor ID.
Reserved	all other	Reserved

169 7 MCTP physical medium identifiers

170 Table 2 defines a set of numbers that correspond to different media types that can be used with MCTP.

171 The identifier is primarily used to identify which physical addressing format is used for MCTP packets on 172 the bus.

173

Table 2 – MCTP physical medium identifiers

Physical Media Identifier	Description
0x00	Unspecified
0x01	SMBus 2.0 100 kHz compatible
0x02	SMBus 2.0 + I ² C 100 kHz compatible
0x03	I ² C 100 kHz compatible (Standard-mode)
0x04	I ² C 400 kHz compatible (Fast-mode)
0x05	I ² C 1 MHz compatible (Fast-mode Plus)
0x06	I ² C 3.4 MHz compatible (High-speed mode)
0x07	Reserved
0x08	PCIe 1.1 compatible
0x09	PCIe 2.0 compatible
0x0A	PCIe 2.1 compatible
0x0B	PCIe 3.0 compatible
0x0C:0x0E	Reserved
0x0F	PCI compatible (PCI 1.0,2.0,2.1,2.2,2.3,3.0,PCI-X 1.0, PCI-X 2.0)
0x10	USB 1.1 compatible
0x11	USB 2.0 compatible
0x12	USB 3.0 compatible
0x13:0x17	Reserved
0x18	NC-SI over RBT (A physical interface based on RMII as defined in DSP0222)
0x20	KCS ¹ / Legacy (Fixed Address Decoding)
0x21	KCS ¹ / PCI (Base Class 0xC0 Subclass 0x01)
0x22	Serial Host ² / Legacy (Fixed Address Decoding)
0x23	Serial Host ² / PCI (Base Class 0x07 Subclass 0x00)
0x24	Asynchronous Serial ³ (Between MCs and IMDs)
all other	Reserved
 Keyboard Controller Style Interfa Serial Host refers to a register ba Asynchronous Serial refers to an traperited independently (i.e. application) 	sed UART interface. 8–bit asynchronous bi-directional serial transmission media where characters are

Published

3. Asynchronous Serial refers to an 8–bit asynchronous bi-directiona transmitted independently (i.e., each frame carries 8-bits of data).

174 175

175

8 MCTP physical transport binding identifiers

Table 3 defines as set of numbers that correspond to different media types that can be used with MCTP.The identifier indicates which physical addressing format is used for MCTP packets on the bus.

179

Table 3 – MCTP physical transport binding identifiers

MCTP Physical Transport Binding Identifier	Description
0x00	Reserved
0x01	MCTP over SMBus (<u>DSP0237</u>)
0x02	MCTP over PCIe VDM (<u>DSP0238</u>)
0x03	Reserved for MCTP over USB
0x04	MCTP over KCS (<u>DSP0254</u>)
0x05	MCTP over Serial (<u>DSP0253</u>)
Oxff	Vendor defined NOTE A vendor-defined transport binding must meet the requirements in <u>DSP0236</u> (in particular, when being bridged to or from standard MCTP transport binding and media combinations).
All other	Reserved

MCTP host interface type identifiers 9 181

The SMBIOS specification (DSP0134) reserves a range of host interface type identifiers 0x00 through 182

0x3F for use by this specification. Table 4 defines a set of numbers that correspond to different MCTP 183 host interface types that can be used with MCTP. The identifier indicates which physical interface to

184 transfer MCTP packets between the host and the management controller. 185

186

MCTP Host Interface Type Identifier	Description
0x00	Reserved
0x01	Reserved
0x02	KCS: Keyboard Controller Style – refer to <u>Intelligent Platform</u> <u>Management Interface Specification</u> Section 9 Keyboard Controller Style (KCS) Interface
0x03	8250 UART Register Compatible
0x04	16450 UART Register Compatible
0x05	16550/16550A UART Register Compatible
0x06	16650/16650A UART Register Compatible
0x07	16750/16750A UART Register Compatible
0x08	16850/16850A UART Register Compatible
0x09:0x3F	Reserved
all other	Assigned by the SMBIOS specification (DSP0134)

10 Host interface protocol identifiers 187

188 In earlier versions of this specification, this section contained a table of host interface protocol identifiers.

That table has been moved to the description of the Type 42 record of the SMBIOS specification 189 190 (DSP0134) with a version greater than 3.1.0.

191 192 193			ANNEX A (informative) Notation and conventions
194	Notatio	ons	
195	Example	es of notat	tions used in this document are as follows:
196 197 198	•	2:N	In field descriptions, this will typically be used to represent a range of byte offsets starting from byte two and continuing to and including byte N. The lowest offset is on the left, the highest is on the right.
199 200	•	(6)	Parentheses around a single number can be used in message field descriptions to indicate a byte field that may be present or absent.
201 202	•	(3:6)	Parentheses around a field consisting of a range of bytes indicates the entire range may be present or absent. The lowest offset is on the left, the highest is on the right.
203 204 205	•	<u>PCle</u>	Underlined, blue text is typically used to indicate a reference to a document or specification called out in the "Normative References" section or to items hyperlinked within the document.
206	•	rsvd	Abbreviation for "reserved." Case insensitive.
207 208	•	[4]	Square brackets around a number are typically used to indicate a bit offset. Bit offsets are given as zero-based values (that is, the least significant bit [LSb] offset = 0).
209 210	•	[7:5]	A range of bit offsets. The most significant bit is on the left, the least significant bit is on the right.
211 212	•	1b	The lower case "b" following a number consisting of $0s$ and $1s$ is used to indicate the number is being given in binary format.
213	•	0x12A	A leading " $0x$ " is used to indicate a number given in hexadecimal format.
214			

216

210

217

ANNEX B (informative) Change log

Version	Date	Description
1.0.0	2009-07-28	
1.1.0	2009-11-03	Added Host Interface Type Identifiers. Added Host Interface Protocol Identifiers. Added reference to NC-SI and added clarification on physical medium identifiers.
1.2.0	2012-06-04	Added Ethernet over MCTP message type. Clarified the description of NC-SI over MCTP and PLDM over MCTP. Added I2C fast plus and high-speed physical medium identifiers. Clarified RMII/NC-SI physical medium identifier description. Fixed references.
1.3.0	2015-03-06	Added message type NVMe (NVM Express) Management Messages over MCTP. Updated references.
1.4.0	2016-12-30	Limited host interface type identifiers to the range 0x00:0x3F. Moved the host interface protocol identifier table to the SMBIOS specification.