



Redfish

Document Identifier: DSP-IS0017

Date: 2020-10-23

Version: 0.5a

Redfish Control Schema Proposal

Document Class: Informative

Document Status: Work in progress

Document Language: en-US

Information for Work-in-Progress version:

IMPORTANT: This document is not a standard. It does not necessarily reflect the views of the DMTF or its members. Because this document is a Work in Progress, this document may still change, perhaps profoundly and without notice. This document is available for public review and comment until superseded.

Provide any comments through the DMTF Feedback Portal: <http://www.dmtf.org/standards/feedback>

Copyright Notice

Copyright © 2016-2020 DMTF. All rights reserved.

DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability. Members and non-members may reproduce DMTF specifications and documents, provided that correct attribution is given. As DMTF specifications may be revised from time to time, the particular version and release date should always be noted.

Implementation of certain elements of this standard or proposed standard may be subject to third party patent rights, including provisional patent rights (herein "patent rights"). DMTF makes no representations to users of the standard as to the existence of such rights, and is not responsible to recognize, disclose, or identify any or all such third party patent right, owners or claimants, nor for any incomplete or inaccurate identification or disclosure of such rights, owners or claimants. DMTF shall have no liability to any party, in any manner or circumstance, under any legal theory whatsoever, for failure to recognize, disclose, or identify any such third party patent rights, or for such party's reliance on the standard or incorporation thereof in its product, protocols or testing procedures. DMTF shall have no liability to any party implementing such standard, whether such implementation is foreseeable or not, nor to any patent owner or claimant, and shall have no liability or responsibility for costs or losses incurred if a standard is withdrawn or modified after publication, and shall be indemnified and held harmless by any party implementing the standard from any and all claims of infringement by a patent owner for such implementations.

For information about patents held by third-parties which have notified the DMTF that, in their opinion, such patent may relate to or impact implementations of DMTF standards, visit <http://www.dmtf.org/about/policies/disclosures.php>.

This document's normative language is English. Translation into other languages is permitted.

Contents

[Contents](#)

[Foreword](#)

[How can I provide feedback?](#)

[Where can I find more information?](#)

[Using the reference guide](#)

[Common Properties](#)

[Schema Reference Guide](#)

[Chassis 1.15.0](#)

[Control 0.5.0](#)

[Sensor 1.2.0](#)

[Redfish documentation generator](#)

Foreword

This Informational Specification covers a proposal to enhance the Power and Thermal monitoring schemas for Redfish.

IMPORTANT: These documents are not final. They do not necessarily reflect the views of the DMTF or its members. Because these documents are a Work in Progress, these documents may still change, perhaps profoundly and without notice. These documents are available for public review and comment until superseded.

The following files are part of the Redfish Power and Thermal Enhancement proposal:

- wip-controls - Mockup containing a "Widget" and Chassis showing examples of Control and Sensor components. The "Widget" is an example of a managed element that contains the excerpts of Control and Sensor resources to provide control and sensor data in context.
- DSP-IS0017_v0.5a.pdf - Presentation describing the Redfish Control proposal

How can I provide feedback?

Feedback on all Redfish specifications and documents is encouraged. Feedback can be directed to the DMTF and the Redfish Forum by the following means:

- **Redfish User Forum:** <http://www.redfishforum.com> User forum monitored by DMTF Redfish Forum personnel to answer questions about any Redfish-related topics.
- **DMTF Feedback Portal:** <https://www.dmtf.org/standards/feedback> Formal submission portal for enhancements or proposals to the DMTF and Redfish Forum.
- **Redfish Github Repository:** DMTF Redfish Forum member companies are encouraged to open issues on the group's private repository on Github.

Where can I find more information?

The following web sites provide more information about the Redfish standard:

- **Redfish Developer Hub:** <http://redfish.dmtf.org> Resources for developers building applications using Redfish. Contains an interactive schema explorer, hosted schema and other links.
- **Redfish User Forum:** <http://www.redfishforum.com> User forum monitored by DMTF Redfish personnel to answer questions about any Redfish-related topics.
- **DMTF Github Repositories:** <http://www.github.com/DMTF> Open source tools and libraries for working with the Redfish API.
- **Redfish Standards:** <http://www.dmtf.org/standards/redfish> Schemas, specs, mockups, white papers, FAQ, educational material and more.
- **DMTF Redfish Forum** (Working group that maintains the Redfish standard): <http://www.dmtf.org/standards/spmf> Companies involved, upcoming schedules and future work, charter, and information about joining.

Using the reference guide

The proposed power and thermal subsystem schemas are listed in the following section for reference. This section should be considered an extension to the contents of DSP2046, the Redfish Resource and Schema Guide, which lists the common Redfish properties, other object definitions, and all released Redfish schemas (including those shown here).

This guide was produced using the contents of the schema files from DMTF Redfish Schema bundle DSP8010 and merged with supplemental text using the DMTF's [Redfish Documentation Generator](#).

Common Properties

Properties and objects defined for all Redfish schemas, or referenced by this white paper are detailed in the Redfish

Schema Reference Guide

Chassis 1.15.0

| | | | | | | | | | | | |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-----|
| v1.15 | v1.14 | v1.13 | v1.12 | v1.11 | v1.10 | v1.9 | v1.8 | v1.7 | v1.6 | v1.5 | ... |
| TBD | 2020.3 | 2020.2 | 2020.1 | 2019.4 | 2019.2 | 2018.3 | 2018.2 | 2018.1 | 2017.3 | 2017.1 | ... |

The Chassis schema represents the physical components of a system. This resource represents the sheet-metal confined spaces and logical zones such as racks, enclosures, chassis and all other containers. Subsystems, such as sensors, that operate outside of a system's data plane are linked either directly or indirectly through this resource. A subsystem that operates outside of a system's data plane are not accessible to software that runs on the system.

URIs:

/redfish/v1/Chassis/{[ChassisId](#)}

| | | | |
|----------------------------------------|------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Assembly (v1.6+) { | object | | The link to the assembly associated with this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| AssetTag | string | read-write (null) | The user-assigned asset tag of this chassis. |
| ChassisType | string (enum) | read-only required | The type of physical form factor of the chassis. <i>For the possible property values, see ChassisType in Property details.</i> |
| Controls (v1.15+) { | object | | The link to the collection of controls located in this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| DepthMm (v1.4+) | number (mm) | read-only (null) | The depth of the chassis. |
| Drives (v1.14+) { | object | | The link to the collection of drives within this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| EnvironmentalClass (v1.9+) | string (enum) | read-only (null) | The ASHRAE Environmental Class for this chassis. <i>For the possible property values, see EnvironmentalClass in Property details.</i> |
| HeightMm (v1.4+) | number (mm) | read-only (null) | The height of the chassis. |
| IndicatorLED (deprecated v1.14) | string (enum) | read-write (null) | The state of the indicator LED, which identifies the chassis. <i>For the possible property values, see IndicatorLED in Property details. Deprecated in</i> |

| | | | |
|--------------------------------------|-----------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| | | | <i>v1.14 and later. This property has been deprecated in favor of the LocationIndicatorActive property.</i> |
| Links { | object | | The links to other resources that are related to this resource. |
| ComputerSystems [{ | array | | An array of links to the computer systems that this chassis directly and wholly contains. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| ComputerSystems@odata.count | integer | read-only | The number of items in a collection. |
| ContainedBy { | object | | The link to the chassis that contains this chassis. |
| @odata.id } | string | read-write | <i>Link to another Chassis resource.</i> |
| Contains [{ | array | | An array of links to any other chassis that this chassis has in it. |
| @odata.id }] | string | read-write | <i>Link to another Chassis resource.</i> |
| Contains@odata.count | integer | read-only | The number of items in a collection. |
| CooledBy [{ | array | | An array of links to resources or objects that cool this chassis. Normally, the link is for either a chassis or a specific set of fans. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| CooledBy@odata.count | integer | read-only | The number of items in a collection. |
| Drives (v1.2+) [{ | array | | An array of links to the drives located in this chassis. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| Drives@odata.count | integer | read-only | The number of items in a collection. |
| Facility (v1.11+) { | object | | The link to the facility that contains this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| ManagedBy [{ | array | | An array of links to the managers responsible for managing this chassis. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| ManagedBy@odata.count | integer | read-only | The number of items in a collection. |
| ManagersInChassis (v1.2+) [{ | array | | An array of links to the managers located in this chassis. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| ManagersInChassis@odata.count | integer | read-only | The number of items in a collection. |

| | | | |
|--------------------------------------------------|-----------------|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Oem { } | object | | The OEM extension property. <i>See the Resource schema for details on this property.</i> |
| PCleDevices (v1.4+, deprecated v1.10) [{ | array | | An array of links to the PCIe devices located in this chassis. <i>Deprecated in v1.10 and later. This property has been deprecated in favor of the PCIeDevices resource collection in the root of this resource.</i> |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| PCleDevices@odata.count | integer | read-only | The number of items in a collection. |
| PoweredBy [{ | array | | An array of links to resources or objects that power this chassis. Normally, the link is for either a chassis or a specific set of power supplies. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| PoweredBy@odata.count | integer | read-only | The number of items in a collection. |
| Processors (v1.9+) [{ | array | | An array of links to the processors located in this chassis. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| Processors@odata.count | integer | read-only | The number of items in a collection. |
| ResourceBlocks (v1.5+) [{ | array | | An array of links to the resource blocks located in this chassis. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| ResourceBlocks@odata.count | integer | read-only | The number of items in a collection. |
| Storage (v1.2+) [{ | array | | An array of links to the storage subsystems connected to or inside this chassis. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| Storage@odata.count | integer | read-only | The number of items in a collection. |
| Switches (v1.7+) [{ | array | | An array of links to the switches located in this chassis. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| Switches@odata.count } | integer | read-only | The number of items in a collection. |
| Location (v1.2+) { } | object | | The location of the chassis. <i>See the Resource schema for details on this property.</i> |
| LocationIndicatorActive (v1.14+) | boolean | read-write (null) | An indicator allowing an operator to physically locate this resource. |

| | | | |
|------------------------------------|-------------------|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LogServices { | object | | The link to the logs for this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| Manufacturer | string | read-only (null) | The manufacturer of this chassis. |
| MaxPowerWatts (v1.12+) | number (Watts) | read-only (null) | The upper bound of the total power consumed by the chassis. |
| MediaControllers (v1.11+) { | object | | The link to the collection of media controllers located in this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| Memory (v1.11+) { | object | | The link to the collection of memory located in this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| MemoryDomains (v1.11+) { | object | | The link to the collection of memory domains located in this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| MinPowerWatts (v1.12+) | number (Watts) | read-only (null) | The lower bound of the total power consumed by the chassis. |
| Model | string | read-only (null) | The model number of the chassis. |
| NetworkAdapters (v1.4+) { | object | | The link to the collection of network adapters associated with this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| PartNumber | string | read-only (null) | The part number of the chassis. |
| PCleDevices (v1.10+) { | object | | The link to the collection of PCIe devices located in this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| PCleSlots (v1.8+) { | object | | The link to the PCIe slot properties for this chassis. |
| @odata.id } | string (URI) | read-only | The unique identifier for a resource. |
| PhysicalSecurity (v1.1+) { | object | | The state of the physical security sensor. |
| IntrusionSensor (v1.1+) | string (enum) | read-write (null) | This indicates the known state of the physical security sensor, such as if it is hardware intrusion detected. <i>For the possible property values, see IntrusionSensor in Property details.</i> |

| | | | |
|------------------------------------------|------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IntrusionSensorNumber (v1.1+) | integer | read-only (null) | A numerical identifier to represent the physical security sensor. |
| IntrusionSensorReArm (v1.1+) { | string (enum) | read-only (null) | The method that restores this physical security sensor to the normal state. <i>For the possible property values, see IntrusionSensorReArm in Property details.</i> |
| Power { | object | | The link to the power properties, or power supplies, power policies, and sensors, for this chassis. |
| @odata.id { | string (URI) | read-only | The unique identifier for a resource. |
| PowerState (v1.0.1+) | string (enum) | read-only (null) | The current power state of the chassis. <i>For the possible property values, see PowerState in Property details.</i> |
| Sensors (v1.9+) { | object | | The link to the collection of sensors located in the equipment and sub-components. |
| @odata.id { | string (URI) | read-only | The unique identifier for a resource. |
| SerialNumber | string | read-only (null) | The serial number of the chassis. |
| SKU | string | read-only (null) | The SKU of the chassis. |
| Status { } | object | | The status and health of the resource and its subordinate or dependent resources. <i>See the Resource schema for details on this property.</i> |
| Thermal { | object | | The link to the thermal properties, such as fans, cooling, and sensors, for this chassis. |
| @odata.id { | string (URI) | read-only | The unique identifier for a resource. |
| UUID (v1.7+) | string | read-only (null) | The UUID for this chassis. |
| WeightKg (v1.4+) | number (kg) | read-only (null) | The weight of the chassis. |
| WidthMm (v1.4+) | number (mm) | read-only (null) | The width of the chassis. |

Actions

Reset

This action resets the chassis but does not reset systems or other contained resources, although side effects might occur that affect those resources.

Action URI: {Base URI of target resource}/Actions/Chassis.Reset

Perform the action using a POST to the specific Action URI for this resource. Parameters for the action are passed in a JSON body and are defined as follows:

| | | | |
|---|--|--|--|
| { | | | |
|---|--|--|--|

| | | | |
|-----------------------|------------------|----------|-------------------------------------------------------------------------------------------------------------------|
| ResetType } | string (enum) | optional | The type of reset. <i>For the possible property values, see ResetType in Property details.</i> |
|-----------------------|------------------|----------|-------------------------------------------------------------------------------------------------------------------|

Property details

ChassisType:

The type of physical form factor of the chassis.

| string | Description |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Blade | An enclosed or semi-enclosed, typically vertically-oriented, system chassis that must be plugged into a multi-system chassis to function normally. |
| Card | A loose device or circuit board intended to be installed in a system or other enclosure. |
| Cartridge | A small self-contained system intended to be plugged into a multi-system chassis. |
| Component | A small chassis, card, or device that contains devices for a particular subsystem or function. |
| Drawer | An enclosed or semi-enclosed, typically horizontally-oriented, system chassis that can be slid into a multi-system chassis. |
| Enclosure | A generic term for a chassis that does not fit any other description. |
| Expansion | A chassis that expands the capabilities or capacity of another chassis. |
| IPBasedDrive (v1.3+) | A chassis in a drive form factor with IP-based network connections. |
| Module | A small, typically removable, chassis or card that contains devices for a particular subsystem or function. |
| Other | A chassis that does not fit any of these definitions. |
| Pod | A collection of equipment racks in a large, likely transportable, container. |
| Rack | An equipment rack, typically a 19-inch wide freestanding unit. |
| RackGroup (v1.4+) | A group of racks that form a single entity or share infrastructure. |
| RackMount | A single-system chassis designed specifically for mounting in an equipment rack. |
| Row | A collection of equipment racks. |
| Shelf | An enclosed or semi-enclosed, typically horizontally-oriented, system chassis that must be plugged into a multi-system chassis to function normally. |
| Sidecar | A chassis that mates mechanically with another chassis to expand its capabilities or capacity. |
| Sled | An enclosed or semi-enclosed, system chassis that must be plugged into a multi-system chassis to function normally similar to a blade type chassis. |
| StandAlone | A single, free-standing system, commonly called a tower or desktop chassis. |
| StorageEnclosure (v1.6+) | A chassis that encloses storage. |
| Zone | A logical division or portion of a physical chassis that contains multiple devices or systems that cannot be physically separated. |

EnvironmentalClass:

The ASHRAE Environmental Class for this chassis.

| string | Description |
|--------|----------------------------------|
| A1 | ASHRAE Environmental Class 'A1'. |
| A2 | ASHRAE Environmental Class 'A2'. |
| A3 | ASHRAE Environmental Class 'A3'. |
| A4 | ASHRAE Environmental Class 'A4'. |

IndicatorLED:

The state of the indicator LED, which identifies the chassis.

| string | Description |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Blinking | The indicator LED is blinking. |
| Lit | The indicator LED is lit. |
| Off | The indicator LED is off. |
| Unknown (deprecated v1.2) | The state of the indicator LED cannot be determined. <i>This value has been deprecated in favor of returning null if the state is unknown.</i> |

IntrusionSensor:

This indicates the known state of the physical security sensor, such as if it is hardware intrusion detected.

| string | Description |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| HardwareIntrusion | A door, lock, or other mechanism protecting the internal system hardware from being accessed is detected to be in an insecure state. |
| Normal | No abnormal physical security condition is detected at this time. |
| TamperingDetected | Physical tampering of the monitored entity is detected. |

IntrusionSensorReArm:

The method that restores this physical security sensor to the normal state.

| string | Description |
|-----------|-------------------------------------------------------------------------------------------------------------------------|
| Automatic | Because no abnormal physical security condition is detected, this sensor is automatically restored to the normal state. |
| Manual | A manual re-arm of this sensor restores it to the normal state. |

PowerState:

The current power state of the chassis.

| string | Description |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Off | The components within the chassis have no power, except some components might continue to have AUX power, such as the management controller. |
| On | The components within the chassis have power. |
| PoweringOff | A temporary state between on and off. The components within the chassis can take time to process the power off action. |

| | |
|------------|-----------------------------------------------------------------------------------------------------------------------|
| PoweringOn | A temporary state between off and on. The components within the chassis can take time to process the power on action. |
|------------|-----------------------------------------------------------------------------------------------------------------------|

ResetType:

The type of reset.

| string | Description |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ForceOff | Turn off the unit immediately (non-graceful shutdown). |
| ForceOn | Turn on the unit immediately. |
| ForceRestart | Shut down immediately and non-gracefully and restart the system. |
| GracefulRestart | Shut down gracefully and restart the system. |
| GracefulShutdown | Shut down gracefully and power off. |
| Nmi | Generate a diagnostic interrupt, which is usually an NMI on x86 systems, to stop normal operations, complete diagnostic actions, and, typically, halt the system. |
| On | Turn on the unit. |
| PowerCycle | Power cycle the unit. Behaves like a full power removal, followed by a power restore to the resource. |
| PushPowerButton | Simulate the pressing of the physical power button on this unit. |

Example response

```
{
  "@odata.type": "#Chassis.v1_11_0.Chassis",
  "Id": "1U",
  "Name": "Computer System Chassis",
  "ChassisType": "RackMount",
  "AssetTag": "Chicago-45Z-2381",
  "Manufacturer": "Contoso",
  "Model": "3500RX",
  "SKU": "8675309",
  "SerialNumber": "437XR1138R2",
  "PartNumber": "224071-J23",
  "PowerState": "On",
  "IndicatorLED": "Lit",
  "HeightMm": 44.45,
  "WidthMm": 431.8,
  "DepthMm": 711,
  "WeightKg": 15.31,
  "Location": {
    "PostalAddress": {
      "Country": "US",
      "Territory": "OR",
      "City": "Portland",
      "Street": "1001 SW 5th Avenue",
      "HouseNumber": 1100,
      "Name": "DMTF",
      "PostalCode": "97204"
    },
    "Placement": {
      "Row": "North",
      "Rack": "WEB43",
      "RackOffsetUnits": "EIA_310",
      "RackOffset": 12
    }
  },
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "Thermal": {
    "@odata.id": "/redfish/v1/Chassis/1U/Thermal"
  },
  "Power": {
    "@odata.id": "/redfish/v1/Chassis/1U/Power"
  },
  "Assembly": {
    "@odata.id": "/redfish/v1/Chassis/1U/Assembly"
  },
  "Links": {
    "ComputerSystems": [

```

```

    {
      "@odata.id": "/redfish/v1/Systems/437XR1138R2"
    },
    "ManagedBy": [
      {
        "@odata.id": "/redfish/v1/Managers/BMC"
      }
    ],
    "ManagersInChassis": [
      {
        "@odata.id": "/redfish/v1/Managers/BMC"
      }
    ]
  },
  "@odata.id": "/redfish/v1/Chassis/1U"
}

```

Control 0.5.0

| |
|------|
| v0.5 |
| TBD |

The Control schema describes a control point and its properties.

URIs:

/redfish/v1/Chassis/{[ChassisId](#)}/Controls/{[ControlId](#)}

/redfish/v1/PowerEquipment/Controls/{[ControlId](#)}

| | | | |
|--------------------------------------|---------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Accuracy (v0.5+) | number (%) | read-only (null) | The estimated percent error of measured versus actual values. |
| AssociatedSensors (v0.5+) [{ | array | | An array of links to the sensors associated with this control. |
| @odata.id }] | string | read-only | <i>Link to a Sensor resource. See the Links section and the Sensor schema for details.</i> |
| ControlLoop (v0.5+) { | object | (null) | The control loop details. |
| Differential (v0.5+) | number | read-write (null) | The differential coefficient. |
| Integral (v0.5+) | number | read-write (null) | The integral coefficient. |
| Proportional (v0.5+) } | number | read-write (null) | The proportional coefficient. |
| ControlType (v0.5+) | string (enum) | read-only (null) | The type of control. <i>For the possible property values, see ControlType in Property details.</i> |
| DeadBand (v0.5+) | number | read-write (null) | The maximum deviation from the set point allowed before the control will activate. |
| Increment (v0.5+) | number | read-only (null) | The smallest increment supported for the set point. |
| Location (v0.5+) { } | object | | The location information for this control. <i>See the Resource schema for details on this property.</i> |
| OperatingMode (v0.5+) | string (enum) | read-write (null) | The current operating mode of the control. <i>For the possible property values, see OperatingMode in Property details.</i> |

| | | | |
|-----------------------------------|-----------------------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PhysicalContext (v0.5+) | string (enum) | read-only (null) | The area or device to which this control applies. <i>For the possible property values, see PhysicalContext in Property details.</i> |
| PhysicalSubContext (v0.5+) | string (enum) | read-only (null) | The usage or location within a device to which this control applies. <i>For the possible property values, see PhysicalSubContext in Property details.</i> |
| Sensor (v0.5+) | (excerpt) | read-only | The sensor reading associated with this control. |
| SetPoint (v0.5+) | number | read-write (null) | The desired set point of the control. |
| SetPointRangeMax (v0.5+) | number | read-only (null) | The maximum possible value for this control. |
| SetPointRangeMin (v0.5+) | number | read-only (null) | The minimum possible value for this control. |
| SetPointUnits (v0.5+) | string | read-only (null) | The units of the set point. |
| SetPointUpdateTime (v0.5+) | string (date-time) | read-only (null) | The date and time that the set point was changed. |
| Status (v0.5+) { } | object | | The status and health of the resource and its subordinate or dependent resources. <i>See the Resource schema for details on this property.</i> |

Property details

ControlType:

The type of control.

| string | Description |
|-----------------|----------------------|
| AirFlow | Airflow. |
| Altitude | Altitude. |
| AngularPosition | Position (Angular). |
| Barometric | Barometric pressure. |
| Current | Current. |
| EnergyJoules | Energy (Joules). |
| EnergykWh | Energy (kWh). |
| Force | Force or strain. |
| Frequency | Frequency. |
| Humidity | Relative Humidity. |
| LinearPosition | Position (Linear). |
| LiquidFlow | Liquid flow. |
| LiquidLevel | Liquid level. |

| | |
|-------------|---------------------|
| Luminosity | Luminosity. |
| Percent | Percent. |
| Power | Power. |
| Pressure | Pressure. |
| Rotational | Rotational. |
| Sound | Sound. |
| Temperature | Temperature. |
| Velocity | Velocity. |
| Voltage | Voltage (AC or DC). |
| Weight | Weight. |

OperatingMode:

The current operating mode of the control.

| string | Description |
|-----------|--------------------------------------------------------------------|
| Automatic | Automatically adjust control to meet the set point. |
| Direct | The set point directly affects the control value. |
| Disabled | An automatic control loop has been disabled. |
| Physical | A physical control that cannot be adjusted through this interface. |

PhysicalContext:

The area or device to which this control applies.

| string | Description |
|--------------------------|-----------------------------------------------------------------|
| Accelerator | An accelerator. |
| ACInput | An AC input. |
| ACMaintenanceBypassInput | An AC maintenance bypass input. |
| ACOutput | An AC output. |
| ACStaticBypassInput | An AC static bypass input. |
| ACUtilityInput | An AC utility input. |
| ASIC | An ASIC device, such as a networking chip or chipset component. |
| Back | The back of the chassis. |
| Backplane | A backplane within the chassis. |
| Chassis | The entire chassis. |
| ComputeBay | Within a compute bay. |
| CoolingSubsystem | The entire cooling, or air and liquid, subsystem. |
| CPU | A processor (CPU). |

| | |
|------------------|-----------------------------------------------------------|
| CPUSubsystem | The entire processor (CPU) subsystem. |
| DCBus | A DC bus. |
| Exhaust | The air exhaust point or points or region of the chassis. |
| ExpansionBay | Within an expansion bay. |
| Fan | A fan. |
| FPGA | An FPGA. |
| Front | The front of the chassis. |
| GPU | A graphics processor (GPU). |
| GPUSubsystem | The entire graphics processor (GPU) subsystem. |
| Intake | The air intake point or points or region of the chassis. |
| LiquidInlet | The liquid inlet point of the chassis. |
| LiquidOutlet | The liquid outlet point of the chassis. |
| Lower | The lower portion of the chassis. |
| Memory | A memory device. |
| MemorySubsystem | The entire memory subsystem. |
| Motor | A motor. |
| NetworkBay | Within a networking bay. |
| NetworkingDevice | A networking device. |
| PowerSubsystem | The entire power subsystem. |
| PowerSupply | A power supply. |
| PowerSupplyBay | Within a power supply bay. |
| Rectifier | A rectifier device. |
| Room | The room. |
| StorageBay | Within a storage bay. |
| StorageDevice | A storage device. |
| SystemBoard | The system board (PCB). |
| Transformer | A transformer. |
| Upper | The upper portion of the chassis. |
| VoltageRegulator | A voltage regulator device. |

PhysicalSubContext:

The usage or location within a device to which this control applies.

| string | Description |
|--------|-------------|
| Input | The input. |
| | |

Example response

```
{
  "@odata.type": "#Control.v0_5_0.Control",
  "Id": "Thermostat",
  "Name": "System Thermostat",
  "PhysicalContext": "Chassis",
  "ControlType": "Temperature",
  "OperatingMode": "Automatic",
  "SetPoint": 22,
  "SetPointUnits": "cel",
  "SetPointRangeMax": 45,
  "SetPointRangeMin": 18,
  "SetPointUpdateTime": "2020-09-13T09:14:33",
  "Increment": 0.5,
  "DeadBand": 0.5,
  "Sensor": {
    "Reading": 22.5,
    "DataSourceUri": "/redfish/v1/Chassis/1U/Sensors/AmbientTemp"
  },
  "Status": {
    "Health": "OK",
    "State": "Enabled"
  },
  "@odata.id": "/redfish/v1/Chassis/1/Controls/Thermostat",
  "@Redfish.Copyright": "Copyright 2014-2020 DMTF. For the full DMTF copyright policy, see
http://www.dmtf.org/about/policies/copyright."
}
```

Sensor 1.2.0

| | | |
|------|--------|--------|
| v1.2 | v1.1 | v1.0 |
| TBD | 2019.4 | 2018.3 |

The Sensor schema describes a sensor and its properties.

URIs:

- /redfish/v1/Chassis/{ChassisId}/Sensors/{SensorId}
- /redfish/v1/PowerEquipment/FloorPDUs/{PowerDistributionId}/Sensors/{SensorId}
- /redfish/v1/PowerEquipment/RackPDUs/{PowerDistributionId}/Sensors/{SensorId}
- /redfish/v1/PowerEquipment/Sensors/{SensorId}
- /redfish/v1/PowerEquipment/TransferSwitches/{PowerDistributionId}/Sensors/{SensorId}

| | | | |
|------------------------------------|---------------|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Accuracy | number (%) | read-only (null) | The estimated percent error of measured versus actual values. |
| AdjustedMaxAllowableOperatingValue | number | read-only (null) | The adjusted maximum allowable operating value for this equipment based on the environmental conditions. |
| AdjustedMinAllowableOperatingValue | number | read-only (null) | The adjusted minimum allowable operating value for this equipment based on the environmental conditions. |
| ApparentVA | number (V.A) | read-only (null) | The product of voltage and current for an AC circuit, in Volt-Ampere units. |
| CrestFactor (v1.1+) | number | read-only (null) | The crest factor for this sensor. |
| ElectricalContext | string (enum) | read-only (null) | The combination of current-carrying conductors. For the possible property values, see ElectricalContext in Property details. |
| Implementation (v1.1+) | string (enum) | read-only (null) | The implementation of the sensor. For the possible property values, see Implementation |

| | | | |
|---------------------------------------|-----------------------|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | | <i>in Property details.</i> |
| LifetimeReading (v1.1+) | number | read-only (null) | The total accumulation value for this sensor. |
| Links (v1.2+) { | object | | The links to other resources that are related to this resource. |
| AssociatedControls (v1.2+) [{ | array | | An array of links to the controls that can affect this sensor. |
| @odata.id }] | string | read-only | <i>Link to a Control resource. See the Links section and the Control schema for details.</i> |
| AssociatedControls@odata.count | integer | read-only | The number of items in a collection. |
| Oem { } | object | | The OEM extension property. <i>See the Resource schema for details on this property.</i> |
| LoadPercent (deprecated v1.1) | number (%) | read-only (null) | The power load utilization for this sensor. <i>Deprecated in v1.1 and later. This property has been deprecated in favor of using a sensor instance with a ReadingType of 'Percent' to show utilization values when needed.</i> |
| Location { } | object | | The location information for this sensor. <i>See the Resource schema for details on this property.</i> |
| MaxAllowableOperatingValue | number | read-only (null) | The maximum allowable operating value for this equipment. |
| MinAllowableOperatingValue | number | read-only (null) | The minimum allowable operating value for this equipment. |
| PeakReading | number | read-only (null) | The peak sensor value. |
| PeakReadingTime | string (date-time) | read-only (null) | The time when the peak sensor value occurred. |
| PhysicalContext | string (enum) | read-only (null) | The area or device to which this sensor measurement applies. <i>For the possible property values, see PhysicalContext in Property details.</i> |
| PhysicalSubContext | string (enum) | read-only (null) | The usage or location within a device to which this sensor measurement applies. <i>For the possible property values, see PhysicalSubContext in Property details.</i> |
| PowerFactor | number | read-only (null) | The power factor for this sensor. |
| Precision | number | read-only (null) | The number of significant digits in the reading. |
| ReactiveVAR | number (V.A) | read-only (null) | The square root of the difference term of squared ApparentVA and squared Power (Reading) for a circuit, in var units. |
| Reading | number | read-only (null) | The sensor value. |
| ReadingRangeMax | number | read-only | The maximum possible value for this sensor. |

| | | | |
|-------------------------------------------|-----------------------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | (null) | |
| ReadingRangeMin | number | read-only (null) | The minimum possible value for this sensor. |
| ReadingTime (v1.1+) | string (date-time) | read-only (null) | The date and time that the reading was acquired from the sensor. |
| ReadingType | string (enum) | read-only (null) | The type of sensor. <i>For the possible property values, see ReadingType in Property details.</i> |
| ReadingUnits | string | read-only (null) | The units of the reading and thresholds. |
| RelatedItem (v1.2+) [{ | array | | An array of links to resources or objects that this sensor services. |
| @odata.id }] | string (URI) | read-only | The unique identifier for a resource. |
| SensingFrequency (deprecated v1.1) | number | read-only (null) | The time interval between readings of the physical sensor. <i>Deprecated in v1.1 and later. This property has been deprecated in favor of the SensingInterval property, which uses the duration time format for interoperability.</i> |
| SensingInterval (v1.1+) | string | read-only (null) | The time interval between readings of the sensor. |
| SensorResetTime | string (date-time) | read-only (null) | The date and time when the time-based properties were last reset. |
| SpeedRPM (v1.2+) | number (RPM) | read-only (null) | The rotational speed. |
| Status { } | object | | The status and health of the resource and its subordinate or dependent resources. <i>See the Resource schema for details on this property.</i> |
| THDPercent (v1.1+) | number | read-only (null) | The total harmonic distortion (THD). |
| Thresholds { | object | | The set of thresholds defined for this sensor. |
| LowerCaution { | object | | The value at which the reading is below normal range. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| LowerCautionUser (v1.2+) { | object | | The value at which the reading is below normal range. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |

| | | | |
|------------------------------------|------------------|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| LowerCritical { | object | | The value at which the reading is below normal range but not yet fatal. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| LowerCriticalUser (v1.2+) { | object | | The value at which the reading is below normal range but not yet fatal. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| LowerFatal { | object | | The value at which the reading is below normal range and fatal. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| UpperCaution { | object | | The value at which the reading is above normal range. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| UpperCautionUser (v1.2+) { | object | | The value at which the reading is above normal range. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |

| | | | |
|------------------------------------|------------------|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | (null) | threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| UpperCritical { | object | | The value at which the reading is above normal range but not yet fatal. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| UpperCriticalUser (v1.2+) { | object | | The value at which the reading is above normal range but not yet fatal. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| UpperFatal { | object | | The value at which the reading is above normal range and fatal. |
| Activation | string (enum) | read-write (null) | The direction of crossing that activates this threshold. <i>For the possible property values, see Activation in Property details.</i> |
| DwellTime | string | read-write (null) | The duration the sensor value must violate the threshold before the threshold is activated. |
| Reading } | number | read-write (null) | The threshold value. |
| VoltageType | string (enum) | read-only (null) | The voltage type for this sensor. <i>For the possible property values, see VoltageType in Property details.</i> |

Actions

ResetMetrics

Resets metrics related to this sensor.

Action URI: {Base URI of target resource}/Actions/Sensor.ResetMetrics

Perform the action using a POST to the specific Action URI for this resource. This action takes no parameters.

Property details

Activation:

The direction of crossing that activates this threshold.

| string | Description |
|------------|--------------------------------------------------|
| Decreasing | Value decreases below the threshold. |
| Either | Value crosses the threshold in either direction. |
| Increasing | Value increases above the threshold. |

ElectricalContext:

The combination of current-carrying conductors.

| string | Description |
|-----------------------|------------------------------------------------------------------------------|
| Line1 | The circuits that share the L1 current-carrying conductor. |
| Line1ToLine2 | The circuit formed by L1 and L2 current-carrying conductors. |
| Line1ToNeutral | The circuit formed by L1 and neutral current-carrying conductors. |
| Line1ToNeutralAndL1L2 | The circuit formed by L1, L2, and neutral current-carrying conductors. |
| Line2 | The circuits that share the L2 current-carrying conductor. |
| Line2ToLine3 | The circuit formed by L2 and L3 current-carrying conductors. |
| Line2ToNeutral | The circuit formed by L2 and neutral current-carrying conductors. |
| Line2ToNeutralAndL1L2 | The circuit formed by L1, L2, and Neutral current-carrying conductors. |
| Line2ToNeutralAndL2L3 | The circuits formed by L2, L3, and neutral current-carrying conductors. |
| Line3 | The circuits that share the L3 current-carrying conductor. |
| Line3ToLine1 | The circuit formed by L3 and L1 current-carrying conductors. |
| Line3ToNeutral | The circuit formed by L3 and neutral current-carrying conductors. |
| Line3ToNeutralAndL3L1 | The circuit formed by L3, L1, and neutral current-carrying conductors. |
| LineToLine | The circuit formed by two current-carrying conductors. |
| LineToNeutral | The circuit formed by a line and neutral current-carrying conductor. |
| Neutral | The grounded current-carrying return circuit of current-carrying conductors. |
| Total | The circuit formed by all current-carrying conductors. |

Implementation:

The implementation of the sensor.

| string | Description |
|----------------|---------------------------------------------------------------------------------------------------------------|
| PhysicalSensor | The reading is acquired from a physical sensor. |
| Reported | The reading is obtained from software or a device. |
| Synthesized | The reading is obtained by applying a calculation on one or more properties. The calculation is not provided. |

PhysicalContext:

The area or device to which this sensor measurement applies.

| string | Description |
|--------|-------------|
|--------|-------------|

| | |
|--------------------------|-----------------------------------------------------------------|
| Accelerator | An accelerator. |
| ACInput | An AC input. |
| ACMaintenanceBypassInput | An AC maintenance bypass input. |
| ACOutput | An AC output. |
| ACStaticBypassInput | An AC static bypass input. |
| ACUtilityInput | An AC utility input. |
| ASIC | An ASIC device, such as a networking chip or chipset component. |
| Back | The back of the chassis. |
| Backplane | A backplane within the chassis. |
| Chassis | The entire chassis. |
| ComputeBay | Within a compute bay. |
| CoolingSubsystem | The entire cooling, or air and liquid, subsystem. |
| CPU | A processor (CPU). |
| CPUSubsystem | The entire processor (CPU) subsystem. |
| DCBus | A DC bus. |
| Exhaust | The air exhaust point or points or region of the chassis. |
| ExpansionBay | Within an expansion bay. |
| Fan | A fan. |
| FPGA | An FPGA. |
| Front | The front of the chassis. |
| GPU | A graphics processor (GPU). |
| GPUSubsystem | The entire graphics processor (GPU) subsystem. |
| Intake | The air intake point or points or region of the chassis. |
| LiquidInlet | The liquid inlet point of the chassis. |
| LiquidOutlet | The liquid outlet point of the chassis. |
| Lower | The lower portion of the chassis. |
| Memory | A memory device. |
| MemorySubsystem | The entire memory subsystem. |
| Motor | A motor. |
| NetworkBay | Within a networking bay. |
| NetworkingDevice | A networking device. |
| PowerSubsystem | The entire power subsystem. |
| PowerSupply | A power supply. |

| | |
|------------------|-----------------------------------|
| PowerSupplyBay | Within a power supply bay. |
| Rectifier | A rectifier device. |
| Room | The room. |
| StorageBay | Within a storage bay. |
| StorageDevice | A storage device. |
| SystemBoard | The system board (PCB). |
| Transformer | A transformer. |
| Upper | The upper portion of the chassis. |
| VoltageRegulator | A voltage regulator device. |

PhysicalSubContext:

The usage or location within a device to which this sensor measurement applies.

| string | Description |
|--------|-------------|
| Input | The input. |
| Output | The output. |

ReadingType:

The type of sensor.

| string | Description |
|-------------------------|----------------------|
| AirFlow | Airflow. |
| Altitude | Altitude. |
| AngularPosition (v1.2+) | Position (Angular). |
| Barometric | Barometric pressure. |
| Current | Current. |
| EnergyJoules | Energy (Joules). |
| EnergykWh | Energy (kWh). |
| Force (v1.2+) | Force or strain. |
| Frequency | Frequency. |
| Humidity | Relative Humidity. |
| LinearPosition (v1.2+) | Position (Linear). |
| LiquidFlow | Liquid flow. |
| LiquidLevel | Liquid level. |
| Luminosity (v1.2+) | Luminosity. |
| Percent (v1.1+) | Percent. |
| Power | Power. |
| | |

| | |
|------------------|---------------------|
| Pressure | Pressure. |
| Rotational | Rotational. |
| Sound (v1.2+) | Sound. |
| Temperature | Temperature. |
| Velocity (v1.2+) | Velocity. |
| Voltage | Voltage (AC or DC). |
| Weight (v1.2+) | Weight. |

VoltageType:

The voltage type for this sensor.

| string | Description |
|--------|----------------------|
| AC | Alternating current. |
| DC | Direct current. |

Example response

```
{
  "@odata.type": "#Sensor.v1_1_0.Sensor",
  "Id": "CabinetTemp",
  "Name": "Rack Temperature",
  "ReadingType": "Temperature",
  "ReadingTime": "2019-12-25T04:14:33+06:00",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "Reading": 31.6,
  "ReadingUnits": "C",
  "ReadingRangeMin": 0,
  "ReadingRangeMax": 70,
  "Accuracy": 0.25,
  "Precision": 1,
  "SensingInterval": "PT3S",
  "PhysicalContext": "Chassis",
  "Thresholds": {
    "UpperCritical": {
      "Reading": 40,
      "Activation": "Increasing"
    },
    "UpperCaution": {
      "Reading": 35,
      "Activation": "Increasing"
    },
    "LowerCaution": {
      "Reading": 10,
      "Activation": "Increasing"
    }
  },
  "Oem": {},
  "@odata.id": "/redfish/v1/Chassis/1/Sensors/CabinetTemp"
}
```

Redfish documentation generator

This document was created using the Redfish Documentation Generator utility, which uses the contents of the Redfish schema files (in JSON schema format) to automatically generate the bulk of the text. The source code for the utility is available for download at the DMTF's Github repository located at <http://www.github.com/DMTF/Redfish-Tools>.