



Document Identifier: DSP0239

Date: 2019-06-17

Version: 1.6.0

Management Component Transport Protocol (MCTP) IDs and Codes

Information for Work-in-Progress version:

IMPORTANT: This document is not a standard. It does not necessarily reflect the views of the DMTF or its members. Because this document is a Work in Progress, this document may still change, perhaps profoundly and without notice. This document is available for public review and comment until superseded.

Provide any comments through the DMTF Feedback Portal:

<http://www.dmtf.org/standards/feedback>

Supersedes: 1.5.0

Document Class: Normative

Document Status: Work in Progress

Document Language: en-US

12 Copyright Notice

13 Copyright © 2009, 2012, 2015, 2019 Distributed Management Task Force, Inc. (DMTF). All rights
14 reserved.

15 DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems
16 management and interoperability. Members and non-members may reproduce DMTF specifications and
17 documents, provided that correct attribution is given. As DMTF specifications may be revised from time to
18 time, the particular version and release date should always be noted.

19 Implementation of certain elements of this standard or proposed standard may be subject to third party
20 patent rights, including provisional patent rights (herein "patent rights"). DMTF makes no representations
21 to users of the standard as to the existence of such rights, and is not responsible to recognize, disclose,
22 or identify any or all such third party patent right, owners or claimants, nor for any incomplete or
23 inaccurate identification or disclosure of such rights, owners or claimants. DMTF shall have no liability to
24 any party, in any manner or circumstance, under any legal theory whatsoever, for failure to recognize,
25 disclose, or identify any such third party patent rights, or for such party's reliance on the standard or
26 incorporation thereof in its product, protocols or testing procedures. DMTF shall have no liability to any
27 party implementing such standard, whether such implementation is foreseeable or not, nor to any patent
28 owner or claimant, and shall have no liability or responsibility for costs or losses incurred if a standard is
29 withdrawn or modified after publication, and shall be indemnified and held harmless by any party
30 implementing the standard from any and all claims of infringement by a patent owner for such
31 implementations.

32 For information about patents held by third-parties which have notified the DMTF that, in their opinion,
33 such patent may relate to or impact implementations of DMTF standards, visit
34 <http://www.dmtf.org/about/policies/disclosures.php>.

35 PCI-SIG, PCIe, and the PCI HOT PLUG design mark are registered trademarks or service marks of PCI-
36 SIG.

37 All other marks and brands are the property of their respective owners.

38

39

CONTENTS

40	Foreword	4
41	Introduction.....	5
42	1 Scope	7
43	2 Normative references	7
44	3 Terms and definitions	8
45	4 Symbols and abbreviated terms.....	8
46	5 Conventions	8
47	5.1 Reserved and unassigned values.....	9
48	5.2 Byte ordering.....	9
49	6 MCTP Message Type codes	10
50	7 MCTP physical medium identifiers	11
51	8 MCTP physical transport binding identifiers	13
52	9 MCTP host interface type identifiers	14
53	10 Host interface protocol identifiers.....	14
54	ANNEX A (informative) Notation and conventions	15
55	ANNEX B (informative) Change log.....	16
56		

57 **Tables**

58	Table 1 – MCTP Message Types	10
59	Table 2 – MCTP physical medium identifiers.....	12
60	Table 3 – MCTP physical transport binding identifiers	13
61	Table 4 – MCTP host interface type identifiers.....	14
62		

63

Foreword

64 The *Management Component Transport Protocol (MCTP) IDs and Codes* (DSP0239) was prepared by
65 the PMCI Working Group.

66 DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems
67 management and interoperability.

68 **Acknowledgments**

69 The DMTF acknowledges the following individuals for their contributions to this document:

70 **Editors:**

- 71 • Hemal Shah – Broadcom Corporation
- 72 • Tom Slaight – Intel Corporation
- 73 • Philip Chidester – Dell Inc.
- 74 • Edward Newman – Hewlett Packard Enterprise

75 **Contributors:**

- 76 • Alan Berenbaum – SMSC
- 77 • Patrick Caporale – Lenovo
- 78 • Kelly Couch – Intel Corporation
- 79 • Ed Klodnicki – IBM
- 80 • Patrick Kutch – Intel Corporation
- 81 • Yuval Itkin – Mellanox Technologies
- 82 • Eliel Louzoun – Intel Corporation
- 83 • Zvika Perry – Cavium
- 84 • Bob Stevens - Dell Inc.

85

Introduction

86 This document presents a collection of IDs and codes that are used across the Management Component
87 Transport Protocol (MCTP) and transport binding specifications.

88 The MCTP defines a communication model intended to facilitate communication between:

- 89 • Management controllers and other management controllers
- 90 • Management controllers and management devices

91 The communication model includes a message format, transport description, message exchange
92 patterns, and configuration and initialization messages.

93 The *MCTP Base Protocol Specification* ([DSP0236](#)) describes the protocol and commands used for
94 communication within and initialization of an MCTP network. Associated with the *Base Protocol*
95 *Specification* are transport binding specifications that define how the MCTP base protocol and MCTP
96 control commands are implemented on a particular physical transport type and medium.
97

99 Management Component Transport Protocol (MCTP) IDs and 100 Codes

101 1 Scope

102 The *Management Component Transport Protocol (MCTP) IDs and Codes* document provides a
103 consolidated list of major IDs and codes used across the MCTP protocol and transport binding
104 specifications. Only IDs and codes that are required by a particular specification should be included in
105 that specification. IDs and codes values for other specifications should not be repeated for reference.
106 Instead, a reference to this specification should be provided.

107 The following is an overview of the different sets of codes and identifiers (enumeration values) that are
108 specified in this document:

- 109 • **MCTP message type codes**
110 Collection of the message type codes used for MCTP messages
- 111 • **MCTP physical medium identifiers**
112 Collection of identifiers for the different types of physical media that have been defined
- 113 • **MCTP physical transport binding identifiers**
114 Collection of identifiers for the specifications that define the operation, formatting, addressing,
115 and encapsulation of MCTP packets over different physical media
- 116 • **MCTP host interface type identifiers**
117 Collection of identifiers for the different physical interfaces used to transfer MCTP packets
118 between the host and the management controller

119 2 Normative references

120 The following referenced documents are indispensable for the application of this document. For dated or
121 versioned references, only the edition cited (including any corrigenda or DMTF update versions) applies.
122 For references without a date or version, the latest published edition of the referenced document
123 (including any corrigenda or DMTF update versions) applies.

124 DMTF specifications are available at http://www.dmtf.org/standards/published_documents. Unless
125 otherwise specified, values defined in this document apply to all published DMTF Standard versions of
126 the particular referenced DMTF specification.

127 DMTF DSP0134, *SMBIOS Reference Specification*

128 DMTF DSP0222, *Network Controller Sideband Interface (NC-SI) Specification*

129 DMTF DSP0235, *NVMe (NVM Express) Management Messages over MCTP Binding Specification*

130 DMTF DSP0236, *Management Component Transport Protocol (MCTP) Base Specification*

131 DMTF DSP0237, *Management Component Transport Protocol (MCTP) SMBus²C Transporting Binding
132 Specification*

133 DMTF DSP0238, *Management Component Transport Protocol (MCTP) PCIe VDM Transport Binding
134 Specification*

- 135 DMTF DSP0241, *PLDM Over MCTP Binding Specification*
- 136 DMTF DSP0253, *MCTP Serial Transport Binding Specification*
- 137 DMTF DSP0254, *MCTP KCS Transport Binding Specification*
- 138 DMTF DSP0261, *NC-SI Over MCTP Binding Specification*
- 139 DMTF DSP0275, *Security Protocol and Data Model (SPDM) over MCTP Binding Specification*
- 140 ISO/IEC Directives, Part 2, *Rules for the structure and drafting of International Standards*,
141 <http://isotc.iso.org/livelink/livelink?func=ll&objId=4230456&objAction=browse&sort=subtype>
- 142 PCI-SIG, *PCI Express Base Specification 1.1*, PCIeV1.1, March 28, 2005, <http://pcisig.com/specifications>
- 143 PCI-SIG, *PCI Express Base Specification 2.0*, PCIeV2.1, March 4, 2009, <http://pcisig.com/specifications>
- 144 PCI-SIG, *PCI Express Base Specification 3.0*, PCIeV3.0, November 10, 2010,
145 <http://pcisig.com/specifications>
- 146 PCI-SIG, *PCI Express Base Specification 4.0*, PCIeV4.0, October 5, 2017, <http://pcisig.com/specifications>
- 147 PCI-SIG, *PCI Express Base Specification 5.0*, PCIeV5.0, May 28, 2019, <http://pcisig.com/specifications>
- 148 NXP Semiconductors, *I²C-bus specification and user manual*, Rev. 6, 4 April 2014
149 http://www.nxp.com/documents/user_manual/UM10204.pdf
- 150 SMBus, *System Management Bus (SMBus) Specification v2.0*, SMBus, 2000,
151 <http://www.smbus.org/specs/smbus20.pdf>
- 152 SMBus, *System Management Bus (SMBus) Specification v3.0*, SMBus, December 20, 2014,
153 http://www.smbus.org/specs/SMBus_3_0_20141220.pdf
- 154 *MIPI Alliance Specification for I3C® (Improved Inter Integrated Circuit)*, version 1.0, MIPI Alliance, Inc.,
155 23 December 2016 (Adopted 31 December 2016), <https://www.mipi.org/specifications/i3c-sensor-specification>,
156 [specification](https://www.mipi.org/specifications/i3c-sensor-specification).
- 157 *MIPI Alliance Specification for I3C BasicSM (Improved Inter Integrated Circuit – Basic)*, version 1.0, MIPI
158 Alliance, Inc., 19 July 2018 (Adopted 8 October 2018), [http://resources.mipi.org/mipi-i3c-basic-v1-](http://resources.mipi.org/mipi-i3c-basic-v1-download)
159 [download](http://resources.mipi.org/mipi-i3c-basic-v1-download).

160 **3 Terms and definitions**

161 Refer to [DSP0236](#) for terms and definitions that are used in the MCTP specifications.

162 **4 Symbols and abbreviated terms**

163 Refer to [DSP0236](#) for symbols and abbreviated terms that are used in the MCTP specifications.

164 **5 Conventions**

165 The conventions described in the following clauses apply to this specification.

166 5.1 Reserved and unassigned values

167 Unless otherwise specified, any reserved, unspecified, or unassigned values in enumerations or other
168 numeric ranges are reserved for future definition by the DMTF.

169 Unless otherwise specified, numeric or bit fields that are designated as reserved shall be written as 0
170 (zero) and ignored when read.

171 5.2 Byte ordering

172 Unless otherwise specified, byte ordering of multi-byte numeric fields or bit fields is "Big Endian" (that is,
173 the lower byte offset holds the most significant byte, and higher offsets hold lesser significant bytes).

174 **6 MCTP Message Type codes**175 Table 1 defines the values for the Message Type field for different message types transported through
176 MCTP.177 **NOTE** A device that supports a given message type may not support that message type equally across all busses
178 that connect to the device.179 **Table 1 – MCTP Message Types**

Message Type	Message Type Code	Description
MCTP Control	0x00	Messages used to support initialization and configuration of MCTP communication within an MCTP network, as specified in DSP0236
Platform Level Data Model (PLDM)	0x01	Messages used to convey Platform Level Data Model (PLDM) traffic over MCTP, as specified in DSP0241 .
NC-SI over MCTP	0x02	Messages used to convey NC-SI Control traffic over MCTP, as specified in DSP0261 .
Ethernet over MCTP	0x03	Messages used to convey Ethernet traffic over MCTP. See DSP0261 . This message type can also be used separately by other specifications.
NVM Express Management Messages over MCTP	0x04	Messages used to convey NVM Express (NVMe) Management Messages over MCTP, as specified in DSP0235 .
SPDM over MCTP	0x05	Messages used to convey Security Protocol and Data Model Specification (SPDM) traffic over MCTP, as specified in DSP0275 .
Vendor Defined – PCI	0x7E	Message type used to support VDMs where the vendor is identified using a PCI-based vendor ID. The specification of the initial Message Header bytes for this message type is provided within this specification. The specification of the format of this message is given in DSP0236 . Otherwise, the message body content is specified by the vendor, company, or organization identified by the given vendor ID.
Vendor Defined – IANA	0x7F	Message type used to support VDMs where the vendor is identified using an IANA-based vendor ID. This format uses an "Enterprise Number" that is assigned and maintained by the Internet Assigned Numbers Authority (IANA), www.iana.org , as the means of identifying a particular vendor, company, or organization. The specification of the format of this message is given in DSP0236 . Otherwise, the message body content is specified by the vendor, company, or organization identified by the given vendor ID.
Reserved	all other	Reserved

180 **7 MCTP physical medium identifiers**

181 Table 2 defines a set of numbers that correspond to different media types that can be used with MCTP.
182 The identifier is primarily used to identify which physical addressing format is used for MCTP packets on
183 the bus.

184 NOTE PCIe revision numbers are intended to indicate specification compatibility, not bit transfer rate or
185 throughput.
186

187

188

Table 2 – MCTP physical medium identifiers

Physical Media Identifier	Description
0x00	Unspecified
0x01	SMBus 2.0 100 kHz compatible
0x02	SMBus 2.0 + I ² C 100 kHz compatible
0x03	I ² C 100 kHz compatible (Standard-mode)
0x04	SMBus 3.0 or I ² C 400 kHz compatible (Fast-mode)
0x05	SMBus 3.0 or I ² C 1 MHz compatible (Fast-mode Plus)
0x06	I ² C 3.4 MHz compatible (High-speed mode)
0x07	Reserved
0x08	PCIe revision 1.1 compatible
0x09	PCIe revision 2.0 compatible
0x0A	PCIe revision 2.1 compatible
0x0B	PCIe revision 3.0 compatible
0x0C	PCIe revision 4.0 compatible
0x0D	PCIe revision 5.0 compatible
0x0E	Reserved
0x0F	PCI compatible (PCI 1.0,2.0,2.1,2.2,2.3,3.0,PCI-X 1.0, PCI-X 2.0)
0x10	USB 1.1 compatible
0x11	USB 2.0 compatible
0x12	USB 3.0 compatible
0x13:0x17	Reserved
0x18	NC-SI over RBT (A physical interface based on RMI as defined in DSP0222)
0x20	KCS ¹ / Legacy (Fixed Address Decoding)
0x21	KCS ¹ / PCI (Base Class 0xC0 Subclass 0x01)
0x22	Serial Host ² / Legacy (Fixed Address Decoding)
0x23	Serial Host ² / PCI (Base Class 0x07 Subclass 0x00)
0x24	Asynchronous Serial ³ (Between MCs and IMDs)
0x30	I ³ C 12.5 MHz compatible (SDR)
0x31	I ³ C 25 MHz compatible (HDR-DDR)
all other	Reserved
<p>1. Keyboard Controller Style Interface – refer to DSP0236.</p> <p>2. Serial Host refers to a register based UART interface.</p> <p>3. Asynchronous Serial refers to an 8-bit asynchronous bi-directional serial transmission media where characters are transmitted independently (i.e., each frame carries 8-bits of data).</p>	

189

190

191 **8 MCTP physical transport binding identifiers**

192 Table 3 defines as set of numbers that correspond to different media types that can be used with MCTP.
 193 The identifier indicates which physical addressing format is used for MCTP packets on the bus.

194 **Table 3 – MCTP physical transport binding identifiers**

MCTP Physical Transport Binding Identifier	Description
0x00	Reserved
0x01	MCTP over SMBus (DSP0237)
0x02	MCTP over PCIe VDM (DSP0238)
0x03	Reserved for MCTP over USB
0x04	MCTP over KCS (DSP0254)
0x05	MCTP over Serial (DSP0253)
0xFF	Vendor defined NOTE A vendor-defined transport binding must meet the requirements in DSP0236 (in particular, when being bridged to or from standard MCTP transport binding and media combinations).
All other	Reserved

195

196 9 MCTP host interface type identifiers

197 The SMBIOS specification ([DSP0134](#)) reserves a range of host interface type identifiers 0x00 through
 198 0x3F for use by this specification. Table 4 defines a set of numbers that correspond to different MCTP
 199 host interface types that can be used with MCTP. The identifier indicates which physical interface to
 200 transfer MCTP packets between the host and the management controller.

201 **Table 4 – MCTP host interface type identifiers**

MCTP Host Interface Type Identifier	Description
0x00	Reserved
0x01	Reserved
0x02	KCS: Keyboard Controller Style – refer to Intelligent Platform Management Interface Specification Section 9 Keyboard Controller Style (KCS) Interface
0x03	8250 UART Register Compatible
0x04	16450 UART Register Compatible
0x05	16550/16550A UART Register Compatible
0x06	16650/16650A UART Register Compatible
0x07	16750/16750A UART Register Compatible
0x08	16850/16850A UART Register Compatible
0x09 : 0x3F	Reserved
all other	Assigned by the SMBIOS specification (DSP0134)

202 10 Host interface protocol identifiers

203 In earlier versions of this specification, this section contained a table of host interface protocol identifiers.
 204 That table has been moved to the description of the Type 42 record of the SMBIOS specification
 205 ([DSP0134](#)) with a version greater than 3.1.0.

206
207
208

ANNEX A (informative) Notation and conventions

209 Notations

210 Examples of notations used in this document are as follows:

- 211 • 2:N In field descriptions, this will typically be used to represent a range of byte offsets
212 starting from byte two and continuing to and including byte N. The lowest offset is on
213 the left, the highest is on the right.
- 214 • (6) Parentheses around a single number can be used in message field descriptions to
215 indicate a byte field that may be present or absent.
- 216 • (3:6) Parentheses around a field consisting of a range of bytes indicates the entire range
217 may be present or absent. The lowest offset is on the left, the highest is on the right.
- 218 • [PCIe](#) Underlined, blue text is typically used to indicate a reference to a document or
219 specification called out in the “Normative References” section or to items hyperlinked
220 within the document.
- 221 • rsvd Abbreviation for “reserved.” Case insensitive.
- 222 • [4] Square brackets around a number are typically used to indicate a bit offset. Bit offsets
223 are given as zero-based values (that is, the least significant bit [LSb] offset = 0).
- 224 • [7:5] A range of bit offsets. The most significant bit is on the left, the least significant bit is
225 on the right.
- 226 • 1b The lower case “b” following a number consisting of 0s and 1s is used to indicate the
227 number is being given in binary format.
- 228 • 0x12A A leading “0x” is used to indicate a number given in hexadecimal format.

229

230
231
232

ANNEX B (informative) Change log

Version	Date	Description
1.0.0	2009-07-28	
1.1.0	2009-11-03	Added Host Interface Type Identifiers. Added Host Interface Protocol Identifiers. Added reference to NC-SI and added clarification on physical medium identifiers.
1.2.0	2012-06-04	Added Ethernet over MCTP message type. Clarified the description of NC-SI over MCTP and PLDM over MCTP. Added I2C fast plus and high-speed physical medium identifiers. Clarified RMI/NC-SI physical medium identifier description. Fixed references.
1.3.0	2015-03-06	Added message type NVMe (NVM Express) Management Messages over MCTP. Updated references.
1.4.0	2017-01-11	Limited host interface type identifiers to the range 0x00:0x3F. Moved the host interface protocol identifier table to the SMBIOS specification. Updated references.
1.5.0	2017-11-16	Updated contributors and references. Added support for SMBus 3.0 and PCIe Gen 4.
1.6.0	2019-06-17	Added an MCTP Message Type for SPD. Added an MCTP physical medium identifiers for PCIe revision 5.0, and I3C.

233

Bibliography

234 RMI Consortium, *Reduced Media Independent Interface (RMII) Specification v1.2*, RMI, March 20, 1988,
235 http://ebook.pldworld.com/_eBook/-Telecommunications,Networks-/TCPIP/RMII/rmii_rev12.pdf

236