



Document Number: DSP0244

Date: 2009-11-02

Version: 1.1.0

IPMI PET to Platform Message Registry Mapping

Document Type: Specification

Document Status: DMTF Standard

Document Language: E

Copyright Notice

Copyright © 2008, 2009 Distributed Management Task Force, Inc. (DMTF). All rights reserved.

DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability. Members and non-members may reproduce DMTF specifications and documents, provided that correct attribution is given. As DMTF specifications may be revised from time to time, the particular version and release date should always be noted.

Implementation of certain elements of this standard or proposed standard may be subject to third party patent rights, including provisional patent rights (herein "patent rights"). DMTF makes no representations to users of the standard as to the existence of such rights, and is not responsible to recognize, disclose, or identify any or all such third party patent right, owners or claimants, nor for any incomplete or inaccurate identification or disclosure of such rights, owners or claimants. DMTF shall have no liability to any party, in any manner or circumstance, under any legal theory whatsoever, for failure to recognize, disclose, or identify any such third party patent rights, or for such party's reliance on the standard or incorporation thereof in its product, protocols or testing procedures. DMTF shall have no liability to any party implementing such standard, whether such implementation is foreseeable or not, nor to any patent owner or claimant, and shall have no liability or responsibility for costs or losses incurred if a standard is withdrawn or modified after publication, and shall be indemnified and held harmless by any party implementing the standard from any and all claims of infringement by a patent owner for such implementations.

For information about patents held by third-parties which have notified the DMTF that, in their opinion, such patent may relate to or impact implementations of DMTF standards, visit <http://www.dmtf.org/about/policies/disclosures.php>.

CONTENTS

Foreword	5
Introduction	6
1 Scope	7
2 Normative References.....	7
3 Terms and Definitions	7
4 Symbols and Abbreviated Terms	8
5 IPMI PET to Platform Message Registry Mapping.....	9
5.1 Intrusion Sensor.....	9
5.2 Security Violation Sensor.....	11
5.3 Processor Sensor	12
5.4 Power Supply Sensor	13
5.5 Power Unit Sensor	14
5.6 Memory Sensor.....	15
5.7 Drive Bay Slot Sensor.....	17
5.8 System Firmware Progress Sensor	18
5.9 Event Logging Sensor.....	18
5.10 System Event Sensor	19
5.11 Critical Interrupt Sensor	20
5.12 Button/Switch Sensor.....	21
5.13 Chip Set Sensor.....	22
5.14 Cable/Interconnect Sensor	22
5.15 System Boot Initiated Sensor	23
5.16 Boot Error Sensor	24
5.17 OS Boot Sensor	25
5.18 OS Stop/Shutdown Sensor.....	25
5.19 Slot Sensor	26
5.20 System ACPI Power State Sensor	27
5.21 Watchdog 2 Sensor	28
5.22 Platform Alert Sensor.....	29
5.23 Entity Presence Sensor	30
5.24 LAN Sensor.....	30
5.25 Management Subsystem Health Sensor	31
5.26 Battery Sensor.....	31
5.27 Session Audit Sensor.....	32
5.28 Version Change Sensor.....	32
5.29 FRU State Sensor.....	33
5.30 Type 1 (Numeric/Threshold) Sensor.....	34
5.31 Type 2 (Discrete) Sensor	36
5.32 Type 3 (Discrete) Sensor.....	37
5.33 Type 4 (Discrete) Sensor.....	37
5.34 Type 5 (Discrete) Sensor.....	38
5.35 Type 6 (Discrete) Sensor.....	38
5.36 Type 7 (Discrete) Sensor.....	38
5.37 Type 8 (Discrete) Sensor.....	40
5.38 Type 9 (Discrete) Sensor.....	41
5.39 Type A (Discrete) Sensor	41
5.40 Type B (Redundant) Sensor	42
5.41 Type C (Discrete) Sensor	44
ANNEX A (informative) Change Log.....	46

Tables

Table 1 – Intrusion Sensor PET to Platform Message Registry Mapping	9
Table 2 – Security Violation Sensor PET to Platform Message Registry Mapping	11
Table 3 – Processor Sensor PET to Platform Message Registry Mapping	12
Table 4 – Power Supply Sensor PET to Platform Message Registry Mapping	13
Table 5 – Power Unit Sensor PET to Platform Message Registry Mapping	14
Table 6 – Memory Sensor PET to Platform Message Registry Mapping	16
Table 7 – Drive Bay Slot Sensor PET to Platform Message Registry Mapping	17
Table 8 – System Firmware Progress Sensor PET to Platform Message Registry Mapping	18
Table 9 – Event Logging Disabled Sensor PET to Platform Message Registry Mapping	19
Table 10 – System Event Sensor PET to Platform Message Registry Mapping	19
Table 11 – Critical Interrupt Sensor PET to Platform Message Registry Mapping	20
Table 12 – Button/Switch Sensor PET to Platform Message Registry Mapping	22
Table 13 – Chip Set Sensor PET to Platform Message Registry Mapping	22
Table 14 – Cable/Interconnect Sensor PET to Platform Message Registry Mapping	23
Table 15 – System Boot Initiated Sensor PET to Platform Message Registry Mapping	23
Table 16 – Boot Error Sensor PET to Platform Message Registry Mapping	24
Table 17 – OS BOOT Sensor PET to Platform Message Registry Mapping	25
Table 18 – OS Stop/Shutdown Sensor PET to Platform Message Registry Mapping	26
Table 19 – Slot Sensor PET to Platform Message Registry Mapping	26
Table 20 – System ACPI Power State Sensor PET to Platform Message Registry Mapping	27
Table 21 – Watchdog 2 Sensor PET to Platform Message Registry Mapping	29
Table 22 – Platform Alert Sensor PET to Platform Message Registry Mapping	29
Table 23 – Entity Presence Sensor PET to Platform Message Registry Mapping	30
Table 24 – LAN Sensor PET to Platform Message Registry Mapping	30
Table 25 – Management Subsystem Health Sensor PET to Platform Message Registry Mapping	31
Table 26 – Battery Sensor PET to Platform Message Registry Mapping	31
Table 27 – Session Audit Sensor PET to Platform Message Registry Mapping	32
Table 28 – Version Change Sensor PET to Platform Message Registry Mapping	32
Table 29 – FRU State Sensor PET to Platform Message Registry Mapping	33
Table 30 – Type 1 (Numeric/Threshold) Sensor PET to Platform Message Registry Mapping	34
Table 31 – Type 2 (Discrete) Sensor PET to Platform Message Registry Mapping	36
Table 32 – Type 3 (Discrete) Sensor PET to Platform Message Registry Mapping	37
Table 33 – Type 4 (Discrete) Sensor PET to Platform Message Registry Mapping	37
Table 34 – Type 5 (Discrete) Sensor PET to Platform Message Registry Mapping	38
Table 35 – Type 6 (Discrete) Sensor PET to Platform Message Registry Mapping	38
Table 36 – Type 7 (Discrete) Sensor PET to Platform Message Registry Mapping	39
Table 37 – Type 8 (Discrete) Sensor PET to Platform Message Registry Mapping	40
Table 38 – Type 9 (Discrete) Sensor PET to Platform Message Registry Mapping	41
Table 39 – Type A (Discrete) Sensor PET to Platform Message Registry Mapping	41
Table 40 – Type B (Redundant) Sensor PET to Platform Message Registry Mapping	43
Table 41 – Type C (Discrete) Sensor PET to Platform Message Registry Mapping	44

Foreword

The *IPMI PET to Platform Message Registry Mapping* (DSP0244) was prepared by the Physical Platform Profiles Working Group and the Server Management Working Group of the DMTF.

DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability.

Acknowledgments

The authors wish to acknowledge the following people.

Editor:

- Deb McDonald – IBM

Contributors:

- Jon Hass – Dell
- Jeff Hilland – HP
- Aaron Merkin – IBM
- Jianwen Yin – Dell
- Tom Slaight – Intel

Introduction

The information in this specification should be sufficient for a provider or consumer of this data to unambiguously identify the mapping from IPMI PET to Platform Message Registry.

The target audience for this specification is implementers who are writing CIM-based providers or consumers of management interfaces that represent the components described in this document.

1 IPMI PET to Platform Message Registry Mapping

2 1 Scope

3 The *IPMI PET to Platform Message Registry Mapping* defines the mapping from IPMI PET to Platform
4 Message Registry.

5 2 Normative References

6 The following referenced documents are indispensable for the application of this document. For dated
7 references, only the edition cited applies. For undated references, the latest edition of the referenced
8 document (including any amendments) applies.

9 DMTF DSP0136, *Alert Standard Format Specification 2.0*,
10 <http://www.dmtf.org/standards/documents/ASF/DSP0136.pdf>

11 DMTF DSP8007, *Platform Message Registry 1.1*,

12 http://schemas.dmtf.org/wbem/messageregistry/1/dsp8007_1.1.xml

13 ISO/IEC Directives, Part 2, *Rules for the structure and drafting of International Standards*,
14 <http://isotc.iso.org/livelink/livelink.exe?func=ll&objId=4230456&objAction=browse&sort=subtype>

15 IPMI – *Intelligent Platform Management Interface Specification Second Generation 2.0*; Document
16 Revision 1.0 February 12, 2004 February 15, 2006 Markup

17 3 Terms and Definitions

18 For the purposes of this document, the following terms and definitions apply.

19 **can**

20 used for statements of possibility and capability, whether material, physical, or causal

21 **3.1**

22 **cannot**

23 used for statements of possibility and capability, whether material, physical, or causal

24 **3.2**

25 **conditional**

26 indicates requirements to be followed strictly to conform to the document when the specified conditions
27 are met

28 **3.3**

29 **mandatory**

30 indicates requirements to be followed strictly to conform to the document and from which no deviation is
31 permitted

32 **3.4**

33 **may**

34 indicates a course of action permissible within the limits of the document

- 35 **3.5**
36 **need not**
37 indicates a course of action permissible within the limits of the document
- 38 **3.6**
39 **optional**
40 indicates a course of action permissible within the limits of the document
- 41 **3.7**
42 **shall**
43 indicates requirements to be followed strictly to conform to the document and from which no deviation is
44 permitted
- 45 **3.8**
46 **shall not**
47 indicates requirements to be followed strictly to conform to the document and from which no deviation is
48 permitted
- 49 **3.9**
50 **should**
51 indicates that among several possibilities, one is recommended as particularly suitable, without
52 mentioning or excluding others, or that a certain course of action is preferred but not necessarily required
- 53 **3.10**
54 **should not**
55 indicates that a certain possibility or course of action is deprecated but not prohibited

56 **4 Symbols and Abbreviated Terms**

- 57 **4.1**
58 **ASF**
59 Alert Standard Format
- 60 **4.2**
61 **CIM**
62 Common Information Model
- 63 **4.3**
64 **DASH**
65 Desktop and Mobile Architecture for System Hardware
- 66 **4.4**
67 **IPMI**
68 Intelligent Platform Management Interface
- 69 **4.5**
70 **PET**
71 Platform Event Trap
- 72 **4.6**
73 **SMASH**
74 System Management Architecture for Server Hardware
75

76 **5 IPMI PET to Platform Message Registry Mapping**

77 This purpose of this document is to capture the mapping from IPMI and ASF PETs to CIM standard
 78 messages for eventing. It is desirable to simplify migration from the existing ASF and IPMI standards
 79 prevalent in the industry to the emerging SMASH and DASH initiatives of the DMTF. Defining a normative
 80 mapping from these event contents in these existing standards to SMASH and DASH will guide
 81 implementers as they transition their products.

82 If an IPMI or ASF PET can be mapped to a CIM standard message in the Platform Message Registry,
 83 there shall be an entry in column “Platform Message Registry MessageID” in the table specifying the
 84 MessageID of the message.

85 Note: N/A means a Platform Message Registry MessageID is not defined in the referenced version of [DSP8007](#).

86 **5.1 Intrusion Sensor**

87 Sensor Type: Intrusion Sensor

88 Sensor Type Code: 05h

89 Reading Type: 6Fh

90 **Table 1 – Intrusion Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Chassis Intrusion	Chassis Open	PLAT0004
00h	Deassert	Chassis Intrusion	Chassis Closed	PLAT0005
01h	Assert	Drive Bay Intrusion	Drive Bay Open	PLAT0006
01h	Deassert	Drive Bay Intrusion	Drive Bay Closed	PLAT0007
02h	Assert	I/O Card Area Intrusion	I/O Card Area Open	PLAT0008
02h	Deassert	I/O Card Area Intrusion	I/O Card Area Closed	PLAT0009
03h	Assert	Processor Area Intrusion	Processor Area Open	PLAT0010
03h	Deassert	Processor Area Intrusion	Processor Area Closed	PLAT0011
04h	Assert	LAN Disconnect	LAN Disconnected	PLAT0012
04h	Deassert	LAN Disconnect	LAN Connected	PLAT0013
05h	Assert	Unauthorized Dock	Docking Permission Deasserted	PLAT0017
05h	Deassert	Unauthorized Dock	Docking Permission Asserted	PLAT0016
06h	Assert	FAN Area	Fan Area	PLAT0018

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
		Intrusion	Open	
06h	Deassert	FAN Area Intrusion	Fan Area Closed.	PLAT0019

91 **5.2 Security Violation Sensor**

92 Sensor Type: Security Violation Sensor

93 Sensor Type Code: 06h

94 Reading Type: 6Fh

95 **Table 2 – Security Violation Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Secure Mode Violation	Secure Mode Violation	PLAT0022
00h	Deassert	Secure Mode Violation		N/A
01h	Assert	Pre-boot User Password Violation	Pre-boot User password violation	PLAT0024
01h	Deassert	Pre-boot User Password Violation		N/A
02h	Assert	Pre-boot Setup Password Violation	Pre-boot Setup password violation	PLAT0026
02h	Deassert	Pre-boot Setup Password Violation		N/A
03h	Assert	Network Boot Password Violation	Network Boot Password Violation	PLAT0028
03h	Deassert	Network Boot Password Violation		N/A
04h	Assert	Password Violation	Password Violation	PLAT0030
04h	Deassert	Password Violation		N/A
05h	Assert	Out-of-band Password Violation	Out-of-band Password Violation	PLAT0032
05h	Deassert	Out-of-band Password Violation		N/A

96

97 **5.3 Processor Sensor**

98 Sensor Type: Processor Sensor

99 Sensor Type Code: 07h

100 Reading Type: 6Fh

101 **Table 3 – Processor Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	IERR	Processor Failed – IERR	PLAT0042
00h	Deassert	IERR	Processor Recovered From IERR	PLAT0043
01h	Assert	Thermal Tripped	Over Temperature Condition Detected for Processor	PLAT0036
01h	Deassert	Thermal Tripped	Over Temperature Condition Removed for Processor	PLAT0037
02h	Assert	FRB1/BIST Failure	Processor Failed – FRB1/BIST	PLAT0044
02h	Deassert	FRB1/BIST Failure	Processor Recovered from FRB1/BIST	PLAT0045
03h	Assert	FRB2/Hang in POST Failure	Processor Failed – FRB2/POST	PLAT0046
03h	Deassert	FRB2/Hang in POST Failure	Processor Recovered from FRB2/Hang in POST Failure	PLAT0047
04h	Assert	FRB3 Initialization Failure	Processor Failed – FRB3	PLAT0048
04h	Deassert	FRB3 Initialization Failure	Processor Recovered from FRB3 Initialization Failure	PLAT0049
05h	Assert	Configuration Error	Processor Configuration Mismatch	PLAT0062
05h	Deassert	Configuration Error	Processor Recovered – Configuration Mismatch	PLAT0063

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
06h	Assert	Uncorrectable CPU Complex asserted	SM BIOS Uncorrectable CPU Complex Error asserted	PLAT0816
06h	Deassert	Uncorrectable CPU Complex deasserted	SM BIOS Uncorrectable CPU Complex Error deasserted	PLAT0817
07h	Assert	Presence	Processor Added	PLAT0034
07h	Deassert	Presence	Processor Removed	PLAT0035
08h	Assert	Disabled	Processor Disabled	PLAT0061
08h	Deassert	Disabled	Processor Enabled	PLAT0060
09h	Assert	Terminator Presence	Processor Terminator Detected	PLAT0064
09h	Deassert	Terminator Presence	Processor Terminator Not Detected	PLAT0065
0Ah	Assert	Throttled	Processor Degraded	PLAT0038
0Ah	Deassert	Throttled	Processor Not Degraded	PLAT0039

102 **5.4 Power Supply Sensor**

103 Sensor Type: Power Supply Sensor

104 Sensor Type Code: 08h

105 Reading Type: 6Fh

106 **Table 4 – Power Supply Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Presence	Power Supply Added	PLAT0084
00h	Deassert	Presence	Power Supply Removed	PLAT0085
01h	Assert	Failure	Power Supply Failed	PLAT0086
01h	Deassert	Failure	Power Supply Failed deasserted	PLAT0087
02h	Assert	Predictive Failure	Power Supply failure predicted	PLAT0088

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
02h	Deassert	Predictive Failure	Power Supply failure no longer predicted	PLAT0089
03h	Assert	Input Lost	Power Supply input lost	PLAT0100
03h	Deassert	Input Lost	Power Supply input normal	PLAT0099
04h	Assert	Input Lost or Out of Range	Power Supply input lost or out of range	PLAT0096
04h	Deassert	Input Lost or Out of Range	Power Supply input normal	PLAT0097
05h	Assert	Input Present but Out of Range	Power Supply input out of range	PLAT0098
05h	Deassert	Input Present but Out of Range	Power Supply input normal	PLAT0099
06h	Assert	Configuration Error	Power Supply Configuration Error	PLAT0104
06h	Deassert	Configuration Error	Power Supply configuration is OK	PLAT0105

107 5.5 Power Unit Sensor

108 Sensor Type: Power Unit Sensor

109 Sensor Type Code: 09h

110 Reading Type: 6Fh

111 240VA Power down Error with offset 02h Asset, Power Unit power down error is due to a safety interlock
112 (chassis switch).

113 **Table 5 – Power Unit Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Power Off	Power Unit Disabled	PLAT0106
00h	Deassert	Power Off	Power Unit Enabled	PLAT0107
01h	Assert	Power Cycle	Power Unit power cycled	PLAT0108
01h	Deassert	Power Cycle	N/A	N/A
02h	Assert	240VA Power Down Error	Power Unit power down error	PLAT0110

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
02h	Deassert	240VA Power Down Error	Power Unit power down error recovery	PLAT0111
03h	Assert	Interlock Power Down Error	Power Unit power down error	PLAT0110
03h	Deassert	Interlock Power Down Error	Power Unit power down error recovery	PLAT0111
04h	Assert	Power Lost Error	Power Unit power lost	PLAT0112
04h	Deassert	Power Lost Error	Power Unit power restored	PLAT0113
05h	Assert	Soft Power Control Failure	Power Unit soft power control failed	PLAT0114
05h	Deassert	Soft Power Control Failure	Power Unit soft power control recovered	PLAT0115
06h	Assert	Power Unit Failure	Power Unit failed	PLAT0116
06h	Deassert	Power Unit Recovered	Power Unit recovered	PLAT0117
07h	Assert	Predictive Failure	Power Unit Predictive Failure	PLAT0118
07h	Deassert	Predictive Failure	Power Unit no longer Predicted to Fail	PLAT0119

114 **5.6 Memory Sensor**

115 Sensor Type: Memory Sensor

116 Sensor Type Code: 0Ch

117 Reading Type: 6Fh

118

119

120

Table 6 – Memory Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Correctable ECC	Memory Corrected Error Detected	PLAT0124
00h	Deassert	Correctable ECC		N/A
01h	Assert	Uncorrectable ECC	Memory uncorrectable error detected	PLAT0138
01h	Deassert	Uncorrectable ECC	Memory uncorrectable error recovered	PLAT0139
02h	Assert	Parity Error	Memory Parity Error Detected	PLAT0134
02h	Deassert	Parity Error	Memory Parity Error Recovered	PLAT0135
03h	Assert	Scrub Failed (stuck bit)	Memory Scrub Failure	PLAT0136
03h	Deassert	Scrub Failed (stuck bit)	Memory Scrub Failure Recovered	PLAT0137
04h	Assert	Device Disabled	Memory Disabled	PLAT0131
04h	Deassert	Device Disabled	Memory Enabled	PLAT0130
05h	Assert	ECC Logging Limit Reached	Memory Logging Limit Reached	PLAT0144
05h	Deassert	ECC Logging Limit Reached	Memory Logging Limit Removed	PLAT0145
06h	Assert	Presence	Memory Added	PLAT0128
06h	Deassert	Presence	Memory Removed	PLAT0129
07h	Assert	Configuration Error	Memory DIMM Configuration Error	PLAT0126
07h	Deassert	Configuration Error	Memory DIMM Configuration Error Recovery	PLAT0127
08h	Assert	Spare	Memory double chip sparing initiated	PLAT0140
08h	Deassert	Spare	Memory double chip sparing concluded	PLAT0141
09h	Assert	Throttled	Memory Throttled	PLAT0142

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
09h	Deassert	Throttled	Memory no longer Throttled	PLAT0143
0Ah	Assert	Critical Overtemperature	Over Temperature Condition Detected for Memory	PLAT0146
0Ah	Deassert	Critical Overtemperature	Over Temperature Condition Removed for Memory	PLAT0147

121 **5.7 Drive Bay Slot Sensor**

122 Sensor Type: Drive Bay Slot Sensor

123 Sensor Type Code: 0Dh

124 Reading Type: 6Fh

125 **Table 7 – Drive Bay Slot Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Drive Presence	Drive Added	PLAT0536
00h	Deassert	Drive Presence	Drive Removed	PLAT0163
01h	Assert	Drive Fault	Drive Disabled due to fault	PLAT0537
01h	Deassert	Drive Fault	Drive Enabled	PLAT0539
02h	Assert	Predictive Failure	Array Failure Predicted	PLAT0538
02h	Deassert	Predictive Failure	Array Failure no longer Predicted	PLAT0510
03h	Assert	Hot Spare	Hot Spare Enabled	PLAT0170
03h	Deassert	Hot Spare	Hot Spare Disabled	PLAT0171
04h	Assert	Consistency Check in Progress	Consistency Check Begun	PLAT0172
04h	Deassert	Consistency Check in Progress	Consistency Check Completed	PLAT0173
05h	Assert	In Critical Array	Array Critical	PLAT0174
05h	Deassert	In Critical Array	Critical Array Recovered	PLAT0175

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
06h	Assert	In Failed Array	Failed Array	PLAT0176
06h	Deassert	In Failed Array	Failed Array restored	PLAT0177
07h	Assert	Rebuild in Progress	Rebuild in Progress	PLAT0178
07h	Deassert	Rebuild in Progress	Rebuild Completed	PLAT0179
08h	Assert	Rebuild Aborted	Rebuild Aborted	PLAT0180
08h	Deassert	Rebuild Aborted		N/A

126 5.8 System Firmware Progress Sensor

127 Sensor Type: System Firmware Progress Sensor

128 Sensor Type Code: 0Fh

129 Reading Type: 6Fh

130

131 **Table 8 – System Firmware Progress Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	POST Error	Post Error	PLAT0184
00h	Deassert	POST Error	Post completed normally	PLAT0185
01h	Assert	System Firmware Hang	System Firmware Hang	PLAT0186
01h	Deassert	System Firmware Hang	System Firmware completed normally	PLAT0187
02h	Assert	System Firmware Progress	System Firmware Progress	PLAT0188
02h	Deassert	System Firmware Progress		N/A

132 5.9 Event Logging Sensor

133 Sensor Type: Event Logging Disabled Sensor

134 Sensor Type Code: 10h

135 Reading Type: 6Fh

136

Table 9 – Event Logging Disabled Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Correctable Memory Error Logging Disabled	Memory Logging Disabled	PLAT0192
00h	Deassert	Correctable Memory Error Logging Disabled	Memory Logging Enabled	PLAT0193
01h	Assert	Event Logging Disabled	Event Logging Disabled	PLAT0194
01h	Deassert	Event Logging Disabled	Event Logging Enabled	PLAT0195
02h	Assert	Log Cleared	Log Cleared	PLAT0200
02h	Deassert	Log Cleared		N/A
03h	Assert	All Event Logging Disabled	All Event Logging Disabled	PLAT0196
03h	Deassert	All Event Logging Disabled	All Event Logging Enabled	PLAT0198
04h	Assert	Log Full	Log Full	PLAT0202
04h	Deassert	Log Full	Log no longer full	PLAT0203
05h	Assert	Log Almost Full	Log Almost Full	PLAT0204
05h	Deassert	Log Almost Full		N/A

137 **5.10 System Event Sensor**

138 Sensor Type: System Event Sensor

139 Sensor Type Code: 12h

140 Reading Type: 6Fh

141 **Table 10 – System Event Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	System Reconfigured	System Reconfigured	PLAT0210
00h	Deassert	System Reconfigured		N/A
01h	Assert	OEM System Boot Event	OEM System Boot Event	PLAT0212
01h	Deassert	OEM System Boot Event		N/A

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
02h	Assert	Unknown System Hardware Failure	Unknown System Hardware Failure	PLAT0214
02h	Deassert	Unknown System Hardware Failure	Unknown System Hardware failure recovered	PLAT0215
03h	Assert	Auxiliary Log Entry Event	Auxiliary Log Entry Event	PLAT0216
03h	Deassert	Auxiliary Log Entry Event		N/A
04h	Assert	PEF Action Executed	PEF Action Executed	PLAT0218
04h	Deassert	PEF Action Executed		N/A
05h	Assert	Timestamp Clock Synch	Timestamp Clock Synch	PLAT0220
05h	Deassert	Timestamp Clock Synch		N/A

142 5.11 Critical Interrupt Sensor

143 Sensor Type: Critical Interrupt Sensor

144 Sensor Type Code: 13h

145 Reading Type: 6Fh

146 **Table 11 – Critical Interrupt Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Front Panel NMI / Diagnostic Interrupt	Front Panel NMI / Diagnostic Interrupt	PLAT0222
00h	Deassert	Front Panel NMI / Diagnostic Interrupt		N/A
01h	Assert	Bus Timeout	Bus Timeout	PLAT0224
01h	Deassert	Bus Timeout	Bus Timeout Recovered	PLAT0225
02h	Assert	I/O Channel Check NMI	I/O Channel Check NMI	PLAT0226
02h	Deassert	I/O Channel Check NMI	I/O Channel Check NMI Recovered	PLAT0230
03h	Assert	Software NMI	Software NMI	PLAT0228

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
03h	Deassert	Software NMI	Software NMI Recovered	PLAT0230
04h	Assert	PCI PERR	PCI PERR	PLAT0232
04h	Deassert	PCI PERR	PCI PERR Recovered	PLAT0233
05h	Assert	PCI SERR	PCI SERR	PLAT0234
05h	Deassert	PCI SERR	PCI SERR Recovered	PLAT0235
06h	Assert	EISA Fail Safe Timeout	EISA Fail Safe Timeout	PLAT0236
06h	Deassert	EISA Fail Safe Timeout	EISA Fail Safe Timeout Recovered	PLAT0237
07h	Assert	Bus Correctable Error	Bus Correctable Error	PLAT0238
07h	Deassert	Bus Correctable Error	Bus Correctable Error Recovered	PLAT0239
08h	Assert	Bus Uncorrectable Error	Bus Uncorrectable Error	PLAT0240
08h	Deassert	Bus Uncorrectable Error	Bus Uncorrectable Error Recovered	PLAT0241
09h	Assert	Fatal NMI	Fatal NMI	PLAT0242
09h	Deassert	Fatal NMI Recovered	Fatal NMI Recovered	PLAT0243
0Ah	Assert	Bus Fatal Error	Bus Fatal Error	PLAT0244
0Ah	Deassert	Bus Fatal Error	Bus Fatal Error Recovered	PLAT0245
0Bh	Assert	Bus Degraded	Bus Degraded	PLAT0246
0Bh	Deassert	Bus Degraded	Bus No Longer Degraded	PLAT0247

147 **5.12 Button/Switch Sensor**

148 Sensor Type: Button/Switch Sensor

149 Sensor Type Code: 14h

150 Reading Type: 6Fh

151

Table 12 – Button/Switch Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Power Button	Power Button Pressed	PLAT0248
00h	Deassert	Power Button	Power Button Released	PLAT0249
01h	Assert	Sleep Button	Sleep Button Pressed	PLAT0250
01h	Deassert	Sleep Button	Sleep Button Released	PLAT0251
02h	Assert	Reset Button	Reset Button Pressed	PLAT0252
02h	Deassert	Reset Button	Reset Button Released	PLAT0253
03h	Assert	FRU Latch	FRU Latch Opened	PLAT0254
03h	Deassert	FRU Latch	FRU Latch Closed	PLAT0255
04h	Assert	FRU Service Request	FRU Service Request	PLAT0256
04h	Deassert	FRU Service Request	FRU Service Request Completed	PLAT0257

152 5.13 Chip Set Sensor

153 Sensor Type: Chip Set Sensor

154 Sensor Type Code: 19h

155 Reading Type: 6Fh

156

Table 13 – Chip Set Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Soft Power Control Failure	Soft Power Control Failure	PLAT0258
00h	Deassert	Soft Power Control Failure Recovered	Software Power Control Recovered	PLAT0259

157 5.14 Cable/Interconnect Sensor

158 Sensor Type: Cable/Interconnect Sensor

159 Sensor Type Code: 1Bh

160 Reading Type: 6Fh

161 **Table 14 – Cable/Interconnect Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Connection	Cable Connected	PLAT0262
00h	Deassert	Connection	Cable Disconnected	PLAT0263
01h	Assert	Configuration Error	Interconnect Configuration Error	PLAT0266
01h	Deassert	Configuration Error	Interconnect Configuration Recovered	PLAT0267

162 **5.15 System Boot Initiated Sensor**

163 Sensor Type: System Boot Initiated Sensor

164 Sensor Type Code: 1Dh

165 Reading Type: 6Fh

166 **Table 15 – System Boot Initiated Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Power Up	Power On	PLAT0272
00h	Deassert	Power Up		N/A
01h	Assert	Hard Reset	Hard Reset	PLAT0274
01h	Deassert	Hard Reset		N/A
02h	Assert	Warm Reset	Warm Reset	PLAT0276
02h	Deassert	Warm Reset		N/A
03h	Assert	User Requested PXE Boot	PXE Boot Requested	PLAT0278
03h	Deassert	User Requested PXE Boot		N/A
04h	Assert	Automatic Boot to Diagnostic	Diagnostics Boot Requested	PLAT0280
04h	Deassert	Automatic Boot to Diagnostic		N/A
05h	Assert	OS/Run-Time Software Initiated Hard Reset	Power-cycle Hard	PLAT0274
05h	Deassert	OS/Run-Time Software Initiated Hard Reset		N/A

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
06h	Assert	OS/Run-Time Software Initiated Warm Reset	Power-cycle- Soft	PLAT0276
06h	Deassert	OS/Run-Time Software Initiated Warm Reset		N/A
07h	Assert	System Restart	System Restart Requested	PLAT0282
07h	Deassert	System Restart	N/A	N/A

167 5.16 Boot Error Sensor

168 Sensor Type: Boot Error Sensor

169 Sensor Type Code: 1Eh

170 Reading Type: 6Fh

171 **Table 16 – Boot Error Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	No Bootable Media	No Bootable Media	PLAT0286
00h	Deassert	No Bootable Media		N/A
01h	Assert	Non-bootable Diskette	non-bootable Diskette	PLAT0288
01h	Deassert	Non-bootable Diskette		N/A
02h	Assert	PXE Server Not Found	PXE Server Not Found	PLAT0290
02h	Deassert	PXE Server Not Found		N/A
03h	Assert	Invalid Boot Sector	Non-bootable Media	PLAT0288
03h	Deassert	Invalid Boot Sector		N/A
04h	Assert	Timeout Waiting for User to Select Boot Source	User-timeout on boot	PLAT0292
04h	Deassert	Timeout Waiting for User to Select Boot Source		N/A

172 **5.17 OS Boot Sensor**

173 Sensor Type: OS Boot Sensor

174 Sensor Type Code: 1Fh

175 Reading Type: 6Fh

176 **Table 17 – OS BOOT Sensor PET to Platform Message Registry Mapping**

Offset	Assert/Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	A: Boot Completed	Boot from floppy	PLAT0296
00h	Deassert	A: Boot Completed		N/A
01h	Assert	C: Boot Completed	Boot from local drive completed	PLAT0298
01h	Deassert	C: Boot Completed		N/A
02h	Assert	PXE Boot Completed	PXE Boot completed	PLAT0300
02h	Deassert	PXE Boot Completed		N/A
03h	Assert	Diagnostic Boot Completed	Diags Boot Completed	PLAT0302
03h	Deassert	Diagnostic Boot Completed		N/A
04h	Assert	CD-ROM Boot Completed	CD Boot Completed	PLAT0304
04h	Deassert	CD-ROM Boot Completed		N/A
05h	Assert	ROM Boot Completed	ROM Boot completed	PLAT0306
05h	Deassert	ROM Boot Completed		N/A
06h	Assert	Boot Completed	Boot Completed	PLAT0312
06h	Deassert	Boot Completed		N/A

177 **5.18 OS Stop/Shutdown Sensor**

178 Sensor Type: OS Stop/Shutdown Sensor

179 Sensor Type Code: 20h

180 Reading Type: 6Fh

181

Table 18 – OS Stop/Shutdown Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Critical Stop During OS Load	Critical Stop During OS Load	PLAT0320
00h	Deassert	Critical Stop During OS Load		N/A
01h	Assert	Run-time Critical Stop	Run-time Critical Stop	PLAT0322
01h	Deassert	Run-time Critical Stop		N/A
02h	Assert	OS Graceful Stop	OS Graceful Stop	PLAT0324
02h	Deassert	OS Graceful Stop		N/A
03h	Assert	OS Graceful Shutdown	OS Graceful Shutdown begun	PLAT0326
03h	Deassert	OS Graceful Shutdown	OS Graceful Shutdown completed	PLAT0327
04h	Assert	Soft Shutdown Initiated by PEF	OS Graceful Shutdown begun	PLAT0326
04h	Deassert	Soft Shutdown Initiated by PEF	OS Graceful Shutdown completed	PLAT0327
05h	Assert	Agent Not Responding	Agent Not Responding	PLAT0328
05h	Deassert	Agent Not Responding	Agent Responding	PLAT0329

182 5.19 Slot Sensor

183 Sensor Type: Slot Sensor

184 Sensor Type Code: 21h

185 Reading Type: 6Fh

186

Table 19 – Slot Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Fault Status	Fault	PLAT0330
00h	Deassert	Fault Status	Fault condition removed	PLAT0331

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
01h	Assert	Identify Status	Identify Enabled	PLAT0332
01h	Deassert	Identify Status	Identify Disabled	PLAT0333
02h	Assert	Installed	Installed	PLAT0334
02h	Deassert	Installed	Empty	PLAT0336
03h	Assert	Ready for Installation	Ready for Installation	PLAT0338
03h	Deassert	Ready for Installation		N/A
04h	Assert	Ready for Removal	Ready for Removal	PLAT0340
04h	Deassert	Ready for Removal		N/A
05h	Assert	Power is Off	Power is Off	PLAT0342
05h	Deassert	Power is Off	Power is On	PLAT0344
06h	Assert	Removal Requested	Removal Requested	PLAT0346
06h	Deassert	Removal Requested		N/A
07h	Assert	Interlock Active	Interlock Active	PLAT0348
07h	Deassert	Interlock Active	Interlock De- asserted	PLAT0349
08h	Assert	Slot Disabled	Slot Disabled	PLAT0350
08h	Deassert	Slot Disabled	Slot Enabled	PLAT0351
09h	Assert	Slot Holds Spare Device	Slot holds spare	PLAT0352
09h	Deassert	Slot Holds Spare Device	Slot no longer holds spare	PLAT0353

187 **5.20 System ACPI Power State Sensor**

188 Sensor Type: System ACPI Power State

189 Sensor Type Code: 22h

190 Reading Type: 6Fh

191 **Table 20 – System ACPI Power State Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	S0/G0	System Enabled	PLAT0354
00h	Deassert	S0/G0		N/A
01h	Assert	S1 State	Sleep – light	PLAT0356

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
01h	Deassert	S1 State		N/A
02h	Assert	S2 State	Sleep – light	PLAT0356
02h	Deassert	S2 State		N/A
03h	Assert	S3 State	Standby	PLAT0360
03h	Deassert	S3 State		N/A
04h	Assert	S4 State	Hibernate – off soft	PLAT0358
04h	Deassert	S4 State		N/A
05h	Assert	S5/G2 Soft- off	Soft – off	PLAT0362
05h	Deassert	S5/G2 Soft- off		N/A
06h	Assert	S4/S5 Soft- off	Soft – off	PLAT0362
06h	Deassert	S4/S5 Soft- off		N/A
07h	Assert	G3/Mechanic al Off	Hard – off	PLAT0364
07h	Deassert	G3/Mechanic al Off		N/A
08h	Assert	Sleeping in an S1	Sleep – light	PLAT0356
08h	Deassert	Sleeping in an S1		N/A
09h	Assert	G1 Sleeping	Sleep – G1	PLAT0366
09h	Deassert	G1 Sleeping		N/A
0Ah	Assert	S5 Entered by Override	Soft – off	PLAT0362
0Ah	Deassert	S5 Entered by Override		N/A
0Bh	Assert	Legacy ON	Power On	PLAT0272
0Bh	Deassert	Legacy ON		N/A
0Ch	Assert	Legacy OFF	Hard – off	PLAT0364
0Ch	Deassert	Legacy OFF		N/A

192 5.21 Watchdog 2 Sensor

193 Sensor Type: Watchdog 2 Sensor

194 Sensor Type Code: 23h

195 Reading Type: 6Fh

196

Table 21 – Watchdog 2 Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Timer Expired	Watchdog Timer Expired	PLAT0368
00h	Deassert	Timer Expired	Watchdog Timer Reset	PLAT0369
01h	Assert	Reboot	Reboot by Watchdog	PLAT0370
01h	Deassert	Reboot		N/A
02h	Assert	Power Off	Power off by Watchdog	PLAT0372
02h	Deassert	Power Off		N/A
03h	Assert	Power Cycle	Power Cycle by Watchdog	PLAT0374
03h	Deassert	Power Cycle		N/A
08h	Assert	Timer Interrupt	Watchdog Timer interrupt occurred	PLAT0376
08h	Deassert	Timer Interrupt		N/A

197 **5.22 Platform Alert Sensor**

198 Sensor Type: Platform Alert Sensor

199 Sensor Type Code: 24h

200 Reading Type: 6Fh

201

Table 22 – Platform Alert Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Generated Page	Generated Page Alert	PLAT0378
00h	Deassert	Generated Page		N/A
01h	Assert	Generated LAN Alert	Generated LAN Alert	PLAT0380
01h	Deassert	Generated LAN Alert		N/A
02h	Assert	Generated Event Trap	Generated Event Trap	PLAT0382
02h	Deassert	Generated Event Trap		N/A
03h	Assert	Generated SNMP Trap	Generated SNMP Trap	PLAT0384

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
03h	Deassert	Generated SNMP Trap		N/A

202 5.23 Entity Presence Sensor

203 Sensor Type: Entity Presence Sensor

204 Sensor Type Code: 25h

205 Reading Type: 6Fh

206 **Table 23 – Entity Presence Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry ID
00h	Assert	Presence	Present	PLAT0390
00h	Deassert	Presence	Absent	PLAT0392
01h	Assert	Absent	Absent	PLAT0392
01h	Deassert	Absent	Present	PLAT0390
02h	Assert	Disable	Disabled	PLAT0394
02h	Deassert	Disable	Enabled	PLAT0395

207 5.24 LAN Sensor

208 Sensor Type: LAN Sensor

209 Sensor Type Code: 27h

210 Reading Type: 6Fh

211 **Table 24 – LAN Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	LAN Heartbeat Lost	LAN Heartbeat Lost	PLAT0396
00h	Deassert	LAN Heartbeat Lost	LAN Heartbeat Detected	PLAT0397
01h	Assert	LAN Heartbeat	LAN Heartbeat Detected	PLAT0397
01h	Deassert	LAN Heartbeat	LAN Heartbeat Lost	PLAT0396

212 **5.25 Management Subsystem Health Sensor**

213 Sensor Type: Management Subsystem Health Sensor

214 Sensor Type Code: 28h

215 Reading Type: 6Fh

216 **Table 25 – Management Subsystem Health Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Sensor Access Degraded/Unavailable	Sensor Unavailable or degraded	PLAT0398
00h	Deassert	Sensor Access Degraded/Unavailable	Sensor returned from degraded/unavailable	PLAT0399
01h	Assert	Controller Access Degraded/Unavailable	Controller unavailable or degraded	PLAT0400
01h	Deassert	Controller Access Degraded/Unavailable	Controller returned from degraded/unavailable	PLAT0401
02h	Assert	Management Controller Off-line	Management Controller Off-line	PLAT0402
02h	Deassert	Management Controller Off-line	Management Controller Enabled	PLAT0405
03h	Assert	Management Controller Unavailable	Management Controller Disabled	PLAT0404
03h	Deassert	Management Controller Unavailable	Management Controller Enabled	PLAT0405
04h	Assert	Sensor Failure	Sensor Failed	PLAT0406
04h	Deassert	Sensor Failure	Sensor returned from degraded/unavailable /failure	PLAT0399
05h	Assert	FRU Failure	FRU Failed	PLAT0408
05h	Deassert	FRU Failure	FRU Recovered	PLAT0409

217 **5.26 Battery Sensor**

218 Sensor Type: Battery Sensor

219 Sensor Type Code: 29h

220 Reading Type: 6Fh

221 **Table 26 – Battery Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Is Low	Battery level is critically low	PLAT0424
00h	Deassert	Is Low	Battery level no longer critically low	PLAT0427

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
01h	Assert	Failed	Battery Failed	PLAT0432
01h	Deassert	Failed	Battery Recovered	PLAT0433
02h	Assert	Presence	Battery Added	PLAT0431
02h	Deassert	Presence	Battery Removed	PLAT0430

222

223 5.27 Session Audit Sensor

224 Sensor Type: Session Audit Sensor

225 Sensor Type Code: 2Ah

226 Reading Type: 6Fh

227

Table 27 – Session Audit Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Session Activation	Session Audit activated	PLAT0435
00h	Deassert	Session Activation	Session Audit Deactivated	PLAT0434
01h	Assert	Session Deactivation	Session Audit Deactivated	PLAT0434
01h	Deassert	Session Deactivation	Session Audit activated	PLAT0435

228 5.28 Version Change Sensor

229 Sensor Type: Version Change Sensor

230 Sensor Type Code: 2Bh

231 Reading Type: 6Fh

232

Table 28 – Version Change Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Hardware Changed	Hardware Changed	PLAT0436
00h	Deassert	Hardware Changed		N/A
01h	Assert	Firmware or Software Changed	Firmware or Software Changed	PLAT0438
01h	Deassert	Firmware or Software Changed		N/A

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
02h	Assert	Hardware Incompatibility	Hardware Incompatibility	PLAT0440
02h	Deassert	Hardware Incompatibility	Hardware Compatible	PLAT0441
03h	Assert	Firmware or Software Incompatibility	Firmware or Software Incompatibility	PLAT0442
03h	Deassert	Firmware or Software Incompatibility	Firmware and Software Compatible	PLAT0443
04h	Assert	Invalid/Unsupported Hardware Version	Invalid/Unsupported Hardware Version	PLAT0444
04h	Deassert	Invalid/Unsupported Hardware Version	Valid/Supported Hardware Version	PLAT0445
05h	Assert	Invalid/Unsupported Firmware/Software Version	Invalid/Unsupported Firmware/Software Version	PLAT0446
05h	Deassert	Invalid/Unsupported Firmware/Software Version	Valid/Supported Firmware/Software Version	PLAT0447
06h	Assert	Successful Hardware Change	Successful Hardware Change	PLAT0448
06h	Deassert	Successful Hardware Change		N/A
07h	Assert	Successful Software or F/W Change	Successful Software or Firmware Change	PLAT0450
07h	Deassert	Successful Software or F/W Change		N/A

233 **5.29 FRU State Sensor**

234 Sensor Type: FRU State Sensor

235 Sensor Type Code: 2Ch

236 Reading Type: 6Fh

237 **Table 29 – FRU State Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Not Installed	FRU not installed	PLAT0464
00h	Deassert	Not Installed	FRU installed	PLAT0465
01h	Assert	Inactive (in standby or 'hot spare' state)	FRU inactive	PLAT0471
01h	Deassert	Inactive (in standby or 'hot spare' state)		N/A
02h	Assert	Activation Request	FRU activation requested	PLAT0466

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
02h	Deassert	Activation Request		N/A
03h	Assert	Activation in Progress	FRU activation in progress	PLAT0468
03h	Deassert	Activation in Progress		N/A
04h	Assert	Active	FRU active	PLAT0467
04h	Deassert	Active		N/A
05h	Assert	Deactivation Request	FRU deactivation requested	PLAT0470
05h	Deassert	Deactivation Request		N/A
06h	Assert	Deactivation in Progress	FRU deactivation in progress	PLAT0472
06h	Deassert	Deactivation in Progress		N/A
07h	Assert	Communication Lost	FRU communication lost	PLAT0474
07h	Deassert	Communication Lost		N/A

238 5.30 Type 1 (Numeric/Threshold) Sensor

239 Sensor Type: Type 1 (Numeric/Threshold) Sensor

240 Sensor Type Code: 01h

241 Reading Type: 01-0Ch

242 **Table 30 – Type 1 (Numeric/Threshold) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Lower Non- critical – going low asserted	Lower Non- critical sensor going low asserted	PLAT0476
00h	Deassert	Lower Non- critical – going low deasserted	Lower Non- critical sensor going low deasserted	PLAT0477
01h	Assert	Lower Non- critical – going high asserted	Lower Non- critical sensor going high asserted	PLAT0478
01h	Deassert	Lower Non- critical – going high deasserted	Lower Non- critical sensor going high deasserted	PLAT0479

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
02h	Assert	Lower Critical – going low asserted	Lower Critical sensor going low asserted	PLAT0480
02h	Deassert	Lower Critical – going low deasserted	Lower Critical sensor going low deasserted	PLAT0481
03h	Assert	Lower Critical – going high asserted	Lower Critical sensor going high asserted	PLAT0482
03h	Deassert	Lower Critical – going high deasserted	Lower Critical sensor going high deasserted	PLAT0483
04h	Assert	Lower Non-recoverable – going low asserted	Lower Non-recoverable sensor going low asserted	PLAT0484
04h	Deassert	Lower Non-recoverable – going low deasserted	Lower Non-recoverable sensor going low deasserted	PLAT0485
05h	Assert	Lower Non-recoverable – going high asserted	Lower Non-recoverable sensor going high asserted	PLAT0486
05h	Deassert	Lower Non-recoverable – going high deasserted	Lower Non-recoverable sensor going high deasserted	PLAT0487
06h	Assert	Upper Non-critical – going low asserted	Upper Non-critical sensor going low asserted	PLAT0488
06h	Deassert	Upper Non-critical – going low deasserted	Upper Non-critical sensor going low deasserted	PLAT0489
07h	Assert	Upper Non-critical – going high asserted	Upper Non-critical sensor going high asserted	PLAT0490
07h	Deassert	Upper Non-critical – going high deasserted	Upper Non-critical sensor going high deasserted	PLAT0491
08h	Assert	Upper Critical – going low asserted	Upper Critical sensor going low asserted	PLAT0492
08h	Deassert	Upper Critical – going low deasserted	Upper Critical sensor going low deasserted	PLAT0493

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
09h	Assert	Upper Critical – going high asserted	Upper Critical sensor going high asserted	PLAT0494
09h	Deassert	Upper Critical – going high deasserted	Upper Critical sensor going high deasserted	PLAT0495
0Ah	Assert	Upper Non- recoverable – going low asserted	Upper Non- recoverable sensor going low asserted	PLAT0496
0Ah	Deassert	Upper Non- recoverable – going low deasserted	Upper Non- recoverable sensor going low deasserted	PLAT0497
0Bh	Assert	Upper Non- recoverable – going high asserted	Upper Non- recoverable sensor going high asserted	PLAT0498
0Bh	Deassert	Upper Non- recoverable – going high deasserted	Upper Non- recoverable sensor going high deasserted	PLAT0499

243 5.31 Type 2 (Discrete) Sensor

244 Sensor Type: Type 2 (Discrete) Sensor

245 Sensor Type Code: 02h

246 Reading Type: 01-0Ch

247

248 **Table 31 – Type 2 (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Transition to idle	Sensor transition to idle	PLAT0500
00h	Deassert	Transition to idle		N/A
01h	Assert	Transition to active	Sensor transition to active	PLAT0502
01h	Deassert	Transition to active		N/A
02h	Assert	Transition to busy	Sensor transition to busy	PLAT0504

249 **5.32 Type 3 (Discrete) Sensor**

250 Sensor Type: Type 3 (Discrete) Sensor

251 Sensor Type Code: 03h

252 Reading Type: 01-0Ch

253

254 **Table 32 – Type 3 (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	State deasserted	Sensor state deasserted	PLAT0509
00h	Deassert	State deasserted	Sensor state asserted	PLAT0508
01h	Assert	State asserted	Sensor state asserted	PLAT0508
01h	Deassert	State asserted	Sensor state deasserted	PLAT0509

255 **5.33 Type 4 (Discrete) Sensor**

256 Sensor Type: Type 4 (Discrete) Sensor

257 Sensor Type Code: 04h

258 Reading Type: 01-0Ch

259

260 **Table 33 – Type 4 (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Predictive failure deasserted	Sensor predictive failure deasserted	PLAT0511
00h	Deassert	Predictive failure deasserted	Sensor predictive failure asserted	PLAT0512
01h	Assert	Predictive failure asserted	Sensor predictive failure asserted	PLAT0512
01h	Deassert	Predictive failure asserted	Sensor predictive failure deasserted	PLAT0511

261 **5.34 Type 5 (Discrete) Sensor**

262 Sensor Type: Type 5 (Discrete) Sensor

263 Sensor Type Code: 05h

264 Reading Type: 01-0Ch

265 **Table 34 – Type 5 (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Limit not exceeded	Sensor limit not exceeded	PLAT0513
00h	Deassert	Limit not exceeded	Sensor limit exceeded	PLAT0512
01h	Assert	Limit exceeded	Sensor limit exceeded	PLAT0512
01h	Deassert	Limit exceeded	Sensor limit not exceeded	PLAT0513

266 **5.35 Type 6 (Discrete) Sensor**

267 Sensor Type: Type 6 (Discrete) Sensor

268 Sensor Type Code: 06h

269 Reading Type: 01-0Ch

270 **Table 35 – Type 6 (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Performance met	Sensor performance met	PLAT0514
00h	Deassert	Performance met	Sensor performance lags	PLAT0516
01h	Assert	Performance lags	Sensor performance lags	PLAT0516
01h	Deassert	Performance lags	Sensor performance met	PLAT0514

271 **5.36 Type 7 (Discrete) Sensor**

272 Sensor Type: Type 7 (Discrete) Sensor

273 Sensor Type Code: 07h

274 Reading Type: 01-0Ch

275

276

Table 36 – Type 7 (Discrete) Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Transition to OK asserted	Sensor transition to OK asserted	PLAT0518
00h	Deassert	Transition to OK deasserted		N/A
01h	Assert	Transition to non-critical from OK asserted	Sensor transition to non-critical from OK asserted	PLAT0520
01h	Deassert	Transition to non-critical from OK deasserted	Sensor transition to non-critical from OK deasserted	PLAT0521
02h	Assert	Transition to critical from less severe asserted	Sensor transition to critical from less severe asserted	PLAT0522
02h	Deassert	Transition to critical from less severe deasserted	Sensor transition to critical from less severe deasserted	PLAT0523
03h	Assert	Transition to non- recoverable from less severe asserted	Sensor transition to non- recoverable from less severe asserted	PLAT0524
03h	Deassert	Transition to non- recoverable from less severe deasserted	Sensor transition to non- recoverable from less severe deasserted	PLAT0525
04h	Assert	Transition to non-critical from more severe asserted	Sensor transition to non-critical from more severe asserted	PLAT0526
04h	Deassert	Transition to non-critical from more severe deasserted	Sensor transition to non-critical from more severe deasserted	N/A

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
05h	Assert	Transition to critical from Non-recoverable asserted	Sensor transition to critical from Non-recoverable asserted	PLAT0528
05h	Deassert	Transition to critical from Non-recoverable deasserted	Sensor transition to critical from Non-recoverable deasserted	N/A
06h	Assert	Transition to non-recoverable asserted	Sensor transition to non-recoverable asserted	PLAT0530
06h	Deassert	Transition to non-recoverable deasserted	Sensor transition to Non-recoverable deasserted	PLAT0531
07h	Assert	Monitor	Sensor monitor	PLAT0532
07h	Deassert	Monitor		N/A
08h	Assert	Informational	Sensor informational	PLAT0534
08h	Deassert	Informational		N/A

277 5.37 Type 8 (Discrete) Sensor

278 Sensor Type: Type 8 (Discrete) Sensor

279 Sensor Type Code: 08h

280 Reading Type: 01-0Ch

281 **Table 37 – Type 8 (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Device removed	Device removed	PLAT0537
00h	Deassert	Device removed		N/A
01h	Assert	Device inserted	Device inserted	PLAT0536
01h	Deassert	Device inserted		N/A

282 **5.38 Type 9 (Discrete) Sensor**

283 Sensor Type: Type 9 (Discrete) Sensor

284 Sensor Type Code: 09h

285 Reading Type: 01-0Ch

286 **Table 38 – Type 9 (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Device disabled	Device disabled	PLAT0539
00h	Deassert	Device disabled		N/A
01h	Assert	Device enabled	Device enabled	PLAT0538
01h	Deassert	Device enabled		N/A

287 **5.39 Type A (Discrete) Sensor**

288 Sensor Type: Type A (Discrete) Sensor

289 Sensor Type Code: 0Ah

290 Reading Type: 01-0Ch

291 **Table 39 – Type A (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Transitioned to running	Sensor transitioned to running	PLAT0540
00h	Deassert	Transitioned to running		N/A
01h	Assert	Transitioned to in-test	Sensor transitioned to in-test	PLAT0542
01h	Deassert	Transitioned to in-test		N/A
02h	Assert	Transitioned to power off	Sensor transitioned to power off	PLAT0544
02h	Deassert	Transitioned to power off		N/A
03h	Assert	Transitioned to on-line	Sensor transitioned to on-line	PLAT0546

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
03h	Deassert	Transitioned to on-line		N/A
04h	Assert	Transitioned to off-line	Sensor transitioned to off-line	PLAT0548
04h	Deassert	Transitioned to off-line		N/A
05h	Assert	Transitioned to off-duty	Sensor transitioned to off-duty	PLAT0550
05h	Deassert	Transitioned to off-duty		N/A
06h	Assert	Transitioned to a degraded state	Sensor transitioned to a degraded state	PLAT0552
06h	Deassert	Transitioned to a degraded state		N/A
07h	Assert	Transitioned to power save state	Sensor transitioned to power save state	PLAT0554
07h	Deassert	Transitioned to power save state		N/A
08h	Assert	Install error	Sensor install error	PLAT0556
08h	Deassert	Install error		PLAT0557

292 5.40 Type B (Redundant) Sensor

293 Sensor Type: Type B (Redundant) Sensor

294 Sensor Type Code: 0Bh

295 Reading Type: 01-0Ch

296

297

Table 40 – Type B (Redundant) Sensor PET to Platform Message Registry Mapping

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	Fully redundant	Fully Redundant	PLAT0561
00h	Deassert	Fully redundant		N/A
01h	Assert	Redundancy lost asserted	Redundancy Lost asserted	PLAT0802
01h	Deassert	Redundancy lost deasserted	Redundancy Lost deasserted	PLAT0803
02h	Assert	Redundancy degraded asserted	Redundancy Degraded asserted	PLAT0804
02h	Deassert	Redundancy degraded deasserted	Redundancy Degraded deasserted	PLAT0805
03h	Assert	Non- redundant: sufficient from redundant asserted	Non- Redundant: Sufficient Resources from Degraded or Full Redundant asserted	PLAT0806
03h	Deassert	Non- redundant: sufficient from redundant deasserted	Non- Redundant: Sufficient Resources from Degraded or Full Redundant asserted	PLAT0807
04h	Assert	Non- redundant: sufficient from insufficient asserted	Non- redundant: Sufficient Resources from Insufficient Resources asserted	PLAT0808
04h	Deassert	Non- redundant: sufficient from insufficient deasserted	Non- redundant: Sufficient Resources from Insufficient Resources deasserted	PLAT0809
05h	Assert	Non- redundant: insufficient	Non- redundant: Insufficient	PLAT0810

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
		asserted	Resources asserted	
05h	Deassert	Non- redundant: insufficient asserted	Non- redundant: Insufficient Resources deasserted	PLAT0811
06h	Assert	Redundancy degraded from fully redundant asserted	Redundancy Degraded from Fully Redundant asserted	PLAT0812
06h	Deassert	Redundancy degraded from fully redundant deasserted	Redundancy Degraded from Fully Redundant deasserted	PLAT0813
07h	Assert	Redundancy degraded from non- redundant asserted	Redundancy Degraded from Non- redundant asserted	PLAT0814
07h	Deassert	Redundancy degraded from non- redundant deasserted	Redundancy Degraded from Non- redundant deasserted	PLAT0815

298 5.41 Type C (Discrete) Sensor

299 Sensor Type: Type C (Discrete) Sensor

300 Sensor Type Code: 0Ch

301 Reading Type: 01-0Ch

302 **Table 41 – Type C (Discrete) Sensor PET to Platform Message Registry Mapping**

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
00h	Assert	D0 power state	Sensor indicates device transitioned to D0 power state	PLAT0562
00h	Deassert	D0 power state		N/A
01h	Assert	D1 power state	Sensor indicates device transitioned to D1 power state	PLAT0564

Offset	Assert/ Deassert	Event Message Label	Use Case	Platform Message Registry MessageID
01h	Deassert	D1 power state		N/A
02h	Assert	D2 power state	Sensor indicates device transitioned to D2 power state	PLAT0566
02h	Deassert	D2 power state		N/A
03h	Assert	D3 power state	Sensor indicates device transitioned to D3 power state	PLAT0568
03h	Deassert	D3 power state		N/A

303

304

305
306
307
308

ANNEX A (informative)

Change Log

Version	Date	Description
1.0.0	2009/05/13	DMTF Standard Release
1.1.0	2009/11/02	<p>Added mappings for many of the Deassertions. Updated the Type B (Redundant) Sensor. Added PET definition and normative references to the IPMI and ASF specifications.</p> <p>Updated description in section 5 and using full Message ID in "Platform Message Registry ID" column in the tables. Renamed columns to "Platform Message Registry MessageID" to more clearly define what it means.</p> <p>Updated reference to DSP8007 to list a resolvable URL to the version of the registry that is referenced. The version 1.1. URL was used: http://schemas.dmtf.org/wbem/messageregistry/1/dsp8007_1.1.xml</p> <p>Put all 1.1.0 change log in one row.</p> <p>Add Acronyms for: ASF, CIM, IPMI, DASH and SMASH</p> <p>Remove the references DSP0004,DSP1001, and DSP1054. Also statement referring to DSP1001.</p> <p>Remove subclass headers subclauses 2.1 (Approved References) and 2.2 (Other References) and all the references just go under 2 Normative References.</p>

309
310