



**Document Identifier: DSP0266**

**Date: 2021-01-18**

**Version: 1.12.0**

# Redfish Specification

**Supersedes: 1.9.1**

**Document Class: Normative**

**Document Status: Published**

**Document Language: en-US**

#### Copyright Notice

Copyright © 2015-2021 DMTF. All rights reserved.

DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability. Members and non-members may reproduce DMTF specifications and documents, provided that correct attribution is given. As DMTF specifications may be revised from time to time, the particular version and release date should always be noted.

Implementation of certain elements of this standard or proposed standard may be subject to third party patent rights, including provisional patent rights (herein "patent rights"). DMTF makes no representations to users of the standard as to the existence of such rights, and is not responsible to recognize, disclose, or identify any or all such third party patent right, owners or claimants, nor for any incomplete or inaccurate identification or disclosure of such rights, owners or claimants. DMTF shall have no liability to any party, in any manner or circumstance, under any legal theory whatsoever, for failure to recognize, disclose, or identify any such third party patent rights, or for such party's reliance on the standard or incorporation thereof in its product, protocols or testing procedures. DMTF shall have no liability to any party implementing such standard, whether such implementation is foreseeable or not, nor to any patent owner or claimant, and shall have no liability or responsibility for costs or losses incurred if a standard is withdrawn or modified after publication, and shall be indemnified and held harmless by any party implementing the standard from any and all claims of infringement by a patent owner for such implementations.

For information about patents held by third-parties which have notified the DMTF that, in their opinion, such patent may relate to or impact implementations of DMTF standards, visit <http://www.dmtf.org/about/policies/disclosures.php>.

This document's normative language is English. Translation into other languages is permitted.

## CONTENTS

1 Foreword	10
1.1 Acknowledgments	10
2 Abstract	12
3 Normative references	13
4 Terms and definitions	15
5 Symbols and abbreviated terms	18
6 Overview	19
6.1 Scope	19
6.2 Goals	19
6.3 Design tenets	20
6.4 Limitations	20
6.5 Additional design background and rationale	21
6.5.1 REST-based interface	21
6.5.2 Data-oriented	21
6.5.3 Separation of protocol from data model	21
6.5.4 Hypermedia API Service Root	22
6.5.5 OpenAPI v3.0 support	22
6.5.6 OData conventions	22
6.6 Service elements	22
6.6.1 Synchronous and asynchronous operation support	22
6.6.2 Eventing mechanism	22
6.6.3 Actions	23
6.6.4 Service discovery	23
6.6.5 Remote access support	23
6.7 Security	23
7 Protocol details	25
7.1 Universal Resource Identifiers	25
7.2 HTTP methods	27
7.3 HTTP redirect	28
7.4 Media types	28
7.5 ETags	28
7.6 Protocol version	29
7.7 Redfish-defined URIs and relative reference rules	30
8 Service requests	32
8.1 Request headers	32
8.2 GET (read requests)	35
8.2.1 Resource collection requests	36
8.2.2 Service Root request	36
8.2.3 OData service and metadata document requests	37
8.3 Query parameters	37
8.3.1 The \$expand query parameter	39

8.3.2	The \$select query parameter	42
8.3.3	The \$filter query parameter	43
8.4	HEAD	44
8.4.1	Data modification requests	44
8.4.2	Modification success responses	45
8.4.3	Modification error responses	45
8.5	PATCH (update)	45
8.6	PATCH on array properties	47
8.7	PUT (replace)	48
8.8	POST (create)	48
8.9	DELETE (delete)	49
8.10	POST (Action)	49
8.11	Operation apply time	52
8.12	Deep operations	54
9	Service responses	59
9.1	Response headers	59
9.2	Link header	61
9.3	Status codes	61
9.4	OData metadata responses	64
9.4.1	OData \$metadata	64
9.4.1.1	Referencing other schemas	64
9.4.1.2	Referencing OEM extensions	65
9.4.2	OData service document	16
9.5	Resource responses	66
9.6	Error responses	66
10	Data model	69
10.1	Resources	69
10.2	Resource collections	69
10.3	OEM resources	70
10.4	Common data types	70
10.4.1	Primitive types	70
10.4.2	Empty string values	71
10.4.3	GUID and UUID values	71
10.4.4	Date-Time values	71
10.4.5	Duration values	72
10.4.6	Reference properties	73
10.4.7	Non-resource reference properties	73
10.4.8	Array properties	73
10.4.9	Structured properties	74
10.4.10	Message object	75
10.4.10.1	Overview	75
10.4.10.2	MessageId format	76
10.5	Properties	76

- 10.5.1 Resource identifier (@odata.id) property . . . . . 77
- 10.5.2 Resource type (@odata.type) property . . . . . 77
- 10.5.3 Resource ETag (@odata.etag) property . . . . . 78
- 10.5.4 Resource context (@odata.context) property . . . . . 78
- 10.5.5 Id . . . . . 78
- 10.5.6 Name . . . . . 78
- 10.5.7 Description . . . . . 79
- 10.5.8 MemberId . . . . . 79
- 10.5.9 Count (Members@odata.count) property . . . . . 79
- 10.5.10 Members . . . . . 79
- 10.5.11 Next link (Members@odata.nextLink) property . . . . . 79
- 10.5.12 Links . . . . . 80
  - 10.5.12.1 Reference to a related resource . . . . . 80
  - 10.5.12.2 References to multiple related resources . . . . . 80
- 10.5.13 Actions property . . . . . 81
  - 10.5.13.1 Action representation . . . . . 81
  - 10.5.13.2 Action responses . . . . . 82
- 10.5.14 Oem . . . . . 82
- 10.5.15 Status . . . . . 82
- 10.6 Resource, schema, property, and URI naming conventions . . . . . 83
- 10.7 Extending standard resources . . . . . 84
  - 10.7.1 OEM property format and content . . . . . 84
  - 10.7.2 OEM property naming . . . . . 85
  - 10.7.3 OEM resource naming and URIs . . . . . 86
  - 10.7.4 OEM property examples . . . . . 86
  - 10.7.5 OEM actions . . . . . 87
- 10.8 Payload annotations . . . . . 88
  - 10.8.1 Allowable values . . . . . 89
  - 10.8.2 Extended information . . . . . 89
    - 10.8.2.1 Extended object information . . . . . 89
    - 10.8.2.2 Extended property information . . . . . 90
  - 10.8.3 Action info annotation . . . . . 91
  - 10.8.4 Settings and settings apply time annotations . . . . . 92
  - 10.8.5 Operation apply time and operation apply time support annotations . . . . . 92
  - 10.8.6 Maintenance window annotation . . . . . 92
  - 10.8.7 Collection capabilities annotation . . . . . 92
  - 10.8.8 Requested count and allow over-provisioning annotations . . . . . 94
  - 10.8.9 Zone affinity annotation . . . . . 95
  - 10.8.10 Supported certificates annotation . . . . . 95
  - 10.8.11 Deprecated annotation . . . . . 96
- 10.9 Settings resource . . . . . 96
- 10.10 Special resource situations . . . . . 98
  - 10.10.1 Overview . . . . . 98

10.10.2	Absent resources	98
10.11	Registries	99
10.12	Schema annotations	99
10.12.1	Description annotation	100
10.12.2	Long description annotation	100
10.12.3	Resource capabilities annotation	100
10.12.4	Resource URI patterns annotation	101
10.12.5	Additional properties annotation	102
10.12.6	Permissions annotation	102
10.12.7	Required annotation	102
10.12.8	Required on create annotation	102
10.12.9	Units of measure annotation	102
10.12.10	Expanded resource annotation	102
10.12.11	Owning entity annotation	103
10.12.12	Deprecated annotation	103
10.13	Versioning	103
10.14	Localization	104
11	File naming and publication	105
11.1	Registry file naming	105
11.2	Profile file naming	105
11.3	Dictionary file naming	105
11.4	Localized file naming	105
11.5	DMTF Redfish file repository	106
12	Schema definition languages	108
12.1	OData Common Schema Definition Language	108
12.1.1	File naming conventions for CSDL	108
12.1.2	Core CSDL files	108
12.1.3	CSDL format	108
12.1.3.1	Referencing other CSDL files	109
12.1.3.2	CSDL data services	110
12.1.4	Elements of CSDL namespaces	110
12.1.4.1	Qualified names	110
12.1.4.2	Entity type and complex type elements	111
12.1.4.3	Action element	111
12.1.4.3.1	Action element for OEM actions	112
12.1.4.3.2	Action with a response body	113
12.1.4.4	Property element	113
12.1.4.5	Navigation property element	114
12.1.4.6	Enum type element	115
12.1.4.7	Annotation element	116
12.2	JSON Schema	118
12.2.1	File naming conventions for JSON Schema	118
12.2.2	Core JSON Schema files	119

- 12.2.3 JSON Schema format . . . . . 119
- 12.2.4 JSON Schema definitions body . . . . . 119
  - 12.2.4.1 Resource definitions in JSON Schema . . . . . 120
  - 12.2.4.2 Enumerations in JSON Schema . . . . . 121
  - 12.2.4.3 Actions in JSON Schema . . . . . 121
    - 12.2.4.3.1 OEM actions in JSON Schema . . . . . 123
    - 12.2.4.3.2 Action with a response body . . . . . 123
- 12.2.5 JSON Schema terms . . . . . 124
- 12.3 OpenAPI . . . . . 125
  - 12.3.1 File naming conventions for OpenAPI schema . . . . . 125
  - 12.3.2 Core OpenAPI schema files . . . . . 126
  - 12.3.3 openapi.yaml . . . . . 126
  - 12.3.4 OpenAPI file format . . . . . 128
  - 12.3.5 OpenAPI components body . . . . . 128
    - 12.3.5.1 Resource definitions in OpenAPI . . . . . 128
    - 12.3.5.2 Enumerations in OpenAPI . . . . . 129
    - 12.3.5.3 Actions in OpenAPI . . . . . 130
      - 12.3.5.3.1 OEM actions in OpenAPI . . . . . 131
  - 12.3.6 OpenAPI terms used by Redfish . . . . . 131
- 12.4 Schema modification rules . . . . . 132
- 13 Service details . . . . . 133
  - 13.1 Eventing . . . . . 133
    - 13.1.1 POST to subscription collection . . . . . 133
    - 13.1.2 Open an SSE connection . . . . . 134
    - 13.1.3 EventType-based eventing . . . . . 134
    - 13.1.4 Subscribing to events . . . . . 135
    - 13.1.5 Event formats . . . . . 136
    - 13.1.6 OEM extensions . . . . . 137
  - 13.2 Asynchronous operations . . . . . 137
  - 13.3 Resource tree stability . . . . . 139
  - 13.4 Discovery . . . . . 139
    - 13.4.1 UPnP compatibility . . . . . 140
    - 13.4.2 USN format . . . . . 140
    - 13.4.3 M-SEARCH response . . . . . 140
    - 13.4.4 Notify, alive, and shutdown messages . . . . . 141
  - 13.5 Server-Sent Events . . . . . 141
    - 13.5.1 General . . . . . 141
    - 13.5.2 Event service . . . . . 142
      - 13.5.2.1 Event message SSE stream . . . . . 144
      - 13.5.2.2 Metric report SSE stream . . . . . 145
  - 13.6 Update Service . . . . . 146
    - 13.6.1 Overview . . . . . 146
    - 13.6.2 Software update types . . . . . 146

13.6.2.1	Simple updates	146
13.6.2.2	Multipart HTTP push updates	146
14	Security details	149
14.1	Transport Layer Security (TLS) protocol	149
14.1.1	Cipher suites	149
14.1.2	Certificates	150
14.2	Sensitive data	150
14.3	Authentication	150
14.3.1	Authentication requirements	151
14.3.1.1	Resource and operation authentication requirements	151
14.3.1.2	HTTP header authentication requirements	151
14.3.1.3	Authentication failure requirements	151
14.3.2	HTTP Basic authentication	151
14.3.3	Redfish session login authentication	152
14.3.3.1	Redfish login sessions	152
14.3.3.2	Session login	152
14.3.3.3	Session lifetime	154
14.3.3.4	Session termination or logout	154
14.4	Authorization	154
14.4.1	Privilege model	155
14.4.1.1	Roles	155
14.4.1.2	Restricted roles and restricted privileges	156
14.4.1.3	OEM privileges	156
14.4.2	Redfish service operation-to-privilege mapping	157
14.4.2.1	Why specify operation-to-privilege mapping?	157
14.4.2.2	Representing operation-to-privilege mappings	157
14.4.2.3	Operation map syntax	158
14.4.2.4	Mapping overrides syntax	159
14.4.2.5	Property override example	159
14.4.2.6	Subordinate override	161
14.4.2.7	Resource URI override	162
14.4.2.8	Privilege AND and OR syntax	164
14.5	Account service	164
14.5.1	Password management	165
14.5.2	Password change required handling	165
14.6	Asynchronous tasks	165
14.7	Event subscriptions	166
15	Redfish Host Interface	167
16	Redfish Composability	168
16.1	Composition requests	168
16.1.1	Specific composition	168
16.1.2	Constrained composition	169
16.1.3	Expandable resources	171



- 16.2 Updating a composed resource . . . . . 171
- 17 Aggregation . . . . . 172
  - 17.1 Classes of aggregators . . . . . 172
    - 17.1.1 Use cases . . . . . 172
  - 17.2 Aggregation service . . . . . 173
    - 17.2.1 Aggregator requirements . . . . . 173
      - 17.2.1.1 Aggregates . . . . . 174
    - 17.2.2 Aggregation sources and connection methods . . . . . 174
- 18 ANNEX A (informative) Change log . . . . . 175

# 1 Foreword

---

The Redfish Forum of the DMTF develops the Redfish standard.

DMTF is a not-for-profit association of industry members that promotes enterprise and systems management and interoperability. For information about the DMTF, see [DMTF](#).

## 1.1 Acknowledgments

---

The DMTF acknowledges the following individuals for their contributions to the Redfish standard, including this document and Redfish schemas, interoperability profiles, and Message Registries:

- Rafiq Ahamed - Hewlett Packard Enterprise
- Richelle Ahlvers - Broadcom Inc.
- Jeff Autor - Hewlett Packard Enterprise
- David Black - Dell Inc.
- Jeff Bobzin - Insyde Software Corp.
- Patrick Boyd - Dell Inc.
- David Brockhaus - Vertiv
- Richard Brunner - VMware Inc.
- Sean Byland - Cray Inc.
- Lee Calcote - Seagate Technology
- Keith Campbell - Lenovo
- P Chandrasekhar - Dell Inc.
- Barbara Craig - Hewlett Packard Enterprise
- Chris Davenport - Hewlett Packard Enterprise
- Gamma Dean - Vertiv
- Daniel Dufresne - Dell Inc.
- Samer El-Haj-Mahmoud - Arm Limited, Lenovo, Hewlett Packard Enterprise
- George Ericson - Dell Inc.
- Wassim Fayed - Microsoft Corporation
- Kevin Ferguson - Vertiv
- Mike Garrett - Hewlett Packard Enterprise
- Steve Geffin - Vertiv
- Joe Handzik - Hewlett Packard Enterprise
- Jon Hass - Dell Inc.
- Jeff Hilland - Hewlett Packard Enterprise
- Chris Hoffman - Vertiv

- Cactus Jiang - Vertiv
- Barry Kittner - Intel Corporation
- Steven Krig - Intel Corporation
- Jennifer Lee - Intel Corporation
- John Leung - Intel Corporation
- Magnus Lundmark - Ericsson AB
- Steve Lyle - Hewlett Packard Enterprise
- Gunnar Mills - IBM
- Jagan Molleti - Dell Inc.
- Milena Natanov - Microsoft Corporation
- Scott Phuong - Cisco Systems, Inc.
- Michael Pizzo - Microsoft Corporation
- Chris Poblete - Dell Inc.
- Michael Raineri - Dell Inc.
- Joseph Reynolds - IBM
- Irina Salvan - Microsoft Corporation
- Bill Scherer - Hewlett Packard Enterprise
- Hemal Shah - Broadcom Inc.
- Jim Shelton - Vertiv
- Tom Slaight - Intel Corporation
- Josiah Smith - Eaton
- Donnie Sturgeon - Vertiv
- Pawel Szymanski - Intel Corporation
- Paul Vancil - Dell Inc.
- Joseph White - Dell Inc.
- Linda Wu - NVIDIA Corporation, Super Micro Computer, Inc.

## 2 Abstract

---

Redfish is a standard that uses RESTful interface semantics to access a schema based data model to conduct management operations. It is suitable for a wide range of devices, from stand-alone servers, to composable infrastructures, and to large-scale cloud environments.

The initial Redfish scope targeted servers.

The DMTF and its alliance partners expanded that scope to cover most data center IT equipment and other solutions, and both in- and out-of-band access methods.

Additionally, the DMTF and other organizations that use Redfish as part of their industry standard or solution have added educational material.

## 3 Normative references

---

The following referenced documents are indispensable for the application of this document. For dated or versioned references, only the edition cited (including any corrigenda or DMTF update versions) applies. For references without a date or version, the latest published edition of the referenced document (including any corrigenda or DMTF update versions) applies.

- Architectural Styles and the Design of Network-based Software Architectures, R. Fielding, 2000.  
<https://www.ics.uci.edu/~fielding/pubs/dissertation/top.htm>
- DMTF DSP0270 Redfish Host Interface Specification, [https://www.dmtf.org/sites/default/files/standards/documents/DSP0270\\_1.0.pdf](https://www.dmtf.org/sites/default/files/standards/documents/DSP0270_1.0.pdf)
- HTML Living Standard: Server-sent events <https://html.spec.whatwg.org/multipage/server-sent-events.html>
- IANA: Transport Layer Security (TLS) Parameters, <https://www.iana.org/assignments/tls-parameters/tls-parameters.xhtml>
- ISO 639-1:2002 [ISO 639-1:2002 Codes for the representation of names of languages -- Part 1: Alpha-2 code](#)
- IETF RFC1738, T. Berners-Lee et al, Uniform Resource Locators (URL), <https://tools.ietf.org/html/rfc1738>
- IETF RFC3986, T. Berners-Lee et al, Uniform Resource Identifier (URI): Generic Syntax, <https://tools.ietf.org/html/rfc3986>
- IETF RFC5280, D. Cooper et al, Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile, <https://tools.ietf.org/html/rfc5280>
- IETF RFC5288, J. Salowey et al, AES Galois Counter Mode (GCM) Cipher Suites for TLS, <https://tools.ietf.org/html/rfc5288>
- IETF RFC5487, M. Badra et al, Pre-Shared Key Cipher Suites for TLS with SHA-256/384 and AES Galois Counter Mode, <https://tools.ietf.org/html/rfc5487>
- IETF RFC5789, L. Dusseault et al, PATCH Method for HTTP, <https://tools.ietf.org/html/rfc5789>
- IETF RFC6585, M. Nottingham, et al, Additional HTTP Status Codes, <https://tools.ietf.org/html/rfc6585>
- IETF RFC6901, P. Bryan, Ed. et al, JavaScript Object Notation (JSON) Pointer, <https://tools.ietf.org/html/rfc6901>
- IETF RFC6906, E. Wilde, The 'profile' Link Relation Type, <https://tools.ietf.org/html/rfc6906>
- IETF RFC7230, R. Fielding et al., Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing, <https://tools.ietf.org/html/rfc7230>
- IETF RFC7231, R. Fielding et al., Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content, <https://tools.ietf.org/html/rfc7231>
- IETF RFC7232, R. Fielding et al., Hypertext Transfer Protocol (HTTP/1.1): Conditional Requests, <https://tools.ietf.org/html/rfc7232>
- IETF RFC7234, R. Fielding et al., Hypertext Transfer Protocol (HTTP/1.1): Caching, <https://tools.ietf.org/html/rfc7234>
- IETF RFC7525, Y. Sheffer et al., Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS), <https://tools.ietf.org/html/rfc7525>

- IETF RFC7578, L. Masinter et al., Returning Values from Forms: multipart/form-data, <https://tools.ietf.org/html/rfc7578>
- IETF RFC7617, J. Reschke et al., The 'Basic' HTTP Authentication Scheme, <https://tools.ietf.org/html/rfc7617>
- IETF RFC8259, T. Bray, Ed., The JavaScript Object Notation (JSON) Data Interchange Format, <https://tools.ietf.org/html/rfc8259>
- IETF RFC8288, M. Nottingham, Web Linking, <https://tools.ietf.org/html/rfc8288>
- ISO/IEC Directives, ISO/IEC Directives, Part 2 (English), <https://isotc.iso.org/livelink/livelink.exe?func=ll&objId=4230456&objAction=browse&sort=subtypeH>
- JSON Schema: A Media Type for Describing JSON Documents draft-handrews-json-schema-01, <https://tools.ietf.org/html/draft-handrews-json-schema-01>
- JSON Schema Validation: A Vocabulary for Structural Validation of JSON draft-handrews-json-schema-validation-01, <https://tools.ietf.org/html/draft-handrews-json-schema-validation-01>
- OData Version 4.0 Plus Errata 03: Core Vocabulary. 10 March 2016. <https://docs.oasis-open.org/odata/odata/v4.0/errata03/csd01/complete/vocabularies/Org.OData.Core.V1.xml>
- OData JSON Format Version 4.0. 24 February 2014. <https://docs.oasis-open.org/odata/odata-json-format/v4.0/os/odata-json-format-v4.0-os.html>
- OData Version 4.0 Part 1: Protocol. 24 February 2014. <https://docs.oasis-open.org/odata/odata/v4.0/os/part1-protocol/odata-v4.0-os-part1-protocol.html>
- OData Version 4.0 Part 2: URL Conventions. 24 February 2014. <https://docs.oasis-open.org/odata/odata/v4.0/os/part2-url-conventions/odata-v4.0-os-part2-url-conventions.html>
- OData Version 4.0 Part 3: Common Schema Definition Language (CSDL). 24 February 2014. <https://docs.oasis-open.org/odata/odata/v4.0/os/part3-csdl/odata-v4.0-os-part3-csdl.html>
- OData Version 4.0 Plus Errata 03: Units of Measure Vocabulary. 10 March 2016. <https://docs.oasis-open.org/odata/odata/v4.0/errata03/csd01/complete/vocabularies/Org.OData.Measures.V1.xml>
- The OpenAPI Specification <https://github.com/OAI/OpenAPI-Specification>
- Redfish Schema: RedfishExtensions. [https://redfish.dmtf.org/schemas/v1/RedfishExtensions\\_v1.xml](https://redfish.dmtf.org/schemas/v1/RedfishExtensions_v1.xml)
- Simple Service Discovery Protocol/1.0 Operating without an Arbiter. 28 October 1999. <https://tools.ietf.org/html/draft-cai-ssdp-v1-03>
- SNIA TLS Specification for Storage Systems. 20 November 2014. [https://www.snia.org/tech\\_activities/standards/curr\\_standards/tls](https://www.snia.org/tech_activities/standards/curr_standards/tls)
- The Unified Code for Units of Measure. <https://www.unitsofmeasure.org/ucum.html>
- W3C Cross-Origin Resource Sharing. 16 January 2014. <https://www.w3.org/TR/cors/>

## 4 Terms and definitions

---

Some terms and phrases in this document have specific meanings beyond their typical English meanings. This clause defines those terms and phrases.

The terms "shall" ("required"), "shall not", "should" ("recommended"), "should not" ("not recommended"), "may", "need not" ("not required"), "can" and "cannot" in this document are to be interpreted as described in ISO/IEC Directives, Part 2, Clause 7. The terms in parenthesis are alternatives for the preceding term, for use in exceptional cases when the preceding term cannot be used for linguistic reasons. Note that ISO/IEC Directives, Part 2, Clause 7 specifies additional alternatives. Occurrences of such additional alternatives shall be interpreted in their normal English meaning.

The terms "clause", "subclause", "paragraph", and "annex" in this document are to be interpreted as described in ISO/IEC Directives, Part 2, Clause 6.

The terms "normative" and "informative" in this document are to be interpreted as described in ISO/IEC Directives, Part 2, Clause 3. In this document, clauses, subclauses, or annexes labeled "(informative)" do not contain normative content. Notes and examples are always informative elements.

The term "deprecated" in this document is to be interpreted as material that is not recommended for use in new development efforts. Existing and new implementations may use this material, but they should move to the favored approach. Deprecated material may be implemented in order to achieve backwards compatibility. Deprecated material should contain references to the last published version that included the deprecated material as normative material and to a description of the favored approach. Deprecated material may be removed from the next major version of the specification.

The following typographical convention indicates deprecated material:

---

### **DEPRECATED**

Deprecated material appears here.

### **END DEPRECATED**

---

In places where this typographical convention cannot be used, such as tables or figures, the "DEPRECATED" label is used alone.

This document defines these additional terms:

---

Term	Definition
baseboard management controller (BMC)	Embedded device or service. Typically an independent microprocessor or system-on-chip with associated firmware in a computer system that completes out-of-band systems monitoring and management-related tasks.
collection	See <a href="#">resource collection</a> .
CRUD	Basic <b>C</b> reate, <b>R</b> ead, <b>U</b> ppdate, and <b>D</b> eleate operations that any interface can support.
event	Data structure that corresponds to one or more alerts.
excerpt	Subset of data that is copied from one resource and presented in another resource. An excerpt provides data in convenient locations without duplication of entire resources.
hypermedia API	API that enables you to navigate through URIs that a service returns.
managed system	System that provides information, status, or control through a Redfish-defined interface.
member	Single <a href="#">resource</a> instance in a <a href="#">resource collection</a> .
message	Complete HTTP- or HTTPS-formatted request or response. In the REST-based Redfish protocol, every request should result in a response.
OData service document	Resource that provides information about the <a href="#">Service Root</a> for generic OData clients.
OData	Open Data Protocol, as defined in <a href="#">OData Protocol</a> .
operation	HTTP POST, GET, PUT, PATCH, HEAD, and DELETE request methods that map to generic <a href="#">CRUD</a> operations.
parent resource	A resource is a parent to another resource if the initial segment of the resource URI is the same as the URI of the other resource, but is at least one level higher. For example, <code>/redfish/v1/Chassis/A88</code> is a parent resource of <code>/redfish/v1/Chassis/A88/Assembly</code> .
property	Name-and-value pair in a Redfish-defined request or response. A property can be any valid JSON data type.
Redfish client	Communicates with a <a href="#">Redfish Service</a> and accesses one or more of the service's resources or functions.
Redfish event receiver	Software that runs at the event destination that receives events from a <a href="#">Redfish Service</a> .
Redfish protocol	Discovers, connects to, and inter-communicates with a <a href="#">Redfish Service</a> .



Term	Definition
Redfish provider	<p>Interacts with a Redfish Service to contribute resources to the Redfish resource tree and reacts to changes in its resources.</p> <p>Redfish providers include:</p> <ul style="list-style-type: none"> <li>• <b>Internal provider.</b> The Redfish Service itself that has a data model and can react to RESTful operations from a client.</li> <li>• <b>External provider.</b> A designed means for agents external to the Redfish Service to augment the Redfish resource tree.</li> </ul> <p>This specification does not describe the interaction between a Redfish provider and a Redfish Service.</p>
Redfish schema	Defines Redfish resources according to OData schema representation. You can directly translate a Redfish schema to a JSON Schema representation.
Redfish Service	Implementation of the protocols, resources, and functions that deliver the interface that this specification defines and its associated behaviors for one or more <a href="#">managed systems</a> . Also known as the <i>service</i> .
request	Message from a client to a service.
resource collection	Set of similar resources where the number of instances can shrink or grow.
resource tree	Tree structure of resources accessible through a well-known starting URI. A client may discover the available resources on a Redfish Service by following the resource hyperlinks from the base of the tree.
resource	Redfish data structure that is addressable by a URI.
response	Message from a service to a client in response to a request message.
Service Root	Starting-point resource for locating and accessing the other resources and associated metadata that make up an instance of a Redfish Service.
subordinate resource	A resource is subordinate to another resource if the initial segment of the resource URI is the same as the URI of the other resource, but is at least one level deeper. For example, <code>/redfish/v1/Chassis/A88/Assembly</code> is a subordinate resource of the <code>Chassis</code> resource named <code>A88</code> .
subscription	Registration of a destination to receive events.
task	Representation of a long-running <a href="#">operation</a> .
task monitor	Opaque service-generated URI that the client who initiates the request can use to monitor an <a href="#">asynchronous operation</a> .

## 5 Symbols and abbreviated terms

---

This document uses these symbols and abbreviated terms:

Symbol or abbreviated term	Definition
BMC	Baseboard management controller
CORS	Cross-origin resource sharing
CRUD	Create, read, update, and delete
CSRF	Cross-Site Request Forgery
HTTP	Hypertext Transfer Protocol
HTTPS	Hypertext Transfer Protocol over TLS
IP	Internet Protocol
IPMI	Intelligent Platform Management Interface
JSON	JavaScript Object Notation
KVM-IP	Keyboard, Video, Mouse redirection over IP
NIC	Network interface controller
PCI	Peripheral Component Interconnect
PCIe	Peripheral Component Interconnect Express
TCP	Transmission Control Protocol
XSS	Cross-site scripting

## 6 Overview

---

Redfish is a management standard that uses a data model representation with a RESTful interface.

Being RESTful, Redfish is easier to use and implement.

Being model-oriented, it can express the relationships between components and the semantics of the Redfish Services and components within them. The model is also easy to extend.

By requiring JSON representation, Redfish enables easy integration with programming environments. It is also easy to interpret by humans.

An interoperable Redfish schema defines this model, which is freely available and published in OpenAPI YAML, OData CSDL, and JSON Schema formats.

### 6.1 Scope

---

This specification defines the required protocols, data model, behaviors, and other architectural components for an interoperable, multivendor, remote, and out-of-band capable interface. This interface meets the cloud-based and web-based IT professionals' expectations for scalable platform management. While large and hyperscale environments are the primary focus, clients can use the specification for individual system management.

The specification defines the required elements for all Redfish implementations, and the optional elements that system vendors and manufacturers can choose. This specification also defines at which points an implementation can provide OEM-specific extensions.

The specification sets normative requirements for [Redfish Services](#) and associated materials, such as Redfish schema files. In general, the specification does not set requirements for Redfish clients but indicates what a client should do to successfully and effectively access and use a Redfish Service.

The specification does not require that implementations of the Redfish interfaces and functions require particular hardware or firmware.

### 6.2 Goals

---

As an architecture, data representation, and definition of protocols that enable a client to access Redfish Services, Redfish has these goals:

Goal	Purpose
Scalable	Can scale on stand-alone machines or racks of equipment.

Goal	Purpose
Flexible	Can implement through existing hardware or entirely as a software service.
Extensible	Can easily add new and vendor-specific capabilities to the data model.
Backward-compatible	Can add capabilities while preserving investments in earlier implementations.
Interoperable	Provides consistent functionality across multiple vendor implementations.
Standards-based	Built on ubiquitous and secure protocols. Leverages other standards where applicable.
Simple	Easy-to-use without the need for highly specialized programming skills or systems knowledge.
Lightweight	Designed to reduce complexity and implementation costs. Minimizes the required footprint for implementations.

## 6.3 Design tenets

---

To deliver these goals, Redfish:

- Provides a RESTful interface by using a JSON payload and a data model.
- Separates the protocol from the data model, which enables the independent revision and use of each.
- Specifies versioning rules for protocols and schema.
- Leverages strength of ubiquitous standards where it meets architectural requirements, such as JSON, HTTP, OData, OpenAPI, and the RFCs that this document references.
- Organizes the data model so that it provides clearly demarcated and value-add features in the same payload as standardized items.
- Makes data in payloads as obvious in context as possible.
- Maintains implementation flexibility. Does not tie the interface to any particular underlying implementation or architecture.
- Focuses on widely used capabilities. To avoid complexity, does not add functions that only a small percentage of users value.

## 6.4 Limitations

---

Redfish minimizes the need for clients to complete upgrades by using strict versioning and forward-compatibility rules, and separation of the protocols from the data model. However, Redfish does not guarantee that clients never need to update their software. For example, clients might need to upgrade to manage new system or component types, or update the data model.

Interoperable does not mean identical. Many elements of Redfish are optional. Clients should be prepared to discover the optional elements by using the built-in discovery methods.

The [resource tree](#) reflects the topology of the system and its devices. Consequently, different hardware or device

types result in different resource trees, even for identical systems from the same manufacturer. References between resources may result in a graph instead of a tree. Clients that traverse the resource tree should provide logic to avoid infinite loops.

Additionally, not all Redfish resources use simple REST read-and-write semantics. Different use cases may follow other types of client logic. For example, clients cannot simply read user credentials or certificates from one service and write them to another service.

Finally, the hyperlink values between resources and other elements can vary across implementations. Clients should not assume that they can reuse hyperlinks across different Redfish Service instances.

## 6.5 Additional design background and rationale

---

### 6.5.1 REST-based interface

Redfish exposes many service applications as RESTful interfaces. This document defines a RESTful interface.

Redfish defines a RESTful interface because it:

- Enables a lightweight implementation, using fewer layers than previous standards.
- Is a prevalent access method in the industry.
- Is easy to learn, document, and implement in modern programming languages.
- Has a number of development environments and a healthy tooling ecosystem.
- Fits with the design goal of simplicity.
- Equally applies to software application space as it does to embedded environments, which enables convergence and sharing of code within the management ecosystem.
- Adapts well to any data modeling language.
- Has industry-provided security and discovery mechanisms.

### 6.5.2 Data-oriented

The Redfish data model is developed by focusing on the contents of the payload. By concentrating on the contents of the payload first, Redfish payloads are easily mapped to schema definition languages and encoding types. The data model is defined in various schema languages, including OpenAPI YAML, OData CSDL, and JSON Schema.

### 6.5.3 Separation of protocol from data model

Redfish separates the protocol operations from the data model and versions the protocol independently from the data model. This enables clients to extend and change the data model as needed without requiring the protocol version to change.

## 6.5.4 Hypermedia API Service Root

Redfish has a single Service Root URI and clients can discover all resources through referenced URIs. The [hypermedia API](#) enables the discovery of resources through hyperlinks.

## 6.5.5 OpenAPI v3.0 support

The OpenAPI v3.0 provides a rich ecosystem of tools for using RESTful interfaces that meet the design requirements of that specification. Starting with Redfish Specification v1.6.0, the Redfish schemas support the OpenAPI YAML file format and URI patterns that conform to the OpenAPI Specification were defined. Conforming Redfish Services that support the Redfish protocol version v1.6.0 or later implement those URI patterns to enable use of the OpenAPI ecosystem.

For details, see [OpenAPI Specification v3.0](#).

## 6.5.6 OData conventions

With the popularity of RESTful APIs, there are nearly as many RESTful interfaces as there are applications. While following REST patterns helps promote good practices, due to design differences between the many RESTful APIs there few common conventions between them.

To provide for interoperability between APIs, [OData](#) defines a set of common RESTful conventions and annotations. Redfish adopts OData conventions for describing schema, URL conventions, and definitions for typical properties in a JSON payload.

# 6.6 Service elements

---

## 6.6.1 Synchronous and asynchronous operation support

Some operations can take more time than a client typically wants to wait. For this reason, some operations can be asynchronous at the discretion of the service. The request portion of an asynchronous operation is no different from the request portion of a synchronous operation.

To determine whether an operation was completed synchronously or asynchronously, clients can review the [HTTP status codes](#). For more information, see the [Asynchronous operations](#) clause.

## 6.6.2 Eventing mechanism

Redfish enables clients to receive messages outside the normal request and response paradigm. The service uses these messages, or *events*, to asynchronously notify the client of a state change or error condition, usually of a time critical nature.

This specification defines two styles of eventing:

- Push-style eventing.

When the service detects the need to send an event, it calls HTTP POST to push the event message to the client. Clients can enable reception of events by creating a [subscription](#) entry in the Event Service, or an administrator can create subscriptions as part of the Redfish Service configuration.

- [Server-Sent Events \(SSE\)](#)-style eventing.

The client opens an SSE connection to the service through a GET on the `ServerSentEventUri`-specified URI in the Event Service.

For information, see the [Eventing](#) clause.

### 6.6.3 Actions

Actions are Redfish operations that do not easily map to RESTful interface semantics. These types of operations may not directly affect properties in the Redfish resources. The Redfish schema defines certain standard actions for common Redfish resources. For these standard actions, the Redfish schema contains the normative language on the behavior of the action.

### 6.6.4 Service discovery

While the service itself is at a well-known URI, clients need to discover the network address of the service. Like UPnP, Redfish uses SSDP for discovery. A wide variety of devices, such as printers and client operating systems, support SSDP. It is simple, lightweight, IPv6 capable, and suitable for implementation in embedded environments.

For more information, see the [Discovery](#) clause.

### 6.6.5 Remote access support

Remote management functionality typically includes access mechanisms for redirecting operator interfaces such as serial console, keyboard video and mouse (KVM-IP), command shell, or command-line interface, and virtual media. While these mechanisms are critical functionality, they cannot be reasonably implemented as a RESTful interface.

Therefore, this standard does not define the protocols or access mechanisms for those services but encourages implementations that leverage existing standards. However, the Redfish schema includes resources and properties that enable client discovery of these capabilities and access mechanisms to enable interoperability.

## 6.7 Security

---

The challenge of remote interface security is to protect both the interface and exchanged data. To accomplish this,

---

Redfish provides authentication and encryption. As part of this security, Redfish defines and requires minimum levels of encryption.

For more information, see the [Security details](#) clause.



## 7 Protocol details

In this document, the Redfish protocol refers to the RESTful mapping to HTTP, TCP/IP, and other protocol, transport, and messaging layer aspects. HTTP is the application protocol that transports the messages and TCP/IP is the transport protocol. The RESTful interface is a mapping to the message protocol.

The Redfish protocol is designed around a web service-based interface model. This provides network and interaction efficiency for both user interface (UI) and automation usage. Specifically, the protocol can leverage existing tool chains.

The Redfish protocol uses these items for these purposes:

Item	Purpose
<a href="#">HTTP methods</a>	Maps to common CRUD operations.
<a href="#">Actions</a>	Expands operations beyond CRUD-type operations.
<a href="#">Media types</a>	Negotiates the type of data sent in the message body.
<a href="#">HTTP status codes</a>	Indicates the success or failure of the server's request.
<a href="#">Error responses</a>	Returns more information than HTTP status codes.
TLS	Secures messages. See <a href="#">Security details</a> .
<a href="#">Asynchronous semantics</a>	For long-running operations.

A Redfish interface shall be exposed through a web service endpoint implemented by using HTTP version 1.1. See [RFC7230](#), [RFC7231](#), and [RFC7232](#).

The subsequent clauses describe how the Redfish interface uses and adds constraints to HTTP to ensure interoperability of Redfish implementations.

### 7.1 Universal Resource Identifiers

A Universal Resource Identifier (URI) identifies a resource, including the Service Root and all Redfish resources.

- A URI shall identify each unique instance of a resource.
- URIs shall not include any [RFC1738](#)-defined unsafe characters.
  - For example, the `{`, `}`, `!`, `]`, `^`, `~`, `[`, `]`, ```, and `\` characters are unsafe because gateways and other transport agents can sometimes modify these characters.
  - Do not use the `#` character for anything other than the start of a fragment.

- URIs shall not include any percent-encoding of characters. This restriction does not apply to the [query parameters](#) portion of the URI.

Performing a GET operation on a URI returns a representation of the resource with properties and hyperlinks to associated resources. The Service Root URI is well known and is based on the protocol version.

To discover the URIs to additional resources, extract the associated resource hyperlinks from earlier responses. The [hypermedia API](#) enables the discovery of resources through hyperlinks.

Redfish considers the [RFC3986](#)-defined scheme, authority, Service Root, and version, and unique resource path component parts of the URI.

For example, this URI:

```
https://mgmt.vendor.com/redfish/v1/Systems/1
```

Contains these component parts:

Component part	Defines
https:	Scheme.
mgmt.vendor.com	Authority to which to delegate the URI.
redfish/v1	Service Root and version.
Systems/1	Unique resource path.

In a URI:

- The scheme and authority component parts are not part of the unique resource path because redirection capabilities and local operations may cause the connection portion to vary.
- The Service Root and resource path component parts *uniquely identify* the resource in a Redfish Service.

In an implementation:

- The resource path component part shall be unique.
- A [relative reference](#) in the body and HTTP headers payload can identify a resource in that same implementation.
- An absolute URI in the body and HTTP headers payload can identify a resource in a different implementation.

For the absolute URI definition, see [RFC3986](#).

For example, a POST operation may return the `/redfish/v1/Systems/2` URI in the [Location header](#) of the response, which points to the POST-created resource.

Assuming that the client connects through the `mgmt.vendor.com` appliance, the client accesses the resource through the `https://mgmt.vendor.com/redfish/v1/Systems/2` absolute URI.

URIs that conform to [RFC3986](#) may also contain the query, `?query`, and frag, `#frag`, components. For information about queries, see [Query parameters](#). When a URI includes a fragment ( `frag` ) to submit an operation, the server ignores the fragment.

If a property in a response references another property within a resource, use the [RFC6901](#)-defined URI fragment identifier representation format. If the property is a [reference property](#) in the schema, the fragment shall reference a valid [resource identifier](#). For example, the following fragment identifies a property at index 0 of the `Fans` array in the `/redfish/v1/Chassis/MultiBladeEncl/Thermal` resource:

```
{
  "@odata.id": "/redfish/v1/Chassis/MultiBladeEncl/Thermal#/Fans/0"
}
```

For requirements on constructing Redfish URIs, see the [resource URI patterns annotation](#) clause.

## 7.2 HTTP methods

The following table describes the mapping of HTTP methods to the operations that are supported by Redfish. The **Required** column specifies whether a Redfish interface supports the method.

- If the value is **Yes**, the HTTP method shall be supported.
- If the value is **No**, the value may be supported.

For HTTP methods that the Redfish service does not support or that the following table omits, the Redfish service shall return the HTTP [405 Method Not Allowed](#) status code or the HTTP [501 Not Implemented](#) status code.

HTTP method	Interface semantic	Required
POST	Resource create Resource action Eventing	Yes
GET	Resource retrieval	Yes
PUT	Resource replace	No
PATCH	Resource update	Yes
DELETE	Resource delete	Yes
HEAD	Resource header retrieval	No

HTTP method	Interface semantic	Required
OPTIONS	Header retrieval Cross-origin resource sharing (CORS) preflight	No

## 7.3 HTTP redirect

HTTP redirect enables a service to redirect a request to another URL. Among other things, HTTP redirect enables Redfish resources to alias areas of the data model.

All Redfish clients shall correctly handle HTTP redirect.

The service for the redirected resource shall enforce the [authentication](#) and [authorization](#) requirements for the redirected resource.

## 7.4 Media types

Some resources may be available in more than one type of representation. The media type indicates the representation type.

In HTTP messages, the media type is specified in the `Content-Type` header. To tell a service to send the response through certain media types, the client sets the HTTP `Accept` header to a list of the media types.

- All resources shall be available through the JSON `application/json` media type.
- Redfish services shall make every resource available in a JSON-based representation as a JSON object, as specified in [RFC8259](#). Receivers shall not reject a JSON-encoded message, and shall offer at least one JSON-based response representation. An implementation may offer additional non-JSON media type representations.

To request compression in the response body, clients specify an [Accept-Encoding request header](#).

## 7.5 ETags

To reduce unnecessary RESTful accesses to resources, the Redfish Service should support the association of a separate entity tag (ETag) with each resource.

- Implementations should support the return of [ETag properties](#) for each resource.
- Implementations should support the return of ETag headers for each single-resource response.
- Implementations shall support the return of ETag headers for GET requests of `ManagerAccount` resources.

Because the service knows whether the new version of the object is substantially different, the service generates and provides the ETag as part of the resource payload.

The ETag mechanism supports both **strong** and **weak** validation. If a resource supports an ETag, it shall use the [RFC7232](#)-defined ETag.

This specification does not mandate a particular algorithm for ETag creation, but ETags should be highly collision-free.

An ETag can be:

- A hash
- A generation ID
- A time stamp
- Some other value that changes when the underlying object changes

If a client calls [PUT](#) or [PATCH](#) to update a resource, it should include an ETag from a previous GET in the HTTP `If-Match` or `If-None-Match` header. If a service supports the return of the ETag header on a resource, it may respond with the HTTP [428 Precondition Required](#) status code if the `If-Match` or `If-None-Match` header is missing from the PUT or PATCH request for the same resource, as specified in [RFC6585](#).

In addition to the return of the ETag property on each resource, a Redfish Service should return the ETag header on:

- A client PUT, POST, or PATCH operation
- A GET operation for an individual resource

The format of the ETag header is:

```
ETag: <string>
```

## 7.6 Protocol version

---

The protocol version is separate from the resources' version or the Redfish schema version that the resources support.

Each Redfish protocol version is strongly typed by using the URI of the Redfish Service in combination with the resource obtained at that URI, called the `ServiceRoot` resource.

The root URI for this version of the Redfish protocol shall be `/redfish/v1/`.

The URI defines the major version of the protocol.

The `RedfishVersion` property of the `ServiceRoot` resource defines the protocol version, which includes the major version, minor version, and errata version of the protocol, as defined in the Redfish schema for that resource.

The protocol version is a string in the format:

`MajorVersion` . `MinorVersion` . `ErrataVersion`

where

Variable	Type	Version	Description
<code>MajorVersion</code>	Integer	Major	Backward-compatible class change.
<code>MinorVersion</code>	Integer	Minor	Minor update. Redfish introduces functionality but does not remove any functionality. The minor version preserves compatibility with earlier minor versions.
<code>ErrataVersion</code>	Integer	Errata	Fix to the earlier version.

Any resource that a client discovers through hyperlinks that the Service Root or any Service Root-referenced service or resource returns shall conform to the same protocol version that the Service Root supports.

A GET operation on the `/redfish` resource shall return this response body:

```
{
  "v1": "/redfish/v1/"
}
```

## 7.7 Redfish-defined URIs and relative reference rules

A Redfish Service shall support these Redfish-defined URIs:

URI	Returns
<code>/redfish</code>	The <a href="#">version</a> . A major update that does not preserve compatibility with earlier minor versions.
<code>/redfish/v1/</code>	The Redfish <a href="#">Service Root</a> .
<code>/redfish/v1/odata</code>	The Redfish <a href="#">OData service document</a> .
<code>/redfish/v1/\$metadata</code>	The Redfish <a href="#">metadata document</a> .

A Redfish Service should support these Redfish-defined URIs:

URI	Returns
<code>/redfish/v1/openapi.yaml</code>	The Redfish <a href="#">OpenAPI YAML document</a> .

In addition, the service shall process the following URI without a trailing slash in one of these ways:

- Redirect it to the associated Redfish-defined URI.
- Treat it as the equivalent URI to the associated Redfish-defined URI:

URI	Associated Redfish-defined URI
/redfish/v1	/redfish/v1/
/redfish/	/redfish

All other Redfish Service-supported URIs shall match the [resource URI patterns definitions](#), except the supplemental resources that the `@Redfish.Settings`, `@Redfish.ActionInfo`, and `@Redfish.CollectionCapabilities` [payload annotations](#) reference. The client shall treat the URIs for these supplemental resources as opaque.

All Redfish Service-supported URIs are reserved for future standardization by DMTF and DMTF alliance partners, except OEM extension URIs, which shall conform to the [OEM resource URI](#) requirements.

All relative references that the service uses shall start with either:

- A double forward slash ( // ) and include the authority (network-path), such as `//mgmt.vendor.com/redfish/v1/Systems`.
- A single forward slash ( / ) and include the absolute-path, such as `/redfish/v1/Systems`.

For details, see [RFC3986](#).

## 8 Service requests

---

This clause describes the requests that clients can send to Redfish Services.

### 8.1 Request headers

---

The HTTP Specification defines headers for request messages. The following table defines those headers and their requirements for Redfish Services and clients.

For Redfish Services:

- Redfish Services shall process the headers in the following table as defined by the HTTP 1.1 Specification if the value in the **Service requirement** column is **Yes**, or if the value is **Conditional** under the conditions noted in the Description column.
- Redfish Services should process the headers in the following tables as defined by the HTTP 1.1 Specification if the value in the **Service requirement** column is **No**.

For Redfish clients (sending the HTTP requests):

- Redfish clients shall include the headers in the following table as defined by the HTTP 1.1 Specification if the value in the **Client requirement** column is **Yes**, or if the value is **Conditional** under the conditions noted in the Description column.
- Redfish clients should transmit the headers in the following tables as defined by the HTTP 1.1 Specification if the value in the **Client requirement** column is **No**.



Header	Service requirement	Client requirement	Supported values	Description
Accept	Yes	No	<a href="#">RFC7231</a>	<p>Communicates to the server the media type or types that this client is prepared to accept.</p> <p>Services shall support resource requests with <code>Accept</code> header values of <code>application/json</code> or <code>application/json; charset=utf-8</code>.</p> <p>Services shall support XML metadata requests with <code>Accept</code> header values of <code>application/xml</code> or <code>application/xml; charset=utf-8</code>.</p> <p>Services shall support OpenAPI YAML schema requests with <code>Accept</code> header values of <code>application/yaml</code> or <code>application/yaml; charset=utf-8</code> or <code>application/vnd.oai.openapi</code> or <code>application/vnd.oai.openapi; charset=utf-8</code>.</p> <p>Services shall support SSE requests with <code>Accept</code> header values of <code>text/event-stream</code> or <code>text/event-stream; charset=utf-8</code>.</p> <p>Services shall support any request with <code>Accept</code> header values of <code>application/*</code>, <code>application/*; charset=utf-8</code>, <code>/*/*</code>, or <code>/*/*; charset=utf-8</code>.</p>
Accept-Encoding	No	No	<a href="#">RFC7231</a>	<p>Indicates whether the client can handle gzip-encoded responses.</p> <p>If a service cannot send an acceptable response to a request with this header, it shall respond with the HTTP <a href="#">406 Not Acceptable</a> status code.</p> <p>If the request omits this header, the service shall not return gzip-encoded responses.</p>
Accept-Language	No	No	<a href="#">RFC7231</a>	<p>The languages that the client accepts in the response.</p> <p>If the request omits this header, uses the service's default language for the response.</p>
Authorization	Conditional	Conditional	<a href="#">RFC7617</a>	<p>Required for <a href="#">HTTP basic authentication</a>.</p> <p>A client can access unsecured resources without this header on systems that support basic authentication.</p>

Header	Service requirement	Client requirement	Supported values	Description
<code>Content-Length</code>	No	No	<a href="#">RFC7231</a>	<p>The size of the message body.</p> <p>To indicate the size of the body, a client can use the <code>Transfer-Encoding: chunked</code> header.</p> <p>If a service needs to use <code>Content-Length</code> and does not support <code>Transfer-Encoding</code>, it responds with the HTTP <a href="#">406 Not Acceptable</a> status code.</p>
<code>Content-Type</code>	Conditional	Conditional	<a href="#">RFC7231</a>	<p>The request format. Required for operations with a request body.</p> <p>Services shall accept the <code>Content-Type</code> header set to either <code>application/json</code> or <code>application/json;charset=utf-8</code>.</p> <p>It is recommended that clients use these values in requests because other values can cause an error.</p>
<code>Host</code>	Yes	No	<a href="#">RFC7230</a>	Enables support of multiple origin hosts at a single IP address.
<code>If-Match</code>	Conditional	No	<a href="#">RFC7232</a>	<p>To ensure that clients update the resource from a known state, PUT and PATCH requests for resources for which a service returns ETags shall support <code>If-Match</code>.</p> <p>While not required for clients, it is highly recommended for PUT and PATCH operations.</p>
<code>If-None-Match</code>	No	No	<a href="#">RFC7232</a>	<p>A service only returns the resource if the current ETag of that resource does not match the ETag sent in this header.</p> <p>If the ETag in this header matches the resource's current ETag, the GET operation returns the HTTP <a href="#">304 Not Modified</a> status code.</p>
<code>Last-Event-ID</code>	No	No	<a href="#">HTML5 SSE</a>	<p>The event source's last <code>id</code> field from the SSE stream. Requests history event data.</p> <p>See <a href="#">Server-Sent Events</a>.</p>
<code>Max-Forwards</code>	No	No	<a href="#">RFC7231</a>	<p>Limits gateway and proxy hops.</p> <p>Prevents messages from remaining in the network indefinitely.</p>
<code>OData-MaxVersion</code>	No	No	4.0	The maximum OData version that an OData-aware client understands.

Header	Service requirement	Client requirement	Supported values	Description
OData-Version	Yes	No	4.0	The OData version. Services shall reject requests that specify an unsupported OData version. If a service encounters an unsupported OData version, it should reject the request with the HTTP <a href="#">412 Precondition Failed</a> status code.
Origin	Yes	No	<a href="#">W3C CORS</a> , Section 5.7	Enables web applications to consume a Redfish Service while preventing CSRF attacks.
User-Agent	Yes	No	<a href="#">RFC7231</a>	Traces product tokens and their versions. The header can list multiple product tokens.
Via	No	No	<a href="#">RFC7230</a>	Defines the network hierarchy and recognizes message loops. Each pass inserts its own <code>Via</code> header.

Redfish Services shall understand and be able to process the headers in the following table as defined by this specification if the value in the **Required** column is **Yes**.

Header	Service requirement	Client requirement	Supported values	Description
X-Auth-Token	Yes	Conditional	Opaque encoded octet strings	Authenticates user sessions. The token value shall be indistinguishable from random. While services shall support this header, a client can access unsecured resources without establishing a session.

## 8.2 GET (read requests)

The GET operation retrieves resources from a Redfish Service. Clients make a GET request to the individual resource URI. Clients may obtain the resource URI from published sources, such as the OpenAPI document, or from a [resource identifier property](#) in a previously retrieved resource response, such as the [links property](#).

The service shall return the resource representation using one of the media types listed in the `Accept` header, subject to the requirements of the [media types](#). If the `Accept` header is absent, the service shall return the resource's representation as `application/json`. Services may, but are not required to, support the convention of retrieving individual properties within a resource by appending a segment containing the property name to the URI of the resource.

- The HTTP GET operation shall retrieve a resource without causing any side effects.
- The service shall ignore the content of the body on a GET.
- The GET operation shall be idempotent in the absence of outside changes to the resource.

### 8.2.1 Resource collection requests

Clients retrieve a resource collection by making a GET request to the resource collection URI. The response includes the resource collection's properties and an array of its *members*.

No requirements are placed on implementations to return a consistent set of members when a series of requests that use paging query parameters are made over time to obtain the entire set of members. These calls can result in missed or duplicate elements if multiple GETs use paging to retrieve the `Members` array instances.

- Clients shall not make assumptions about the URIs for the members of a resource collection.
- Retrieved resource collections shall always include the `count` property to specify the total number of entries in its `Members` array.
- Regardless of the `next link property` or paging, the `count` property shall return the total number of resources that the `Members` array references.

A subset of the members can be retrieved using client paging `query parameters`.

A service may not be able to return all of the contents of a resource collection request in a single response body. In this case, the response can be paged by the service. If a service pages a response to a resource collection request, the following rules shall apply:

- Responses may contain a subset of the full resource collection's members.
- Individual members shall not be split across response bodies.
- A `next link` annotation shall be supplied in the response body with the URI to the next set of members in the collection.
- The `next link` property shall adhere to the rules in the `Next link property` clause.
- GET Operations on the `next link` shall return the subsequent section of the resource collection response.

### 8.2.2 Service Root request

The root URL for Redfish version 1.x services shall be `/redfish/v1/`.

The service returns the `ServiceRoot` resource, as defined by this specification, as a response for the root URL.

Services shall not require authentication to retrieve the Service Root and `/redfish` resources.

### 8.2.3 OData service and metadata document requests

Redfish Services expose two OData-defined documents at specific URIs to enable generic OData clients to navigate the Redfish Service.

- Service shall expose an [OData metadata document](#) at the `/redfish/v1/$metadata` URI.
- Service shall expose an [OData service document](#) at the `/redfish/v1/odata` URI.
- Service shall not require authentication to retrieve the OData metadata document or the OData service document.

## 8.3 Query parameters

---

To paginate, retrieve subsets of resources, or expand the results in a single response, clients can include the query parameters. Some query parameters apply only to resource collections.

Services:

- Shall only support query parameters on GET operations.
- Should support the `$top`, `$skip`, `only`, and `excerpt` query parameters.
- May support the `$expand`, `$filter`, and `$select` query parameters.
- Shall include the `ProtocolFeaturesSupported` object in the Service Root, if the service supports query parameters.
  - This object indicates which parameters and options have been implemented.
- Shall ignore unknown or unsupported query parameters that do not begin with `$`.
- Shall use the `&` operator to separate multiple query parameters in a single request.

Services shall return:

- The HTTP [501 Not Implemented](#) status code for any unsupported query parameters that start with `$`.
- An [extended error](#) that indicates the unsupported query parameters for this resource.
- The HTTP [400 Bad Request](#) status code for any query parameters that contain values that are invalid, or values applied to query parameters without defined values, such as `excerpt` or `only`.

Services should return:

- The HTTP [400 Bad Request](#) status code with the `QueryNotSupportedOnResource` message from the Base Message Registry for any implemented query parameters that are not supported on a resource in the request.
- The HTTP [400 Bad Request](#) status code with the `QueryNotSupportedOnResource` message from the Base Message Registry for any supported query parameters that apply only to resource collections but are used on singular resources. This includes query parameters such as `$filter`, `$top`, `$skip`, and `only`.
- The HTTP [400 Bad Request](#) status code with the `QueryNotSupportedOnOperation` message from the Base

Message Registry for any supported query parameters on operations other than GET.

The response body shall reflect the evaluation of the query parameters in this order:

- Prior to service-side pagination: `$filter`, `$skip`, `$top`
- After applying any service-side pagination: `$expand`, `$select`

Query parameter	Description and example
<code>excerpt</code>	<p>Returns a subset of the resource's properties that match the defined <code>Excerpt</code> schema annotation.</p> <p>If no <code>Excerpt</code> schema annotation is defined for the resource, the entire resource is returned.</p> <p><b>Example:</b></p> <p><code>https://resource?excerpt</code></p>
<code>\$expand=&lt;string&gt;</code>	<p>Returns a hyperlink and its contents in-line with retrieved resources, as if a GET call response was included in-line with that hyperlink.</p> <p>See <a href="#">The \$expand query parameter</a>.</p> <p><b>Example:</b></p> <p><code>https://resource?\$expand=*(.\$levels=3)</code></p> <p><code>https://resourcecollection?\$expand=.(.\$levels=1)</code></p>
<code>\$filter=&lt;string&gt;</code>	<p>Applies to resource collections. Returns a subset of collection members that match the <code>\$filter</code> expression.</p> <p>See <a href="#">The \$filter query parameter</a>.</p> <p><b>Example:</b></p> <p><code>https://resourcecollection?\$filter=SystemType eq 'Physical'</code></p>

Query parameter	Description and example
<code>only</code>	<p>Applies to resource collections. If the target resource collection contains exactly one member, clients can use this query parameter to return that member's resource.</p> <p>If the collection contains either zero members or more than one member, the response returns the resource collection, as expected.</p> <p>Services should return the HTTP <a href="#">400 Bad Request</a> with the <code>QueryCombinationInvalid</code> message from the Base Message Registry if <code>only</code> is being combined with other query parameters.</p> <p><b>Example:</b></p> <pre>https://resourcecollection?only</pre>
<code>\$select=&lt;string&gt;</code>	<p>Returns a subset of the resource's properties that match the <code>\$select</code> expression.</p> <p>See <a href="#">The \$select query parameter</a>.</p> <p><b>Example:</b></p> <pre>https://resource?\$select=SystemType,Status</pre>
<code>\$skip=&lt;integer&gt;</code>	<p>Applies to resource collections. Returns a subset of the members in a resource collection, or an empty set of members if the <code>\$skip</code> value is greater than or equal to the member count. This paging query parameter defines the number of <a href="#">members</a> in the <a href="#">resource collection</a> to skip.</p> <p><b>Example:</b></p> <pre>https://resourcecollection?\$skip=5</pre>
<code>\$top=&lt;integer&gt;</code>	<p>Applies to resource collections. Defines the number of members to show in the response.</p> <p>Minimum value is <code>0</code>, though a value of <code>0</code> will return an empty set of members.</p> <p><b>Example:</b></p> <pre>https://resourcecollection?\$top=30</pre>

### 8.3.1 The \$expand query parameter

The `$expand` query parameter enables a client to request a response that includes not only the requested resource, but also includes the contents of the [subordinate](#) or hyperlinked resources. The definition of this query parameter follows the [OData Protocol](#) Specification.

The `$expand` query parameter has a set of possible options that determine which hyperlinks in a resource are included in the expanded response. Some resources may already be expanded due to the resource's schema annotation `AutoExpand`, such as the `Temperature` object in the `Thermal` resource.

The Redfish-supported options for the `$expand` query parameter are listed in the following table. The service may implement some of these options but not others. Any other supported syntax for `$expand` is outside the scope of this specification.

Option	Description	Example
asterisk ( * )	Shall expand all hyperlinks, including those in <a href="#">payload annotations</a> , such as <code>@Redfish.Settings</code> , <code>@Redfish.ActionInfo</code> , and <code>@Redfish.CollectionCapabilities</code> .	<code>https://resource?\$expand=*</code>
<code>\$levels</code>	Number of levels the service should cascade the <code>\$expand</code> operation.  The default level shall be 1.  For example, <code>\$levels=2</code> expands both: <ul style="list-style-type: none"> <li>The hyperlinks in the current resource (level 1).</li> <li>The hyperlinks in the resulting expanded resources (level 2).</li> </ul>	<code>https://resourcecollection?\$expand=.( \$levels=2)</code>
period ( . )	Shall expand all hyperlinks <b>not</b> in any <a href="#">links property</a> instances of the resource, including those in payload annotations, such as <code>@Redfish.Settings</code> , <code>@Redfish.ActionInfo</code> , and <code>@Redfish.CollectionCapabilities</code> .	<code>https://resourcecollection?\$expand=.</code>
tilde ( ~ )	Shall expand all hyperlinks found in all <a href="#">links property</a> instances of the resource.	<code>https://resourcecollection?\$expand=~</code>

Examples of `$expand` usage include:

- GET of a `SoftwareInventoryCollection`.

With `$expand`, the client can request multiple `SoftwareInventory` collection member resources in one request rather than fetching them one at a time.

- GET of a `ComputerSystem`.

With `$levels`, a single GET request can include the subordinate resource collections, such as `Processors` and `Memory`.

- GET all UUIDs in members of the `ComputerSystem` collection.

To accomplish this result, include both `$select` and `$expand` on the URI.



The syntax is `GET /redfish/v1/Systems?$select=UUID&$expand=.(($levels=1)`

When services execute `$expand`, they may omit some of the referenced resource's properties.

When clients use `$expand`, they should be aware that the payload may increase beyond what can be sent in a single response.

If a service cannot return the payload due to its size, it shall return the HTTP [507 Insufficient Storage](#) status code.

If a service cannot return the payload corresponding to an individual [member](#) of a resource collection, it should return the `@odata.id` property for that member and should return [extended information](#) indicating the reason that member was not returned, such as when a provider internal to the service returns an error or times out.

The following is an example showing the `RoleCollection` resource being expanded with the level set to 1:

```
{
  "@odata.id": "/redfish/v1/AccountService/Roles",
  "@odata.type": "#RoleCollection.RoleCollection",
  "Name": "Roles Collection",
  "Members@odata.count": 3,
  "Members": [
    {
      "@odata.id": "/redfish/v1/AccountService/Roles/Administrator",
      "@odata.type": "#Role.v1_1_0.Role",
      "Id": "Administrator",
      "Name": "User Role",
      "Description": "Admin User Role",
      "IsPredefined": true,
      "AssignedPrivileges": [
        "Login",
        "ConfigureManager",
        "ConfigureUsers",
        "ConfigureSelf",
        "ConfigureComponents"
      ]
    },
    {
      "@odata.id": "/redfish/v1/AccountService/Roles/Operator",
      "@odata.type": "#Role.v1_1_0.Role",
      "Id": "Operator",
      "Name": "User Role",
      "Description": "Operator User Role",
      "IsPredefined": true,
      "AssignedPrivileges": [
        "Login",
        "ConfigureSelf",
        "ConfigureComponents"
      ]
    }
  ]
}
```

```
    ]
  },
  {
    "@odata.id": "/redfish/v1/AccountService/Roles/ReadOnly",
    "@odata.type": "#Role.v1_1_0.Role",
    "Id": "ReadOnly",
    "Name": "User Role",
    "Description": "ReadOnly User Role",
    "IsPredefined": true,
    "AssignedPrivileges": [
      "Login",
      "ConfigureSelf"
    ]
  }
]
```

### 8.3.2 The \$select query parameter

The `$select` query parameter indicates that the implementation should return a subset of the resource's properties that match the `$select` expression. If a request omits the `$select` query parameter, the response returns all properties by default. The definition of this query parameter follows the [OData Protocol Specification](#).

The `$select` expression shall not affect the resource itself.

The `$select` expression defines a comma-separated list of properties to return in the response body.

The syntax for properties in object types shall be the object and property names concatenated with a slash ( / ).

An example of `$select` usage is:

```
GET /redfish/v1/Systems/1?$select=Name,SystemType,Status/State
```

When services execute `$select`, they shall return all requested properties of the referenced resource. The `@odata.id` and `@odata.type` properties shall be in the response payload and contain the same values as if `$select` was not performed. If the `@odata.context` property is supported, it shall be in the response payload and should be in the [Context property](#) recommended format. If the `@odata.etag` property is supported, it shall be in the response payload and contain the same values as if `$select` was not performed.

Any other supported syntax for `$select` is outside the scope of this specification.

### 8.3.3 The \$filter query parameter

The `$filter` parameter enables a client to request a subset of the resource collection's members based on the `$filter` expression. The definition of this query parameter follows the [OData Protocol Specification](#).

The `$filter` query parameter defines a set of properties and literals with an operator.

A literal value can be:

- A string enclosed in single quotes.
- A number.
- A boolean value.

If the literal value does not match the data type for the specified property, the service should reject `$filter` requests with the HTTP [400 Bad Request](#) status code.

The `$filter` section of the OData ABNF Components Specification contains the grammar for the allowable syntax of the `$filter` query parameter, with the additional restriction that only built-in filter operations are supported.

The following table lists the Redfish-supported values for the `$filter` query parameter. Any other supported syntax for `$filter` is outside the scope of this specification.

Value	Description	Example
<code>()</code>	Precedence grouping operator.	<code>(Status/State eq 'Enabled' and Status/Health eq 'OK') or SystemType eq 'Physical'</code>
<code>and</code>	Logical and operator.	<code>ProcessorSummary/Count eq 2 and MemorySummary/TotalSystemMemoryGiB gt 64</code>
<code>eq</code>	Equal comparison operator.	<code>ProcessorSummary/Count eq 2</code>
<code>ge</code>	Greater than or equal to comparison operator.	<code>ProcessorSummary/Count ge 2</code>
<code>gt</code>	Great than comparison operator.	<code>ProcessorSummary/Count gt 2</code>
<code>le</code>	Less than or equal to comparison operator.	<code>MemorySummary/TotalSystemMemoryGiB le 64</code>
<code>lt</code>	Less than comparison operator.	<code>MemorySummary/TotalSystemMemoryGiB lt 64</code>
<code>ne</code>	Not equal comparison operator.	<code>SystemType ne 'Physical'</code>
<code>not</code>	Logical negation operator.	<code>not (ProcessorSummary/Count eq 2)</code>
<code>or</code>	Logical or operator.	<code>ProcessorSummary/Count eq 2 or ProcessorSummary/Count eq 4</code>

When evaluating expressions, services shall use the following operator precedence:

- Grouping
- Logical negation
- Relational comparison. `gt`, `ge`, `lt`, and `le` all have equal precedence.
- Equality comparison. `eq` and `ne` both have equal precedence.
- Logical `and`
- Logical `or`

If the service receives an unsupported `$filter` query parameter, it shall reject the request and return the HTTP [501 Not Implemented](#) status code.

## 8.4 HEAD

---

The HEAD method differs from the GET method in that it shall not return message body information.

However, the HEAD method completes the same authorization checks and returns all the same meta information and status codes in the HTTP headers as a GET method.

Services may support the HEAD method to:

- Return meta information in the form of HTTP response headers.
- Verify hyperlink validity.

Services may support the HEAD method to verify resource accessibility.

Services shall not support any other use of the HEAD method.

The HEAD method shall be idempotent in the absence of outside changes to the resource.

Services shall reject HEAD requests that contain [query parameters](#). Services should return the HTTP [400 Bad Request](#) status code if provided with a query parameter in a HEAD request.

### 8.4.1 Data modification requests

To create, modify, and delete resources, clients issue the following operations:

- [POST \(create\)](#)
- [PATCH \(update\)](#)
- [PUT \(replace\)](#)
- [DELETE \(delete\)](#)
- [POST \(action\)](#) on the resource

The following clauses describe the success and error response requirements common to all data modification requests.

### 8.4.2 Modification success responses

For create operations, the response from the service, after the create request succeeds, should be one of these responses:

- The HTTP `201 Created` status code with a body that contains the JSON representation of the newly created resource after the request has been applied.
- The HTTP `202 Accepted` status code with a `Location` header set to the URI of a *task monitor* when the processing of the request requires additional time to be completed.
  - After processing of the *task* is complete, the created resource may be returned in response to a request to the task monitor URI with the HTTP `201 Created` status code.
- The HTTP `204 No Content` status code with empty payload in the event that the service cannot return a representation of the created resource.

For update, replace, and delete operations, the response from the service, after successful modification, should be one of the following responses:

- The HTTP `200 OK` status code with a body that contains the JSON representation of the targeted resource after the modification has been applied, or, for the delete operation, a representation of the deleted resource.
- The HTTP `202 Accepted` status code with a `Location` header set to the URI of a task monitor when the processing of the modification requires additional time.
  - After processing of the task is complete, the modified resource may be returned in response to a request to the task monitor URI with the HTTP `200 OK` status code.
- The HTTP `204 No Content` status code with an empty payload in the event that service cannot return a representation of the modified or deleted resource.

For details on successful responses to action requests, see [POST \(action\)](#).

### 8.4.3 Modification error responses

If the resource exists but does not support the requested operation, services may return the HTTP `405 Method Not Allowed` status code.

Otherwise, if the service returns a client `4xx` or service `5xx` status code, the service encountered an error and the resource shall not have been modified or created as a result of the operation.

## 8.5 PATCH (update)

---

To update a resource's properties, the service shall support the PATCH method.

---

The request body defines the changes to make to one or more properties in the resource that the request URI references. The PATCH request does not change any properties that are not in the request body. The service shall ignore OData annotations in the request body, such as [resource identifier](#), [type](#), and [ETag](#) properties. Services may accept a PATCH with an empty JSON object, which indicates that the service should make no changes to the resource.

See the [Modification success responses](#) clause for behavior when the PATCH operation is successful.

To gain the protection semantics of an ETag, the service shall use the `If-Match` or `If-None-Match` header and not the `@odata.etag` property value for that protection.

The implementation may reject the update on certain properties based on its own policies and, in this case, not perform the requested update. For the following exception cases, services shall return the following HTTP status codes and other information:

Exception case	The service returns
<p>Modify several properties where one or more properties can never be updated, but at least one property was successfully updated.</p> <p>For example, when a property is read-only, unknown, or unsupported.</p>	<ul style="list-style-type: none"> <li>The HTTP <a href="#">200 OK</a> status code.</li> <li>A resource representation with a message <a href="#">annotation</a> that lists the non-updatable properties.</li> </ul>
<p>Modify several properties where one or more properties could not be updated due to service-side errors, but at least one property was successfully updated.</p> <p>For example, a write failure for an EEPROM.</p>	<ul style="list-style-type: none"> <li>The HTTP <a href="#">200 OK</a> status code.</li> <li>A resource representation with a message <a href="#">annotation</a> that lists the properties that could not be updated due to service-side errors.</li> </ul>
<p>Modify one or more properties where all properties in the request can never be updated, but the resource can be updated.</p> <p>For example, a property that is read-only, unknown, or unsupported.</p>	<ul style="list-style-type: none"> <li>The HTTP <a href="#">400 Bad Request</a> status code.</li> <li>An <a href="#">extended error response</a> with a messages <a href="#">annotation</a> that show the non-updatable properties.</li> </ul>
<p>A client PATCH request against a resource where the resource or all properties in the resource can never be updated.</p>	<ul style="list-style-type: none"> <li>The HTTP <a href="#">405 Method Not Allowed</a> status code.</li> </ul>
<p>A client PATCH request against a resource collection.</p>	<ul style="list-style-type: none"> <li>The HTTP <a href="#">405 Method Not Allowed</a> status code.</li> </ul>
<p>A client only provides OData annotations.</p>	<ul style="list-style-type: none"> <li>The HTTP <a href="#">400 Bad Request</a> status code with the <code>NoOperation</code> message from the Base Message Registry or one of the <a href="#">modification success responses</a>.</li> </ul>

In the absence of outside changes to the resource, the PATCH operation should be idempotent, although the original `ETag` value may no longer match.

## 8.6 PATCH on array properties

The [Array properties](#) clause describes the three styles of array properties in a resource.

Within a PATCH request, the service shall accept `null` to remove an element, and accept an empty object `{}` to leave an element unchanged. Array properties that use the fixed or variable length style remove those elements, while array properties that use the rigid style replace removed elements with `null` elements. A service may indicate the maximum size of an array by padding `null` elements at the end of the array sequence.

When processing a PATCH request, the order of operations shall be:

- Modifications
- Deletions
- Additions

A PATCH request with fewer elements than in the current array shall remove the remaining elements of the array.

For example, a fixed length-style `Flavors` array indicates that the service supports a maximum of six elements, by padding the array with `null` elements, with four populated.

```
{
  "Flavors": [
    "Chocolate",
    "Vanilla",
    "Mango",
    "Strawberry",
    null,
    null
  ]
}
```

A client could issue the following PATCH request to remove `Vanilla`, replace `Strawberry` with `Cherry`, and add `Coffee` and `Banana` to the array, while leaving the other elements unchanged.

```
{
  "Flavors": [
    {},
    null,
    {},
    "Cherry",
    "Coffee",
    "Banana"
  ]
}
```

```
    ]  
  }
```

After the PATCH operation, the resulting array is:

```
{  
  "Flavors": [  
    "Chocolate",  
    "Mango",  
    "Cherry",  
    "Coffee",  
    "Banana",  
    null  
  ]  
}
```

## 8.7 PUT (replace)

---

To completely replace a resource, services may support the PUT method. The service may add properties to the response resource that the client omits from the request body, the resource definition requires, or the service normally supplies.

The PUT operation should be idempotent in the absence of outside changes to the resource, with the possible exception that the operation might change ETag values.

See the [Modification success responses](#) clause for behavior when the PUT operation is successful.

The following list contains the exception cases for PUT:

- If a service does not implement this method, the service shall return the HTTP [405 Method Not Allowed](#) status code.
- Services may reject requests that do not include properties that the resource definition (schema) requires.
- If the client makes a PUT request against a resource collection, services should return the HTTP [405 Method Not Allowed](#) status code.

## 8.8 POST (create)

---

To create a resource, services shall support the POST method on resource collections.



The POST request is submitted to the resource collection to which the new resource will belong. See the [Modification success responses](#) clause for behavior when the POST operation is successful.

The body of the create request contains a representation of the object to create. The service may ignore any service-controlled properties, such as `Id`, which would force the service to overwrite those properties. Additionally, the service shall set the [Location header](#) in the response to the URI of the new resource.

- Submitting a POST request to a resource collection is equivalent to submitting the same request to the `Members` property of that resource collection. Services that support the addition of `Members` to a resource collection shall support both forms.
  - For example, if a client adds a member to the resource collection at `/redfish/v1/EventService/Subscriptions`, it can send a POST request to either `/redfish/v1/EventService/Subscriptions` or `/redfish/v1/EventService/Subscriptions/Members`.
- If the service does not enable creation of resources, the service shall return the HTTP `405 Method Not Allowed` status code.
- The POST operation shall not be idempotent.
- Services may allow the inclusion of `@Redfish.OperationApplyTime` property in the request body. See [Operation apply time](#).
- Services should return the HTTP `400 Bad Request` status code for requests containing properties with the value `null`.

## 8.9 DELETE (delete)

---

To remove a resource, the service shall support the DELETE method. Resources [subordinate](#) to the resource removed by a DELETE method are typically removed, as the contents of subordinate resources are dependent on the [parent resource](#). In some cases, related resources may also be relocated in the resource tree based on their definition and usage. Other resources in the resource tree may also be removed or incur side effects of a resource removal.

See the [Modification success responses](#) clause for behavior when the DELETE operation is successful.

- If the resource can never be deleted, the service shall return the HTTP `405 Method Not Allowed` status code.
- If the resource was already deleted, the service may return the HTTP `404 Not Found` status code or a [success code](#).
- The service may allow the inclusion of the `@Redfish.OperationApplyTime` property in the request body. See [Operation apply time](#).

## 8.10 POST (Action)

---

Services shall support the POST method to send actions to resources.

- The POST operation may not be idempotent.

- Services may allow the inclusion of the `@Redfish.OperationApplyTime` property in the request body. See [Operation apply time](#).

To request actions on a resource, send the HTTP POST method to the URI of the action. The `target` property in the resource's [Actions property](#) shall contain the URI of the action. The URI of the action shall be in the format:

```
ResourceUri /Actions/ QualifiedActionName
```

where

Variable	Description
<code>ResourceUri</code>	URI of the resource that supports the action.
<code>Actions</code>	Name of the property that contains the actions for a resource, as defined by this specification.
<code>QualifiedActionName</code>	Qualified name of the action. Includes the namespace.

To determine the available [actions](#) and the [valid parameter values](#) for those actions, clients can query a resource directly.

Clients provide parameters for the action as a JSON object within the request body of the POST operation. For information about the structure of the request and required parameters, see the [Actions property](#) clause. Some parameter information may require that the client examine the [Redfish schema](#) that corresponds to the resource.

The service may ignore unsupported parameters provided by the client. If an action does not have any required parameters, the service should accept an empty JSON object in the HTTP body for the action request.

To indicate the success or failure of the action request processing, the service may return a response with one of the following HTTP status codes and additional information:

To indicate	HTTP status code	Additional information
The action request succeeds, and the schema does not contain a response definition.	<code>200 OK</code>	The JSON message body, as described in <a href="#">Error responses</a> , with a message that indicates success or any additional relevant messages. If the action was successfully processed and completed without errors, warnings, or other notifications for the client, the service should return the <code>Success</code> message from the Base Message Registry in the <code>code</code> property in the response body.
The action request succeeds, and the schema contains a response definition for the action.	<code>200 OK</code>	The JSON body in the response conforms to the <a href="#">action response</a> defined in the schema.

To indicate	HTTP status code	Additional information
The action request succeeds, the schema does not contain a response definition, and a <code>Location</code> header in the response contains the URI of a created resource.	201 Created	A <code>Location</code> response header set to the URI of the created resource. The JSON message body, as described in <a href="#">Error responses</a> , with a message that indicates success or any additional relevant messages. If the action was successfully processed and completed without errors, warnings, or other notifications for the client, the service should return the <code>Success</code> message from the Base Message Registry in the <code>code</code> property in the response body.
The action request succeeds, the schema contains a response definition for the action, and a <code>Location</code> header in the response contains the URI of a created resource.	201 Created	A <code>Location</code> response header set to the URI of the created resource. The JSON body in the response conforms to the <a href="#">action response</a> defined in the schema.
The action request may require extra time to process.	202 Accepted	A <code>Location</code> response header set to the URI of a <i>task monitor</i> .
The action request succeeds, and the schema does not contain a response definition.	204 No Content	No JSON message body.
The client did not provide all required parameters.	400 Bad Request	The response may contain a JSON object, as described in <a href="#">Error responses</a> , which details the error or errors.
The client provides a parameter that the service does not support, and the service does not ignore unsupported parameters.	400 Bad Request	The response may contain a JSON object, as described in <a href="#">Error responses</a> , which details the error or errors.
An error was detected and the action request was not processed.	400 or greater	The response may contain a JSON object, as described in <a href="#">Error responses</a> , which details the error or errors.

If an action requested by the client will have no effect, such as performing a reset of a `ComputerSystem` where the `ResetType` parameter is set to `On` and the `ComputerSystem` is already `On`, the service should respond with the HTTP `200 OK` status code and return the `NoOperation` message from the Base Message Registry.

Example successful action response:

```

{
  "error": {
    "code": "Base.1.8.Success",
    "message": "Successfully Completed Request",
    "@Message.ExtendedInfo": [
      {
        "@odata.type": "#Message.v1_1_1.Message",

```

```

        "MessageId": "Base.1.8.Success",
        "Message": "Successfully Completed Request",
        "Severity": "OK",
        "MessageSeverity": "OK",
        "Resolution": "None"
    }
]
}
}

```

## 8.11 Operation apply time

Services may accept the `@Redfish.OperationApplyTime` annotation in the [POST \(create\)](#), [DELETE \(delete\)](#), or [POST \(action\)](#) request body. This annotation enables the client to control when an operation is carried out.

For example, if the client wants to delete a particular `Volume` resource, but can only safely do so when a reset occurs, the client can use this annotation to instruct the service to delete the `Volume` on the next reset.

If multiple operations are pending, the service shall process them in the order in which the service receives them.

Services that support the `@Redfish.OperationApplyTime` annotation for create and delete operations on a resource collection shall include the `@Redfish.OperationApplyTimeSupport` response annotation for the resource collection.

The following example response for a resource collection supports the `@Redfish.OperationApplyTime` annotation in the create and delete requests:

```

{
  "@odata.id": "/redfish/v1/Systems/1/Storage/SATAEmbedded/Volumes",
  "@odata.type": "#VolumeCollection.VolumeCollection",
  "Name": "Storage Volume Collection",
  "Description": "Storage Volume Collection",
  "Members@odata.count": 2,
  "Members": [
    {
      "@odata.id": "/redfish/v1/Systems/1/Storage/SATAEmbedded/Volumes/1"
    },
    {
      "@odata.id": "/redfish/v1/Systems/1/Storage/SATAEmbedded/Volumes/2"
    }
  ],
  "@Redfish.OperationApplyTimeSupport": {
    "@odata.type": "#Settings.v1_2_0.OperationApplyTimeSupport",
    "SupportedValues": [ "Immediate", "OnReset" ]
  }
}

```

```
}

```

In the previous example, a client can annotate their create request body on the `VolumeCollection` itself, or a delete operation on the `volumes` within the `VolumeCollection`.

The following sample request deletes a `Volume` on the next reset:

```
DELETE /redfish/v1/Systems/1/Storage/SATAEmbedded/Volumes/2 HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
OData-Version: 4.0

{
  "@Redfish.OperationApplyTime": "OnReset"
}
```

Services that support the `@Redfish.OperationApplyTime` annotation for an action shall include the `@Redfish.OperationApplyTimeSupport` response annotation for the action.

The following example response for a `ComputerSystem` resource supports the `@Redfish.OperationApplyTime` annotation in the reset action request:

```
{
  "@odata.id": "/redfish/v1/Systems/1",
  "@odata.type": "#ComputerSystem.v1_5_0.ComputerSystem",
  "Actions": {
    "#ComputerSystem.Reset": {
      "target": "/redfish/v1/Systems/1/Actions/ComputerSystem.Reset",
      "ResetType@Redfish.AllowableValues": [
        "On",
        "ForceOff",
        "ForceRestart",
        "Nmi",
        "ForceOn",
        "PushPowerButton"
      ],
    },
    "@Redfish.OperationApplyTimeSupport": {
      "@odata.type": "#Settings.v1_2_0.OperationApplyTimeSupport",
      "SupportedValues": [ "Immediate", "AtMaintenanceWindowStart" ],
      "MaintenanceWindowStartTime": "2017-05-03T23:12:37-05:00",
      "MaintenanceWindowDurationInSeconds": 600,
      "MaintenanceWindowResource": {
        "@odata.id": "/redfish/v1/Systems/1"
      }
    }
  }
}
```

```

    }
  },
  ...
}

```

In the previous example, a client can annotate their reset action request body on the `ComputerSystem` in the payload.

The following sample request completes a reset at the start of the next maintenance window:

```

POST /redfish/v1/Systems/1/Actions/ComputerSystem.Reset HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
OData-Version: 4.0

{
  "ResetType": "ForceRestart",
  "@Redfish.OperationApplyTime": "AtMaintenanceWindowStart"
}

```

Services that support the `@Redfish.OperationApplyTime` annotation for a resource collection or action shall create a *task*, and respond with the HTTP `202 Accepted` status code with a `Location` header set to the URI of a *task monitor*, if the client's request body contains `@Redfish.OperationApplyTime` in the request.

The `Settings` Redfish schema defines the structure of the `@Redfish.OperationApplyTimeSupport` object and the `@Redfish.OperationApplyTime` annotation value.

## 8.12 Deep operations

Implementations may support operations that modify the current resource as well as subordinate resources. These operations are known as deep operations. They give the client the ability to modify more than one resource with a single operation.

The following types of deep operations are defined by this specification:

Operation	Description	Example
Deep PATCH (update)	Modify a resource and one or more subordinate resources.	Modify a <code>ComputerSystem</code> resource as well as subordinate <code>storage</code> and <code>NetworkAdapter</code> resources.
Deep POST (create)	Create multiple resources in a resource collection.	Create <code>ManagerAccount</code> resources.

- Services that support deep PATCH for updating resources shall set the value of the `DeepPATCH` property in the `DeepOperations` property in the `ProtocolFeaturesSupported` property within the service root to `true`.
- Services that support deep POST for creating resources shall set the value of the `DeepPOST` property in the `DeepOperations` property in the `ProtocolFeaturesSupported` property within the service root to `true`.
- The `Members` property in resource collections shall not be removed when using a deep PATCH.
- `Action` URIs shall not support deep POST operations.
- If the service supports deep operations, the `MaxLevels` property in the `DeepOperations` property in the `ProtocolFeaturesSupported` property in the service root shall indicate the maximum number of levels that the service supports for deep operations.
- To request deep operations on a resource, send the HTTP method to the deep operation URI of the resource. The URI for deep operations on any resource shall be in the format: `ResourceUri`.Deep.
- The schema used for validating the root level of the request body shall be the schema of the resource in the resource URI.
  - The subordinate resources included in the request body shall be validated against their corresponding schema.

The body of deep operations contains the resource being modified as well as the subordinate resources being modified. This resource can be a collection or a single instance. These resources could be subordinate resources, subordinate resource collections, or subordinate members of resource collections. The client can omit properties from the request such as those it does not want to modify or that the service controls. Requests that include references to multiple instances, such as members of a collection, shall include the `Members` property as part of the request body.

In order to determine which members of subordinate resource collections are to be modified by a deep PATCH, services shall use the `@odata.id` property provided by the client to identify the member of the resource collection to be modified.

Clients may provide the `@odata.etag` property in subordinate resources being modified by a deep PATCH. If the `If-Match` or `If-None-Match` header is specified in the request, the service shall compare the ETag in the request header with the ETag of the resource specified by the URI. If this check passes, then the operation can proceed using the `@odata.etag` values contained in the body of the subordinate resources. The operation on each subordinate resource shall be performed independently in this case, where some subordinate values that pass the condition check proceed and the resources that fail do not proceed. In this case, annotated `extended information` shall be included in the subordinate resource representation of the response.

Failure semantics for deep operations are similar to that of other `operations of similar type`. If any properties in a deep PATCH operation succeeded, then the result is a `200 OK` with the results returned in the response, and the service should include extended information indicating warnings or errors. For a deep POST operation, if any member of the collection was created then a `201 Created` shall be returned, and any members that were not created should have extended information in their place holders with sufficient identifying information, such as returning all of the properties provided in the POST request body for that member, as well as extended information indicating why the creation was not successful. When performing a deep POST, the value of the `Location` header shall be that of one of

the URIs created and should be that of one of the least subordinate URIs, such as that of a `ComputerSystem` resource and not one of the devices subordinate to the `ComputerSystem` resource.

Deep POST shall not be allowed on the Sessions Collection.

The following is an example of a deep PATCH showing the `RoleCollection` resource with two members being modified:

```
PATCH /redfish/v1/AccountService/Roles.Deep HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
OData-Version: 4.0

{
  "Members": [
    {
      "@odata.id": "/redfish/v1/AccountService/Roles/OperatorRestricted",
      "AssignedPrivileges": [
        "Login",
        "ConfigureComponents"
      ]
    },
    {
      "@odata.id": "/redfish/v1/AccountService/Roles/ReadOnlyRestricted",
      "AssignedPrivileges": [
        "Login"
      ]
    }
  ]
}
```

The following is an example of a deep POST showing the `RoleCollection` resource with two members being created:

```
POST /redfish/v1/AccountService/Roles.Deep HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
OData-Version: 4.0

{
  "Members": [
    {
      "RoleId": "OperatorRestricted",
      "AssignedPrivileges": [
        "Login",
        "ConfigureComponents"
      ]
    }
  ],
}
```



```

    {
      "RoleId": "ReadOnlyRestricted",
      "AssignedPrivileges": [
        "Login"
      ]
    }
  ]
}

```

The following is an example of a deep PATCH showing a `ComputerSystem` resource where there is a request to modify its asset tag and BIOS settings:

```

PATCH /redfish/v1/Systems/47832/Deep HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
OData-Version: 4.0

{
  "AssetTag": "Inventory Tag 12394783431",
  "Bios": {
    "@odata.id": "/redfish/v1/Systems/47832/Bios",
    "@Redfish.Settings": {
      "SettingsObject": {
        "@odata.id": "/redfish/v1/Systems/1/Bios/SD",
        "Attributes": {
          "AdminPhone": "(123) 456-789",
          "BootMode": "Uefi"
        }
      }
    }
  }
}

```

The following shows a deep PATCH operation with ETAGs:

```

PATCH /redfish/v1/AccountService/Roles/Deep HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
If-Match: <Collection ETag>
OData-Version: 4.0

{
  "Members": [
    {
      "@odata.id": "/redfish/v1/AccountService/Roles/OperatorRestricted",
      "@odata.etag": "W/\"ABCDEFGH\"",
    }
  ]
}

```

```

        "AssignedPrivileges": [
            "Login",
            "ConfigureComponents"
        ]
    },
    {
        "@odata.id": "/redfish/v1/AccountService/Roles/ReadOnlyRestricted",
        "@odata.etag": "W/\"ABCDEFGH\"",
        "AssignedPrivileges": [
            "Login"
        ]
    }
]
}

```

The following is an example of a partial failure of a deep PATCH operation with ETags:

```

HTTP/1.1 200 OK
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
ETag: <Resource collection ETag>
OData-Version: 4.0

{
  "Members": [
    {
      "@odata.id": "/redfish/v1/AccountService/Roles/OperatorRestricted",
      "@odata.etag": "W/\"ABCDEFGH\"",
      "AssignedPrivileges": [
        "Login",
        "ConfigureComponents"
      ]
    },
    {
      "@odata.id": "/redfish/v1/AccountService/Roles/ReadOnlyRestricted",
      "@Message.ExtendedInfo": [
        {
          "@odata.type": "#Message.v1_1_1.Message",
          "MessageId": "Base.1.8.PreconditionFailed",
          "RelatedProperties": [
            "#/AssignedPrivileges"
          ]
        }
      ]
    }
  ]
}

```

## 9 Service responses

This clause describes the responses that Redfish services can send to clients.

### 9.1 Response headers

HTTP defines headers for use in response messages. The following table defines those headers and their requirements for Redfish services:

- Redfish services shall return the HTTP 1.1 Specification-defined headers if the value in the **Required** column is **Yes**.
- Redfish services should return the HTTP 1.1 Specification-defined headers if the value in the **Required** column is **No**.
- Redfish clients shall be able to both understand and process all the HTTP 1.1 Specification-defined headers.

Header	Required	Supported values	Description
Access-Control-Allow-Origin	Yes	<a href="#">W3C CORS</a> , Section 5.1	Prevents or allows requests based on originating domain. Prevents CSRF attacks.
Allow	Yes	POST, PUT, PATCH, DELETE, GET, HEAD	Shall be returned with the HTTP <a href="#">405</a> (Method Not Allowed) status code to indicate the valid methods for the request URI. Shall be returned with any GET or HEAD operation to indicate the other allowable operations for this resource.
Cache-Control	Yes	<a href="#">RFC7234</a>	Shall be supported and indicates whether a response can or cannot be cached.
Content-Encoding	No	<a href="#">RFC7231</a>	The encoding that has been performed on the media type.
Content-Length	No	<a href="#">RFC7231</a>	The size of the message body. An optional means of indicating size of the body uses <code>Transfer-Encoding: chunked</code> , that does not use the <code>Content-Length</code> header. If a service does not support <code>Transfer-Encoding</code> and needs <code>Content-Length</code> instead, the service shall respond with the HTTP <a href="#">411 Length Required</a> status code.

Header	Required	Supported values	Description
Content-Type	Yes	RFC7231	<p>The message body's representation type.</p> <p>Services shall specify a <code>Content-Type</code> of <code>application/json</code> when returning resources as JSON.</p> <p>Services shall specify a <code>Content-Type</code> of <code>application/xml</code> when returning metadata as XML.</p> <p>Services shall specify a <code>Content-Type</code> of <code>application/yaml</code> or <code>application/vnd.oai.openapi</code> when returning OpenAPI schema as YAML.</p> <p>Services shall specify a <code>Content-Type</code> of <code>text/event-stream</code> when returning an <a href="#">SSE</a> stream.</p> <p><code>;charset=utf-8</code> shall be appended to the <code>Content-Type</code> if specified in the chosen media-type in the <code>Accept</code> header for the request.</p>
ETag	Conditional	RFC7232	An identifier for a specific version of a resource, often a message digest. The <code>ETag</code> header shall be included on responses to GETs of <code>ManagerAccount</code> resources.
Link	Yes	RFC8288	<code>Link</code> headers shall be returned, as described in the <a href="#">Link headers</a> clause.
Location	Conditional	RFC7231	The URI of a newly created resource. Shall be returned upon creation of a resource. <code>Location</code> and <code>X-Auth-Token</code> shall be included on responses that create user sessions.
Max-Forwards	No	RFC7231	Limits gateway and proxy hops. Prevents messages from remaining in the network indefinitely.
OData-Version	Yes	4.0	The OData version of the payload to which the response conforms.
Retry-After	No	RFC7231, Section 7.1.3	Informs a client how long to wait before requesting the <a href="#">task</a> information again.
Server	No	RFC7231	A product token and its version. Multiple product tokens may be listed.  <b>Note:</b> Previous versions of the Specification marked this header as required. This has been changed as no use cases for requiring it have been identified.
Via	No	RFC7230	Defines the network hierarchy and recognizes message loops. Each pass inserts its own <code>Via</code> header.
WWW-Authenticate	Yes	RFC7617	Required for Basic and other optional authentication mechanisms. For details, see the <a href="#">Security details</a> clause.
X-Auth-Token	Yes	Opaque encoded octet strings	Contains the authentication token for user sessions. The token value shall be indistinguishable from random.

## 9.2 Link header

---

The [Link header](#) provides metadata information on the accessed resource in response to a HEAD or GET request. The metadata information can include hyperlinks from the resource and JSON Schemas that describe the resource.

The following example shows the [Link](#) headers for a [ManagerAccount](#) with an [Administrator](#) role, in addition to a [Settings](#) annotation:

```
Link: </redfish/v1/AccountService/Roles/Administrator>; path=/Links/Role
Link: <http://redfish.dmtf.org/schemas/Settings.json>
Link: </redfish/v1/JsonSchemas/ManagerAccount.v1_0_2.json>; rel=describedby
```

- The first [Link](#) header is an example of a hyperlink that comes from the resource. It describes hyperlinks within the resource. This type of header is outside the scope of this specification.
- The second [Link](#) header is an example of an annotation [Link](#) header as it references the JSON Schema that describes the annotation and does not have [rel=describedby](#). This example references the public copy of the annotation on the DMTF's Redfish schema repository.
- The third [Link](#) header is an example for the JSON Schema that describes the actual resource.
  - Note that the URL can reference an unversioned JSON Schema because the [@odata.type](#) in the resource indicates the appropriate version, or reference the versioned JSON Schema, which according to previous normative statements need to match the version in the [@odata.type](#) property of the resource.

A [Link](#) header containing [rel=describedby](#) shall be returned on GET and HEAD requests. If the referenced JSON Schema is a versioned schema, it shall match the version contained in the value of the [@odata.type](#) property returned in this resource.

A [Link](#) header satisfying annotations should be returned on GET and HEAD requests.

## 9.3 Status codes

---

HTTP defines status codes that appear in responses. The status codes themselves provide general information about how the request was processed, such as whether the request was successful, if the client provided bad information, or the service encountered an error when performing the request.

- When the service returns a status code in the [4xx](#) or [5xx](#) range, services should return an [extended error response](#) in the response body to provide the client more meaningful and deterministic error semantics.
- When the service returns a status code in the [2xx](#) range and the response contains a representation of a resource, services may use [extended information](#) to convey additional information about the resource.
- Extended error messages shall not provide privileged information when authentication failures occur.

**Note:** For security implications of extended errors, See [Security details](#).

The following table lists HTTP status codes that have meaning or usage defined for a Redfish Service, or are otherwise referenced by this specification. Other codes may be returned by the service as appropriate, and their usage is implementation-specific. For usage and additional requirements imposed by this specification, see the **Description** column.

- Clients shall understand and be able to process the status codes in the following table as defined by the HTTP 1.1 Specification and constrained by additional requirements defined by this specification.
- Services shall respond with the status codes in the following table as defined in description column.
- Redfish Services should not return the HTTP 100 status code. Using the HTTP protocol for a multipass data transfer should be avoided, except for the upload of extremely large data.
- If no other status code in the 4XX range is appropriate for client-side errors, the default status code should be the HTTP 400 [Bad Request](#) status code.
- If no other status code in the 5XX range is appropriate for service-side errors, the default status code should be the HTTP 500 [Internal Server Error](#) status code.

HTTP status code	Description
200 OK	Request completed successfully and includes a representation in its body.
201 Created	Request to create a resource completed successfully. The <a href="#">Location header</a> shall be set to the canonical URI for the newly created resource. The response body may include a representation of the newly created resource.
202 Accepted	Request has been accepted for processing but the processing has not been completed. The <a href="#">Location header</a> shall be set to the URI of a <a href="#">task monitor</a> that can later be queried to determine the status of the operation. The response body may include a representation of the <a href="#">Task</a> resource.
204 No Content	The request succeeded, but no content is being returned in the body of the response.
301 Moved Permanently	Requested resource resides under a different URI.
302 Found	Requested resource resides temporarily under a different URI.
304 Not Modified	Service has performed a conditional GET request where access is allowed but the resource content has not changed. Either or both the <a href="#">If-Modified-Since</a> and <a href="#">If-None-Match</a> headers initiate conditional requests to save network bandwidth if no change has occurred. See HTTP 1.1, sections 14.25 and 14.26.
400 Bad Request	Request could not be processed because it contains invalid information, such as an invalid input field, or is missing a required value. The response body shall return an extended error as defined in the <a href="#">Error responses</a> clause.
401 Unauthorized	Authentication credentials included with this request are missing or invalid.
403 Forbidden	Service recognized the credentials in the request but those credentials do not possess authorization to complete this request. This code is also returned when the user credentials provided need to be changed before access to the service can be granted. For details, see the <a href="#">Security details</a> clause.

HTTP status code	Description
404 Not Found	Request specified a URI of a resource that does not exist.
405 Method Not Allowed	HTTP verb in the request, such as DELETE, GET, HEAD, POST, PUT, or PATCH, is not supported for this request URI. The response shall include an <code>Allow</code> header that provides a list of methods that the resource identified by the URI in the client request supports.
406 Not Acceptable	<code>Accept</code> header was specified in the request and the resource identified by this request cannot generate a representation that corresponds to one of the media types in the <code>Accept</code> header.
409 Conflict	Creation or update request could not be completed because it would cause a conflict in the current state of the resources that the platform supports. For example, a conflict occurred due to an attempt to set multiple properties that work in a linked manner by using incompatible values.
410 Gone	Requested resource is no longer available at the service and no forwarding address is known. This condition is expected to be considered permanent. Clients with hyperlink editing capabilities should delete references to the URI in the client request after user approval. If the service does not know or cannot determine whether the condition is permanent, client should use the HTTP <a href="#">404 Not Found</a> status code. This response is cacheable unless otherwise indicated.
411 Length Required	Request did not use the <code>Content-Length</code> header to specify the length of its content but perhaps used the <code>Transfer-Encoding: chunked</code> header instead. The addressed resource requires the <code>Content-Length</code> header.
412 Precondition Failed	Precondition check, such as check of the <code>OData-Version</code> , <code>If-Match</code> , or <code>If-Not-Modified</code> header, failed.
415 Unsupported Media Type	Request specifies a <code>Content-Type</code> for the body that is not supported.
428 Precondition Required	Request did not provide the required precondition, such as an <code>If-Match</code> or <code>If-None-Match</code> header.
431 Request Header Field Too Large	Service is unwilling to process the request because either an individual header field or the collection of all header fields are too large.
500 Internal Server Error	Service encountered an unexpected condition that prevented it from fulfilling the request. The response body shall return an extended error as defined in the <a href="#">Error responses</a> clause.
501 Not Implemented	Service does not currently support the functionality required to fulfill the request. This response is appropriate when the service does not recognize the request method and cannot support the method for any resource.
503 Service Unavailable	Service currently cannot handle the request due to temporary overloading or maintenance of the service. A service may use this response to indicate that the request URI is valid but the service is performing initialization or other maintenance on the resource. It may also use this response to indicate the service itself is undergoing maintenance, such as finishing initialization steps after reboot of the service.
507 Insufficient Storage	Service cannot build the response for the client due to the size of the response.

## 9.4 OData metadata responses

OData metadata describes resources, resource collections, capabilities, and service-dependent behavior to generic OData consumers with no specific understanding of this specification. Clients are not required to request metadata if they already have sufficient understanding of the target service. For example, clients are not required to request metadata to request and interpret a JSON representation of a resource that this specification defines.

A client can access the OData metadata at the `/redfish/v1/$metadata` URI.

A client can access the OData service document at the `/redfish/v1/odata` URI.

### 9.4.1 OData \$metadata

The OData metadata describes top-level service resources and resource types according to [OData Common Schema Definition Language](#). The OData metadata is represented as an XML document with an `Edmx` root element in the `http://docs.oasis-open.org/odata/ns/edmx` namespace with an OData version attribute set to `4.0`.

The service shall use the `application/xml` or `application/xml; charset=utf-8` MIME types to return the OData metadata document as an XML document.

```
<edmx:Edmx xmlns:edmx="http://docs.oasis-open.org/odata/ns/edmx" Version="4.0">
  <!-- edmx:Reference and edmx:Schema elements go here -->
</edmx:Edmx>
```

#### 9.4.1.1 Referencing other schemas

The OData metadata should include the namespaces for each of the Redfish resource types, along with the `RedfishExtensions.v1_0_0` namespace. Dynamic clients that reference the OData metadata document leverage schema definitions that are referenced in order to understand the definitions of the resources in the service. However, there are cases where it might not be practical to maintain an accurate document, such as when resources are dynamically discovered by the service through devices that support Redfish Device Enablement.

These references may use either:

- The standard URI for the published Redfish schema definitions, such as on `http://redfish.dmtf.org/schemas`.
- A URI to a local version of the Redfish schema.

```
<edmx:Reference Uri="http://redfish.dmtf.org/schemas/v1/ServiceRoot_v1.xml">
  <edmx:Include Namespace="ServiceRoot"/>
```



```

    <edm:Include Namespace="ServiceRoot.v1_0_0"/>
  </edm:Reference>

  ...

  <edm:Reference Uri="http://redfish.dmtf.org/schemas/v1/VirtualMedia_v1.xml">
    <edm:Include Namespace="VirtualMedia"/>
    <edm:Include Namespace="VirtualMedia.v1_0_0"/>
  </edm:Reference>
  <edm:Reference Uri="http://redfish.dmtf.org/schemas/v1/RedfishExtensions_v1.xml">
    <edm:Include Namespace="RedfishExtensions.v1_0_0" Alias="Redfish"/>
  </edm:Reference>

```

The service's [OData metadata document](#) shall include an `EntityContainer` that defines the top-level resources and resource collections.

#### 9.4.1.2 Referencing OEM extensions

The OData metadata document may reference additional schema documents that describe OEM-specific extensions that the service uses.

For example, the OData metadata document may reference custom types for additional resource collections.

```

<edm:Reference Uri="http://contoso.org/Schema/CustomTypes">
  <edm:Include Namespace="CustomTypes"/>
</edm:Reference>

```

#### 9.4.2 OData service document

The OData service document serves as a top-level entry point for generic OData clients. More information about the OData service document can be found in the [OData JSON Format Specification](#).

```

{
  "@odata.context": "/redfish/v1/$metadata",
  "value": [
    {
      "name": "Service",
      "kind": "Singleton",
      "url": "/redfish/v1/"
    },
    {
      "name": "Systems",

```

```

        "kind": "Singleton",
        "url": "/redfish/v1/Systems"
    },
    ...
]
}

```

The service shall use the `application/json` MIME type to return the OData service document as a JSON object.

The JSON object shall contain the `@odata.context` context property set to `/redfish/v1/$metadata`.

The JSON object shall include a `value` property set to a JSON array that contains an entry for the [Service Root](#) and each resource that is a direct child of the Service Root.

Each JSON object entry includes:

Property	Defines
<code>name</code>	User-friendly resource name of the resource.
<code>kind</code>	Type of resource. Value is <code>Singleton</code> for all cases defined by Redfish.
<code>url</code>	Relative URL for the top-level resource.

## 9.5 Resource responses

Services use the `application/json` MIME type to return resources and resource collections as JSON payloads. A service shall not break responses for a single resource into multiple results.

The format of these payloads is defined by the Redfish schema. For rules about the Redfish schema and how it maps to JSON payloads, see the [Data model](#) and [Schema definition languages](#) clauses.

## 9.6 Error responses

HTTP status codes often do not provide enough information to enable deterministic error semantics. For example, if a client makes a PATCH call and some properties do not match while others are not supported, the HTTP `400 Bad Request` status code does not tell the client which values are in error. Error responses provide the client more meaningful and deterministic error semantics.

To provide the client with as much information about the error as possible, a Redfish service may provide multiple error responses in the HTTP response. Additionally, the service may provide Redfish standardized errors, OEM-

defined errors, or both, depending on the implementation's ability to convey the most useful information about the underlying error.

An extended error response, which is a single JSON object, defines the error responses, with an `error` property, which contains the following properties.

Property	Description
<code>code</code>	String. Defines a <code>MessageId</code> from the message registry. See the <a href="#">MessageId format clause</a> for the format of <code>MessageId</code> .
<code>message</code>	Displays a human-readable error message that corresponds to the message in the message registry.
<code>@Message.ExtendedInfo</code>	Displays an array of <a href="#">message objects</a> . Describes one or more error messages.

See the [Schema definition languages](#) clause for references to the schema definitions of the error response payload.

The `@Message.ExtendedInfo` property should be present in all error responses. If the `@Message.ExtendedInfo` property is present, all information necessary to process the error should be provided in the `@Message.ExtendedInfo` property. Clients should look for the `@Message.ExtendedInfo` property for error processing first, and fallback on the `code` and `message` properties if `@Message.ExtendedInfo` is not present.

The following sample error response contains two messages in the `@Message.ExtendedInfo` property that describe two different errors. The message described by the `code` and `message` properties do not provide actionable information for the client.

```
{
  "error": {
    "code": "Base.1.8.GeneralError",
    "message": "A general error has occurred. See Resolution for information on how to resolve the error.",
    "@Message.ExtendedInfo": [
      {
        "@odata.type": "#Message.v1_1_1.Message",
        "MessageId": "Base.1.8.PropertyValueNotInList",
        "RelatedProperties": [
          "#/IndicatorLED"
        ],
        "Message": "The value Red for the property IndicatorLED is not in the list of acceptable values.",
        "MessageArgs": [
          "Red",
          "IndicatorLED"
        ],
        "Severity": "Warning",
        "MessageSeverity": "Warning",
        "Resolution": "Choose a value from the enumeration list that the implementation can support and resubmit the r
      },
      {

```

```
    "@odata.type": "#Message.v1_1_1.Message",
    "MessageId": "Base.1.8.PropertyNotWritable",
    "RelatedProperties": [
      "#/SKU"
    ],
    "Message": "The property SKU is a read only property and cannot be assigned a value.",
    "MessageArgs": [
      "SKU"
    ],
    "Severity": "Warning",
    "MessageSeverity": "Warning",
    "Resolution": "Remove the property from the request body and resubmit the request if the operation failed."
  }
]
}
```

## 10 Data model

---

One of the key tenets of Redfish is the separation of protocol from the data model. This separation makes the data both transport and protocol agnostic. By concentrating on the data transported in the payload of the protocol (in HTTP, it is the HTTP body), Redfish can also define the payload in any encoding and the data model is intended to be schema-language agnostic. While Redfish uses the JSON data-interchange format, Redfish provides a common encoding type that ensures property naming conventions that make development easier in JavaScript, Python, and other languages. This encoding type helps the Redfish data model be more easily accessible in modern tools and programming environments.

The data model allows an OEM to extend the model by adding an *OEM resource* or *extending a resource*.

This clause describes common data model, resource, and Redfish schema requirements.

### 10.1 Resources

---

A *resource* is a single entity. Services use the `application/json` MIME type to return resources as JSON payloads.

Each resource shall be strongly typed and defined in a [Redfish schema document](#), and identified in the response payload by a unique [type identifier](#) property.

Responses for a single resource shall contain the following properties:

- `@odata.id`
  - [Registry resources](#) are not required to provide `@odata.id`
- `@odata.type`
- `Id`
- `Name`

Responses may also contain other properties defined within the schema for that resource [type](#). Responses shall not include any properties not defined by that resource type.

### 10.2 Resource collections

---

A *resource collection* is a set of resources that share the same schema definition. Services use the `application/json` MIME type to return resource collections as JSON payloads.

Resource collection responses shall contain the following properties:

- `@odata.id`

- [@odata.type](#)
- [Name](#)
- [Members](#)
- [Members@odata.count](#)

Responses for resource collections may contain the following properties:

- [@odata.context](#)
- [@odata.etag](#)
- [Description](#)
- [Members@odata.nextLink](#)
- [Oem](#)

Responses for resource collections shall not contain any other properties with the exception of [payload annotations](#).

## 10.3 OEM resources

---

OEMs and other third parties can extend the Redfish data model by creating resource types. This is accomplished by defining an OEM schema for each resource type, and connecting instances of those resources to the [resource tree](#).

Companies, OEMs, and other organizations use the [Oem](#) property in resources, the [links property](#), and actions to define additional [properties](#), hyperlinks, and [actions](#) for standard Redfish resources.

While the information and semantics of these extensions are outside of the standard, the schema representing the data, the resource itself, and the semantics around the protocol shall conform to the requirements in this specification. OEMs are encouraged to follow the design tenets and naming conventions in this specification when defining OEM resources or properties.

## 10.4 Common data types

---

The following clause details the data types found throughout the Redfish data model.

### 10.4.1 Primitive types

The following are the primitive data types in the data model:

Type	Description
Boolean	A variable with a value of <code>true</code> or <code>false</code> .

Type	Description
Number	A number with optional decimal point or exponent. Number properties may restrict the representation to an integer or a number with decimal point.
String	A sequence of characters enclosed with double quotes ( " ).
Array	A comma-separated set of the previous types enclosed with square braces ( [ and ] ). See the <a href="#">Array properties</a> clause.
Object	A set of properties enclosed with curly braces ( { and } ). See the <a href="#">Structured properties</a> clause.
Null	The <code>null</code> value, which the service uses when it is unable to determine the property's value due to an error or other temporary condition, or if the schema has requirements for using <code>null</code> for other special conditions.

When receiving values from the client, services should support other valid representations of the data in the specified JSON type. In particular, services should support valid integer and decimal values in exponential notation and integer values that contain a decimal point with no non-zero trailing digits.

### 10.4.2 Empty string values

String properties should return an empty string ("" ) for properties configured by a user or external service that have not been set to an initial value. This allows client software to identify the property as supported by the service, and avoids the use of `null` , which indicates an error condition. For example, the `AssetTag` property must be set by the end user, and therefore would return an empty string ("" ) until assigned a value by the user, while a failure to read the stored `AssetTag` value due to a non-volatile memory error would return `null` . To improve interoperability, implementations should avoid the use of filler strings, such as `N/A` or `<Empty>` , to represent a value not set by a user.

### 10.4.3 GUID and UUID values

Globally Unique Identifier (GUID) and Universally Unique Identifier (UUID) values are unique identifier strings and shall use the format:

```
{[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}}
```

### 10.4.4 Date-Time values

Date-Time values are strings according to the ISO 8601 extended format, including the time offset or UTC suffix.

Date-Time values shall use the format:

```
YYYY - MM - DD T hh : mm : ss [. SSS ](Z|((+|-) HH : MM ))
```

where

Variable or separator	Description
<code>YYYY</code>	Four-digit year.
<code>MM</code>	Two-digit month (1 to 12).
<code>DD</code>	Two-digit day (1 to 31).
<code>T</code>	Time separator. Shall be a capital <code>T</code> .
<code>hh</code>	Two-digit hour (0 to 23).
<code>mm</code>	Two-digit minute (0 to 59).
<code>ss</code>	Two-digit second (0 to 59).
<code>SSS</code>	Optional. Decimal fraction of a second. Shall be one or more digits where the number of digits implies the precision.
<code>Z</code>	Zero offset indicator. Shall be a capital <code>Z</code> .
<code>HH</code>	Two-digit hour offset (0 to 23).
<code>MM</code>	Two-digit minute offset (0 to 59).

For example, `2015-03-13T04:14:33+06:00` represents March 13, 2015 at 4:14:33 with a +06:00 time offset.

When the time of day is unknown or serves no purpose, the service shall report `00:00:00Z` for the time of day value.

### 10.4.5 Duration values

Duration values are strings according to the ISO 8601 duration format, with the exception of not expressing a representation for years, months, or weeks. Duration values shall use the format:

```
P[ d D][T[ h H][ m M][ s [. f ]S]]
```

where

Variable	Description
<code>d</code>	Number of days.
<code>h</code>	Number of hours.
<code>m</code>	Number of minutes.
<code>s</code>	Number of seconds.
<code>f</code>	Fractional seconds.



Each field is optional and may contain more than one digit.

For example, the following values represent the following durations:

Value	Duration
P90D	Ninety days.
P3D	Three days.
PT6H	Six hours.
PT10S	Ten seconds.
PT0.001S	0.001 seconds.
PT1H30M	One hour and 30 minutes.

**DEPRECATED:** Duration values shall use the format:

`P[ y Y][ m M][ w W][ d D][T[ h H][ m M][ s [. f ]S]]`. This definition allows for specifying years, months, and weeks. ISO 8601 does not specify an exact value for the duration of a year or of a month, which introduces interoperability challenges.

## 10.4.6 Reference properties

Reference properties provide a reference to another resource in the data model. Reference properties are JSON objects that contain an `@odata.id` property. The `@odata.id` property value is the URI of the referenced resource.

## 10.4.7 Non-resource reference properties

Non-resource reference properties provide a reference to services or documents that are not Redfish-defined resources. These properties shall include the `uri` term in their property name. For example, `AssemblyBinaryDataUri` in the Assembly schema. The access protocol and data format of the referenced URI may be defined in schema for that property. Non-resource reference properties that refer to local HTTP/S targets shall follow the Redfish protocol, including use of Redfish sessions and access control, unless otherwise specified by the property definition in schema.

## 10.4.8 Array properties

Array properties contain a set of values or objects, and appear as JSON arrays within a response body. Array elements shall all contain values of the same data type.

There are three styles of arrays, regardless of the data type of the elements:

Array style	Description
Fixed length	Contains a static number of elements. The property definition sets or the implementation chooses the size of the array.
Variable length	Contains a variable number of elements. The array size is not specified and the size varies among instances. The array size may change. This array style is the most common style.
Rigid	<p>The array index is meaningful. When elements are added to or removed from the array, the elements do not change their position, or index, in the array. An element that is removed from a rigid array shall be replaced by a <code>null</code> element and all other elements shall remain at their current index.</p> <p>Empty elements in a rigid array property shall be represented by <code>null</code> elements. Any array property that uses this style shall indicate the rigid style in the <a href="#">long description</a> of its schema definition.</p>

Services may pad an array property with `null` elements at the end of the sequence to indicate the array size to clients. This is useful for small fixed length arrays, and for variable or rigid arrays with a restrictive maximum size. Services should not pad array properties if the maximum array size is not restrictive. For example, an array property typically populated with two elements, that a service limits to a maximum of 16 elements, should not pad the array with 14 `null` elements.

### 10.4.9 Structured properties

Structured properties are JSON objects within a response body.

Some structured properties inherit from the `Resource.v1_0_0.ReferenceableMember` definition. Structured properties that follow this definition shall contain the [MemberId](#) and [resource identifier](#) properties.

Because the definition of structured properties can evolve over time, clients need to be aware of the inheritance model that the different structured property definitions use.

For example, the `Location` property definition in the `Resource` schema has gone through several iterations since the `Resource.v1_1_0` namespace was introduced, and each iteration inherits from the earlier version so that existing references in other schemas can leverage the additions.

Structured property references need to be resolved for both local and external references.

A local reference is a resource that has a structured property in its own schema, such as `ProcessorSummary` in the `ComputerSystem` resource. In these cases, the [type](#) property for the resource is the starting point for resolving the structured property definition.

To find the latest applicable version, clients can step the [version of the resource](#) backwards.

For example, if a service returns `#ComputerSystem.v1_4_0.ComputerSystem` as the resource type, a client can step

backwards from `ComputerSystem.v1_4_0`, to `ComputerSystem.v1_3_0`, to `ComputerSystem.v1_2_0`, and so on, until it finds the `ProcessorSummary` structured property definition.

An external reference is a resource that has a property that references a definition found in a different schema, such as the `Location` property in the `Chassis` resource.

In these cases, clients can use the latest version of the external schema file as a starting point to resolve the structured property definition.

For example, if the latest version of the `Resource` schema is `1.6.0`, a client can go backward from `Resource.v1_6_0`, to `Resource.v1_5_0`, to `Resource.v1_4_0`, and so on, until it finds the `Location` structured property definition.

## 10.4.10 Message object

### 10.4.10.1 Overview

A message object provides additional information about an [object](#), [property](#), or [error response](#).

A message object is a JSON object with the following properties:

Property	Type	Required	Defines
<code>MessageId</code>	String	Yes	The error or message. Do not confuse this value with the HTTP status code. Clients can use this code to access a detailed message from a message registry.
<code>Message</code>	String	No	The human-readable error message that indicates the semantics associated with the error. This shall be the complete message, and not rely on substitution variables.
<code>RelatedProperties</code>	An array of JSON pointers	No	The properties in a JSON payload that the message describes.
<code>MessageArgs</code>	An array of strings	No	The substitution parameter values for the message. If the parameterized message defines a <code>MessageId</code> , the service shall include the <code>MessageArgs</code> in the response.
<code>MessageSeverity</code>	String (enumeration)	No	The severity of the error. Services can replace the value of the <code>MessageSeverity</code> property defined in the message registry with a value more applicable to the implementation.
<code>Severity</code>	String	No	The severity of the error. Services can replace the value of the <code>Severity</code> property defined in the message registry with a value more applicable to the implementation.  <b>DEPRECATED:</b> This property has been deprecated in favor of <code>MessageSeverity</code> .
<code>Resolution</code>	String	No	The recommended actions to take to resolve the error. Services can replace the value of the <code>Resolution</code> property defined in the message registry with a service-defined resolution.

Each instance of a message object shall contain at least a `MessageId`, together with any applicable `MessageArgs`, or a `Message` property that defines the complete human-readable error message.

A `MessageId` identifies a specific message that a [message registry](#) defines.

#### 10.4.10.2 MessageId format

The `MessageId` property value shall be in the format:

```
RegistryName . MajorVersion . MinorVersion . MessageKey
```

where

Variable	Description
<code>RegistryName</code>	Name of the registry. The registry name shall be Pascal-cased.
<code>MajorVersion</code>	Non-negative integer. The major version of the registry.
<code>MinorVersion</code>	Non-negative integer. The minor version of the registry.
<code>MessageKey</code>	Human-readable key into the registry. The message key shall be Pascal-cased and shall not include spaces, periods, or special characters.

To search the message registry for a message, the client can use the `MessageId`.

The message registry approach has advantages for internationalization because the registry can be translated easily, and is lightweight for implementations because large strings need not be included with the implementation.

The use of `GeneralError` from the Base Message Registry as a `MessageId` in `ExtendedInfo` is discouraged. If no better message exists or the `ExtendedInfo` array contains multiple messages, use `GeneralError` from the Base Message Registry only in the `code` property of the `error` object.

When an implementation uses `GeneralError` from the Base Message Registry in `ExtendedInfo`, the implementation should include a service-defined value for the `Resolution` property with this error to indicate how to resolve the problem.

## 10.5 Properties

Every property included in a Redfish response payload shall be defined in the schema for that [resource](#). The following attributes apply to all property definitions:

- Property names in the request and response payload shall match the casing of the `Name` attribute value in the defining schema.

- Required properties shall always be returned in a response.
- Properties not returned from a GET operation indicate that the property is not supported by the implementation, or by that particular resource instance. Differences in underlying product support or configuration will vary among resource instances, and therefore the properties returned by each instance will vary accordingly.
- If an implementation supports a property, it shall always provide a value for that property. If a value is unknown at the time of the operation, due to an internal error, the current resource state, or inaccessibility of the data, then the value of `null` is an acceptable value if supported by the schema definition.
- Resource instances should omit properties if the underlying product or service does not provide the function described by the property. For example, a chassis resource instance might not provide a serial number, and therefore should omit the `SerialNumber` property, while other chassis resource instances that have a serial number can provide this property.
- A service may implement a writable property as read-only.

This clause also contains a set of common properties across all Redfish resources. The property names in this clause shall not be used for any other purpose.

### 10.5.1 Resource identifier (@odata.id) property

[Registry resources](#) in a response may include an `@odata.id` property. All other [resources](#) in a response shall include an `@odata.id` property. The value of the identifier property shall be the resource [URI](#).

### 10.5.2 Resource type (@odata.type) property

All [resources](#) in a response shall include an `@odata.type` type property. To support generic OData clients, all [structured properties](#) in a response should include an `@odata.type` type property. The value shall be a URL fragment that specifies the type of the resource and shall be in the format:

```
# Namespace . TypeName
```

where

Variable	Description
<code>Namespace</code>	Full namespace name of the Redfish schema that defines the type. For Redfish resources, the versioned namespace name.
<code>TypeName</code>	Name of the resource type.

An example of a resource type value is `#ComputerSystem.v1_0_0.ComputerSystem`, where `ComputerSystem.v1_0_0` denotes the version 1.0.0 namespace of `ComputerSystem`, and the type itself is `ComputerSystem`.

### 10.5.3 Resource ETag (@odata.etag) property

ETags enable clients to conditionally retrieve or update a [resource](#). Resources should include an `@odata.etag` property. For a resource, the value shall be the [ETag](#).

### 10.5.4 Resource context (@odata.context) property

Responses for a single [resource](#) may contain an `@odata.context` property that describes the source of the payload.

If the `@odata.context` property is present, it shall be the context URL that describes the resource, according to [OData Protocol](#).

The context URL for a resource should be in the format:

```
/redfish/v1/$metadata# ResourceType
```

where

Variable	Description
<i>ResourceType</i>	Fully qualified name of the unversioned resource type. Redfish resource definitions concatenate the resource type namespace with a period ( . ) followed by the resource type.

For example, the following context URL specifies that the results show a single `ComputerSystem` resource:

```
{
  "@odata.context": "/redfish/v1/$metadata#ComputerSystem.ComputerSystem",
  ...
}
```

The context URL for a resource may be in one of the other formats that [OData Protocol](#) specifies.

### 10.5.5 Id

The `Id` property of a [resource](#) uniquely identifies the resource within the resource collection that contains it. The value of `Id` shall be unique across a [resource collection](#). The `Id` property shall follow the definition for `Id` in the `Resource` schema.

### 10.5.6 Name

The `Name` property conveys a human-readable moniker for a [resource](#). The type of the `Name` property shall be string.

The value of `Name` is NOT required to be unique across resource instances within a [resource collection](#). The `Name` property shall follow the definition for `Name` in the `Resource` schema.

### 10.5.7 Description

The `Description` property conveys a human-readable description of the [resource](#). The `Description` property shall follow the definition for `Description` in the `Resource` schema.

### 10.5.8 MemberId

The `MemberId` property uniquely identifies an element within an array, where a [reference property](#) can reference the element. The `MemberId` value shall be unique across the array. The `MemberId` property shall follow the definition for `MemberId` in the `Resource` schema.

### 10.5.9 Count ([Members@odata.count](#)) property

The count property defines the total number of [resource](#), or [members](#), that are available in a [resource collection](#). The count property shall be named `Members@odata.count` and its value shall be the total number of members available in the resource collection. The `$top` or `$skip` [query parameters](#) shall not affect this count. If the number of members available in the resource collection is reduced due to filtering, such as in response to the `$filter` query parameter, the count should be the total number of members available in the resource collection after the filter is applied.

### 10.5.10 Members

The `Members` property of a [resource collection](#) identifies the [members](#) of the collection. The `Members` property is required and shall be returned in the response for any resource collection. The `Members` property shall be an array of JSON objects named `Members`. The `Members` property shall not be `null`. Empty collections shall be an empty JSON array.

### 10.5.11 Next link ([Members@odata.nextLink](#)) property

The value of the Next Link property shall be an opaque URL to a resource, with the same `@odata.type`, which contains the next set of partial [members](#) from the original operation. The Next Link property shall only be present if the number of members in the resource collection is greater than the number of members returned, and if the payload does not represent the end of the requested resource collection.

The [Members@odata.count](#) property value is the total number of resources available if the client enumerates all pages of the resource collection.

## 10.5.12 Links

The `Links` property represents the hyperlinks associated with the [resource](#), as defined by that resource's schema definition. All associated [reference properties](#) defined for a resource shall be nested under the links property. All directly ([subordinate](#)) referenced properties defined for a resource shall be in the root of the resource.

The links property shall be named `Links` and contain a property for each related resource.

To navigate vendor-specific hyperlinks, the `Links` property shall also include an `Oem` property.

### 10.5.12.1 Reference to a related resource

A reference to a single [resource](#) is a JSON object that contains a single [resource identifier property](#). The name of this reference is the name of the relationship. The value of this reference is the URI of the referenced resource.

```
{
  "Links": {
    "ManagedBy": {
      "@odata.id": "/redfish/v1/Chassis/Enc11"
    }
  }
}
```

### 10.5.12.2 References to multiple related resources

A reference to a set of zero or more related [resources](#) is an array of JSON objects. The name of this reference is the name of the relationship. Each element of the array is a JSON object that contains a [resource identifier property](#) with the value of the URI of the referenced resource.

```
{
  "Links": {
    "Contains": [
      {
        "@odata.id": "/redfish/v1/Chassis/1"
      },
      {
        "@odata.id": "/redfish/v1/Chassis/Enc11"
      }
    ]
  }
}
```



### 10.5.13 Actions property

The `Actions` property contains the `actions` supported by a `resource`.

#### 10.5.13.1 Action representation

Each supported action is represented as a property nested under `Actions`. The unique name that identifies the action is used to construct the property name.

This property name shall be in the format:

```
# ResourceType . ActionName
```

where

Variable	Description
<code>ResourceType</code>	Resource where the action is defined.
<code>ActionName</code>	Name of the action.

The client may use this fragment to identify the action definition in the [referenced](#) Redfish schema document.

The property for the action is a JSON object and contains the following properties:

- The `target` property shall be present, and defines the relative or absolute URL to invoke the action.
- The `title` property may be present, and defines the action's name.

The [OData JSON Format](#) Specification defines the `target` and `title` properties.

To specify the list of supported values for a parameter, the service may include the `@Redfish.AllowableValues` annotation.

For example, the following property defines the `Reset` action for a `ComputerSystem`:

```
{
  "#ComputerSystem.Reset": {
    "target": "/redfish/v1/Systems/1/Actions/ComputerSystem.Reset",
    "title": "Computer System Reset",
    "ResetType@Redfish.AllowableValues": [
      "On",
      "ForceOff",
      "GracefulRestart",
    ]
  }
}
```

```
        "GracefulShutdown",
        "ForceRestart",
        "Nmi",
        "ForceOn",
        "PushPowerButton"
    ]
},
...
}
```

Given this, the client could invoke a POST request to `/redfish/v1/Systems/1/Actions/ComputerSystem.Reset` with the following body:

```
POST /redfish/v1/Systems/1/Actions/ComputerSystem.Reset HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
OData-Version: 4.0

{
  "ResetType": "On"
}
```

The resource may provide a separate `@Redfish.ActionInfo` resource to describe the parameters and values that a particular instance or implementation supports. Use the `@Redfish.ActionInfo` annotation to specify the `ActionInfo` resource, which contains a URI to the `@Redfish.ActionInfo` resource for the action. For details, see the [Action info annotation](#) clause.

### 10.5.13.2 Action responses

Response payloads for actions may contain a JSON body that is described by the schema definition for the action. See the [Schema definition languages](#) clause for the representation of these definitions. Actions that do not define a response body may provide an [error response](#) in the response payload.

### 10.5.14 Oem

The `Oem` property is used for [extending standard resources](#) with OEM extensions.

### 10.5.15 Status

The `Status` property represents the status of a [resource](#). The `Status` property shall follow the definition for `Status` in the `Resource` schema.

By having a common representation of status, clients can depend on consistent semantics. The `Status` property is capable of indicating the current state, health of the resource, and the health of subordinate resources.

## 10.6 Resource, schema, property, and URI naming conventions

---

The Redfish interface is intended to be easily readable and intuitive. Thus, consistency helps the consumer who is unfamiliar with a newly discovered property understand its use. While this is no substitute for the normative information in the Redfish Specification and Redfish schema, the following rules help with readability and client usage. In general, names in Redfish are designed and intended to be human-readable and convey the meaning of the name, in context, without the need to consult schema definitions or other documentation.

Standard Redfish [resources](#) defined and published in the repository, or those created by others and republished, shall follow a set of naming conventions. These conventions are intended to ensure consistent naming and eliminate naming collisions. The resource name is used to construct the [type property](#) and the schema file name.

Standard Redfish properties follow similar naming conventions, and should use a common definition when defined in multiple schemas across the Redfish data model. This consistency enables code re-use across resources and increases interoperability. New resource definitions should leverage existing property definitions whenever possible.

The naming rules for schemas, properties, and enumerations are as follows:

- Names shall be Pascal-cased. The first letter of each word in a name shall be uppercase and spaces between words shall be removed. For example, `ComputerSystem`, `PowerState`, and `SerialNumber`.
- Names shall not contain spaces or underscore characters. Names should not contain any special characters that violate naming rules for supported schema description languages or programming languages.
- Both characters should be capitalized for two-character acronyms. For example, `IPAddress` or `RemoteIP`.
- Names constructed from a single acronym or mixed-case name, such as `LDAP`, `PCIe`, or `SNMP`, should use the typical capitalization for that name.
- Names incorporating acronyms with three or more characters should follow the capitalization used in related names for consistency. For example, `EnableSNMPv1` and `EnableSNMPv2` follow the pattern used for `SNMP`.
- Pascal-casing may be used for acronyms longer than two characters to improve readability, especially when two or more acronyms appear together in a name, which should be avoided.
- Enumeration names should start with a letter and be followed by letters or numbers, in order to conform to schema description language requirements. Underscore characters may be used to replace other special characters, or to significantly improve readability, but this usage is discouraged.
- Enumeration names should prioritize readability as they may appear unmodified on user interfaces, whereas property or schema names should follow conventions and strive for consistency.

Exceptions are allowed for the following cases:

- Well-known technology abbreviations, acronyms, or product names should follow their defined capitalization. Examples include `iSCSI`, `iSCSITarget`, and `iLO`.

- OEM appears as `oem` in schema and property names either alone or as a portion of a name, but should be `OEM` when used alone as an enumeration value.

For properties that have units or other special meaning, append a unit identifier to the name. Examples include:

- Bandwidth (Mbps). For example, `PortSpeedMbps` .
- CPU speed (Mhz). For example, `ProcessorSpeedMhz` .
- Memory size (MB). For example, `MemoryMB` .
- Counts of items (Count). For example, `ProcessorCount` or `FanCount` .
- The state of a resource (State). For example, `PowerState` .
- State values where work is in process. For example, `Applying` or `ClearingLogic` .

In addition, the following rules apply to Redfish schema-defined URIs:

- URI segments should generally follow the naming rules, and follow the name of the Redfish schema that defines the resource located at each segment.
- URI segments for resource collections should use the plural form of the resource collection schema name, with the `Collection` term omitted. For example, `Processors` for a `ProcessorCollection` .
- For resources that contain hyperlinks to more than one resource or resource collection of the same schema type, the URI segments should follow the name of the property that provides the hyperlink, for clarity.
- If a hyperlink to a subordinate resource is not found at the root of the resource, the URI segments should contain the property path. For example, for the `Certificates` hyperlink found in `ManagerNetworkProtocol` within the `HTTPS` object, `HTTPS` should be one of the URI segments.

## 10.7 Extending standard resources

---

In the context of this clause, the OEM term refers to any company, manufacturer, or organization that provides or defines an extension to the DMTF-published schema and functionality for Redfish. All Redfish-specified [resources](#) include an empty structured `oem` property. Its value can encapsulate one or more OEM-specified structured properties. This predefined placeholder can contain OEM-specific property definitions.

### 10.7.1 OEM property format and content

Each property contained within the `oem` property shall be a JSON object. The name of the object (property) shall uniquely identify the OEM or organization that defines the properties contained by that object. This is described in more detail in the following clause.

The OEM-specified object shall include a [type property](#) that provides the location of the schema and the type definition for the property within that schema if the OEM-specified object:

- Is not contained in an array of objects.

- Is contained in the first object within an array of objects.
- In subsequent array members containing an OEM-specified object, whose type is different than the first array member.

The `oem` property can simultaneously hold multiple OEM-specified objects, including objects for more than one company or organization.

The definition of any other properties that are contained within the OEM-specific object, along with the functional specifications, validation, or other requirements for that content is OEM-specific and outside the scope of this specification. While there are no Redfish-specified limits on the size or complexity of the OEM-specified elements within an OEM-specified JSON object, it is intended that OEM properties typically be used for only a small number of simple properties that augment the Redfish [resource](#). If a large number of objects or a large quantity of data compared to the size of the Redfish resource is to be supported, the OEM should consider having the OEM-specified object point to a separate resource for their extensions.

### 10.7.2 OEM property naming

The OEM-specified objects within the `oem` property are named by using a unique OEM identifier for the top of the namespace under which the property is defined. There are two specified forms for the identifier. The identifier shall be either an ICANN-recognized domain name (including the top-level domain suffix), with all dot ( `.` ) separators replaced with underscores ( `_` ), or an IANA-assigned Enterprise Number prefixed with "EID\_."

**DEPRECATED:** The identifier shall be either an ICANN-recognized domain name including the top-level domain suffix, or an IANA-assigned Enterprise Number prefixed with `EID:` .

Organizations that use `.com` domain names may omit the `.com` suffix. For example, Contoso.com would use `Contoso` instead of `Contoso_com` , but Contoso.org would use `Contoso_org` . The domain name portion of an OEM identifier shall be considered to be case independent. That is, the text `Contoso_biz` , `contoso_BIZ` , `conT0so_biZ` , and so on all identify the same OEM and top-level namespace.

The OEM identifier portion of the property name may be followed by an underscore ( `_` ) and any additional string to enable further creation of namespaces of OEM-specified objects as desired by the OEM. For example, `Contoso_xxxx` or `EID_412_xxxx` . The form and meaning of any text that follows the trailing underscore is completely OEM-specific. OEM-specified extension suffixes may be case sensitive, depending on the OEM. Generic client software should treat such extensions, if present, as opaque and not try to parse nor interpret the content.

This suffix could be used in many ways, depending on OEM need. For example, the Contoso company may have a *Research* suborganization, in which case the OEM-specified property name might be extended to `Contoso_Research`. Alternatively, it can identify a namespace for a functional area, geography, subsidiary, and so on.

The OEM identifier portion of the name typically identifies the company or organization that created and maintains the schema for the property. However, this is not a requirement. The identifier is only required to uniquely identify the party that is the top-level manager of a namespace to prevent collisions between OEM property definitions from

different vendors or organizations. Consequently, the organization for the top of the namespace may be different than the organization that provides the definition of the OEM-specified property. For example, Contoso may allow one of their customers, such as `CustomerA`, to extend a Contoso product with certain CustomerA proprietary properties. In this case, although Contoso allocated the name `Contoso_customers_CustomerA`, it could be CustomerA that defines the content and functionality under that namespace. In all cases, OEM identifiers should not be used except with permission or as specified by the identified company or organization.

### 10.7.3 OEM resource naming and URIs

Companies, OEMs, and other organizations can define additional [resources](#) and link to them from an [OEM property](#) found in a standard Redfish resource. To avoid naming collisions with current or future standard Redfish schema files, the defining organization's name should be prepended to the resource name. For example, `ContosoDrive` would not conflict with a `Drive` resource or another OEM's drive-related resource.

To avoid URI collisions with other OEM resources and future Redfish standard resources, the URIs for OEM resources within the Redfish [resource tree](#) shall be in the form:

```
BaseUri /Oem/ OemName / ResourcePath
```

where

Variable	Description
<code>BaseUri</code>	URI segment of the standard Redfish resource starting with <code>/redfish/</code> where the <code>Oem</code> property is used. For example, <code>/redfish/v1/Systems/3AZ38944T523</code> .
<code>OemName</code>	Name of the OEM, that follows the same naming as defined in the <a href="#">OEM property format and content</a> clause.
<code>ResourcePath</code>	Path to the OEM-defined resource. This path might contain multiple segments for cases where OEM-defined resources are subordinate to an OEM-defined resource. Each segment in the path contains the name of an OEM-defined resource.

For example, if Contoso defined a new `ContosoAccountServiceMetrics` resource to be linked through the `Oem` property at the `/redfish/v1/AccountService` URI, the OEM resource has the `/redfish/v1/AccountService/Oem/Contoso/AccountServiceMetrics` URI.

### 10.7.4 OEM property examples

The following fragment presents some examples of naming and use of the `Oem` property as it might appear when accessing a [resource](#). The example shows that the OEM identifiers can be of different forms, that OEM-specified content can be simple or complex, and that the format and usage of extensions of the OEM identifier is OEM-specific.

```
{
  "Oem": {
```

```

    "Contoso": {
      "@odata.type": "#Contoso.v1_2_1.AnvilTypes1",
      "slogan": "Contoso anvils never fail",
      "disclaimer": "* Most of the time"
    },
    "Contoso_biz": {
      "@odata.type": "#ContosoBiz.v1_1.RelatedSpeed",
      "speed" : "ludicrous"
    },
    "EID_412_ASB_123": {
      "@odata.type": "#OtherSchema.v1_0_1.powerInfoExt",
      "readingInfo": {
        "readingAccuracy": "5",
        "readingInterval": "20"
      }
    },
    "Contoso_customers_customerA": {
      "@odata.type" : "#ContosoCustomer.v2015.slingPower",
      "AvailableTargets" : [ "rabbit", "duck", "runner" ],
      "launchPowerOptions" : [ "low", "medium", "eliminate" ],
      "powerSetting" : "eliminate",
      "targetSetting" : "rabbit"
    }
  },
  ...
}

```

### 10.7.5 OEM actions

OEM-specific actions appear in the JSON payload as properties of the `Oem` object, nested under an `Actions` property.

The name of the property that represents the action, which shall follow the form:

```
# Namespace . Action
```

where

Variable	Description
<code>Namespace</code>	Namespace.
<code>Action</code>	Action.

```
{
```

```

    "Actions": {
      "Oem": {
        "#Contoso.Ping": {
          "target": "/redfish/v1/Systems/1/Actions/Oem/Contoso.Ping"
        }
      }
    },
    ...
  }

```

The URI of the OEM action in the `target` property shall be in the form:

*ResourceUri* /Actions/Oem/ *Namespace* . *Action*

where

Variable	Description
<i>ResourceUri</i>	URI of the resource that supports invoking the action. For example, <code>/redfish/v1/Systems/1/</code> .
<code>Actions</code>	Name of the property containing the actions for a resource.
<code>Oem</code>	Name of the OEM property within the <code>Actions</code> property.
<i>Namespace</i> . <i>Action</i>	Namespace followed by the action. For example, <code>Contoso.Ping</code> .

## 10.8 Payload annotations

[Resources](#), [objects within a resource](#), and [properties](#) may include additional annotations as properties with the name, in the format:

[ *PropertyName* ]@ *Namespace* . *TermName*

where

Variable	Description
<i>PropertyName</i>	Name of the property to annotate. If absent, the annotation applies to the entire JSON object, which may be an entire resource.
<i>Namespace</i>	Namespace that defines the annotation term.
<i>TermName</i>	Annotation term to apply to the resource or property of the resource.



Services shall limit the annotation usage to the `odata`, `Redfish`, and `Message` namespaces. The [OData JSON Format Specification](#) defines the `odata` namespace. The `Redfish` namespace is an alias for the `RedfishExtensions.v1_0_0` namespace.

The client can get the definition of the annotation from the [OData metadata document](#), the [HTTP Link header](#), or may ignore the annotation entirely, but should not fail reading the resource due to unrecognized annotations, including new annotations that the `Redfish` namespace defines.

### 10.8.1 Allowable values

To specify the list of allowable values for a [property](#) or [action](#) parameter, services may use the `@Redfish.AllowableValues` annotation for properties or action parameters.

To specify the set of allowable values, include a property with the name of the property or action parameter, followed by `@Redfish.AllowableValues`. The property value is a JSON array of strings that define the allowable values for the property or action parameter.

### 10.8.2 Extended information

The following clauses describe the methods of providing extended information:

- [Extended object information](#)
- [Extended property information](#)

#### 10.8.2.1 Extended object information

To specify object-level status information, services may annotate a JSON object with the `@Message.ExtendedInfo` annotation.

```
{
  "@odata.id": "/redfish/v1/Managers/1/SerialInterfaces/1",
  "@odata.type": "#SerialInterface.v1_0_0.SerialInterface",
  "Name": "Managed Serial Interface 1",
  "Description": "Management for Serial Interface",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "InterfaceEnabled": true,
  "SignalType": "Rs232",
  "BitRate": "115200",
  "Parity": "None",
  "DataBits": "8",
  "StopBits": "1",
}
```

```

"FlowControl": "None",
"ConnectorType": "RJ45",
"PinOut": "Cyclades",
"@Message.ExtendedInfo": [
  {
    "MessageId": "Base.1.8.PropertyDuplicate",
    "Message": "Indicates that a duplicate property was included in the request body.",
    "RelatedProperties": [
      "#/InterfaceEnabled"
    ],
    "Severity": "Warning",
    "MessageSeverity": "Warning",
    "Resolution": "Remove the duplicate property from the request body and resubmit the request if the operation failed."
  }
]
}

```

The property contains an array of [message objects](#).

### 10.8.2.2 Extended property information

Services may use `@Message.ExtendedInfo`, prepended with the name of the property to annotate an individual property in a JSON object with extended information:

```

{
  "@odata.id": "/redfish/v1/Managers/1/SerialInterfaces/1",
  "@odata.type": "#SerialInterface.v1_0_0.SerialInterface",
  "Name": "Managed Serial Interface 1",
  "Description": "Management for Serial Interface",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "InterfaceEnabled": true,
  "SignalType": "Rs232",
  "BitRate": 115200,
  "Parity": "None",
  "DataBits": 8,
  "StopBits": 1,
  "FlowControl": "None",
  "ConnectorType": "RJ45",
  "PinOut": "Cyclades",
  "PinOut@Message.ExtendedInfo": [
    {
      "MessageId": "Base.1.8.PropertyValueNotInList",
      "Message": "The value Contoso for the property PinOut is not in the list of acceptable values.",
      "Severity": "Warning",
    }
  ]
}

```

```

        "MessageSeverity": "Warning",
        "Resolution": "Choose a value from the enumeration list that the implementation can support and resubmit the request"
    }
]
}

```

### 10.8.3 Action info annotation

The action info annotation conveys the parameter requirements and allowable values on parameters for [actions](#). This is done using `@Redfish.ActionInfo` term within the [action representation](#). This term contains a URI to the `ActionInfo` resource.

Example `#ComputerSystem.Reset` action with the `@Redfish.ActionInfo` annotation and resource:

```

{
  "Actions": {
    "#ComputerSystem.Reset": {
      "target": "/redfish/v1/Systems/1/Actions/ComputerSystem.Reset",
      "@Redfish.ActionInfo": "/redfish/v1/Systems/1/ResetActionInfo"
    }
  },
  ...
}

```

The `ResetActionInfo` resource contains a more detailed description of the parameters and the supported values. This resource follows the `ActionInfo` schema definition.

```

{
  "@odata.id": "/redfish/v1/Systems/1/ResetActionInfo",
  "@odata.type": "#ActionInfo.v1_0_0.ActionInfo",
  "Id": "ResetActionInfo",
  "Name": "Reset Action Info",
  "Parameters": [
    {
      "Name": "ResetType",
      "Required": true,
      "DataType": "String",
      "AllowableValues": [
        "On",
        "ForceOff",
        "ForceRestart",
        "Nmi",
        "ForceOn",
      ]
    }
  ]
}

```

```

    "PushPowerButton"
  ]
}
]
}

```

### 10.8.4 Settings and settings apply time annotations

See the [Settings resource](#) clause.

### 10.8.5 Operation apply time and operation apply time support annotations

See the [Operation apply time](#) clause.

### 10.8.6 Maintenance window annotation

The [settings apply time](#) and [operation apply time](#) annotations allow for an operation to be performed during a maintenance window. The `@Redfish.MaintenanceWindow` term at the root of a resource configures the start time and duration of a maintenance window for a resource.

The following example body for the `/redfish/v1/Systems/1` resource configures the maintenance window to start at `2017-05-03T23:12:37-05:00` and last for 600 seconds.

```

{
  "@odata.id": "/redfish/v1/Systems/1",
  "@odata.type": "#ComputerSystem.v1_5_0.ComputerSystem",
  "@Redfish.MaintenanceWindow": {
    "MaintenanceWindowStartTime": "2017-05-03T23:12:37-05:00",
    "MaintenanceWindowDurationInSeconds": 600
  },
  ...
}

```

### 10.8.7 Collection capabilities annotation

[Resource collections](#) may contain a collection capabilities annotation. The `@Redfish.CollectionCapabilities` term at the root of a resource collection shows what properties a client is allowed to use in a [POST request](#) for creating a resource.

The following `ComputerSystemCollection` example body contains the collection capabilities annotation. The `UseCase` property contains the `ComputerSystemComposition` value, and the `CapabilitiesObject` property contains the

`/redfish/v1/Systems/Capabilities` value. The resource at `/redfish/v1/Systems/Capabilities` describes the POST request format for creating a `ComputerSystem` resource for compositions.

```
{
  "@odata.id": "/redfish/v1/Systems",
  "@odata.type": "#ComputerSystemCollection.ComputerSystemCollection",
  "Name": "Computer System Collection",
  "Members@odata.count": 0,
  "Members": [],
  "@Redfish.CollectionCapabilities": {
    "@odata.type": "#CollectionCapabilities.v1_1_0.CollectionCapabilities",
    "Capabilities": [
      {
        "CapabilitiesObject": {
          "@odata.id": "/redfish/v1/Systems/Capabilities"
        },
        "UseCase": "ComputerSystemComposition",
        "Links": {
          "TargetCollection": {
            "@odata.id": "/redfish/v1/Systems"
          }
        }
      }
    ]
  }
}
```

The `CapabilitiesObject` resource follows the same schema for the resource that the resource collection contains. It contains annotations to show which properties the client is allowed to use in the POST request body. The annotations describe which properties are required, optional, or if other rules are associated with the properties.

Annotation	Description
<i>PropertyName</i> <code>@Redfish.RequiredOnCreate</code>	Required in the POST request body.
<i>PropertyName</i> <code>@Redfish.OptionalOnCreate</code>	Not required in the POST request body.
<i>PropertyName</i> <code>@Redfish.SetOnlyOnCreate</code>	Cannot be modified after the resource is created.
<i>PropertyName</i> <code>@Redfish.UpdatableAfterCreate</code>	Can be modified after the resource is created.
<i>PropertyName</i> <code>@Redfish.AllowableValues</code>	Can be set to any of the listed values.
<code>@Redfish.RequestedCountRequired</code>	Required in the POST request body for the corresponding object to indicate the number of requested object instances.  Used for <a href="#">composition requests</a> .

Annotation	Description
<code>@Redfish.ResourceBlockLimits</code>	Indicates restrictions regarding quantities of <code>ResourceBlock</code> resources of a given type in the POST request body.  Used for <a href="#">composition requests</a> .

Example `CapabilitiesObject` resource:

```
{
  "@odata.id": "/redfish/v1/Systems/Capabilities",
  "@odata.type": "#ComputerSystem.v1_8_0.ComputerSystem",
  "Id": "Capabilities",
  "Name": "Capabilities for the system collection",
  "Name@Redfish.RequiredOnCreate": true,
  "Name@Redfish.SetOnlyOnCreate": true,
  "Description@Redfish.OptionalOnCreate": true,
  "Description@Redfish.SetOnlyOnCreate": true,
  "HostName@Redfish.OptionalOnCreate": true,
  "HostName@Redfish.UpdatableAfterCreate": true,
  "Links@Redfish.RequiredOnCreate": true,
  "Links": {
    "ResourceBlocks@Redfish.RequiredOnCreate": true,
    "ResourceBlocks@Redfish.UpdatableAfterCreate": true
  },
  "@Redfish.ResourceBlockLimits": {
    "MinCompute": 1,
    "MaxCompute": 1,
    "MaxStorage": 8
  }
}
```

### 10.8.8 Requested count and allow over-provisioning annotations

Clients use the requested count and allow over-provisioning annotations in [composition requests](#) to express the quantity of a type of [resource](#) to allocate:

Annotation	Description
<code>@Redfish.RequestedCount</code>	Number of requested resources.
<code>@Redfish.AllowOverprovisioning</code>	Boolean. If <code>true</code> , the service may provision more resources than the <code>@Redfish.RequestedCount</code> annotation requests. Default is <code>false</code> .

Example client request for four or more `Processor` resources:

```

{
  "Processors": {
    "Members": [
      {
        "@Redfish.RequestedCount": 4,
        "@Redfish.AllowOverprovisioning": true
      }
    ]
  },
  ...
}

```

### 10.8.9 Zone affinity annotation

The zone affinity annotation is used by clients in [composition requests](#) to indicate the components for the composition come from the specified Resource Zone. The `@Redfish.ZoneAffinity` term in the request body contains the value of the `Id` property of the requested Resource Zone.

Example client request for components to be allocated from the Resource Zone with the `Id` property containing `1`:

```

{
  "@Redfish.ZoneAffinity": "1",
  ...
}

```

### 10.8.10 Supported certificates annotation

[Resource collections](#) of type `CertificateCollection` should contain a supported certificates annotation. The `@Redfish.SupportedCertificates` term at the root of a resource collection shows the different certificate formats allowed in the resource collection.

Example `CertificateCollection` that only supports PEM style certificates:

```

{
  "@odata.id": "/redfish/v1/Managers/BMC/NetworkProtocol/HTTPS/Certificates",
  "@odata.type": "#CertificateCollection.CertificateCollection",
  "Name": "Certificate collection",
  "Members@odata.count": 1,
  "Members": [
    {
      "@odata.id": "/redfish/v1/Managers/BMC/NetworkProtocol/HTTPS/Certificates/1"
    }
  ]
}

```

```
    ],
    "@Redfish.SupportedCertificates": [
      "PEM"
    ]
  }
```

### 10.8.11 Deprecated annotation

Services may annotate [properties](#) with `@Redfish.Deprecated` if the schema definition has the property marked as deprecated.

Example deprecated property:

```
{
  "VendorID": "0xABCD",
  "VendorID@Redfish.Deprecated": "This property has been deprecated in favor of ModuleManufacturerID.",
  ...
}
```

## 10.9 Settings resource

A settings resource represents the future intended state of a [resource](#). Some resources have properties that can be updated and the updates take place immediately; however, some properties need to be updated at a certain point in time, such as a system reset. While the resource represents the current state, the settings resource represents the future intended state. The service represents properties of a resource that can only be updated at a certain point in time using a `@Redfish.Settings` [payload annotation](#). The settings annotation contains a link to a [subordinate](#) resource with the same schema definition. The properties within the settings resource contain the properties that are updated at a certain point in time.

For resources that support a future state and configuration, the response shall contain a property with the `@Redfish.Settings` annotation. When a settings annotation is used, the following conditions shall apply:

- The settings resource linked to current resource with the `@Redfish.Settings` annotation shall be of the same schema definition.
- The settings resource should be a subset of properties that can be updated.
- The settings resource shall not contain the `@Redfish.Settings` annotation.
- The settings resource may contain the `@Redfish.SettingsApplyTime` annotation.

The `@Redfish.Settings` annotation includes several properties to help clients monitor when the resource is



consumed by the service and determine the results of applying the values, which may or may not have been successful.

- The `Messages` property is a collection of messages that represent the results of the last time the values of the settings resource were applied.
- The `ETag` property contains the ETag of the settings resource that was last applied.
- The `Time` property indicates the time when the settings resource was last applied.

The following resource example body supports a settings resource. A client can use the `SettingsObject` property to locate the URI of the settings resource.

```
{
  "@Redfish.Settings": {
    "@odata.type": "#Settings.v1_0_0.Settings",
    "SettingsObject": {
      "@odata.id": "/redfish/v1/Systems/1/Bios/SD"
    },
    "Time": "2017-05-03T23:12:37-05:00",
    "ETag": "\"A89B031B62\"",
    "Messages": [
      {
        "MessageId": "Base.1.8.PropertyNotWritable",
        "RelatedProperties": [
          "#/Attributes/ProcTurboMode"
        ]
      }
    ]
  },
  ...
}
```

When a client updates the settings resource, it may include the `@Redfish.SettingsApplyTime` annotation in the request to indicate when to apply the settings.

- If a service enables a client to indicate when to apply settings, the settings resource shall contain a property with the `@Redfish.SettingsApplyTime` annotation.
- Only settings resources shall contain the `@Redfish.SettingsApplyTime` annotation.

In the following example request, the client indicates that the settings resource values are applied either on reset or during the specified maintenance window:

```
{
  "@Redfish.SettingsApplyTime": {
    "@odata.type": "#Settings.v1_1_0.PreferredApplyTime",
```

```
    "ApplyTime": "OnReset",
    "MaintenanceWindowStartTime": "2017-05-03T23:12:37-05:00",
    "MaintenanceWindowDurationInSeconds": 600
  },
  ...
}
```

## 10.10 Special resource situations

---

### 10.10.1 Overview

**Resources** need to exhibit common semantic behavior whenever possible. This can be difficult in some situations discussed in this clause.

### 10.10.2 Absent resources

**Resources** may be absent or their state unknown at the time a client requests information about that resource. For resources that represent removable or optional components, absence provides useful information to clients because it indicates a capability, such as an empty PCIe slot, DIMM socket, or drive bay, that would not be apparent if the resource simply did not exist.

This also applies to resources that represent a limited number of items or unconfigured capabilities within an implementation, but this usage should be applied sparingly and should not apply to resources limited in quantity due to arbitrary limits. For example, an implementation that limits `SoftwareInventory` to a maximum of 20 items should not populate 18 absent resources when only two items are present.

For resources that provide useful data in an absent state and where the URI is expected to remain constant, such as when a DIMM is removed from a memory socket, the resource should exist and should return a value of `Absent` for the `State` property in the `Status` object.

In this circumstance, any required properties for which there is no known value shall be represented as `null`. Properties whose support is based on the configuration choice or the type of component installed, and therefore unknown while in the absent state, should not be returned. Likewise, subordinate resources for an absent resource should not be populated until their support can be determined. For example, the `Power` and `Thermal` resources under a `Chassis` resource should not exist for an absent Chassis.

Client software should be aware that when absent resources are later populated, the updated resource may represent a different configuration or physical item, and previous data, including read-only properties, obtained from that resource may be invalid. For example, the `Memory` resource shows details about a single DIMM socket and the installed DIMM. When that DIMM is removed, the `Memory` resource remains as an absent resource to indicate the

empty DIMM socket. Later, a new DIMM is installed in that socket, and the `Memory` resource represents data about this new DIMM, which could have completely different characteristics.

## 10.11 Registries

Registry [resources](#) assist the client in interpreting Redfish resources beyond the Redfish schema definitions. To get more information about a resource, event, message, or other item, use an identifier to search registries. This information can include other properties, property restrictions, and the like. Registries are themselves resources.

Redfish defines the following types of registries:

Registry	Description	See
BIOS	Determines the semantics of each property in a BIOS or BIOS <a href="#">settings resource</a> . Because BIOS information can vary from platform to platform, Redfish cannot define a fixed schema for these values.  This registry contains both property descriptions and other information, such as data type, allowable values, and user menu information.	
Message	Constructs a message from a <code>MessageId</code> and other message information to present to an end user. The messages in these registries appear in both eventing and error responses to operations.  This registry is the most common type of registry.	<ul style="list-style-type: none"> <li>• <a href="#">Error responses</a></li> <li>• <a href="#">Eventing</a></li> </ul>
Privilege	Maps the resources in a Redfish Service to the privileges that can complete specified operations against those resources.  A client can use this information to: <ul style="list-style-type: none"> <li>• Determine which roles should have specific privileges.</li> <li>• Map accounts to those roles so that the accounts can complete operations on Redfish resources.</li> </ul>	<a href="#">Privilege model</a>

## 10.12 Schema annotations

The schema definitions of the data model use schema annotations to provide additional documentation for developers. This clause describes the different types of schema annotations that the Redfish data model uses. For information about how each of the annotations are implemented in their respective schema languages, see the [Schema definition languages](#) clause.

### 10.12.1 Description annotation

The description annotation can be applied to any type, property, action, or parameter to provide a description of Redfish schema elements suitable for end users or user interface help text.

All schemas that are published or republished by the DMTF's Redfish Forum shall include a description annotation on the following schema definitions:

- Redfish types
- [Properties](#)
- [Reference properties](#)
- Enumeration values
- [Resources](#) and [resource collections](#)
- [Structured types](#)

### 10.12.2 Long description annotation

The long description annotation can be applied to any type, property, action, or parameter to provide a formal, normative specification of the schema element.

When the long descriptions in the Redfish schema contain normative language, the service shall be required to conform with the statement.

All schemas that are published or republished by the DMTF's Redfish Forum shall include a long description annotation on the following schema definitions:

- Redfish types
- [Properties](#)
- [Reference properties](#)
- [Resources](#) and [resource collections](#)
- [Structured types](#)

### 10.12.3 Resource capabilities annotation

The resource capabilities annotation can be applied to [resources](#) and [resource collections](#) to express the different type of HTTP operations a client can invoke on the given resource or resource collection.

- Insert capabilities indicate whether a client can perform a POST on the resource for creating a new resource.
- Update capabilities indicate whether a client can perform a PATCH or PUT on the resource.
- Delete capabilities indicate whether a client can perform a DELETE on the resource.
- A service may implement a subset of the capabilities that are allowed on the resource or resource collection.

All schemas that are published or republished by the DMTF's Redfish Forum for resources and resource collections shall include resource capabilities annotations.

### 10.12.4 Resource URI patterns annotation

The resource URI patterns annotation expresses the valid URI patterns for a [resource](#) or [resource collection](#).

The strings for the URI patterns may use `{` and `}` characters to express parameters within a given URI pattern. Items between the `{` and `}` characters are treated as identifiers within the URI for given instances of a Redfish resource. Clients interpret this as a string to be replaced to access a given resource. A URI pattern may contain multiple identifier terms to support multiple levels of nested resource collections. The identifier term in the URI pattern shall match the `Id` string property for the corresponding resource, or the `MemberId` string property for the corresponding object within a resource. The process for forming the strings that are concatenated to form the URI pattern are in the [resource, schema, property, and URI naming conventions](#) clause.

The following string is an example URI pattern that describes a `ManagerAccount` resource: `/redfish/v1/AccountService/Accounts/{ManagerAccountId}`

Using the previous example, `{ManagerAccountId}` is replaced by the `Id` property of the corresponding `ManagerAccount` resource. If the `Id` property for a `ManagerAccount` resource is `John`, the full URI for that resource is `/redfish/v1/AccountService/Accounts/John`.

The URI patterns are constructed based on the formation of the [resource tree](#). When constructing the URI pattern for a subordinate resource, the URI pattern for the current resource is used and appended. For example, the `RoleCollection` resource is subordinate to `AccountService`. Because the URI pattern for `AccountService` is `/redfish/v1/AccountService`, the URI pattern for the `RoleCollection` resource is `/redfish/v1/AccountService/Roles`.

In some cases, the subordinate resource is found inside of a [structured property](#) of a resource. In these cases, the name of the structured property appears in the URI pattern for the subordinate resource. For example, the `CertificateCollection` resource is subordinate to the `ManagerNetworkProtocol` resource from the `HTTPS` property. Because the URI pattern for `ManagerNetworkProtocol` is `/redfish/v1/Managers/{ManagerId}/NetworkProtocol`, the URI pattern for the `CertificateCollection` resource is `/redfish/v1/Managers/{ManagerId}/NetworkProtocol/HTTPS/Certificates`.

All schemas that are published or republished by the DMTF's Redfish Forum for resources and resource collections shall be annotated with the resource URI patterns annotation.

All Redfish resources and Redfish resource collections implemented by a service shall match the URI pattern described by the resource URI patterns annotation for their given definition.

### 10.12.5 Additional properties annotation

The additional properties annotation specifies whether a type can contain additional [properties](#) outside of those defined in the schema. Types that do not support additional properties shall not contain properties beyond those described in the schema.

### 10.12.6 Permissions annotation

The permissions annotation specifies whether a client can modify the value of a [property](#), or if the property is read-only.

A service may implement a modifiable property as read-only.

### 10.12.7 Required annotation

The required annotation specifies whether a service needs to support a [property](#). Required properties shall be annotated with the required annotation. All other properties are optional.

### 10.12.8 Required on create annotation

The required on create annotation specifies that a [property](#) is required to be provided by the client on creation of the [resource](#). Properties not annotated with the required on create annotation are not required to be provided by the client on a create operation.

### 10.12.9 Units of measure annotation

In addition to following [naming conventions](#), [properties](#) representing units of measure shall be annotated with the units of measure annotation to specify the units of measurement for the property.

The value of the annotation shall be a string that contains the case-sensitive "(c/s)" symbol of the unit of measure as listed in the [Unified Code for Units of Measure \(UCUM\)](#), unless the symbolic representation does not reflect common usage. For example, `RPM` commonly reports fan speeds in revolutions-per-minute but has no simple UCUM representation. For units with prefixes, the case-sensitive ( `c/s` ) symbol for the prefix as listed in UCUM should be prepended to the unit symbol. For example, Mebibyte (1024<sup>2</sup> bytes), which has the UCUM `Mi` prefix and `By` symbol, would use `MiBy` as the value for the annotation. For values that also include rate information, such as megabits per second, the rate unit's symbol should be appended and use a slash ( `/` ) character as a separator. For example, `Mbit/s` .

### 10.12.10 Expanded resource annotation

The expanded resource annotation can be applied to a [reference property](#) to specify that the default behavior for the

service is to include the contents of the related [resource](#) or [resource collection](#) in responses. This behavior follows the same semantics of the [expand query parameter](#) with a level of 1.

Reference properties annotated with this term shall be expanded by the service, even if not requested by the client. A service may page [resource collections](#).

### 10.12.11 Owning entity annotation

The owning entity annotation can be applied to a schema to specify the name of the entity responsible for development, publication, and maintenance of a given schema.

### 10.12.12 Deprecated annotation

The deprecated annotation specifies if a [property](#), enumeration, or other schema element has been deprecated. Schema elements marked as deprecated contain a schema version that shows when the element was deprecated, as well as text that specifies the favored approach.

Existing and new implementations may use deprecated schema elements, but they should move to the favored approach. Deprecated schema elements may be implemented in order to achieve backwards compatibility. Deprecated schema elements may be removed from the next major version of the schema.

## 10.13 Versioning

---

As stated previously, a resource can be an individual entity or a resource collection, which acts as a container for a set of resources.

A [resource collection](#) does not contain any version information because it defines a single `Members` property, and the overall collection definition never grows over time.

A [resource](#) has both unversioned and versioned definitions.

References from other resources use the unversioned definition of a resource to ensure no version dependencies exist between the definitions. The unversioned definition of a resource contains no property information about the resource.

The versioned definition of a resource contains a set of properties, actions, and other definitions associated with the given resource. The version of a resource follows the format:

```
v X . Y . Z
```

where

Variable	Type	Version	Description
x	Integer	Major version.	Backward-incompatible change.
y	Integer	Minor version.	Minor update. Redfish introduces new functionality but does not remove any functionality. The minor version preserves compatibility with earlier minor versions. For example, a new property introduces a new minor version of the resource.
z	Integer	Errata version.	Fix in an earlier version. For example, a fix to a <a href="#">schema annotation</a> on a property introduces an errata version of the resource.

## 10.14 Localization

The creation of separate localized copies of Redfish schemas and registries is allowed and encouraged. Localized schema and registry files may be submitted to the DMTF for republication in the Redfish Schema Repository.

Property names, parameter names, and enumeration values in the JSON response payload are never localized but translated copies of those names may be provided as additional annotations in the localized schema for use by client applications. A separate file for each localized schema or registry shall be provided for each supported language. The English-language versions of Redfish schemas and registries shall be the normative versions, and alterations of meaning due to translation in localized versions of schemas and registries shall be forbidden.

Schemas and registries in non-English languages shall use the appropriate schema annotations to identify their language. Descriptive property, parameter, and enumeration text not translated into the specified language shall be removed from localized versions. This removal enables software and tools to combine normative and localized copies, especially for minor schema version differences.



## 11 File naming and publication

---

For consistency in publication and to enable programmatic access, all Redfish-related files shall follow a set of rules to construct the name of each file. The [Schema definition languages](#) clause describes the file name construction rules, while the following clauses describe the construction rules for other file types.

### 11.1 Registry file naming

---

Redfish Message or Privilege Registry Files shall use the registry name to construct the file name, in this format:

```
RegistryName . MajorVersion . MinorVersion . Errata .json
```

For example, the file name of the Base Message Registry v1.0.2 is `Base.1.0.2.json`.

### 11.2 Profile file naming

---

The document that describes a profile follows the Redfish schema file naming conventions. The file name format for profiles shall be:

```
ProfileName .v MajorVersion _ MinorVersion _ Errata .json
```

For example, the file name of the BasicServer profile v1.2.0 is `BasicServer.v1_2_0.json`. The file name shall include the profile name and version, which matches those property values within the document.

### 11.3 Dictionary file naming

---

The binary file describing a Redfish Device Enablement Dictionary follows the Redfish schema file naming conventions for the schema definition language that the dictionary is converted from. Because a single Dictionary file contains all minor revisions of the schema, only the major version appears in the file name. The file names for Dictionaries shall be formatted as:

```
DictionaryName _v MajorVersion .dict
```

For example, the file name of the Chassis dictionary v1.2.0 is `Chassis_v1.dict`.

### 11.4 Localized file naming

---

Localized schemas and registries shall follow the same file naming conventions as the English language versions.

When multiple localized copies are present in a repository and which have the same file name, files in languages other than English shall be organized into subfolders named to match the [ISO 639-1](#) language code for those files. English language files may be duplicated in an `en` subfolder for consistency.

## 11.5 DMTF Redfish file repository

All Redfish schemas, registries, dictionaries, and profiles published or republished by the DMTF's Redfish Forum are available from the [DMTF website](#) for download. Programs may use the following durable URLs to access the repository. Programs incorporating remote repository access should implement a local cache to reduce latency, program requirements for Internet access and undue traffic burden on the DMTF website.

Organizations creating Redfish-related files such as OEM schemas, Redfish Interoperability Profiles, or Message Registries are encouraged to use the form at <https://redfish.dmtf.org/redfish/portal> to submit those files to the DMTF for republication in the DMTF Redfish file repository.

The files are organized on the site in the following manner:

URL	Folder contents
<code>redfish.dmtf.org/schemas</code>	Current (most recent minor or errata) release of each schema file in CSDL, JSON Schema, and/or OpenAPI formats.
<code>redfish.dmtf.org/schemas/v1</code>	Durable URL for programmatic access to all v1.xx schema files. Every v1.xx minor or errata release of each schema file in CSDL, JSON Schema, OpenAPI formats.
<code>redfish.dmtf.org/schemas/v1/{code}</code>	Durable URL for programmatic access to localized v1.xx schema files. Localized schemas are organized in subfolders using the two-character ISO 639-1 language code as the {code} segment.
<code>redfish.dmtf.org/schemas/archive</code>	Subfolders contain schema files specific to a particular version release.
<code>redfish.dmtf.org/registries</code>	Current (most recent minor or errata) release of each registry file.
<code>redfish.dmtf.org/registries/v1</code>	Durable URL for programmatic access to all v1.xx registry files. Every v1.xx minor or errata release of each registry file.
<code>redfish.dmtf.org/registries/v1/{code}</code>	Durable URL for programmatic access to localized v1.xx registry files. Localized schemas are organized in subfolders using the two-character ISO 639-1 language code as the {code} segment.
<code>redfish.dmtf.org/registries/archive</code>	Subfolders contain registry files specific to a particular version release.
<code>redfish.dmtf.org/profiles</code>	Current release of each Redfish Interoperability Profile (.json) file and associated documentation.
<code>redfish.dmtf.org/profiles/v1</code>	Durable URL for programmatic access to all v1.xx Redfish Interoperability Profile (.json) files.

URL	Folder contents
<code>redfish.dmtf.org/ profiles/archive</code>	Subfolders contain profile files specific to a particular profile version or release.
<code>redfish.dmtf.org/ dictionaries</code>	Durable URL for programmatic access to all v1.xx Redfish Device Enablement Dictionary files.
<code>redfish.dmtf.org/ dictionaries/v1</code>	Durable URL for programmatic access to all v1.xx Redfish Device Enablement Dictionary files.
<code>redfish.dmtf.org/ dictionaries/archive</code>	Subfolders contain dictionary files specific to a particular version release.

## 12 Schema definition languages

Individual resources and their dependent types and actions are defined within a Redfish schema document. This clause describes how these documents are constructed in the following formats:

- [OData Common Schema Definition Language](#)
- [JSON Schema](#)
- [OpenAPI](#)

### 12.1 OData Common Schema Definition Language

OData Common Schema Definition Language (CSDL) is an XML schema format defined by the [OData CSDL Specification](#). The following clause describes how Redfish uses CSDL to describe resources and resource collections.

#### 12.1.1 File naming conventions for CSDL

Redfish CSDL schema files shall be named using the [resource name](#) value, followed by `_v` and the major version of the schema. Because a single CSDL schema file contains all minor revisions of the schema, only the major version appears in the file name. The file name shall be formatted as:

```
TypeName _v* MajorVersion * . xml
```

For example, version 1.3.0 of the Chassis schema is `Chassis_v1.xml`.

#### 12.1.2 Core CSDL files

File	Description
<code>RedfishError_v1.xml</code>	Payload definition of the <a href="#">Redfish error response</a> .
<code>RedfishExtensions_v1.xml</code>	All definitions for Redfish types and annotations.
<code>Resource_v1.xml</code>	All base definitions for resources, resource collections, and common properties, such as <code>Status</code> .

#### 12.1.3 CSDL format

The outer element of the OData schema representation document shall be the `Edmx` element, and shall have a `Version` attribute with a value of `4.0`.

```
<edmx:Edmx xmlns:edmx="http://docs.oasis-open.org/odata/ns/edmx" Version="4.0">
  <!-- edmx:Reference and edmx:DataService elements go here -->
</edmx:Edmx>
```

The [Referencing other CSDL files](#) and [CSDL data services](#) clauses describe the items that are found within the `Edmx` element.

### 12.1.3.1 Referencing other CSDL files

CSDL files may reference types defined in other CSDL documents. This is done by including `Reference` tags.

The `Reference` element uses the `Uri` attribute to specify a CSDL file. The `Reference` element also contains one or more `Include` tags that specify the `Namespace` attribute containing the types to be referenced, along with an optional `Alias` attribute for that namespace.

Type definitions generally reference the OData and Redfish namespaces for common type annotation terms. Redfish CSDL files always use the `Alias` attribute on the following namespaces:

- `Org.OData.Core.V1` is aliased as `OData`.
- `Org.OData.Measures.V1` is aliased as `Measures`.
- `RedfishExtensions.v1_0_0` is aliased as `Redfish`.
- `Validation.v1_0_0` is aliased as `Validation`.

```
<edmx:Reference Uri="http://docs.oasis-open.org/odata/odata/v4.0/cs01/vocabularies/Org.OData.Core.V1.xml">
  <edmx:Include Namespace="Org.OData.Core.V1" Alias="OData"/>
</edmx:Reference>
<edmx:Reference
  Uri="http://docs.oasis-open.org/odata/odata/v4.0/os/vocabularies/Org.OData.Measures.V1.xml">
  <edmx:Include Namespace="Org.OData.Measures.V1" Alias="Measures"/>
</edmx:Reference>
<edmx:Reference Uri="http://redfish.dmtf.org/schemas/v1/RedfishExtensions_v1.xml">
  <edmx:Include Namespace="RedfishExtensions.v1_0_0" Alias="Redfish"/>
  <edmx:Include Namespace="Validation.v1_0_0" Alias="Validation"/>
</edmx:Reference>
<edmx:Reference Uri="http://redfish.dmtf.org/schemas/v1/Resource_v1.xml">
  <edmx:Include Namespace="Resource"/>
  <edmx:Include Namespace="Resource.v1_0_0"/>
</edmx:Reference>
```

### 12.1.3.2 CSDL data services

Define structures, enumerations, and other definitions in CSDL within a namespace. Use a `Schema` tag to define the schema and use the `Namespace` attribute to declare the name of the namespace.

Redfish uses namespaces to differentiate different versions of the schema. CSDL enables structures to inherit from other structures, which enables newer namespaces to define only the changes. The [Elements of CSDL namespaces](#) clause describes this behavior.

The `Schema` element is a child of the `DataServices` element, which is a child of the `Edmx` element:

```
<edmx:DataServices>
  <Schema xmlns="http://docs.oasis-open.org/odata/ns/edm" Namespace="MyTypes.v1_0_0">
    <!-- Type definitions for version 1.0.0 of MyTypes go here -->
  </Schema>
  <Schema xmlns="http://docs.oasis-open.org/odata/ns/edm" Namespace="MyTypes.v1_1_0">
    <!-- Type definitions for version 1.1.0 of MyTypes go here -->
  </Schema>
</edmx:DataServices>
```

## 12.1.4 Elements of CSDL namespaces

The following clauses describe the definitions within each namespace:

- [Qualified names](#)
- [Entity type and complex type elements](#)

### 12.1.4.1 Qualified names

Many definitions in CSDL use references to qualified names. CSDL defines this as a string in the form:

`Namespace . TypeName`

where

Variable	Description
<code>Namespace</code>	Namespace name.
<code>TypeName</code>	Name of the element in the namespace.

For example, if a reference is made to `MyType.v1_0_0.MyDefinition`, the definition can be found in the `MyType.v1_0_0` namespace with an element named `MyDefinition`.

#### 12.1.4.2 Entity type and complex type elements

Use the `EntityType` and `ComplexType` tags to define the entity type and complex type elements, respectively. These elements define a JSON structure and their set of properties. This is done by defining [property elements](#) and [navigation property elements](#) within the `EntityType` or `ComplexType` tags.

All entity types and complex types contain a `Name` attribute, which specifies the name of the definition.

Entity types and complex types may have a `BaseType` attribute, which specifies a [qualified name](#). When the `BaseType` attribute is used, all definitions of the referenced `BaseType` are available to the entity type or complex type being defined.

All [resources](#) and [resource collections](#) are defined with the entity type element. Resources inherit from `Resource.v1_0_0.Resource`, and resource collections inherit from `Resource.v1_0_0.ResourceCollection`.

Most [structured properties](#) are defined with the complex type element. Some use the entity type element that inherits from `Resource.v1_0_0.ReferenceableMember`. The entity type element enables references to be made by using the [Navigation Property element](#), whereas the complex type element does not allow for this usage.

Example entity type and complex type element:

```
<EntityType Name="TypeA" BaseType="Resource.v1_0_0.Resource">
  <Annotation Term="OData.Description" String="The TypeA entity type description."/>
  <Annotation Term="OData.LongDescription" String="The TypeA entity type normative description."/>
  <!-- Property and navigation property definitions go here -->
</EntityType>
<ComplexType Name="PropertyTypeA">
  <Annotation Term="OData.Description" String="The TypeA structured property description."/>
  <Annotation Term="OData.LongDescription" String="The TypeA structured property normative description."/>
  <!-- Property and navigation property definitions go here -->
</ComplexType>
```

#### 12.1.4.3 Action element

Use the `Action` tag to define the action element. This element defines an [action](#) that can be performed on a [resource](#).

All action elements contain a `Name` attribute, which specifies the name of the action. The action shall be represented in payloads as the [qualified name](#) of the action, preceded by `#`.

In Redfish, all action elements contain the `IsBound` attribute that is always set to `true`, which indicates that the action appears as a member of a structured type.

The action element contains one or more `Parameter` tags that specify the `Name` and `Type` of each parameter.

Because all action elements in Redfish use the term `IsBound="true"`, the first parameter is called the "binding parameter" and specifies the [structured type](#) to which the action belongs. In Redfish, this is always going to be one of the following [complex type elements](#):

- For standard actions, the `Actions` complex type for the resource.
- For OEM actions, the `OemActions` complex type for the resource.

The remaining `Parameter` elements describe additional parameters to be passed to the action. Parameters containing the term `Nullable="false"` are required to be provided in the action request.

```
<Schema xmlns="http://docs.oasis-open.org/odata/ns/edm" Namespace="MyType">
  <Action Name="MyAction" IsBound="true">
    <Parameter Name="Thing" Type="MyType.Actions"/>
    <Parameter Name="Parameter1" Type="Edm.Boolean"/>
    <Parameter Name="Parameter2" Type="Edm.String" Nullable="false"/>
  </Action>

  <ComplexType Name="Actions">
    ...
  </ComplexType>

  ...

</Schema>
```

Some action parameters may specify a type that is defined by an entity type element. In these cases, the parameter in the request will be a [reference object](#) to a resource within the service.

#### 12.1.4.3.1 Action element for OEM actions

OEM-specific actions shall be defined by using the action element with the binding parameter set to the `OemActions` complex type for the resource. For example, the following definition defines the OEM `#Contoso.Ping` action for a `ComputerSystem`.

```
<Schema xmlns="http://docs.oasis-open.org/odata/ns/edm" Namespace="Contoso">
  <Action Name="Ping" IsBound="true">
    <Parameter Name="ComputerSystem" Type="ComputerSystem.v1_0_0.OemActions"/>
  </Action>
</Schema>
```



#### 12.1.4.3.2 Action with a response body

A response body for an action shall be defined using the `ReturnType` tag within an Action element. For example, the following definition defines the `GenerateCSR` action with a response that contains the definition specified by `GenerateCSRResponse`.

```
<Action Name="GenerateCSR" IsBound="true">
  <Parameter Name="CertificateService" Type="CertificateService.v1_0_0.Actions"/>
  ...
  <ReturnType Type="CertificateService.v1_0_0.GenerateCSRResponse" Nullable="false"/>
</Action>

<ComplexType Name="GenerateCSRResponse">
  <Annotation Term="OData.AdditionalProperties" Bool="false"/>
  <Annotation Term="OData.Description" String="The response body for the GenerateCSR action."/>
  <NavigationProperty Name="CertificateCollection" Type="CertificateCollection.CertificateCollection" Nullable="false">
    <Annotation Term="OData.Permissions" EnumMember="OData.Permission/Read"/>
    <Annotation Term="OData.Description" String="The link to the certificate resource collection where the certificate is in">
    <Annotation Term="Redfish.Required"/>
  </NavigationProperty>
  <Property Name="CSRString" Type="Edm.String" Nullable="false">
    <Annotation Term="OData.Permissions" EnumMember="OData.Permission/Read"/>
    <Annotation Term="OData.Description" String="The string for the certificate signing request."/>
    <Annotation Term="Redfish.Required"/>
  </Property>
</ComplexType>
```

Using the above example, the following payload is an example response for the `GenerateCSR` action.

```
{
  "CSRString": "-----BEGIN CERTIFICATE REQUEST-----...-----END CERTIFICATE REQUEST-----",
  "CertificateCollection": {
    "@odata.id": "/redfish/v1/Managers/BMC/NetworkProtocol/HTTPS/Certificates"
  }
}
```

#### 12.1.4.4 Property element

Properties of resources, resource collections, and structured properties are defined using the property element. The `Property` tag defines a property element inside [entity type and complex type elements](#).

All property elements contain a `Name` attribute, which specifies the name of the property.

All property elements contain a `Type` attribute specifies the data type. The `Type` attribute shall be one of the following names or types:

- A [qualified name](#) that references an [enum type element](#).
- A [qualified name](#) that references a [complex type element](#).
- A primitive data type.
- An array of the previous names or types by using the `Collection` term.

Primitive data types shall be one of the following:

Type	Meaning
<code>Edm.Boolean</code>	True or False.
<code>Edm.DateTimeOffset</code>	<a href="#">Date-time</a> string.
<code>Edm.Decimal</code>	Numeric values with fixed precision and scale.
<code>Edm.Double</code>	IEEE 754 binary64 floating-point number (15-17 decimal digits).
<code>Edm.Duration</code>	<a href="#">Duration</a> string.
<code>Edm.Guid</code>	<a href="#">GUID/UUID</a> string.
<code>Edm.Int64</code>	Signed 64-bit integer.
<code>Edm.String</code>	UTF-8 string.

Property elements may specify a `Nullable` attribute. If the attribute is `false`, the property value cannot be `null`. If the attribute is `true` or absent, the property value can be `null`.

Example property element:

```
<Property Name="Property1" Type="Edm.String" Nullable="false">
  <Annotation Term="OData.Description" String="The Property1 property description."/>
  <Annotation Term="OData.LongDescription" String="The Property1 property normative description."/>
  <Annotation Term="OData.Permissions" EnumMember="OData.Permission/Read"/>
  <Annotation Term="Redfish.Required"/>
  <Annotation Term="Measures.Unit" String="Watts"/>
</Property>
```

#### 12.1.4.5 Navigation property element

[Reference properties](#) of [resources](#), [resource collections](#), and [structured properties](#) are defined using the navigation property element. The `NavigationProperty` tag defines a navigation property element inside [entity type and complex type elements](#).

All navigation property elements contain a `Name` attribute, which specifies the name of the property.

All navigation property elements contain a `Type` attribute specifies the data type. The `Type` attribute is a [qualified name](#) that references an [entity type element](#). This can also be made into an array using the `Collection` term.

Navigation property elements may specify a `Nullable` attribute. If the attribute is `false`, the property value cannot be `null`. If the attribute is `true` or absent, the property value can be `null`.

Unless the reference property is to be [expanded](#), all navigation properties in Redfish use the `OData.AutoExpandReferences` annotation element to show that the reference is always available.

Example navigation property element:

```
<NavigationProperty Name="RelatedType" Type="MyTypes.TypeB">
  <Annotation Term="OData.Description" String="The RelatedType navigation property description."/>
  <Annotation Term="OData.LongDescription" String="The RelatedType navigation property normative description."/>
  <Annotation Term="OData.AutoExpandReferences"/>
</NavigationProperty>
```

#### 12.1.4.6 Enum type element

Use the `EnumType` tag to define the enum type element. This element defines a set of enumeration values, which may be applied to one or more properties.

All enum type elements contain a `Name` attribute, which specifies the name of the set of enumeration values.

Enum type elements contain `Member` tags that define the members of the enumeration. The `Member` tags contain a `Name` attribute that specifies the string value of the member name.

```
<EnumType Name="EnumTypeA">
  <Annotation Term="OData.Description" String="The EnumTypeA enum type description."/>
  <Annotation Term="OData.LongDescription" String="The EnumTypeA enum type normative description."/>
  <Member Name="MemberA">
    <Annotation Term="OData.Description" String="The description of MemberA"/>
  </Member>
  <Member Name="MemberB">
    <Annotation Term="OData.Description" String="The description of MemberB"/>
  </Member>
</EnumType>
```

### 12.1.4.7 Annotation element

Annotations in CSDL are expressed using the `Annotation` element. The `Annotation` element can be applied to any schema element in CSDL.

The following examples show how each [Redfish schema annotation](#) is expressed in CSDL.

- The [OData Core Schema](#) defines terms with the `OData` prefix.
- The [OData Measures Schema](#) defines terms with the `Measures` prefix.
- The [RedfishExtensions Schema](#) defines terms with the `Redfish` prefix.

Example [description annotation](#):

```
<Annotation Term="OData.Description" String="This property contains the user name for the account."/>
```

Example [long description annotation](#):

```
<Annotation Term="OData.LongDescription" String="This property shall contain the user name for the account."/>
```

Example [additional properties annotation](#):

```
<Annotation Term="OData.AdditionalProperties"/>
```

Example [permissions annotation](#) (read-only):

```
<Annotation Term="OData.Permissions" EnumMember="OData.Permission/Read"/>
```

Example [permissions annotation](#) (read/write):

```
<Annotation Term="OData.Permissions" EnumMember="OData.Permission/ReadWrite"/>
```

Example [required annotation](#):

```
<Annotation Term="Redfish.Required"/>
```

Example [required on create annotation](#):

```
<Annotation Term="Redfish.RequiredOnCreate"/>
```

Example [units of measure annotation](#):

```
<Annotation Term="Measures.Unit" String="MiBy"/>
```

Example [expanded resource annotation](#):

```
<Annotation Term="OData.AutoExpand"/>
```

Example [insert capabilities annotation](#) (showing POST is not allowed):

```
<Annotation Term="Capabilities.InsertRestrictions">
  <Record>
    <PropertyValue Property="Insertable" Bool="false"/>
  </Record>
</Annotation>
```

Example [update capabilities annotation](#) (showing PATCH and PUT are allowed):

```
<Annotation Term="Capabilities.UpdateRestrictions">
  <Record>
    <PropertyValue Property="Updatable" Bool="true"/>
    <Annotation Term="OData.Description" String="Manager accounts can be updated to change the password and other writable p">
  </Record>
</Annotation>
```

Example [delete capabilities annotation](#) (showing DELETE is allowed):

```
<Annotation Term="Capabilities.DeleteRestrictions">
  <Record>
    <PropertyValue Property="Deletable" Bool="true"/>
    <Annotation Term="OData.Description" String="Manager accounts are removed with a Delete operation."/>
  </Record>
</Annotation>
```

Example [resource URI patterns annotation](#):

```
<Annotation Term="Redfish.Uris">
  <Collection>
    <String>/redfish/v1/AccountService/Accounts/{ManagerAccountId}</String>
  </Collection>
</Annotation>
```

Example [owning entity annotation](#):

```
<Annotation Term="Redfish.OwningEntity" String="DMTF"/>
```

Example [deprecated annotation](#):

```
<Annotation Term="Redfish.Revisions">
  <Collection>
    <Record>
      <PropertyValue Property="Kind" EnumMember="Redfish.RevisionKind/Deprecated"/>
      <PropertyValue Property="Version" String="v1_3_0"/>
      <PropertyValue Property="Description" String="This property has been deprecated in favor of ModuleManufacturerID."/>
    </Record>
  </Collection>
</Annotation>
```

## 12.2 JSON Schema

The [JSON Schema Specification](#) defines a JSON format for describing JSON payloads. The following clause describes how Redfish uses JSON Schema to describe resources and resource collections.

### 12.2.1 File naming conventions for JSON Schema

Versioned Redfish JSON Schema files shall use the [resource name](#) to name the file, in this format:

```
ResourceName .v MajorVersion _ MinorVersion _ Errata .json
```

For example, version 1.3.0 of the Chassis schema is `Chassis.v1_3_0.json`.

Unversioned Redfish JSON Schema files shall use the [resource name](#) to name the file, in this format:

```
ResourceName .json
```

For example, the unversioned definition of the Chassis schema is `Chassis.json`.

### 12.2.2 Core JSON Schema files

File	Description
<code>odata-v4.json</code>	Definitions for common OData properties.
<code>redfish-error.v1_0_0.json</code> and its subsequent versions	Payload definition of the <a href="#">Redfish error response</a> .
<code>redfish-schema-v1.json</code>	Extensions to the JSON Schema that define Redfish JSON Schema files.
<code>Resource.json</code> and its subsequent versions	All base definitions for resources, resource collections, and common properties, such as <code>Status</code> .

### 12.2.3 JSON Schema format

Each JSON Schema file contains a JSON object to describe [resources](#), [resource collections](#), and other definitions for the data model.

The JSON object contains the following terms:

Term	Description
<code>\$id</code>	Reference to the URI where the schema file is published.
<code>\$ref</code>	For a schema file that describes a resource or resource collection, the reference to the structural definition of the resource or resource collection.
<code>\$schema</code>	URI to the Redfish schema extensions for JSON Schema. The value should be <code>http://redfish.dmtf.org/schemas/v1/redfish-schema-v1.json</code> .
<code>copyright</code>	Copyright statement for the organization producing the JSON Schema.
<code>definitions</code>	Structures, enumerations, and other definitions defined by the schema.
<code>title</code>	For a schema file that describes a resource or resource collection, the matching <a href="#">type identifier</a> for the resource or resource collection.

### 12.2.4 JSON Schema definitions body

This clause describes the types of definitions found in the `definitions` term of a Redfish JSON Schema file.

### 12.2.4.1 Resource definitions in JSON Schema

To satisfy [versioning](#) requirements, the JSON Schema representation of each [resource](#) has one unversioned schema file, and a set of versioned schema files.

The unversioned definition of a resource contains an `anyOf` statement. This statement consists of an array of `$ref` terms, which point to the following definitions:

- The JSON Schema definition for a [reference property](#).
- The versioned definitions of the resource.

The unversioned definition of a resource also uses the `uris` term to express the [allowable URIs for the resource](#), and the `deletable`, `insertable`, and `updatable` terms to express the [capabilities of the resource](#).

The following example shows an unversioned resource definition in JSON Schema:

```
{
  "ComputerSystem": {
    "anyOf": [
      {
        "$ref": "http://redfish.dmtf.org/schemas/v1/odata.v4_0_3.json#/definitions/idRef"
      },
      {
        "$ref": "http://redfish.dmtf.org/schemas/v1/ComputerSystem.v1_0_0.json#/definitions/ComputerSystem"
      },
      {
        "$ref": "http://redfish.dmtf.org/schemas/v1/ComputerSystem.v1_0_1.json#/definitions/ComputerSystem"
      },
      {
        "$ref": "http://redfish.dmtf.org/schemas/v1/ComputerSystem.v1_6_0.json#/definitions/ComputerSystem"
      }
    ],
    "deletable": true,
    "description": "The ComputerSystem schema represents a general purpose machine or system.",
    "insertable": false,
    "longDescription": "This resource shall represent resources that represent a computing system.",
    "updatable": true,
    "uris": [
      "/redfish/v1/Systems/{ComputerSystemId}"
    ]
  },
  ...
}
```

The versioned definition of a resource contains the property definitions for the given version of the resource.



### 12.2.4.2 Enumerations in JSON Schema

Definitions for enumerations can consist of these terms:

Term	Description
enum	String array that contains the possible enumeration values.
enumDescriptions	Object that contains the <a href="#">descriptions</a> for each of the enumerations as name-value pairs.
enumLongDescriptions	Object that contains the <a href="#">long descriptions</a> for each of the enumerations as name-value pairs.
enumDeprecated	Object that contains the <a href="#">deprecation guidance</a> for each of the enumerations as name-value pairs.
enumVersionDeprecated	Object that contains the <a href="#">deprecation version information</a> for each of the enumerations as name-value pairs.
type	Because all enumerations in Redfish are strings, the <code>type</code> term always has the <code>string</code> value.

The following example shows an enumeration definition in JSON Schema:

```
{
  "IndicatorLED": {
    "enum": [
      "Lit",
      "Blinking",
      "Off"
    ],
    "enumDescriptions": {
      "Blinking": "The Indicator LED is blinking.",
      "Lit": "The Indicator LED is lit.",
      "Off": "The Indicator LED is off."
    },
    "enumLongDescriptions": {
      "Blinking": "This value shall represent the Indicator LED is in a blinking state where the LED is being turned on",
      "Lit": "This value shall represent the Indicator LED is in a solid on state.",
      "Off": "This value shall represent the Indicator LED is in a solid off state."
    },
    "type": "string"
  },
  ...
}
```

### 12.2.4.3 Actions in JSON Schema

Versioned definitions of [resources](#) contain a definition called `Actions`. This definition is a container with a set of terms that point to the different [actions](#) supported by the resource. The names of standard actions shall be in the form:

```
# ResourceType . ActionName
```

Example Actions definition:

```
{
  "Actions": {
    "additionalProperties": false,
    "description": "The available actions for this resource.",
    "longDescription": "This type shall contain the available actions for this resource.",
    "properties": {
      "#ComputerSystem.Reset": {
        "$ref": "#/definitions/Reset"
      }
    },
    "type": "object"
  },
  ...
}
```

Another definition within the same schema file describes the action itself. This definition contains a term called `parameters` to describe the client request body. It also contains property definitions for the `target` and `title` properties shown in response payloads for the resource.

The following example shows a definition of an action:

```
{
  "Reset": {
    "additionalProperties": false,
    "description": "This action resets the system.",
    "longDescription": "This action shall perform a reset of the ComputerSystem.",
    "parameters": {
      "ResetType": {
        "$ref": "http://redfish.dmtf.org/schemas/v1/Resource.json#/definitions/ResetType",
        "description": "The type of reset to be performed.",
        "longDescription": "This parameter shall define the type of reset to be performed."
      }
    },
    "properties": {
      "target": {
        "description": "Link to invoke action",
        "format": "uri",
        "type": "string"
      },
      "title": {
        "description": "Friendly action name",
        "type": "string"
      }
    }
  }
}
```

```

    },
    "type": "object"
  },
  ...
}

```

Some action parameters may specify a type that is a resource definition. In these cases, the parameter in the request will be a [reference object](#) to a resource within the service.

#### 12.2.4.3.1 OEM actions in JSON Schema

OEM-specific actions shall be defined by using an action definition in an appropriately named JSON Schema file. For example, the following definition defines the OEM `#Contoso.Ping` action, assuming it's found in the versioned Contoso JSON Schema file, such as `Contoso.v1_0_0.json`.

```

{
  "Ping": {
    "additionalProperties": false,
    "parameters": {},
    "properties": {
      "target": {
        "description": "Link to invoke action",
        "format": "uri",
        "type": "string"
      },
      "title": {
        "description": "Friendly action name",
        "type": "string"
      }
    },
    "type": "object"
  },
  ...
}

```

#### 12.2.4.3.2 Action with a response body

A response body for an action shall be defined using the `actionResponse` term within the action definition. For example, the following definition defines the `GenerateCSR` action with a response that contains the definition specified by `#/definitions/GenerateCSRResponse`.

```

{
  "GenerateCSR": {

```

```

    "actionResponse": {
      "$ref": "#/definitions/GenerateCSRResponse"
    },
    "parameters": {}
  },
  "GenerateCSRResponse": {
    "additionalProperties": false,
    "description": "The response body for the GenerateCSR action.",
    "properties": {
      "CSRString": {
        "description": "The string for the certificate signing request.",
        "readOnly": true,
        "type": "string"
      },
      "CertificateCollection": {
        "$ref": "http://redfish.dmtf.org/schemas/v1/CertificateCollection.json#/definitions/CertificateCollection",
        "description": "The link to the certificate resource collection where the certificate is installed.",
        "readOnly": true
      }
    },
    "required": [
      "CertificateCollection",
      "CSRString"
    ],
    "type": "object"
  }
}

```

In the previous example, the following payload is an example response for the `GenerateCSR` action.

```

{
  "CSRString": "-----BEGIN CERTIFICATE REQUEST-----.....-----END CERTIFICATE REQUEST-----",
  "CertificateCollection": {
    "@odata.id": "/redfish/v1/Managers/BMC/NetworkProtocol/HTTPS/Certificates"
  }
}

```

### 12.2.5 JSON Schema terms

Redfish uses the following JSON Schema terms to provide [schema annotations](#) for Redfish JSON Schema:

JSON Schema term	Related Redfish schema annotation
<code>description</code>	<a href="#">Description</a>
<code>enumDescriptions</code>	

JSON Schema term	Related Redfish schema annotation
longDescription enumLongDescriptions	Long description
additionalProperties	Additional properties
readonly	Permissions
required	Required
requiredOnCreate	Required on create
units	Units of measure
autoExpand	Expanded resource
deletable insertable updatable	Resource capabilities
uris	Resource URI patterns
owningEntity	Owning entity
deprecated versionDeprecated	Deprecated

## 12.3 OpenAPI

The [OpenAPI Specification](#) defines a format for describing JSON payloads and the set of URIs a client can access on a service. The following clause describes how Redfish uses OpenAPI to describe resources and resource collections.

### 12.3.1 File naming conventions for OpenAPI schema

Versioned Redfish OpenAPI files shall be named using the [resource name](#), following the format:

```
ResourceName .v MajorVersion _ MinorVersion _ Errata .yaml
```

For example, version 1.3.0 of the Chassis schema is `Chassis.v1_3_0.yaml`.

Unversioned Redfish OpenAPI files shall use the [resource name](#) to name the file, in this format:

```
ResourceName .yaml
```

For example, the unversioned definition of the Chassis schema is `Chassis.yaml`.

### 12.3.2 Core OpenAPI schema files

File	Description
<code>odata-v4.yaml</code>	Definitions for common OData properties.
<code>openapi.yaml</code>	URI paths and their respective payload structures.
<code>Resource.yaml</code> and its subsequent versions	All base definitions for resources, resource collections, and common properties, such as <code>Status</code> .

### 12.3.3 `openapi.yaml`

The `openapi.yaml` file is the starting point for clients to understand the construct of the service. It contains the following terms:

Term	Description
<code>components</code>	Global definitions. For Redfish, contains the format of the <a href="#">Redfish error response</a> .
<code>info</code>	Structure consisting of information about what the <code>openapi.yaml</code> is describing, such as the author of the file and any contact information.
<code>openapi</code>	Version of OpenAPI the document follows.
<code>paths</code>	URIs supported by the document, with possible methods, response bodies, and request bodies.

The service shall return the `openapi.yaml`, if present in the Redfish Service, as a YAML document by using either the `application/yaml` or `application/vnd.oai.openapi` MIME types. The service may append `;charset=utf-8` to the MIME type. Note that while the `application/yaml` type is in common use today, the `application/vnd.oai.openapi` type was recently defined and approved specifically to support OpenAPI. Implementations should use caution when selecting the MIME type as this specification may change in the future to reflect adoption of the OpenAPI-defined MIME type.

The `paths` term contains an array of the [possible URIs](#). For each URI, it also lists the [possible methods](#). For each method, it lists the possible response bodies and request bodies.

Example `paths` entry for a resource:

```
/redfish/v1/Systems/{ComputerSystemId}:
  get:
    parameters:
      - description: The value of the Id property of the ComputerSystem resource
```

```

in: path
name: ComputerSystemId
required: true
schema:
  type: string
responses:
  '200':
    content:
      application/json:
        schema:
          $ref: http://redfish.dmtf.org/schemas/v1/ComputerSystem.v1_6_0.yaml#/components/schemas/ComputerSystem
    description: The response contains a representation of the ComputerSystem resource
  default:
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/RedfishError'
    description: Error condition

```

Example `paths` entry for an action:

```

/redfish/v1/Systems/{ComputerSystemId}/Actions/ComputerSystem.Reset:
post:
  parameters:
    - description: The value of the Id property of the ComputerSystem resource
      in: path
      name: ComputerSystemId
      required: true
      type: string
  requestBody:
    content:
      application/json:
        schema:
          $ref: http://redfish.dmtf.org/schemas/v1/ComputerSystem.v1_6_0.yaml#/components/schemas/ResetRequestBody
    required: true
  responses:
    '200':
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/RedfishError'
      description: The response contains the results of the Reset action
    '202':
      content:
        application/json:
          schema:
            $ref: http://redfish.dmtf.org/schemas/v1/Task.v1_4_0.yaml#/components/schemas/Task
      description: Accepted; a task has been generated

```

```

'204':
  description: Success, but no response data
  default:
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/RedfishError'
  description: Error condition

```

### 12.3.4 OpenAPI file format

With the exception of `openapi.yaml`, each OpenAPI file contains a YAML object to describe [resources](#), [resource collections](#), or other definitions for the data model. The YAML object contains the following terms:

Term	Description
<code>components</code>	Structures, enumerations, and other definitions defined by the schema.
<code>x-copyright</code>	Copyright statement for the organization producing the OpenAPI file.
<code>title</code>	For a schema file that describes a resource or resource collection, the matching <a href="#">type identifier</a> for the resource or resource collection.

### 12.3.5 OpenAPI components body

This clause describes the types of definitions that can be found in the `components` term of a Redfish OpenAPI file.

#### 12.3.5.1 Resource definitions in OpenAPI

To satisfy [versioning](#) requirements, the OpenAPI representation of each [resource](#) has one unversioned schema file, and a set of versioned schema files.

The unversioned definition of a resource contains an `anyOf` statement. This statement consists of an array of `$ref` terms, which point to the following definitions:

- The OpenAPI definition for a [reference property](#).
- The versioned definitions of the resource.

Example unversioned resource definition in OpenAPI:

```

ComputerSystem:
  anyOf:

```



```

- $ref: http://redfish.dmtf.org/schemas/v1/odata.v4_0_3.yaml#/components/schemas/idRef
- $ref: http://redfish.dmtf.org/schemas/v1/ComputerSystem.v1_0_0.yaml#/components/schemas/ComputerSystem
- $ref: http://redfish.dmtf.org/schemas/v1/ComputerSystem.v1_0_1.yaml#/components/schemas/ComputerSystem
- $ref: http://redfish.dmtf.org/schemas/v1/ComputerSystem.v1_6_0.yaml#/components/schemas/ComputerSystem
description: The ComputerSystem schema represents a general purpose machine
  or system.
x-longDescription: This resource shall be used to represent resources that represent
  a computing system.
    
```

The versioned definition of a resource contains the property definitions for the given version of the resource.

### 12.3.5.2 Enumerations in OpenAPI

Definitions for enumerations can consist of the following terms:

Term	Description
enum	String array that contains the possible enumeration values.
type	Because all enumerations in Redfish are strings, the <code>type</code> term always has the value <code>string</code> .
x-enumDescriptions	Object that contains the <a href="#">descriptions</a> for each of the enumerations as name-value pairs.
x-enumLongDescriptions	Object that contains the <a href="#">long descriptions</a> for each enumeration as a name-value pair.
x-enumDeprecated	Object that contains the <a href="#">deprecation guidance</a> for each of the enumerations as name-value pairs.
x-enumVersionDeprecated	Object that contains the <a href="#">deprecation version information</a> for each of the enumerations as name-value pairs.

Example enumeration definition in OpenAPI:

```

IndicatorLED:
  enum:
    - Lit
    - Blinking
    - 'Off'
  type: string
  x-enumDescriptions:
    Blinking: The Indicator LED is blinking.
    Lit: The Indicator LED is lit.
    'Off': The Indicator LED is off.
  x-enumLongDescriptions:
    Blinking: This value shall represent the Indicator LED is in a blinking state
      where the LED is being turned on and off in repetition.
    Lit: This value shall represent the Indicator LED is in a solid on state.
    'Off': This value shall represent the Indicator LED is in a solid off state.
    
```

### 12.3.5.3 Actions in OpenAPI

Versioned definitions of [resources](#) contain a definition called `Actions`. This definition is a container with a set of terms that point to the different [actions](#) supported by the resource. The names of standard actions shall be in the form:

```
# ResourceType . ActionName
```

Example `Actions` definition:

```
Actions:
  additionalProperties: false
  description: The available actions for this resource.
  properties:
    '#ComputerSystem.Reset':
      $ref: '#/components/schemas/Reset'
  type: object
  x-longDescription: This type shall contain the available actions for this resource.
```

Another definition within the same schema file describes the action itself. This definition contains property definitions for the `target` and `title` properties shown in response payloads for the resource.

The following example shows a definition of an action:

```
Reset:
  additionalProperties: false
  description: This action resets the system.
  properties:
    target:
      description: Link to invoke action
      format: uri
      type: string
    title:
      description: Friendly action name
      type: string
  type: object
  x-longDescription: This action shall reset the ComputerSystem.
```

The parameters for the action are shown in another definition with `RequestBody` appended to the name of the action. This gets mapped from the `openapi.yaml` file for expressing the POST method for the URI of the action.

The following example shows a definition of parameters of an action:

```

ResetRequestBody:
  additionalProperties: false
  description: This action resets the system.
  properties:
    ResetType:
      $ref: http://redfish.dmtf.org/schemas/v1/Resource.yaml#/components/schemas/ResetType
      description: The reset type.
      x-longDescription: This parameter shall define the type of reset to perform.
  type: object
  x-longDescription: This action shall reset the ComputerSystem.
    
```

### 12.3.5.3.1 OEM actions in OpenAPI

OEM-specific actions shall be defined by using an action definition in an appropriately named OpenAPI file. For example, the following definition defines the OEM #Contoso.Ping action, assuming it's found in the versioned Contoso OpenAPI file with a name, such as Contoso.v1\_0\_0.yaml .

```

Ping:
  additionalProperties: false
  properties:
    target:
      description: Link to invoke action
      format: uri
      type: string
    title:
      description: Friendly action name
      type: string
  type: object
PingRequestBody:
  additionalProperties: false
  properties: {}
  type: object
    
```

### 12.3.6 OpenAPI terms used by Redfish

The following OpenAPI terms provide [schema annotations](#) for Redfish OpenAPI files:

OpenAPI term	Related Redfish schema annotation
description x-enumDescriptions	Description
x-longDescription x-enumLongDescriptions	Long description

OpenAPI term	Related Redfish schema annotation
<code>additionalProperties</code>	Additional properties
<code>readOnly</code>	Permissions
<code>required</code>	Required
<code>x-requiredOnCreate</code>	Required on create
<code>x-units</code>	Units of measure
<code>x-autoExpand</code>	Expanded resource
<code>x-owningEntity</code>	Owning entity
<code>deprecated</code> <code>x-deprecatedReason</code> <code>x-versionDeprecated</code>	Deprecated

## 12.4 Schema modification rules

Schema referenced from the implementation may vary from the canonical definitions of those schema defined by the Redfish schema or other entities, provided they adhere to the following rules. Clients should take this into consideration when attempting operations on the resources defined by schema.

- Modified schema may constrain a [read/write property to be read only](#).
- Modified schema may constrain a property by adding length annotations to properties that do not have those annotations.
- Modified schema may constrain a property by adding a pattern annotation to properties that do not have that annotation.
- Modified schema may constrain the [capabilities of a resource or resource collection](#) to remove support for HTTP operations.
- Modified schema may remove [properties](#) that are not [required](#).
- Modified schema may remove [actions](#).
- Modified schema may remove action parameters that are not required.
- Modified schema may change [description annotations](#).
- Modified schema may change any external references to point to Redfish schema that adheres to the modification rules.
- Modified schema may change the [owning entity annotation](#) to specify who made the modifications.
- Modified schema may remove URIs from the [resource URI patterns annotation](#).
- Modified schema may add URIs to the [resource URI patterns annotation](#) to define OEM URIs for standard resources and shall follow the OEM URI rules specified by the [OEM resource naming and URIs](#) clause.
- Other modifications to the schema shall not be allowed.

## 13 Service details

---

### 13.1 Eventing

---

This clause describes how to use the REST-based mechanism to subscribe to and receive event messages.

**Note:** For security implications of eventing, see the [Security details](#) clause.

The Redfish Service requires a client or administrator to create *subscriptions* to receive events.

To create a subscription, use one of these methods:

- Directly HTTP [POST to the subscription collection](#).
- Indirectly [open a Server-Sent Events \(SSE\) connection](#) for the Event Service.

#### 13.1.1 POST to subscription collection

To locate the Event Service, the client traverses the Redfish Service interface. The Event Service is located in the Service Root, as described in the `ServiceRoot` schema.

Once the client discovers the service, they send an HTTP POST to the resource collection URI for `Subscriptions` in the Event Service to subscribe to events. For the *subscription* body syntax, see the Redfish `EventDestination` schema. This request includes:

- The URI where an event-receiver client expects events to be sent. When an event is triggered within the Redfish Service, the service sends an event to that URI.
- The type of events to send.

If the subscription request succeeds, the service shall return:

- An HTTP [201 Created](#) status code.
- The `Location` header that contains a URI of the newly created subscription resource.

If the subscription request succeeds, the service should return:

- A response body containing a representation of the subscription resource that conforms to the `EventDestination` schema.

After a subscription is registered with the service, clients begin receiving events. Clients do not receive events retroactively. The service does not retain historical events.

Services shall:

- Support *push* style eventing for all resources that can send events.
- Respond to a request to create a subscription with an error if the body of the request is conflicting. For instance, if parameters in the request are not supported, the service shall return the HTTP `400 Bad Request` status code.
- Respond to a request to create a subscription with an error if the body of the request contains both `RegistryPrefixes` and `MessageIds`, and shall return the HTTP `400 Bad Request` status code. These properties are considered mutually exclusive.
- Retain subscriptions as persistent across service restarts.

Services shall not:

- *Push* events by using HTTP POST unless an event subscription has been created. To terminate the event stream at any time, either the client or the service can delete the subscription.
- Send a *push* event payload larger than 1 Mebibyte (1 MiB). If there is more than 1 MiB worth of data to send the service shall divide the payload on the nearest `Event` entry such that the total payload transmitted to the client is less than 1 MiB. This restriction shall not apply to metric reports.

Services may:

- Terminate a subscription by sending a `SubscriptionTerminated` message from the Base Message Registry as the last event.
- Terminate a subscription if the number of delivery errors exceeds preconfigured thresholds.

To unsubscribe from the events associated with this subscription, the client or administrator shall send an HTTP DELETE request to the subscription's resource URI.

Subsequent requests to subscription resources that have been terminated respond with the HTTP `404 Not Found` status code.

Some configurable properties define the behavior for all event subscriptions. For details, see the Redfish `EventService` schema.

### 13.1.2 Open an SSE connection

A service may support the `ServerSentEventUri` property in the `EventService` resource. If a client performs a GET on the URI that the `ServerSentEventUri` contains, an SSE connection opens for the client. For details about this method, see the Server-Sent Events [Event service](#) clause.

### 13.1.3 EventType-based eventing

**DEPRECATED:** `EventType`-based eventing is deprecated in the Redfish schema in favor of using `RegistryPrefix` and `ResourceType`.

**DEPRECATED**

A Redfish Service generates these types of events:

Event	Occurs when	Description
Life cycle	Resources are created, modified, or destroyed.  Usually indicates that the resource and, optionally, its properties have changed.	Not every modification of a resource results in an event. This behavior is similar to when ETags are changed and implementations may not send an event for every resource change.  For example, if an event is sent for every Ethernet packet that is received or each time that a sensor changes one degree, more events than fit in a scalable interface are generated.
Alert	An event of some significance happens.  Depending on the resource, may be generated directly or indirectly.	Usually adopts a Message Registry approach similar to extended error handling in that a <code>MessageId</code> is included.  An example of an alert event is, a chassis is opened, a button is pushed, a cable is unplugged, or a threshold exceeded.  These events usually do not correspond well to life cycle-type events. Therefore, alerts have their own category.
Metric report	The Telemetry Service generates or updates a metric report.	Generated as specified by the <code>MetricReportDefinition</code> resources found <a href="#">subordinate</a> to the Telemetry Service. Can occur periodically, on demand, or when changes are detected in the metric properties.  For details, see the Redfish <code>MetricReportDefinition</code> schema.

**END DEPRECATED**

**13.1.4 Subscribing to events**

To subscribe to events and filter received messages, a subscriber provides these properties:

Property	Description
<code>RegistryPrefixes</code>	<p>An array of standard or OEM Message Registries.</p> <p>An event is sent to the subscriber if one of the Message Registries that <code>RegistryPrefixes</code> lists defines the event message.</p> <p>To receive messages from all registries, pass an empty array.</p> <p>The contents of the array does not include the registry version.</p> <p>For example, if the registry is <code>Base.1.5.0</code>, the property value is <code>Base</code>.</p>
<code>ResourceTypes</code>	<p>An array of standard or OEM resource types.</p> <p>An event is sent to the subscriber if the <code>OriginOfCondition</code> resource type matches one of the <code>ResourceTypes</code> values.</p> <p>The contents of the array does not include the schema version. For example, if the resource type is <code>Task.v1_2_0.Task</code>, the property value is <code>Task</code>.</p> <p>To receive messages from any resource, pass an empty array.</p>
<code>OriginResources</code>	<p>An array of URIs to resources.</p> <p>An event is sent to the subscriber if the <code>OriginOfCondition</code> property matches one of the URIs listed in <code>OriginResources</code>.</p> <p>To receive messages from any resource, pass an empty array.</p> <p>To include subordinate resources regardless of depth, set the <code>SubordinateResources</code> property to <code>true</code>.</p>
<code>EventFormatType</code>	<p>The format that can be sent by using the <code>EventFormatTypes</code> property in the Event Service.</p> <p>Represents the format of the payload sent to the event destination.</p> <p>If the subscriber omits this value, the payload corresponds to the <code>Event</code> schema.</p>

### 13.1.5 Event formats

The event formats are:



Event format	Description
Metric report message objects	Used when the Telemetry Service generates a new or updates an existing metric report. Metric report message objects sent to the specified client endpoint shall contain the properties, as described in the Redfish <code>MetricReport</code> schema.
Event message objects	<p>Used for all other types of events. Event message objects POSTed to the specified client endpoint shall contain the properties as described in the Redfish <code>Event</code> schema. Supports a message registry. In a message registry approach, a message registry lists the <code>MessageIds</code> in a well-known format. These <code>MessageIds</code> are terse in nature and thus they are much smaller than actual messages, making them suitable for embedded environments.</p> <p>The registry also contains a message. The message itself can have arguments and default values for severity and recommended actions. The <code>MessageId</code> property follows the format defined in the <a href="#">MessageId format clause</a></p> <p>Event messages may also have an <code>EventGroupId</code> property, which lets clients know that different messages may be from the same event. For instance, if a LAN cable is disconnected, they may get a specific message from one registry about the LAN cable being disconnected, another message from a general registry about the resource changing, perhaps a message about resource state change, and maybe more. For the client to determine whether these have the same root cause, these messages have the same value for the <code>EventGroupId</code> property.</p>

### 13.1.6 OEM extensions

OEMs can extend both messages and Message Registries. Any individual message, per the `MessageRegistry` schema definition, define OEM sections. Thus, if OEMs wish to provide additional information or properties, use the OEM section.

OEMs shall not supply additional message arguments beyond those in a standard Message Registry. OEMs may substitute their own Message Registry for the standard registry to provide the OEM section within the registry but shall not change the standard values, such as messages, in such registries.

## 13.2 Asynchronous operations

Services that support asynchronous operations implement the `TaskService` and `Task` resources.

The Task Service describes the service that handles `task`. It contains a resource collection of zero or more `Task` resources. The `Task` resource describes a long-running operation that is spawned when a request takes longer than a few seconds, such as when a service is instantiated.

The `Task` schema defines task structure, including the start time, end time, task state, task status, and zero or more task-associated messages.

Each task has a number of possible states. The `Task` schema defines the exact states and their semantics.

When a client issues a request for a long-running operation, the service returns the HTTP `202 Accepted` status code and a `Location` header that contains the URI of the *task monitor* and, optionally, the `Retry-After` header that defines the amount of time that the client should wait before querying the status of the operation.

The task monitor is an opaque service-generated URI that the client who initiates the request can use. To query the status of an operation, and determine when the operation has been completed and whether it succeeded, the client performs a GET request on the task monitor. The client should not include the `application/http` MIME type in the `Accept` header.

The `202 Accepted` response body should contain an instance of the `Task` resource that describes the state of the task.

As long as the operation is in process, the service shall continue to return the HTTP `202 Accepted` status code when the client queries the task monitor URI.

If a service supports cancellation of a task, it shall have `DELETE` in the `Allow` header for the task monitor. To cancel the operation, the client may perform a `DELETE` on the task monitor URI. The service determines when to delete the associated `Task` resource.

To cancel the operation, the client may also perform a `DELETE` on the `Task` resource. Deleting the `Task` resource may invalidate the associated task monitor. A subsequent GET request on the task monitor URI returns either the HTTP `410 Gone` status code or the HTTP `404 Not Found` status code.

In the unlikely event that a `DELETE` of the task monitor or `Task` resource returns the HTTP `202 Accepted` status code, an additional task shall not be started and instead the client may monitor the existing `Task` resource for the status of the cancellation request. When the task finally completes cancellation, operations to the task monitor and `Task` resources shall return the HTTP `404 Not Found` status code.

After the operation has been completed, the service shall update the `TaskState` with the appropriate value. The `Task` schema defines the task completed values.

After the operation has been completed, the task monitor shall return:

- The appropriate HTTP status code, such as but not limited to `200 OK` for most operations or `201 Created` for POST to create a resource.
- The headers and response body of the initial operation, as if it had completed synchronously.

If the initial operation fails, the response body shall contain an [error response](#).

If the operation has been completed and the service has already deleted the task, the service may return the HTTP `410 Gone` or `404 Not Found` status code. This situation can occur if the client waits too long to read the task monitor.

To continue to get status information, the client can use the [resource identifier](#) from the `202 Accepted` response to directly query the `Task` resource.

- Services that support asynchronous operations shall implement the `Task` resource.
- The response to an asynchronous operation shall return the HTTP `202 Accepted` status code and set the `Location` response header to the URI of a task monitor associated with the task. The response may also include the `Retry-After` header that defines the amount of time that the client should wait before polling for status. The response body should contain a representation of the `Task` resource.
- GET requests to either the task monitor or `Task` resource shall return the current status of the operation without blocking.
- HTTP GET, PUT, and PATCH operations should always be synchronous.
- Clients shall be prepared to handle both synchronous and asynchronous responses for HTTP GET, PUT, PATCH, POST, and DELETE requests.
- Services shall persist pending tasks produced by client requests containing `@Redfish.OperationApplyTime` across service restarts, until the task begins execution.
- Tasks that are pending execution should include the `@Redfish.OperationApplyTime` property to indicate when the task will start. If the `@Redfish.OperationApplyTime` value is `AtMaintenanceWindowStart` or `InMaintenanceWindowOnReset`, the task should also include the `@Redfish.MaintenanceWindow` property.

### 13.3 Resource tree stability

---

The *resource tree*, which is defined as the set of URIs and array elements within the implementation, should be consistent on a single service across device resets or power cycles, and should withstand a reasonable amount of configuration change, such as adding an adapter to a server.

The resource tree on one service may not be consistent across instances of devices. The client should traverse the data model and discover resources to interact with them.

Some resources might remain very stable from system to system, such as manager network settings. However, the architecture does not guarantee this stability.

- A resource tree should remain stable across service restarts and minor device configuration changes. Thus, the set of URIs and array element indexes should remain constant.
- A client shall not expect the resource tree to be consistent between instances of services.

### 13.4 Discovery

---

Automatic discovery of managed devices supporting Redfish may be accomplished by using the Simple Service Discovery Protocol (SSDP). This protocol enables network-efficient discovery without resorting to ping-sweeps, router table searches, or restrictive DNS naming schemes. Use of SSDP is optional, and if implemented, shall enable the user to disable the protocol through the `ManagerNetworkProtocol` resource.

The objective of discovery is for client software to locate managed devices that conform to the Redfish Specification. Therefore, the primary SSDP functionality is incorporated in the M-SEARCH query. Redfish also follows the SSDP

extensions and naming that UPnP uses, where applicable, so that systems that conform to the Redfish Specification can also implement UPnP without conflict.

### 13.4.1 UPnP compatibility

For compatibility with general-purpose SSDP client software, primarily UPnP, the service should use UDP port 1900 for all SSDP traffic. In addition, the Time-to-Live (TTL) hop count setting for SSDP multicast messages should default to 2.

### 13.4.2 USN format

The UUID in the USN field of the service shall equal the UUID property in the Service Root. If multiple or redundant managers exist, the UUID of the service shall remain static regardless of redundancy failover. The unique ID shall be in the canonical UUID format, followed by `::dmf-org`.

### 13.4.3 M-SEARCH response

The Redfish Service Search Target (ST) is defined as:

```
urn:dmtf-org:service:redfish-rest:1
```

The managed device shall respond to M-SEARCH queries for Search Target (ST) of the Redfish Service, as well as `ssdp:all`. For UPnP compatibility, the managed device should respond to M-SEARCH queries for Search Target (ST) of `upnp:rootdevice`.

The URN provided in the `ST` header in the reply shall use the `redfish-rest:` service name followed by the major version of the Redfish Specification. If the minor version of the Redfish Specification to which the service conforms is a non-zero value, that minor version shall be appended with and preceded by a colon (`:`).

For example, a service that conforms to a Redfish Specification v1.4 would reply with a `redfish-rest:1:4` service.

The managed device shall provide clients with the `AL` header that points to the Redfish Service Root URL.

For UPnP compatibility, the managed device should provide clients with the `Location` header that points to the UPnP XML descriptor.

The response to an M-SEARCH multicast or unicast query shall use the following format:

```
HTTP/1.1 200 OK
CACHE-CONTROL:max-age=<seconds, at least 1800>
```

```
ST:urn:dmtf-org:service:redfish-rest:1
USN:uuid:<UUID of the service>::urn:dmtf-org:service:redfish-rest:1
AL:<URL of Redfish Service Root>
EXT:
```

A service may provide additional headers for UPnP compatibility. Fields in brackets are placeholders for device-specific values.

### 13.4.4 Notify, alive, and shutdown messages

Redfish devices may implement the additional UPnP-defined SSDP messages to announce their availability to software. If implemented, services shall allow the end user to disable the traffic separately from the M-SEARCH response functionality. This capability enables users to use the discovery functionality with minimal amounts of generated network traffic.

## 13.5 Server-Sent Events

---

### 13.5.1 General

Server-Sent Events (SSE), as defined by the Web Hypertext Application Technology Working Group, enables a client to open a connection with a web service. The web service can continuously push data to the client, as needed.

Successful resource responses for SSE shall:

- Return the HTTP `200 OK` status code.
- Have a `Content-Type` header set as `text/event-stream` or `text/event-stream; charset=utf-8`.

Unsuccessful resource responses for SSE shall:

- Return an HTTP status code of 400 or greater.
- Have a `Content-Type` header set as `application/json` or `application/json; charset=utf-8`.
- Contain a JSON object in the response body, as described in [Error responses](#), which details the error or errors.

A service may occasionally send a comment within a stream to keep the connection alive. Services shall separate events with blank lines. Blank lines should be sent as part of the end of an event, otherwise dispatch may be delayed in conforming consumers.

The following clauses describe how Redfish uses SSE in different Redfish data model contexts. For details about SSE, see the [HTML5 Specification](#).

### 13.5.2 Event service

A service's implementation of the `EventService` resource may contain the `ServerSentEventUri` property. If a client performs a GET on the URI specified by the `ServerSentEventUri` property, the service shall keep the connection open and conform to the [HTML5 Specification](#) until the client closes the socket. Service-generated events shall be sent to the client by using the open connection.

When a client opens an SSE stream for the Event Service, the service shall create an `EventDestination` resource in the `Subscriptions` collection for the Event Service to represent the connection. The `Context` property in the `EventDestination` resource shall be a service-generated opaque string.

The service shall delete the corresponding `EventDestination` resource when the connection is closed. The service shall close the connection if the corresponding `EventDestination` resource is deleted.

The service shall use the `id` field in the SSE stream to uniquely identify a payload in the SSE stream. The value of the `id` field is determined by the service. A service should accept the `Last-Event-ID` header from the client to allow a client to restart the event stream in case the connection is interrupted.

The service shall use the `data` field in the SSE stream based on the payload format. The SSE streams have these formats:

- [Metric report SSE stream](#). Services shall use this format when the Telemetry Service generates or updates a metric report.
- [Event message SSE stream](#). Services shall use this format for all other types of events.

To reduce the amount of data returned to the client, the service should support the `$filter` query parameter in the URI for the SSE stream.

**Note:** The `$filter` syntax shall follow the format in the [\\$filter query parameter](#) clause.

The service should support these properties as filter criteria:

- `EventFormatType`

The service sends events of the matching `EventFormatType`.

Example:

```
https://sseuri?$filter=EventFormatType eq Event
```

Valid values are the `EventFormatType` enumerated string values that the Redfish `EventService` schema defines.

- `EventType`

The service sends events of the matching `EventType` .

Example:

```
https://sseuri?$filter=EventType eq StatusChange
```

Valid values are the `EventType` enumerated string values that the Redfish `Event` schema defines.

- `MessageId`

The service sends events with the matching `MessageId` .

Example:

```
https://sseuri?$filter=MessageId eq 'Contoso.1.0.TempAssert'
```

- `MetricReportDefinition`

The service sends metric reports generated from the `MetricReportDefinition` .

Example:

```
https://sseuri?$filter=MetricReportDefinition eq '/redfish/v1/TelemetryService/MetricReportDefinitions/PowerMetrics'
```

- `OriginResource`

The service sends events for the resource.

Example:

```
https://sseuri?$filter=OriginResource eq '/redfish/v1/Chassis/1/Thermal'
```

- `RegistryPrefix`

The service sends events with messages that are part of the `RegistryPrefix` .

Example:

```
https://sseuri?$filter=(RegistryPrefix eq Resource) or (RegistryPrefix eq Task)
```

- `ResourceType`

The service sends events for resources that match the `ResourceType`.

Example:

```
https://sseuri?filter=(ResourceType eq 'Power') or (ResourceType eq 'Thermal')
```

- `SubordinateResources`

When `SubordinateResources` is true and `OriginResource` is specified, the service sends events for the resource and its subordinate resources.

Example:

```
https://sseuri?filter=(OriginResource eq '/redfish/v1/Systems/1') and (SubordinateResources eq true)
```

### 13.5.2.1 Event message SSE stream

The service shall use the `data` field in the SSE stream to include the JSON representation of the `Event` object.

The following example payload shows a stream that contains a single event with the `id` field set to `1`, and a `data` field that contains a single `Event` object.

```
id: 1
data: {
  data: {
    "@odata.type": "#Event.v1_6_0.Event",
    "Id": "1",
    "Name": "Event Array",
    "Context": "ABCDEFGH",
    "Events": [
      data: {
        "MemberId": "1",
        "EventType": "Alert",
        "EventId": "1",
      }
    ]
  }
}
```



```

data:      "Severity": "Warning",
data:      "MessageSeverity": "Warning",
data:      "EventTimestamp": "2017-11-23T17:17:42-0600",
data:      "Message": "The LAN has been disconnected",
data:      "MessageId": "Alert.1.0.LanDisconnect",
data:      "MessageArgs": [
data:          "EthernetInterface 1",
data:          "/redfish/v1/Systems/1"
data:      ],
data:      "OriginOfCondition": {
data:          "@odata.id": "/redfish/v1/Systems/1/EthernetInterfaces/1"
data:      },
data:      "Context": "ABCDEFGH"
data:    }
data:  ]
data:}

```

### 13.5.2.2 Metric report SSE stream

The service shall use the `data` field in the SSE stream to include the JSON representation of the [MetricReport object](#).

The following example payload shows a stream that contains a metric report with the `id` field set to `127`, and the `data` field containing the metric report object.

```

id: 127
data:{
data:  "@odata.id": "/redfish/v1/TelemetryService/MetricReports/AvgPlatformPowerUsage",
data:  "@odata.type": "#MetricReport.v1_3_0.MetricReport",
data:  "Id": "AvgPlatformPowerUsage",
data:  "Name": "Average Platform Power Usage metric report",
data:  "MetricReportDefinition": {
data:      "@odata.id": "/redfish/v1/TelemetryService/MetricReportDefinitions/AvgPlatformPowerUsage"
data:  },
data:  "MetricValues": [
data:      {
data:          "MetricId": "AverageConsumedWatts",
data:          "MetricValue": "100",
data:          "Timestamp": "2016-11-08T12:25:00-05:00",
data:          "MetricProperty": "/redfish/v1/Chassis/Tray_1/Power#/0/PowerConsumedWatts"
data:      },
data:      {
data:          "MetricId": "AverageConsumedWatts",
data:          "MetricValue": "94",
data:          "Timestamp": "2016-11-08T13:25:00-05:00",
data:          "MetricProperty": "/redfish/v1/Chassis/Tray_1/Power#/0/PowerConsumedWatts"

```

```
data:      },
data:      {
data:      "MetricId": "AverageConsumedWatts",
data:      "MetricValue": "100",
data:      "Timestamp": "2016-11-08T14:25:00-05:00",
data:      "MetricProperty": "/redfish/v1/Chassis/Tray_1/Power#/0/PowerConsumedWatts"
data:      }
data:    ]
data:  }
```

## 13.6 Update Service

---

### 13.6.1 Overview

This clause covers the mechanism for software updates by using the Update Service.

### 13.6.2 Software update types

Clients can use these methods to update software through the Update Service:

- **Simple updates:** The service *pulls* the update from a client-indicated network location.
- **Multipart HTTP push updates:** The client uses HTTP or HTTPS with a multipart-formatted request body to *push* a software image to the service.

#### 13.6.2.1 Simple updates

A service may support the `SimpleUpdate` action within the `UpdateService` resource. A client can perform a POST to the action target URI to initiate a pull-based update, as defined by the `UpdateService` schema. After a successful POST, the service should return the HTTP `202 Accepted` status code with the `Location` header set to the URI of a *task monitor*. Clients can use this *task* to monitor the progress and results of the update, which includes the progress of image transfer to the service.

#### 13.6.2.2 Multipart HTTP push updates

A service may support the `MultipartHttpPushUri` property within the `UpdateService` resource. A client can perform an HTTP or HTTPS POST on the URI specified by this property to initiate a push-based update.

- Access to this URI shall require the same privilege as access to the Update Service.
- A client POST to this URI shall contain the `Content-Type` HTTP header with the value `multipart/form-data`, with the body formatted as defined by this specification. For more information about `multipart/form-data` HTTP requests, see [RFC7578](#).

- The client POST request shall contain the binary image as one of the parts in a `multipart/form-data` request body, as defined by the following table. In addition, the request shall include parameters for the update in a JSON formatted part in the same `multipart/form-data` request body, as defined by the following table. If the request has no parameters, an empty JSON object shall be used.
- A service may require the `Content-Length` HTTP header for POST requests to this URI. In this case, if a client does not include the required `Content-Length` header in the POST request, the service shall return the HTTP [411 Length Required](#) status code.
- A service should return the HTTP [412 Precondition Failed](#) status code if the size of the binary image is larger than the maximum image size that the service supports, as advertised in `MaxImageSizeBytes` property in the `UpdateService` resource.
- After a successful POST to this URI, the service shall return the HTTP [202 Accepted](#) status code with a `Location` header set to the URI of a *task monitor*. This *task* can be used by clients to monitor the progress and results of the update.

The following table describes the requirements of a `multipart/form-data` request body for HTTP push software update:

Request body part	HTTP headers	Header value and parameters	Required	Description
Update parameters JSON part	<code>Content-Disposition</code>	<code>form-data; name="UpdateParameters"</code>	Yes	JSON-formatted part for passing the update parameters. The value of the <code>name</code> field shall be <code>"UpdateParameters"</code> . The format of the JSON shall follow the definition of the <code>UpdateParameters</code> object in the <code>UpdateService</code> schema.
	<code>Content-Type</code>	<code>application/json; charset=utf-8</code> or <code>application/json</code>	Yes	The media type format and character set of this request part.
Update file binary part	<code>Content-Disposition</code>	<code>form-data; name="UpdateFile"; filename=string</code>	Yes	Binary file to use for this software update. The value of the <code>name</code> field shall be <code>"UpdateFile"</code> . The value of the <code>filename</code> field should reflect the name of the file as loaded by the client.
	<code>Content-Type</code>	<code>application/octet-stream</code>	Yes	The media type format of the binary update file.
OEM specific parts	<code>Content-Disposition</code>	<code>form-data; name="OemXXXX"</code>	No	Optional OEM part. The value of the <code>name</code> field shall start with <code>"Oem"</code> . <code>Content-Type</code> is optional, and depends on the OEM part type.

This example shows a `multipart/form-data` request to push an update image:

```
POST /redfish/v1/UpdateService/upload HTTP/1.1
Host: <host-path>
Content-Type: multipart/form-data; boundary=-----d74496d66958873e
```

```
Content-Length: <computed-length>
Connection: keep-alive
X-Auth-Token: <session-auth-token>

-----d74496d66958873e
Content-Disposition: form-data; name="UpdateParameters"
Content-Type: application/json

{
  "Targets": [
    "/redfish/v1/Managers/1"
  ],
  "@Redfish.OperationApplyTime": "OnReset",
  "Oem": {}
}

-----d74496d66958873e
Content-Disposition: form-data; name="UpdateFile"; filename="flash.bin"
Content-Type: application/octet-stream

<software image binary>
```

# 14 Security details

---

## 14.1 Transport Layer Security (TLS) protocol

---

Implementations shall support the Transport Layer Security (TLS) protocol v1.2 with [RFC7525](#) recommendations or later. Implementations may remove support for older versions for TLS in favor of newer versions.

**DEPRECATED:** Previous versions of this specification allowed for TLS v1.1.

Implementations should support:

- The [Storage Networking Industry Association \(SNIA\) TLS Specification for Storage Systems](#).
- The latest version of the TLS v1.x specification.

### 14.1.1 Cipher suites

Implementations shall only support cipher suites listed as "Recommended" in the **TLS Cipher Suites** table defined by the [IANA TLS Parameters registry](#).

Cipher suites that are listed as mandatory in various RFCs, but are not "Recommended" in the **TLS Cipher Suites** table defined by the [IANA TLS Parameters registry](#), shall not be supported.

Implementations should consider the support of pre-shared key ciphers suites listed as "Recommended" in the **TLS Cipher Suites** table defined by the [IANA TLS Parameters registry](#), which enable authentication and identification without trusted certificates.

---

### DEPRECATED

Implementations should support AES-256-based ciphers from the TLS suites.

Redfish implementations should consider the support of ciphers, such as the following ciphers, which enable authentication and identification without trusted certificates:

```
TLS_PSK_WITH_AES_256_GCM_SHA384
TLS_DHE_PSK_WITH_AES_256_GCM_SHA384
TLS_RSA_PSK_WITH_AES_256_GCM_SHA384
```

The advantage of these recommended ciphers is:

---

AES-GCM is not only efficient and secure, but hardware implementations can achieve high speeds with low cost and low latency because the mode can be pipelined.

Additionally, Redfish implementations should support the following cipher:

```
TLS_RSA_WITH_AES_128_CBC_SHA
```

For more information, see [RFC5288](#) and [RFC5487](#).

## END DEPRECATED

---

### 14.1.2 Certificates

Redfish implementations shall support replacement of the default certificate if one is provided.

Redfish implementations shall use certificates that conform to X.509-v3, as defined in [RFC5280](#).

## 14.2 Sensitive data

---

Operations that contain sensitive data should use HTTPS only. For example, a `SimpleUpdate` action with a user name and password should use HTTPS to protect the sensitive data.

Properties in service responses that represent sensitive data, such as passwords, shall be `null`.

Responses from URIs that contain sensitive data may return the HTTP `404 Not Found` status code instead of the HTTP `401 Unauthorized` status code or the HTTP `403 Forbidden` status code to prevent attackers from obtaining the sensitive data in the URI.

## 14.3 Authentication

---

Services:

- Shall support both [HTTP Basic authentication](#) and [Redfish session login authentication](#).
  - Shall use only connections that conform to TLS to transport the data between any third-party authentication service and clients.
  - Shall not require a client that uses HTTP Basic authentication to create a session.
  - May implement other authentication mechanisms.
-

## 14.3.1 Authentication requirements

### 14.3.1.1 Resource and operation authentication requirements

Services shall authenticate all write requests to Redfish resources. For example:

- POST, except to the `Sessions` resource collection for authentication
- PUT
- PATCH
- DELETE

Redfish resources shall not be available as unauthenticated, except for:

- The service root to identify the device and service locations.
- The [Redfish metadata document](#) to get resource types.
- The [OData service document](#) for compatibility with OData clients.
- The Redfish [OpenAPI YAML document](#) for compatibility with OpenAPI clients.
- The `version` object at `/redfish`.

**Note:** This specification does not cover external services that are linked through external references. These services may have other security requirements.

### 14.3.1.2 HTTP header authentication requirements

An authentication header shall accompany every request that establishes a secure channel.

Services:

- Shall process HTTP headers for authentication before other headers that may affect the response. For example, `ETag`, `If-Modified`, and so on.
- Shall not use HTTP cookies to authenticate any activity, such as GET, POST, PUT, PATCH, and DELETE.

### 14.3.1.3 Authentication failure requirements

When authentication fails, extended error messages shall not provide privileged information.

## 14.3.2 HTTP Basic authentication

Services shall support HTTP Basic authentication, as defined by [RFC7617](#), and shall use only connections that conform to TLS to transport the data between any third-party authentication service and clients.

All requests that use HTTP Basic authentication shall require HTTPS.

**Note:** The IETF has highlighted security concerns with HTTP Basic authentication. While HTTPS is required for the usage of HTTP Basic authentication, there are other concerns implementors need to be aware of that are documented in [RFC7617](#).

### 14.3.3 Redfish session login authentication

Service shall provide login sessions that conform with this specification.

Session management is determined by the implementation of the Redfish Service, which includes orphaned session timeout and the management of the number of simultaneous open sessions.

#### 14.3.3.1 Redfish login sessions

For improved performance and security, a client should use the session management interface to create a Redfish login session. The session service specifies the URI for session management.

To establish a session, find the URI in either:

- The session service's `Sessions` property.
- The service root's `links` property under the `Sessions` property.

Both URIs shall be the same.

```
{
  "SessionService": {
    "@odata.id": "/redfish/v1/SessionService"
  },
  "Links": {
    "Sessions": {
      "@odata.id": "/redfish/v1/SessionService/Sessions"
    }
  },
  ...
}
```

#### 14.3.3.2 Session login

To create a Redfish session without an authentication header, perform an HTTP POST request to the session service's `Sessions` resource collection. The POST to create a session shall only be supported with HTTPS. If both HTTP and HTTPS are enabled, a POST request to create a session through the HTTP port should redirect to the HTTPS port. Include the following POST body:



```

POST /redfish/v1/SessionService/Sessions HTTP/1.1
Host: <host-path>
Content-Type: application/json;charset=utf-8
Content-Length: <computed-length>
Accept: application/json;charset=utf-8
OData-Version: 4.0

{
  "UserName": "<username>",
  "Password": "<password>"
}

```

Fields in brackets are placeholders for client-specific values.

To verify that the request has been initiated from an authorized client domain, services should save the `Origin` header in reference to this session creation and compare it to subsequent requests using this session.

The response to the POST request to create a session shall include:

- `X-Auth-Token` header. Contains a session authentication token that the client can use in subsequent requests.
- `Location` header. Contains a hyperlink to the new `Session` resource.
- JSON response body. Contains the full representation of the new `Session` resource.

The following is a sample response of a session being created:

```

HTTP/1.1 201 Created
Location: /redfish/v1/SessionService/Sessions/1
X-Auth-Token: <session-auth-token>

{
  "@odata.id": "/redfish/v1/SessionService/Sessions/1",
  "@odata.type": "#Session.v1_0_0.Session",
  "Id": "1",
  "Name": "User Session",
  "Description": "User Session",
  "UserName": "<username>",
  "Password": null
}

```

The client that sends the session login request should save the session authentication token from the `X-Auth-Token` header and the contents of the `Location` header from the response of the login POST request.

To authenticate subsequent requests, the client sets the `X-Auth-Token` header to the session authentication token that the POST login request returns.

**Note:** The session ID differs from the session authentication token, as follows:

- **Session ID:** The session ID uniquely identifies the `Session` resource. The response data with the last segment of the `Location header` URI returns is the session ID. To view active sessions and terminate any session, an administrator with sufficient privileges can use the session ID.
- **Session authentication token:** Only the client that executes the login has the session authentication token.

#### 14.3.3.3 Session lifetime

Unlike some token-based methods that use token expiration times, Redfish sessions time out. As long as a client continues to send requests more frequently than the session timeout period, the session remains open and the session authentication token remains valid. If the session times out, it is automatically terminated.

#### 14.3.3.4 Session termination or logout

When the client logs out, the Redfish session terminates. The session terminates through a DELETE request to the `Session` resource defined in either the `Location header` URI or the session ID in the response data.

This ability to DELETE a session through the `Session` resource enables an administrator with sufficient privileges to terminate other users' sessions from a different session.

When a session is terminated, the service shall not affect independent connections established originally by this session for other purposes, such as connections for [Server-Sent Events](#) or transferring an image for the [update service](#).

## 14.4 Authorization

---

The Redfish authorization subsystem controls which users have access to resources and the type of access that users have. It consists of two parts: the [privilege model](#) and the [operation-to-privilege mapping](#).

The privilege model maps users to roles and maps roles to privileges. A privilege is a permission to complete an operation, such as read or write, within a defined management domain. For example the `ConfigureUsers` privilege allows adding a user. A user is authorized to access a resource if they have the privileges required for that resource. The operation-to-privilege mapping defines which privileges are required to access any given operation.

Redfish allows vendors to extend the standard privilege model with OEM privileges and custom OEM roles. OEM privileges and custom roles participate in the privilege model the same as Redfish standard privileges and roles. Services may also allow clients to create custom roles. Restricted roles and restricted privileges allow vendors to further refine their authority model.

Services shall enforce the same privilege model for ETag-related activity as is enforced for the data being represented by the ETag. For example, the privilege required to read an ETag shall be the same as the privilege to read the data item that the ETag represents.

## 14.4.1 Privilege model

Each user shall be assigned exactly one role with the `RoleId` property in the `ManagerAccount` resource. The value of the `RoleId` property identifies a `Role` resource in the `RoleCollection` resource, where a role defines a set of privileges. A role shall be assigned to a user when a manager account is created. The client shall provide the `RoleId` property when creating a manager account to select one of the standard or custom roles.

Services shall provide information about all roles through the `RoleCollection` resource. The `AssignedPrivileges` and `OemPrivileges` arrays in the `Role` resource define a set of assigned privileges for the associated role. Two roles with the same privileges shall behave equivalently.

### 14.4.1.1 Roles

Redfish defines a set of standard roles, allows a service to define custom OEM roles, and allows client-defined custom roles.

A service shall support all of the standard roles in the following table. The value of the `Id` and `AssignedPrivileges` properties in the `Role` resource for the standard roles shall contain the value of the **Role name** and **Assigned privileges** columns respectively. The `AssignedPrivileges` property for standard roles shall not be modifiable. The `IsPredefined` property for standard roles shall contain the value `true`.

Role name	Assigned privileges
Administrator	Login, ConfigureManager, ConfigureUsers, ConfigureComponents, ConfigureSelf
Operator	Login, ConfigureComponents, ConfigureSelf
ReadOnly	Login, ConfigureSelf

A service may define custom OEM roles. The `IsPredefined` property for OEM roles shall contain the value `true`. A service shall not allow users to modify predefined OEM roles. OEM role names should begin with a lowercase character or "Oem" followed by a vendor name to avoid conflict with future Redfish predefined role names.

A service may allow custom client-defined roles to be created, modified, and deleted. If allowed, a user can create a new role through a POST to the `RoleCollection` resource, indicating privileges in the `AssignedPrivileges` and `OemPrivileges` properties in the `Role` resource. A service may restrict which privileges are allowed. The `IsPredefined` property for client-defined roles shall contain the value `false`. A service shall not allow a client-defined role to be deleted while it is in use, for example, when it is assigned to a local user or an LDAP `RemoteRoleMapping` property.

The value of the `RoleId` property shall be unique across all roles within the `RoleCollection` resource.

Non-Redfish services, such as those enabled by the `AccountTypes` property within the `ManagerAccount` resource, should map the Redfish `RoleId` to their permission system. For example, an SSH user with `Administrator` as the value of the `RoleId` property could map to "root" for the SSH service. However, the privileges specified by the `AssignedPrivileges` and `OemPrivileges` do not necessarily map to non-Redfish services.

#### 14.4.1.2 Restricted roles and restricted privileges

Restricted roles and restricted privileges are intended to prevent privilege escalation. Restricted roles and restricted privileges are not less functional, but their usage is restricted to particular users. For example, to have a security administrator have privileges that the administrator does not have, you need to ensure the administrator cannot escalate to the security administrator role. An implementation can help achieve this by restricting the `Administrator` role and providing an alternate administrator role that lacks the security privilege.

A service may restrict any role. The `Restricted` property for restricted roles shall contain the value `true`. When a standard role is restricted, services shall provide the `AlternateRoleId` property to reference a non-restricted custom role intended for clients to use as an alternate. Services may predefine or create accounts that are configured with a restricted role.

Services shall not allow:

- A `RoleId` value for a restricted role to be specified when creating or modifying a `ManagerAccount` resource. This ensures administrators cannot create an account for themselves that has a restricted role.
- Modification of `ManagerAccount` resources with a `RoleId` property containing a value for a restricted role, with the exception of the `Enabled` property. This ensures administrators cannot gain access to another account.
- Deletion of `ManagerAccount` resources with a `RoleId` property containing a value for a restricted role.
- A restricted role to be specified in the `LocalRole` property within the `RemoteRoleMapping` property within the `AccountService` and `ExternalAccountProvider` resources.

A service may restrict any privilege, including standard and OEM privileges. The `RestrictedPrivileges` and `RestrictedOemPrivileges` properties in the `AccountService` resource shall specify the restricted privileges. Services shall not allow custom roles to specify restricted privileges. Services may contain predefined roles that are configured with restricted privileges.

#### 14.4.1.3 OEM privileges

OEM privileges allow a service to extend the privilege model by adding additional privileges to have additional control of what operations are allowed. It can be used when a standard privilege is overly broad.

A service may define OEM privileges and may include OEM privileges in any predefined role, including standard and custom OEM roles. The `OemPrivileges` property within the `Role` resource shall contain the OEM privileges that are assigned to the role. The `OemPrivileges` property in the `Role` resource for the predefined roles shall not be modifiable.

A service may allow OEM privileges to be assigned to client-defined roles.

## 14.4.2 Redfish service operation-to-privilege mapping

For every request that a client makes to a service, the service shall determine that the authenticated identity of the requester has the authorization to complete the requested operation on the resource in the request.

Using the role and privileges authorization model where an authenticated identity context is assigned a role and a role is a set of privileges, the service typically checks an HTTP request against a mapping of the authenticated requesting identity role and privileges to determine whether the identity privileges are sufficient to complete the operation in the request.

### 14.4.2.1 Why specify operation-to-privilege mapping?

Initial versions of the Redfish Specifications defined several role-to-privilege mappings for standardized roles and normatively identified several privilege labels but did not normatively detail what these privileges or how privilege-to-operations mappings could be specified or represented in a normative fashion.

The lack of a methodology to define which privileges are required to complete a requested operation against the URI in the request puts at risk the interoperability between service implementations that clients may encounter due to variances in privilege requirements between implementations.

Also, a lack of methodology for specifying and representing the operation-to-privilege mapping prevents the Redfish Forum or other governing organizations from normatively defining privilege requirements for a service.

### 14.4.2.2 Representing operation-to-privilege mappings

A service should provide a Privilege Registry in the registry collection. This registry represents the privileges required to complete HTTP operations against resources supported by the service.

The Privilege Registry is a JSON document that contains a `Mappings` array of where an individual entry exists for every resource type that the service supports.

The operation-to-privilege mapping is defined for every resource type and applies to every resource the service implements for the applicable resource type.

In several situations, specific resources or properties may have differing operation-to-privilege mappings than the resource type-level mappings. In these cases, the resource type-level mappings need to be overridden. The `PrivilegeRegistry` schema defines the methodology for resource type-level operation-to-privilege mappings and related overrides.

If a service provides a Privilege Registry, the service shall use the Redfish Forum's Privilege Registry definition as a base operation-to-privilege mapping definition for operations that the service supports to promote interoperability for Redfish clients.

### 14.4.2.3 Operation map syntax

An operation map defines the set of privileges required to complete an operation on a resource-type.

The mapped operations are GET, PUT, PATCH, POST, DELETE, and HEAD. A privilege mapping is defined for each operation, irrespective of whether the service or data model supports the operation on the resource-type.

The privilege labels may be the Redfish standardized labels that the `PrivilegeType` enumeration in the `Privileges` schema defines and they may be OEM-defined privilege labels. The required privileges for an operation are specified using logical AND and OR behavior. For more information, see the [Privilege AND and OR syntax](#) clause.

The following example defines the privileges required for various operations on the `Manager` resource. Unless the implementation defines mapping overrides to the `OperationMap` array, the specified operation-to-privilege mapping represents behavior for all `Manager` resources in a service implementation.

```
{
  "Entity": "Manager",
  "OperationMap": {
    "GET": [
      {
        "Privilege": [ "Login" ]
      }
    ],
    "HEAD": [
      {
        "Privilege": [ "Login" ]
      }
    ],
    "PATCH": [
      {
        "Privilege": [ "ConfigureManager" ]
      }
    ],
    "POST": [
      {
        "Privilege": [ "ConfigureManager" ]
      }
    ],
    "PUT": [
      {
        "Privilege": [ "ConfigureManager" ]
      }
    ],
    "DELETE": [
      {
        "Privilege": [ "ConfigureManager" ]
      }
    ]
  }
}
```

```

    ]
  }
}

```

#### 14.4.2.4 Mapping overrides syntax

In several situations, operation-to-privilege mapping varies from the resource type-level mapping.

Situation	Description
Property override	A property has different privilege requirements than the resource in which it resides. For example, the <code>Password</code> property in the <code>ManagerAccount</code> resource requires the <code>ConfigureSelf</code> or <code>ConfigureUsers</code> privilege to change, in contrast to the <code>ConfigureUsers</code> privilege required for the other properties in <code>ManagerAccount</code> resources. If multiple properties with the same name are present in a resource, the property override applies to all property instances.
Subordinate override	A resource is used in context of another resource and the contextual privileges need to govern. For example, the privileges for PATCH operations on <code>EthernetInterface</code> resources depend on whether the resource is <code>subordinate</code> to the <code>Manager</code> resource, where <code>ConfigureManager</code> is required, or the <code>ComputerSystem</code> resource, where <code>ConfigureComponents</code> is required.
Resource URI override	A resource instance has different privilege requirements for an operation than those defined for the resource type.

The overrides are defined in the context of the operation-to-privilege mapping for a resource type.

If multiple overrides are specified for a single resource type, the following precedence should be used for determining the appropriate override to apply:

- Property override
- Resource URI override
- Subordinate override

#### 14.4.2.5 Property override example

In the following example, the `Password` property on the `ManagerAccount` resource requires the `ConfigureSelf` or `ConfigureUsers` privilege to change, in contrast to the `ConfigureUsers` privilege required for the other properties in `ManagerAccount` resources:

```

{
  "Entity": "ManagerAccount",
  "OperationMap": {
    "GET": [
      {

```

```
        "Privilege": [ "ConfigureManager" ]
      },
      {
        "Privilege": [ "ConfigureUsers" ]
      },
      {
        "Privilege": [ "ConfigureSelf" ]
      }
    ],
    "HEAD": [
      {
        "Privilege": [ "Login" ]
      }
    ],
    "PATCH": [
      {
        "Privilege": [ "ConfigureUsers" ]
      }
    ],
    "POST": [
      {
        "Privilege": [ "ConfigureUsers" ]
      }
    ],
    "PUT": [
      {
        "Privilege": [ "ConfigureUsers" ]
      }
    ],
    "DELETE": [
      {
        "Privilege": [ "ConfigureUsers" ]
      }
    ]
  ],
  "PropertyOverrides": [
    {
      "Targets": [ "Password" ],
      "OperationMap": {
        "PATCH": [
          {
            "Privilege": [ "ConfigureUsers" ]
          },
          {
            "Privilege": [ "ConfigureSelf" ]
          }
        ]
      }
    }
  ]
}
```



```
}
```

#### 14.4.2.6 Subordinate override

The `Targets` property in `SubordinateOverrides` lists a hierarchical representation for when to apply the override. In the following example, the override for an `EthernetInterface` resource is applied when it is subordinate to an `EthernetInterfaceCollection` resource, which in turn is subordinate to a `Manager` resource. If a client were to PATCH an `EthernetInterface` resource that matches this override condition, it requires the `ConfigureManager` privilege. Otherwise, the client requires the `ConfigureComponents` privilege.

```
{
  "Entity": "EthernetInterface",
  "OperationMap": {
    "GET": [
      {
        "Privilege": [ "Login" ]
      }
    ],
    "HEAD": [
      {
        "Privilege": [ "Login" ]
      }
    ],
    "PATCH": [
      {
        "Privilege": [ "ConfigureComponents" ]
      }
    ],
    "POST": [
      {
        "Privilege": [ "ConfigureComponents" ]
      }
    ],
    "PUT": [
      {
        "Privilege": [ "ConfigureComponents" ]
      }
    ],
    "DELETE": [
      {
        "Privilege": [ "ConfigureComponents" ]
      }
    ]
  },
  "SubordinateOverrides": [
    {
```

```

    "Targets": [
      "Manager",
      "EthernetInterfaceCollection"
    ],
    "OperationMap": {
      "PATCH": [
        {
          "Privilege": [ "ConfigureManager" ]
        }
      ],
      "POST": [
        {
          "Privilege": [ "ConfigureManager" ]
        }
      ],
      "PUT": [
        {
          "Privilege": [ "ConfigureManager" ]
        }
      ],
      "DELETE": [
        {
          "Privilege": [ "ConfigureManager" ]
        }
      ]
    }
  }
]
}

```

#### 14.4.2.7 Resource URI override

The following example demonstrates the resource URI override syntax to define operation privilege variations for resource URIs.

The example defines both `ConfigureComponents` and `OEMAdminPriv` privileges as required to make a PATCH operation on the two resource URIs listed as targets.

```

{
  "Entity": "ComputerSystem",
  "OperationMap": {
    "GET": [
      {
        "Privilege": [ "Login" ]
      }
    ],

```

```
    "HEAD": [
      {
        "Privilege": [ "Login" ]
      }
    ],
    "PATCH": [
      {
        "Privilege": [ "ConfigureComponents" ]
      }
    ],
    "POST": [
      {
        "Privilege": [ "ConfigureComponents" ]
      }
    ],
    "PUT": [
      {
        "Privilege": [ "ConfigureComponents" ]
      }
    ],
    "DELETE": [
      {
        "Privilege": [ "ConfigureComponents" ]
      }
    ]
  ],
  "ResourceURIOverrides": [
    {
      "Targets": [
        "/redfish/v1/Systems/VM6",
        "/redfish/v1/Systems/Sys1"
      ],
      "OperationMap": {
        "GET": [
          {
            "Privilege": [ "Login" ]
          }
        ],
        "PATCH": [
          {
            "Privilege": [ "ConfigureComponents", "OEMSysAdminPriv" ]
          }
        ]
      }
    }
  ]
}
```

#### 14.4.2.8 Privilege AND and OR syntax

The array placement of the privilege labels in the `OperationMap` GET, HEAD, PATCH, POST, PUT, and DELETE operation element arrays define the logical combinations of privileges that are required to call an operation on a resource or property.

For OR logical combinations, the privilege label appears in the operation element array as individual elements.

The following example defines either `Login` or `OEMPrivilege1` privileges as required to perform a GET operation.

```
{
  "GET": [
    {
      "Privilege": [ "Login" ]
    },
    {
      "Privilege": [ "OEMPrivilege1" ]
    }
  ]
}
```

For logical AND combinations, the privilege label appears in the `Privilege` property array in the operation element.

The following example defines both `ConfigureComponents` and `OEMSysAdminPriv` as required to perform a PATCH operation.

```
{
  "PATCH": [
    {
      "Privilege": [ "ConfigureComponents", "OEMSysAdminPriv" ]
    }
  ]
}
```

## 14.5 Account service

- Implementations should store user passwords with one-way encryption techniques.
- Implementations may support exporting user accounts with passwords, but shall do so using encryption methods to protect them.
- User accounts shall support ETags and atomic operations. Implementations may reject requests that do not include an ETag.

- When authentication fails, extended error messages shall not provide privileged information.

### 14.5.1 Password management

A Redfish service provides local user accounts through a collection of `ManagerAccount` resources located under the account service. The `ManagerAccount` resources enable users to manage their own account information, and for administrators to create, delete, and manage other user accounts.

When account properties are changed, the service may close open sessions for this account and require re-authentication.

### 14.5.2 Password change required handling

The service may require that passwords assigned by the manufacturer be changed by the end user prior to accessing the service. In addition, administrators may require users to change their account's password upon first access.

The `ManagerAccount` resource contains a `PasswordChangeRequired` boolean property to enable this functionality. Resources that have the property set to `true` shall require the user to change the write-only `Password` property in that resource before access is granted. Manufacturers including user credentials for the service may use this method to force a change to those credentials before access is granted.

When a client accesses the service by using credentials from a `ManagerAccount` resource that has a `PasswordChangeRequired` value of `true`, the service shall allow:

- A session login and include a `@Message.ExtendedInfo` object in the response containing the `PasswordChangeRequired` message from the Base Message Registry. This indicates to the client that their session is restricted to performing only the password change operation before access is granted.
- A GET operation on the `ManagerAccount` resource associated with the account.
- A PATCH operation on the `ManagerAccount` resource associated with the account to update the `Password` property. If the value of `Password` is changed, the service shall also set the `PasswordChangeRequired` property to `false`.

For all other operations, the service shall respond with the HTTP `403 Forbidden` status code and include a `@Message.ExtendedInfo` object that contains the `PasswordChangeRequired` message from the Base Message Registry.

## 14.6 Asynchronous tasks

---

Irrespective of which user or privileged context starts a *task*, the information in the task object shall enforce the privileges required to access that object.

## 14.7 Event subscriptions

---

Before pushing event data object to the destination, the service may verify the destination for identity purposes.

## 15 Redfish Host Interface

---

The Redfish Host Interface Specification defines how software that runs on a host computer system can interface with a Redfish Service that manages the host. For details, see [DSP0270](#).

## 16 Redfish Composability

---

A service may implement the `CompositionService` resource off of `ServiceRoot` to bind resources. One example is disaggregated hardware, which allows for independent components, such as processors, memory, I/O controllers, and drives, to be bound together to create logical constructs that operate together. This enables a client to dynamically assign resources for an application.

A service that supports composability shall implement Resource Blocks, defined by the `ResourceBlock` schema, and the Resource Zones, defined in the `Zone` schema, for the Composition Service. Resource Blocks provide an inventory of components available to the client for building compositions. Resource Zones describe the binding restrictions of the Resource Blocks that the service manages.

The Resource Zones within the Composition Service shall include the [collection capabilities annotation](#) in responses. The collection capabilities annotation allows a client to discover which resource collections in the service support compositions, the different [composition request](#) types allowed, and how the POST request for the resource collection is formatted, as well as what properties are required.

### 16.1 Composition requests

---

A service that implements the Composition Service, as defined by the `CompositionService` schema, shall support one or more of the following types of composition requests:

- [Specific composition](#)
- [Constrained composition](#)
- [Expandable resources](#)

A service that supports the removal of a composed resource shall support the DELETE method on the composed resource.

#### 16.1.1 Specific composition

A specific composition is when a client identifies an exact set of resources in which to build a logical entity.

A service that supports specific compositions shall support a POST request that contains an array of hyperlinks to Resource Blocks. The schema for the resource being composed defines where the Resource Blocks are specified in the request.

The following example shows a `ComputerSystem` being composed with a specific composition request:



```

POST /redfish/v1/Systems HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
OData-Version: 4.0

{
  "Name": "Sample Composed System",
  "Links": {
    "ResourceBlocks": [
      {
        "@odata.id": "/redfish/v1/CompositionService/ResourceBlocks/ComputeBlock0"
      },
      {
        "@odata.id": "/redfish/v1/CompositionService/ResourceBlocks/DriveBlock2"
      },
      {
        "@odata.id": "/redfish/v1/CompositionService/ResourceBlocks/NetBlock4"
      }
    ]
  }
}

```

## 16.1.2 Constrained composition

A constrained composition is when a client has identified a set of criteria, or constraints, in which to build a logical entity. This includes criteria such as quantities of components, or characteristics of components. A service that supports constrained compositions shall support a POST request that contains the set of characteristics to apply to the composed resource. The specific format of the request is defined by the schema for the resource being composed. This type of request may include expanded elements of resources [subordinate](#) to the composed resource.

The following example shows a `ComputerSystem` being composed with a constrained composition request:

```

POST /redfish/v1/Systems HTTP/1.1
Content-Type: application/json;charset=utf-8
Content-Length: <computed length>
OData-Version: 4.0

{
  "Name": "Sample Composed System",
  "PowerState": "On",
  "BiosVersion": "P79 v1.00 (09/20/2013)",
  "Processors": {
    "Members": [
      {
        "@Redfish.RequestedCount": 4,
        "@Redfish.AllowOverprovisioning": true,
        "ProcessorType": "CPU",

```

```
        "ProcessorArchitecture": "x86",
        "InstructionSet": "x86-64",
        "MaxSpeedMHz": 3700,
        "TotalCores": 8,
        "TotalThreads": 16
    }
]
},
"Memory": {
    "Members": [
        {
            "@Redfish.RequestedCount": 4,
            "CapacityMiB": 8192,
            "MemoryType": "DRAM",
            "MemoryDeviceType": "DDR4"
        }
    ]
},
"SimpleStorage": {
    "Members" : [
        {
            "@Redfish.RequestedCount": 6,
            "Devices": [
                {
                    "CapacityBytes": 322122547200
                }
            ]
        }
    ]
},
"EthernetInterfaces": {
    "Members": [
        {
            "@Redfish.RequestedCount": 1,
            "SpeedMbps": 1000,
            "FullDuplex": true,
            "NameServers": [
                "names.redfishspecification.org"
            ],
            "IPv4Addresses": [
                {
                    "SubnetMask": "255.255.252.0",
                    "AddressOrigin": "Dynamic",
                    "Gateway": "192.168.0.1"
                }
            ]
        }
    ]
}
}
```

### 16.1.3 Expandable resources

An expandable resource is when a service has a baseline composition that cannot be removed. Instead of a client making requests to create a composed resource, a client can only add or remove resources from the composed resource. A service that supports expandable resources shall support one or more of the update methods that the [Updating a composed resource](#) clause describes.

## 16.2 Updating a composed resource

---

A service that supports updating a composed resource shall provide one or more of the following methods to update composed resources:

- The PUT or PATCH methods on the composed resource with a modified list of Resource Blocks.
- Actions on the composed resource for adding and removing Resource Blocks.
  - If the actions for adding and removing Resource Blocks are present in the resource, clients should use this method before attempting PUT or PATCH.

# 17 Aggregation

---

Aggregation has been a Redfish concept since its inception. Redfish uses collection for services that can represent more than one system. As the scale of Redfish implementations increase, clients want to operate on Redfish resources in bulk.

Aggregation is the representation of Redfish resources from a variety of sources so that they can be managed, in whole or in part, by a Redfish client. Membership can be heterogeneous and arbitrary, but it is expected that most aggregate members will be of the same resource type, such as an aggregate of `ComputerSystem` resource, which would be represented by an `Aggregate` resource whose members of its `Elements` array are exclusively of type `ComputerSystem`. The Redfish service proxies on behalf of the aggregated components in order to provide common operations. The Redfish service is representing resources on behalf of the components and incoming operations must be tracked by the Redfish service before being accomplished by communicating with the individual resources. Thus, aggregation also allows a Redfish client to act on resources as a group using aggregates.

## 17.1 Classes of aggregators

---

There are at least two classes of Redfish aggregators.

There are implicit aggregators. An example of this might be an enclosure manager, such as a manager of blades in an enclosure. This implementation has `ComputerSystem` resources representing blades in the `ComputerSystemCollection` resource, and one or more `Manager` resources in the `ManagerCollection` resource. It also would likely have a `Chassis` resource for each blade and a `Chassis` resource for the enclosure, which would use the `Contains` property in `Links` to express the containment relationship to the individual blades. This class of aggregator has tight coupling with system design, and proxies requests to and from the blades to perform management functions.

There are complex aggregators. An example of this type of aggregator might be a rack level manager, fabric manager, or a manager of similar scale, especially if it represents resources that it gathers through the proxy of information from other managers, like BMCs. The sources that this manager aggregates are more complex in nature and potentially varying. This manager probably has an interface to the resources and proxies the Redfish service on behalf of each set of resources. At this scale, a Redfish client would prefer to provide common functions, such as resetting a set of systems, to the Redfish service as a whole rather than invoking actions individually in order to achieve scalability requirements. This class of service also may need assistance in adding members to the service, such as providing address and account information in order for the aggregator to contact the components and initiate the proxy of Redfish operations.

### 17.1.1 Use cases

There are several use cases that make explicit aggregator representation necessary. What they have in common is the need for common functions for scalability. There are several classes of these common functions.

One use case is for service type functions. An example of this would be a firmware update on a large number of systems. Rather than invoke actions on individual resources, it is more efficient for a client to indicate the image and the list of resources to which it is applied. In this case, there is already a service in existence in the model, and so an aggregation service isn't needed. Instead the existing service needs just be augmented to enable the application to a list of resources.

Another use case is to perform common actions. Examples of this are the `Reset` or `SetDefaultBootOrder` actions. These actions are defined in the `ComputerSystem` schema, but the Redfish URI structure requires the action to be on each `ComputerSystem` resource. Thus there is an individual operation on each resource. It is more efficient for a client to invoke the action and a list of the resources to which the action needs to be applied. For example, if one thousand systems need to be reset, there is significant overhead in performing one thousand individual reset operations than it is to perform a single operation that specifies the one thousand system to be reset.

A final use case would be to change an attribute on multiple members of a collection. An example of this might be to change the boot order on a large number of systems. This would require an operation per system. However, assuming the resources are in the same collection, the [deep PATCH operation](#) suffices to meet the requirements of this use case.

## 17.2 Aggregation service

---

The `AggregationService` resource is used to represent that this Redfish service provides aggregation functions.

The aggregation service is used to contain the group actions that can take place on groups of resources. The `AggregationService` schema defines the common actions that are available to be performed on groups of resources by a client. These actions take an array of resource URIs as one of the parameters to which the action will apply. If all members of the resource array do not support the method, a `4xx` status code shall be returned and the body shall contain an [error response](#). If at least one member of the resource array successfully completed the action, but others did not, the status code should be `200 OK` with `@Message.ExtendedInfo` objects for the failed members.

The aggregation service also contains `Aggregate`, `AggregationSource`, and `ConnectionMethod` resources.

### 17.2.1 Aggregator requirements

A complex aggregator shall represent it is capable of the following requirements by implementing the `AggregationService` resource and including an `AggregationSourceCollection` resource. If there is an `AggregationService` resource with an `AggregationSourceCollection` resource, the Redfish service shall:

- Proxy to the aggregated resources on behalf of the service.
- Provide error and state propagation, such as health roll-up, when needed to provide such data to the [parent resource](#).
- Combine resource collections from the aggregated resources.
  - For example, `ComputerSystem` resources that were gathered through proxy shall be in one

`ComputerSystemCollection` resource.

- Services shall perform a "URI fix-up" for all aggregated resources since every system can't be at `/redfish/v1/Systems/1`.
- It is advisable for Redfish implementations to use unique values for the `Id` properties. For example, base the `Id` property of a `ComputerSystem` resource on something unique like a UUID or serial number, or the manufacturer MAC address for network adapters, or WWN for Fibre Channel controllers.
- Unify other services.
  - There is only one event service hosted by the aggregation implementation and it shall combine all of the events into one stream. This is also true for sessions, telemetry, update service, and other services. Thus the aggregator is representing a unification of Redfish services that it communicates with and proxies on the client's behalf to the providers of those services and information.

### 17.2.1.1 Aggregates

The `Aggregate` resource is the grouping mechanism used by clients to indicate to the service that this group of resources can be treated the same for certain functions, such as the actions. Each aggregate contains the list of individual resources that are to be treated as a single unit for operations. For example, if a client wishes to express that a subset of the `ComputerSystemCollection` resource be treated as a single unit for certain operations like reset, reset boot order, or firmware update, it can express the aggregate as the target URI for the operation.

The `Aggregate` schema defines the common actions that are available to be performed on an aggregate by a client. The `Aggregate` resource contains an `Elements` array that specifies the members of the aggregate. Actions that are supported on an aggregate but not supported on all `Elements`, such as a `Reset` action that is not supported on an individual member of the `Elements` array, are not silently skipped. If all members of the `Elements` array do not support the method, a `4xx` status code shall be returned and the body shall contain an [error response](#). If at least one member of the `Elements` array successfully completed the action, but others did not, the status code should be `200 OK` with `@Message.ExtendedInfo` objects for the failed members.

## 17.2.2 Aggregation sources and connection methods

The aggregation service model also includes a definition for the information used to access the resources being represented by the aggregator. Two collections of resources are used to represent this. These are the `AggregationSource` and `ConnectionMethod` resources.

The `AggregationSource` resource is used to represent the source of information for the resources being reflected by the aggregator. It typically represents a lower layer service provided by another manager. It contains information needed to access that source, such as the address and account information. It also has a reference to the `ConnectionMethod` resource used to access it.

The `ConnectionMethod` resource is used to represent the protocol and other semantics required to communicate with the resources being aggregated. Examples of connection methods are Redfish, IPMI, and proprietary access methods. For methods such as IPMI, it's also possible to specify the variations and nuances from multiple vendors.

## 18 ANNEX A (informative) Change log

Version	Date	Description
1.12.0	2020-12-01	Added introductory text to the <b>Authorization</b> clause.
		Clarified usage of <code>roleId</code> and how there are standard roles, custom OEM roles, and client-defined custom roles.
		Added <b>Restricted roles and restricted privileges</b> to describe behavior for when roles and privileges are marked as restricted.
1.11.2	2020-12-01	Clarified that the <code>Accept-Encoding</code> header is used to request compression of response bodies.
		Corrected the <b>PATCH (update)</b> , <b>PUT (replace)</b> , and <b>DELETE (delete)</b> clauses to leverage all normative statements for successful operations found in the <b>Modification success responses</b> clause.
		Replaced RFC5988 reference with RFC8288.
		Updated IETF links to use the "IETF Tools" site.
		Clarified that insert capabilities is just for resource creation.
		Fixed ETag examples to be RFC7234-conformant.
		Clarified that OEM resources can have subordinate resources.
		Replaced RFC4627 reference with RFC8259.
		Replaced conflicting statements found in "HTTP redirect authentication requirements" with general clause for enforcing authentication and authorization at the target resource.
		Clarified behavior of <code>@odata.count</code> when a collection is filtered.
		Created standalone "MessageId format" clause.
		Removed duplicative text found in the event format table and referenced the message object clauses as needed.
		Corrected the response body specified for a PATCH operation containing read-only properties.
		Added informative text in the intro to the <b>Data model</b> clause describing the methods for OEM extensions.
		Clarified that sensitive data in URIs can be hidden from unauthorized users by returning HTTP <code>404 Not Found</code> .
		Added embedded links to the <code>Location</code> header entry in the response header table.
Corrected <code>\$select</code> example in the <b>The \$select query parameter</b> clause.		
Corrected several embedded links to direct to the correct clause.		
1.11.1	2020-08-04	Added missing clause requiring sensitive data to be returned as <code>null</code> .

Version	Date	Description
		Clarified that <code>Resolution</code> , <code>Severity</code> , and <code>MessageSeverity</code> in responses can be service-defined and not come from a message registry.
		Relaxed schema rules to require description, long description, URI, and capabilities annotations only for schemas published or republished by the DMTF.
		Added clauses to <b>Schema modification rules</b> to allow for properties, actions, parameters, and URIs to be removed, descriptions to be modified, and pattern and length annotations to be added if not specified.
		Relaxed rule for the OData metadata document to not require, but only recommend that all referenced namespaces are included in the document.
		Added clause to clarify the usage of empty strings.
		Clarified behavior of <code>\$skip</code> when the value is greater than or equal to the number of members in a resource collection.
		Corrected the minimum value for <code>\$top</code> to align with OData.
		Clarified behavior of PATCH for partial success scenarios.
		Various clarifications and style fixes to the <b>Aggregation</b> clause.
		Clarified that HEAD requests shall be rejected when a query parameter is provided.
		Removed erroneous requirement for ETags to be strong.
1.11.0	2020-04-30	Added <b>Aggregation</b> clause.
		Clarified that services are allowed use HTTP <code>501 Not Implemented</code> for unsupported HTTP methods.
		Clarified the normative semantics around the term "deprecated".
		Clarified clauses describing the usage of <code>null</code> for properties versus not reporting a property.
1.10.0	2020-03-27	Restructured the <b>Security details</b> clause for ease of reading. Other than the changes listed below, no other changes were intended. Any clarifications that inadvertently altered the normative behavior are considered errata, and will be corrected in future revisions to the specification.
		Deprecated TLS v1.1, and set the minimum TLS requirement to be TLS v1.2 with RFC7525 recommendations.
		Deprecated existing cipher suites clause in favor of new clause to leverage IANA recommendations.
		Added requirement for supporting the URI <code>/redfish</code> .
		Added support for deep operations.
1.9.1	2020-03-27	Deprecated full ISO8601 duration format in favor of a simplified version that does not contain years, months, and weeks.
		Added missing normative language for how actions with response bodies are defined in schema.
		Added HTTP <code>201 Created</code> as valid responses for actions.



Version	Date	Description
		Clarified the <code>~</code> operator for the <code>\$expand</code> query parameter to expand hyperlinks found in all <code>Links</code> properties.
		Clarified the <code>*</code> and <code>.</code> operators for the <code>\$expand</code> query parameter to expand hyperlinks found in payload annotations, such as <code>@Redfish.Settings</code> .
		Clarified usage of action parameters that point to resources; the expectation is a reference object pointing to the resource in question is passed by the client.
		Clarified that DELETE on a resource will likely delete subordinate resources.
		Clarified best practices for naming rules, in particular with regards to acronyms.
		Clarified behavior for when individual members of a resource collection cannot be returned as part of a <code>\$expand</code> request.
		Clarified usage of <code>@Message.ExtendedInfo</code> in error responses and provided guidance for clients for handling error responses.
1.9.0	2019-12-06	Made change to no longer require the <code>Server</code> response header.
		Added clause to <b>Schema modification rules</b> to allow for the addition of OEM URIs to standard resources.
		Loosened requirements on <code>@odata.type</code> within <code>Oem</code> to not require it in arrays where the type is used repeatedly.
1.8.1	2019-12-06	Many changes for style consistency, grammar, and general clarity. Except for the following additions, no normative changes were made. Any clarifications that inadvertently altered the normative behavior are considered errata, and will be corrected in future revisions to the Specification.
		Clarified SSE with regards to requiring a blank line after each event.
		Clarified order of precedence for resolving multiple operation overrides within the Privilege Registry.
		Clarified cases for property overrides in the Privilege Registry where multiple objects in the same resource contain the same property name.
		Updated references for HTTP Basic authentication to use RFC7617 instead of RFC7235.
		Added <code>text/event-stream</code> , <code>application/yaml</code> , and <code>application/vnd.oai.openapi</code> usage to the <code>Accept</code> and <code>Content-Type</code> header table entries.
		Added clause that provides guidance on service behavior when <code>null</code> is a property value in POST (create) operations.
		Loosened requirements on SSE <code>id</code> based on client usage.
		Added documentation for settings, settings apply time, operation apply time, operation apply time support, maintenance window, collection capabilities, requested count, allow over-provisioning, zone affinity, supported certificates, and deprecated terms to the <b>Payload annotations</b> clause.
		Added clauses that document responses for actions with a response body defined in schema.
		Clarified the allowable values payload annotation to show it can be used for both properties and action parameters.
1.8.0	2019-08-08	Added clause for using <code>/redfish/v1/openapi.yaml</code> as the well-known URI for the OpenAPI document.

Version	Date	Description
		Added clause that specifies non-resource reference properties with <code>uri</code> in the name are accessed using Redfish protocol semantics.
		Added <code>SubordinateResources \$filter</code> parameter for SSE.
		Added <b>Update Service</b> clause that describes requirements for the <code>SimpleUpdate</code> action and the <code>MultipartHttpPushUri</code> property.
1.7.1	2019-08-08	Added statements about the <i>owning entity</i> annotation term and its usage in schema modifications.
		Clarified SSE <code>id</code> from <code>Id</code> in an event payload and <code>EventId</code> within an event record.
		Fixed recommended sequencing of the SSE <code>id</code> to be related to <code>EventId</code> within an event record.
		Clarified that services are allowed to close sessions for an account when its password has changed.
		Corrected the <b>Password management</b> clause to describe how a user can GET their respective account resources when a password change is required.
		Clarified that registries are not required to return <code>@odata.id</code> .
		Clarified that services should use HTTP <code>400 Bad Request</code> for invalid query requests.
		Clarified that services should use HTTP <code>400 Bad Request</code> when the <code>only</code> query is being combined with other query parameters.
		Clarified that services should use HTTP <code>400 Bad Request</code> when query parameters are used on non-GET operations.
		Added clause about how to construct enumeration values.
		Clarified references to specific messages to also reference their Message Registry.
		Added language about the construction of action names in payloads.
		Added informative text for how OEM actions can be defined.
		Added guidance for using HTTPS whenever sensitive data is being transmitted.
		Added clause restricting the maximum size of an event payload to be 1MiB.
		Clarified that auto expanded resource collections can use paging.
		Clarified error response format for SSE.
		Clarified that <code>charset=utf-8</code> is not required within the <code>Content-Type</code> header for SSE.
		Added clause about how URI patterns are constructed.
		Added Excerpt term.
1.7.0	2019-05-16	The Specification has been significantly rewritten for clarity. Except for the following additions, no normative changes were made. Any clarifications that inadvertently altered the normative behavior are considered errata, and will be corrected in future revisions to the Specification.

Version	Date	Description
		Added normative statements about how to handle array properties and PATCH operations on arrays.
		Separated data model and schema language clauses.
		Added clauses that describe how JSON Schema and OpenAPI files are formatted.
		Added clause that describes the schema versioning methodology.
		Added clause about how URI patterns are constructed based on the resource tree and property hierarchy.
		Added Dictionary file naming rules and repository locations.
		Enhanced localization definitions and defined repository locations.
		Added statement about SSE to the <b>Eventing mechanism</b> clause.
		Added <b>Constrained composition</b> and <b>Expandable resources</b> clauses to Redfish Composability.
		Added clause about requiring event subscriptions to be persistent across service restarts.
		Added clause about persistence of tasks generated as a result of using <code>@Redfish.OperationApplyTime</code> across service restarts.
		Added clause about using <code>@Redfish.OperationApplyTime</code> and <code>@Redfish.MaintenanceWindow</code> within task responses.
		Removed <code>@odata.context</code> property from example payloads.
		Added <b>Password management</b> clause to describe functional behavior for restricting access when an account requires a password change.
		Added clause around the usage of the HTTP <code>403 Forbidden</code> status code when an account requires a password change.
1.6.1	2018-12-13	Added clause about percent encoding being allowed for query parameters.
		Changed <code>\$expand</code> example to use <code>SoftwareInventory</code> instead of <code>LogEntry</code> .
		Added clause about the use of a separator for multiple query parameters.
		Fixed <code>\$filter</code> examples to use <code>/</code> instead of <code>.</code> for property paths.
		Clarified the usage of messages in a successful action response; provided an example.
		Added clarification about services supporting a subset of HTTP operations on resources specified in schema.
		Added clarification about services implementing writable properties as read only.
		Added clarification about session termination not affecting connections opened by the session.
		Added "Redfish Provider" term definition.
		Updated JSON Schema references to point to Draft 7 of the JSON Schema Specification.

Version	Date	Description
		Added clarifications about scenarios for when a request to add an event subscription contains conflicting information and how services respond.
		Removed language about ignoring the <code>Links</code> property in PATCH requests.
		Clarified usage of ETags to show that a client is not supposed to PATCH <code>@odata.etag</code> when attempting to use ETag protection for a resource.
		Clarified usage of the <code>only</code> query parameter to show it's not to be combined with <code>\$expand</code> and not to be used with singular resources.
		Clarified the usage of the HTTP status codes with task monitors.
		Various spelling and grammar fixes.
1.6.0	2018-08-23	Added methods of using <code>\$filter</code> on the SSE URI for the Event Service.
		Added support for the OpenAPI Specification v3.0. This allows OpenAPI-conforming software to access Redfish Service implementations.
		Added strict definitions for the URI patterns used for Redfish resources to support OpenAPI. Each URI is now constructed using a combination of fixed, defined path segments and the values of <code>Id</code> properties for resource collections. Also added restrictions on usage of unsafe characters in URIs. Implementations reporting support for Redfish v1.6.0 conform to these URI patterns.
		Added support for creating and naming Redfish schema files in the OpenAPI YAML-based format.
		Added URI construction rules for OEM extensions.
		Changed ETag usage to require strong ETag format.
		Added requirement for HTTP <code>Allow</code> header as a response header for GET and HEAD operations.
		Added metric reports as a type of event that can be produced by a Redfish Service. Added support for SSE streaming of metric reports in support of new Telemetry Service.
		Added registry, resource, origin, or <code>EventFormatType</code> -based event subscription methods as detailed in the Specification and schema. Added an <code>EventFormatType</code> to enable additional payload types for subscription-based or streaming events. Deprecated <code>EventType</code> -based event subscription mechanism.
		Added Event message grouping capability.
		Provided guidance for defining and using OEM extensions for messages and Message Registries.
		Added <code>excerpt</code> and <code>only</code> query parameters.
		Clarified requirements for resource collection responses, which includes required properties that were expected, but not listed explicitly in the Specification.
		Made inclusion of the <code>@odata.context</code> annotation optional.
		Removed requirement for clients to include the <code>OData-Version</code> HTTP header in all requests.

Version	Date	Description
1.5.1	2018-08-10	Added clarifications to required properties in structured properties derived from <code>ReferenceableMembers</code> .
		Reorganized <b>Eventing</b> clause to break out the different subscription methods to differentiate pub-sub from SSE.
		Removed statements referencing OData conformance levels.
		Clarified terminology to explain usage of absolute versus relative reference throughout.
		Clarified client-side HTTP <code>Accept</code> header requirements.
		Added evaluation order for supported query parameters and clarified examples.
		Clarified handling of annotations in response payloads when used with <code>\$select</code> queries.
		Clarified service handling of annotations in PATCH requests.
		Clarified handling of various PATCH request error conditions.
		Clarified ability to create resource collection members by POST operations to the resource collection or the <code>Members</code> array within the resource.
		Corrected several examples to show required properties in payload.
		Clarified usage of the <code>Link</code> header and values of <code>rel=describedBy</code> .
		Clarified that the HTTP status code table only describes Redfish-specific behavior and that unless specified, all other usage follows the definitions within the appropriate RFCs.
		Added entry for the HTTP <code>431 Request Header Fields Too Large</code> status code.
		Added statement that the HTTP <code>503 Service Unavailable</code> status code can be used during reboot or reset of a service to indicate that the service is temporarily unavailable.
		Clarified usage of the <code>@odata.type</code> annotation within embedded objects.
		Added statements about the required <code>Name</code> , <code>Id</code> , and <code>MemberId</code> properties, and the common <code>Description</code> property, which have always been shown as required in schema files, but which the Specification did not mention.
		Added guidance for the value of time-date properties when time is unknown.
		Added the <code>title</code> property description in actions.
		Clarified usage of the <code>@odata.nextLink</code> annotation at the end of resource collections.
		Added additional guidance for naming properties and enumeration values that contain "OEM" or that include acronyms.
		Corrected requirements for description and long description annotations.
		Corrected name of <code>ConfigureComponents</code> in the <b>Operation-to-privilege mapping</b> clause.
		Various typographical errors and grammatical improvements.

Version	Date	Description
1.5.0	2018-04-05	Added support for Server-Sent Eventing for streaming events to web-based GUIs or other clients.
		Added <code>@Redfish.OperationApplyTime</code> annotation to provide a mechanism for specifying deterministic behavior for the application of Create, Delete or Action (POST) operations.
1.4.1	2018-04-05	Updated name of the DMTF Forum from <i>SPMF</i> to <i>Redfish Forum</i> .
		Consistently used the term, <i>hyperlink</i> .
		Added example to clarify usage of <code>\$select</code> query parameter with <code>\$expand</code> , and clarified expected results when using <code>AutoExpand</code> . Corrected order of precedence for <code>\$filter</code> parameter options.
		Corrected terminology for OEM-defined actions removing "custom" in favor of OEM, and clarified that the action <code>target</code> property is always required for an action, along with its usage.
		Corrected location header values for responses to data modification requests that create a task ( <code>Task</code> resource vs. task monitor). Clarified error handling of DELETE operations on <code>Task</code> resources.
		Removed references to obsolete and unused <code>Privilege</code> annotation namespace.
		Clarified usage of the <code>Base.1.0.GeneralError</code> message in the Base Message Registry.
		Added durable URIs for registries and profiles, and clarified intended usage for each folder in the repository. Added file naming conventions for registries and profiles, and clarified file naming for schemas.
		Added statement to clarify that additional headers may be added to M-SEARCH responses for SSDP to enable UPnP compatibility.
		Clarified assignment requirements for predefined or custom roles when new manager account instances are created, using the <code>RoleId</code> property.
1.4.0	2017-11-17	Added support for optional query parameters ( <code>\$expand</code> , <code>\$filter</code> , and <code>\$select</code> ) on requests to enable more efficient retrieval of resources or properties from a Redfish Service.
		Clarified HTTP status and payload responses after successful processing of data modification requests. This includes POST operations for performing actions, as well as other POST, PATCH, or PUT requests.
		Added entries for the HTTP <code>428 Precondition Required</code> and <code>507 Insufficient Storage</code> status codes to clarify the proper response to certain error conditions. Added reference links to the HTTP status code table throughout.
		Updated the Abstract to reflect the current state of the Specification.
		Added reference to RFC6585 and clarified expected behavior when ETag support is used in conjunction with PUT or PATCH operations.
		Added definition for "Property" term and updated text to use term consistently.
		Added "Client requirement" column and information for HTTP headers on requests.
		Clarified the usage and expected format of the <code>@odata.context</code> property value.
		Added clause to describe how to revise structured properties and resolve their definitions in schema.

Version	Date	Description
		Added more descriptive definition for the settings resource. Added an example for the <code>SettingsObject</code> . Added description and example for using the <code>@Redfish.SettingsApplyTime</code> annotation.
		Added Action example using the <code>ActionInfo</code> resource in addition to the simple <code>@Redfish.AllowableValues</code> example. Updated example to show a proper subset of the available enumerations to reflect a real-world example.
		Added statement explaining the updates required to <code>TaskState</code> upon task completion.
1.3.0	2017-08-11	Added support for a service to optionally reject a PATCH or PUT operation if the <code>If-Match</code> or <code>If-Match-None</code> HTTP header is required by returning the HTTP <code>428 Precondition Required</code> status code.
		Added support for a service to describe when the values in the settings object for a resource are applied via the <code>@Redfish.SettingsApplyTime</code> annotation.
1.2.1	2017-08-10	Clarified wording of the <code>Oem</code> object definition.
		Clarified wording of the <b>Partial resource results</b> clause.
		Clarified behavior of a service when receiving a PATCH with an empty JSON object.
		Added statement about other uses of the HTTP <code>503 Service Unavailable</code> status code.
		Clarified format of URI fragments to conform to RFC6901.
		Clarified use of absolute and relative URIs.
		Clarified definition of the <code>target</code> property as originating from OData.
		Clarified distinction between <i>hyperlinks</i> and the <i>links property</i> .
		Corrected the JSON example of the privilege map.
		Clarified format of the <code>@odata.context</code> property.
		Added clauses about the schema file naming conventions.
		Clarified behavior of a service when receiving a PUT with missing properties.
		Clarified valid values in the <code>Accept</code> header to include wildcards per RFC7231.
		Corrected <code>ConfigureUser</code> privilege to be spelled <code>ConfigureUsers</code> .
		Corrected the <b>Session login</b> clause to include normative language.
1.2.0	2017-04-14	Added support for the Redfish Composability Service.
		Clarified service handling of the <code>Accept-Encoding</code> header in a request.
		Improved consistency and formatting of example requests and responses throughout.
		Corrected usage of the <code>@odata.type</code> property in response examples.
		Clarified usage of the required annotation.

Version	Date	Description
		Clarified usage of <code>SubordinateOverrides</code> in the Privilege Registry.
1.1.0	2016-12-09	Added <b>Redfish Service operation-to-privilege mapping</b> clause. This functionality enables a service to present a resource or even property-level mapping of HTTP operations to roles and privileges.
		Added references to the Redfish Host Interface Specification (DSP0270).
1.0.5	2016-12-09	Errata release. Various typographical errors.
		Corrected the use of <i>collection</i> , <i>resource collection</i> , and <i>members</i> throughout.
		Added glossary entries for <i>resource collection</i> and <i>members</i> .
		Corrected certificate requirements to reference definitions and requirements in RFC5280 and added a normative reference to RFC5280.
		Clarified usage of the HTTP POST and PATCH operations.
		Clarified usage of the HTTP status codes and error responses.
1.0.4	2016-08-28	Errata release. Various typographical errors.
		Added example of an HTTP <code>Link</code> Header and clarified usage and content.
		Added the <b>Schema modification</b> clause, which describes the allowed usage of the schema files.
		Added recommendation to use TLS 1.2 or later, and to follow the SNIA TLS Specification. Added reference to the SNIA TLS Specification. Added additional recommended <code>TLS_RSA_WITH_AES_128_CBC_SHA</code> cipher suite.
		Clarified that the <code>Id</code> property of a <code>Role</code> resource matches the role name.
1.0.3	2016-06-17	Errata release. Fixed the missing numbering in the table of contents and clauses. Corrected URL references to external specifications. Added missing normative references. Corrected typographical error in ETag example.
		Clarified examples for <code>@Message.ExtendedInfo</code> to show arrays of messages.
		Clarified that a POST to Session Service to create a new session does not require authorization headers.
1.0.2	2016-03-31	Errata release. Various typographical errors.
		Corrected normative language for M-SEARCH queries and responses.
		Corrected <code>Cache-Control</code> and <code>USN</code> format in M-SEARCH responses.
		Corrected schema namespace rules to conform to OData namespace requirements and updated examples throughout the document to conform to this format. Specifically, <code>namespace . n . n . n</code> becomes <code>namespace .v n _ n _ n</code> . File naming rules for JSON Schema and CSDL (XML) schemas were also corrected to match this format and to enable future major (v2) versions to coexist.
		Added clause that details the location of the schema repository and lists the durable URLs for the repository.
		Added definition for the value of the Units annotation, using the definitions from the UCUM Specification. Updated examples throughout to use this standardized form.



Version	Date	Description
		Modified the naming requirements for <code>Oem</code> property naming to avoid future use of colon (:) and period (.) in property names, which can produce invalid or problematic variable names when used in some programming languages or environments. Both separators have been replaced with underscore (_), with colon (:) and period (.) usage now deprecated (but valid).
		Removed duplicative or out-of-scope subclauses from the <b>Security</b> clause, which made unintended requirements on Redfish Service implementations.
		Added the requirement that property names in resource responses match the casing (capitalization) as specified in schema.
		Updated normative references to current HTTP RFCs and added clause references throughout the document where applicable.
		Clarified ETag header requirements.
		Clarified that no authentication is required for accessing the Service Root.
		Clarified description of retrieving resource collections.
		Clarified usage of <code>charset=utf-8</code> in the HTTP <code>Accept</code> and <code>Content-Type</code> headers.
		Clarified usage of the <code>Allow</code> HTTP response header and added a table entry for the <code>Retry-After</code> header usage.
		Clarified normative usage of the type property and context property, explaining the ability to use two URL forms, and corrected the <code>@odata.context</code> URL examples throughout.
		Corrected inconsistent terminology throughout the resource collection response clause.
		Corrected name of normative resource <code>Members</code> property ( <code>Members</code> , not <code>value</code> ).
		Clarified that error responses may include information about multiple error conditions.
		Corrected name of <code>Measures.Unit</code> annotation term as used in examples.
		Corrected outdated reference to Core OData Specification in annotation term examples.
		Added the <code>Members</code> property to the <b>Common Redfish resource properties</b> clause.
		Clarified terminology and usage of the task monitor and related operations in the <b>Asynchronous operations</b> clause.
		Clarified that implementation of the SSDP protocol is optional.
		Corrected typographical error in the SSDP <code>USN</code> field's string definition (now <code>:::dmf-org</code> ).
		Added the <code>OPTIONS</code> method to the allowed HTTP methods list.
		Fixed nullability in example.
1.0.1	2015-09-17	Errata release. Various grammatical corrections.
		Clarified normative use of long description in schema files.

Version	Date	Description
		Clarified usage of the <code>rel-describedby</code> <code>Link</code> header.
		Corrected text in example of "Select List" in OData context property.
		Clarified <code>Accept-Encoding</code> request header handling.
		Deleted duplicative and conflicting statement on returning extended error resources.
		Clarified relative URI resolution rules.
		Clarified USN format.
1.0.0	2015-08-04	Initial release.