



Document Identifier: DSP0272

Date: 2021-10-06

Version: 1.4.1

Redfish Interoperability Profiles

Supersedes: 1.4.0

Document Class: Normative

Document Status: Published

Document Language: en-US

Copyright Notice

Copyright © 2017-2021 DMTF. All rights reserved.

DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability. Members and non-members may reproduce DMTF specifications and documents, provided that correct attribution is given. As DMTF specifications may be revised from time to time, the particular version and release date should always be noted.

Implementation of certain elements of this standard or proposed standard may be subject to third party patent rights, including provisional patent rights (herein "patent rights"). DMTF makes no representations to users of the standard as to the existence of such rights, and is not responsible to recognize, disclose, or identify any or all such third party patent right, owners or claimants, nor for any incomplete or inaccurate identification or disclosure of such rights, owners or claimants. DMTF shall have no liability to any party, in any manner or circumstance, under any legal theory whatsoever, for failure to recognize, disclose, or identify any such third party patent rights, or for such party's reliance on the standard or incorporation thereof in its product, protocols or testing procedures. DMTF shall have no liability to any party implementing such standard, whether such implementation is foreseeable or not, nor to any patent owner or claimant, and shall have no liability or responsibility for costs or losses incurred if a standard is withdrawn or modified after publication, and shall be indemnified and held harmless by any party implementing the standard from any and all claims of infringement by a patent owner for such implementations.

For information about patents held by third-parties which have notified the DMTF that, in their opinion, such patent may relate to or impact implementations of DMTF standards, visit <http://www.dmtf.org/about/policies/disclosures.php>.

This document's normative language is English. Translation into other languages is permitted.

CONTENTS

1 Foreword {-}	4
1.1 Acknowledgments {-}	4
2 Abstract	5
3 Overview	6
4 Normative references	7
5 Terms and definitions	8
6 Design tenets	9
7 Profile tools	10
8 Profile repository	11
9 Profile document definition	12
9.1 File name conventions	12
9.2 Basic functions	12
9.2.1 Required profiles	13
9.2.2 Example	13
9.3 Protocol requirements	14
9.3.1 Example	15
9.3.2 Requirement values	15
9.4 Resource (schema) requirements	15
9.4.1 Schema-level functions	16
9.4.1.0.1 URI patterns	17
9.4.1.1 Example	17
9.4.2 Property-level functions	18
9.4.2.1 Example	18
9.4.2.2 Comparison	19
9.4.2.3 Read requirement	20
9.4.2.4 Write requirement	21
9.4.2.5 Conditional requirements	21
9.4.2.5.1 Parent and subordinate resources	22
9.4.2.5.2 Example	22
9.4.2.5.3 Compare property	23
9.4.2.5.4 Examples	24
9.4.3 Action requirements	25
9.4.3.1 Parameters	25
9.4.3.2 Example	25
9.5 Registry-level requirements	26
9.5.1 Messages	27
9.5.2 Example	27
9.5.3 Supported features	28
9.5.4 Example	28
10 ANNEX A (informative) Change log	29

1 Foreword {-}

The Redfish Interoperability Profile specification was prepared by the Redfish Forum of the DMTF.

DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability. For information about the DMTF, see <http://www.dmtf.org>.

1.1 Acknowledgments {-}

The DMTF acknowledges the following individuals for their contributions to this document:

- Richelle Ahlvers - Broadcom Inc.
- Jeff Autor - Hewlett Packard Enterprise
- George Ericson - Dell Inc.
- Tomas Gonzalez - Majec Systems, Inc.
- Jon Hass - Dell Inc.
- Jeff Hilland - Hewlett Packard Enterprise
- John Leung - Intel Corporation
- Michael Raineri - Dell Inc.
- Paul Vancil - Dell Inc.

2 Abstract

As schema definitions for the *Redfish Specification* ("Redfish") are designed to provide significant flexibility, and allow conforming implementations on a wide variety of products, very few properties within the schemas are required by the *Redfish Specification*. But consumers and software developers need a more rigidly defined set of required properties (features) in order to accomplish management tasks. This set allows users to compare implementations, specify needs to vendors, and allows software to rely on the availability of data. To provide that "common ground", a Redfish interoperability profile allows the definition of a set of schemas and property requirements, which meet the needs of a particular class of product or service.

A Redfish interoperability profile is a JSON document that contains schema-level, property-level, and registry-level requirements. At the property level, these requirements can include a variety of conditions under which the requirement applies.

3 Overview

The *Redfish Specification* separates the definition of the protocol from the data model (schema), and in addition, allows each resource defined in the data model to be revised independently. While this creates significant flexibility and extensibility, it can cause confusion when developers and end users attempt to answer the question "What version of Redfish does your product support?" The answer is not a simple one, because fully describing a Redfish implementation would require listing each property supported in each schema implemented, as well as the protocol version and supported features. That level of detail and version reporting would be extremely cumbersome to create or maintain, and difficult to use to compare implementations across products or vendors.

The Redfish interoperability profile concept was created to simplify that process, by providing a means to communicate the functionality provided with a single statement - that an implementation meets the requirements set forth in a Redfish interoperability profile.

A profile is constructed in a machine-readable (JSON) document that serves two purposes. First, it enables the creation of a human-readable document that merges the profile requirements with the Redfish schema into a single document for developers or users. Second, it allow a conformance test utility to test a Redfish service implementation for conformance with the profile.

4 Normative references

The following referenced documents are indispensable for the application of this document. For dated or versioned references, only the edition cited (including any corrigenda or DMTF update versions) applies. For references without a date or version, the latest published edition of the referenced document (including any corrigenda or DMTF update versions) applies.

- IETF RFC 3986 T. Berners-Lee et al, Uniform Resource Identifier (URI): Generic Syntax, <http://www.ietf.org/rfc/rfc3986.txt>
- ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards, <http://isotc.iso.org/livelink/livelink.exe?func=ll&objId=4230456&objAction=browse&sort=subtypeH>
- IETF RFC 6901, P. Bryan, Ed. et al, JavaScript Object Notation (JSON) Pointer, <http://www.ietf.org/rfc/rfc6901.txt>
- JSON Schema: A Media Type for Describing JSON Documents, Draft 7 <https://tools.ietf.org/html/draft-handrews-json-schema-01>
- JSON Schema Validation: A Vocabulary for Structural Validation of JSON, Draft 7 <https://tools.ietf.org/html/draft-handrews-json-schema-validation-01>
- DMTF Redfish Specification, DSP0266 http://www.dmtf.org/sites/default/files/standards/documents/DSP0266_1.6.0.pdf
- OpenAPI Specification <https://github.com/OAI/OpenAPI-Specification>

5 Terms and definitions

Some terms and phrases in this document have specific meanings beyond their typical English meanings. This clause defines those terms and phrases.

The terms "shall" ("required"), "shall not", "should" ("recommended"), "should not" ("not recommended"), "may", "need not" ("not required"), "can" and "cannot" in this document are to be interpreted as described in ISO/IEC Directives, Part 2, Clause 7. The terms in parenthesis are alternatives for the preceding term, for use in exceptional cases when the preceding term cannot be used for linguistic reasons. Note that ISO/IEC Directives, Part 2, Clause 7 specifies additional alternatives. Occurrences of such additional alternatives shall be interpreted in their normal English meaning.

The terms "clause", "subclause", "paragraph", and "annex" in this document are to be interpreted as described in ISO/IEC Directives, Part 2, Clause 6.

The terms "normative" and "informative" in this document are to be interpreted as described in ISO/IEC Directives, Part 2, Clause 3. In this document, clauses, subclauses, or annexes labeled "(informative)" do not contain normative content. Notes and examples are always informative elements.

The term "deprecated" in this document is to be interpreted as material that is not recommended for use in new development efforts. Existing and new implementations may use this material, but they should move to the favored approach. Deprecated material may be implemented in order to achieve backwards compatibility. Deprecated material should contain references to the last published version that included the deprecated material as normative material and to a description of the favored approach. Deprecated material may be removed from the next major version of the specification.

6 Design tenets

All profile entries, at the profile, resource, or property level, are "additive". That is, each requirement can only apply more rigid requirements that override less rigid requirements.

Profile requirements do not allow for exclusions of data. Implementations are able to provide more data in their resources than required by a profile, as an implementation likely addresses multiple use cases or profiles. This includes both standard properties and OEM extensions.

7 Profile tools

A free, open source utility has been created by the Redfish Forum to verify that a Redfish service implementation conforms to the requirements included in a Redfish interoperability profile. The Redfish Interop Validator is available for download from the DMTF's organization on GitHub at: <https://github.com/DMTF/Redfish-Interop-Validator>

A documentation generator has also been created by the Redfish Forum that will create a "guide" using the Redfish schema and the profile document. The output is intended for use by both developers and end users to understand the implementation requirements of a profile. The Redfish Documentation Generator is available for download from the DMTF's organization on GitHub at: <https://github.com/DMTF/Redfish-Tools>

8 Profile repository

Redfish interoperability profiles published or re-distributed by the DMTF are available for download from the Redfish profile repository located at: <http://redfish.dmtf.org/profiles>

9 Profile document definition

A Redfish interoperability profile is specified in a JSON document. The JSON objects and properties contained in the document are described in this specification, and are also available in a JSON-schema form (RedfishInteroperabilityProfile.v1_x_x.json) from the DMTF's Redfish schema repository at <http://redfish.dmtf.org/profiles> for download. The json-schema can be used to validate a profile document to ensure compatibility with automated conformance tools or utilities.

The JSON document structure is intended to align easily with JSON payloads retrieved from Redfish service implementations, to allow for easy comparisons and conformance testing. Many of the properties defined within this structure have assumed default values that correspond with the most common use case, so that those properties can be omitted from the document for brevity.

9.1 File name conventions

The document that describes a profile follows the Redfish schema file naming conventions from the *Redfish Specification*. The file name format for profiles shall be:

```
<ProfileName>.v<MajorVersion>_<MinorVersion>_<Errata>.json
```

For example, the file name of the BasicServer profile v1.2.0 is `BasicServer.v1_2_0.json`. The file name shall include the profile name and version, which matches those property values within the document.

9.2 Basic functions

At the top level of the JSON document are the basic properties, which describe the profile, including authorship and contact information, versioning, and other profiles to include in order to build upon previous work.

Property	Type	Description
SchemaDefinition	string	The JSON schema that defines this Redfish interoperability profile document and can be used to validate its contents.
ProfileName	string	The name of this Redfish profile.
ProfileVersion	string	The version of this Redfish profile. The version shall be represented using a <code><major>.<minor>.<errata></code> format.
Purpose	string	A description of the purpose of this Redfish profile, such as its intended target audience, product segments, etc.
ContactInfo	string	An email address that can be used to provide feedback about this Redfish profile.

Property	Type	Description
OwningEntity	string	The name of the owning entity that defined this Redfish interoperability profile.
ContributedBy	string	The name of the original author or entity that contributed the content of this profile to the owning entity.
License	string	The license statement for this profile.
RequiredProfiles	object	A set of Redfish profiles that serve as a basis for this profile. The requirements set forth in these profiles are included in this profile.
Protocol	object	Requirements related to the Redfish protocol outside of the JSON resources. See the Protocol requirements clause.
Resources	object	The JSON resource requirements. See the Resource (schema) requirements clause.
Registries	object	The registry requirements. See the Registry-level requirements clause.

9.2.1 Required profiles

The `RequiredProfiles` object contains object properties that are named to match the name of the profile to be included. Each of these sub-objects contains the properties listed below.

Property	Type	Description
Repository	string	A URI providing the location of the repository that contains the JSON files to be included. The filenames of the JSON files contained in the repository are expected to follow the Redfish interoperability profile filename conventions. If absent, the repository location shall be the Redfish profile repository (http://redfish.dmtf.org/profiles).
MinVersion	string	The minimum version required by this Redfish profile. The version shall be represented using a <code><major>.<minor>.<errata></code> format, including an optional errata version. If this property is absent, the minimum value shall be <code>1.0.0</code> .

9.2.2 Example

The following is an example of the top-level properties in a profile, with two required profiles included.

```
{
  "SchemaDefinition": "RedfishInteroperabilityProfile.v1_0_0",
  "ProfileName": "Anchovy",
  "ProfileVersion": "1.0.2",
  "OwningEntity": "Pizza Box Consortium",
  "ContributedBy": "Contoso Anchovy Committee",
  "License": "BSD 3-clause.",
  "Purpose": "This is a sample Redfish Interoperability profile.",
  "ContactInfo": "pizza@contoso.com",
  "RequiredProfiles": {
```

```

    "DMTFBasic": {
      "MinVersion": "1.0.0"
    },
    "ContosoPizza": {
      "Repository": "http://contoso.com/profiles",
      "MinVersion": "1.0.0"
    }
  }
}

```

9.3 Protocol requirements

An object named `Protocol` contains properties which describe Redfish protocol functionality that is not related to the supported schemas or properties. Therefore, these functions cannot be validated by comparing retrieved JSON payloads.

Property	Type	Description
<code>MinVersion</code>	string	Indicates the minimum version of the <i>Redfish Specification</i> protocol support required by this profile. This version shall be reported by the Redfish service in the <code>ServiceRoot</code> resource property <code>RedfishVersion</code> . The version shall be represented using a <code><major>.<minor>.<errata></code> format, including an optional errata version. If this property is absent, the minimum value shall be <code>1.0.0</code> .
<code>Discovery</code>	string	Indicates support requirements for the Redfish SSDP discovery protocol. If this property is absent, there is no requirement for SSDP. See the Requirement values clause.
<code>HostInterface</code>	string	Indicates support requirements for the Redfish host interface. If this property is absent, there is no requirement for a host interface. See the Requirement values clause.
<code>ExpandQuery</code>	string	Indicates support requirements for the <code>\$expand</code> query parameter. Additional <code>\$expand</code> support requirements may be specified in the resource entry for the <code>ProtocolFeaturesSupported</code> object within <code>ServiceRoot</code> . If this property is absent, there is no requirement for support of the <code>\$expand</code> query parameter. See the Requirement values clause.
<code>FilterQuery</code>	string	Indicates support requirements for the <code>\$filter</code> query parameter. If this property is absent, there is no requirement for support of the <code>\$filter</code> query parameter. See the Requirement values clause.
<code>SelectQuery</code>	string	Indicates support requirements for the <code>\$select</code> query parameter. If this property is absent, there is no requirement for support of the <code>\$select</code> query parameter. See the Requirement values clause.
<code>OnlyQuery</code>	string	Indicates support requirements for the <code>only</code> query parameter. If this property is absent, there is no requirement for support of the <code>only</code> query parameter. See the Requirement values clause.
<code>ExcerptQuery</code>	string	Indicates support requirements for the <code>excerpt</code> query parameter. If this property is absent, there is no requirement for support of the <code>excerpt</code> query parameter. See the Requirement values clause.

9.3.1 Example

```
{
  "Protocol": {
    "MinVersion": "1.6",
    "Discovery": "Mandatory",
    "HostInterface": "Recommended",
    "ExpandQuery": "Mandatory",
    "SelectQuery": "None",
    "FilterQuery": "Recommended",
    "OnlyQuery": "Mandatory",
    "ExcerptQuery": "Recommended"
  }
}
```

9.3.2 Requirement values

Value	Description
Mandatory	This protocol feature is required for this profile.
Recommended	It is recommended, but not required, that this protocol feature be supported.
None	This feature is not required by this profile. It is listed here for clarity.

9.4 Resource (schema) requirements

The primary content in a Redfish profile is the set of supported property requirements. As Redfish is organized and defined by schema-backed JSON resources, these requirements are also organized by schema.

For each schema, an object is created in the JSON document, named to match the schema name. Within this object, properties describe the location of the schema file, and schema-level requirements. Within each schema-level object is a `PropertyRequirements` object that describes the property-level requirements for that schema. The definition of both the schema/resource-level and property-level requirements are accomplished using the same mechanisms, which are described in the next clause.

The structure of the resource and property requirements is:

```
{
  "<schema-name>": {
    "MinVersion": "<version>",
    "CreateResource": "<boolean>",

```

```

"DeleteResource": "<boolean>",
"UpdateResource": "<boolean>",
"URIs": [
  "<uri-pattern>",
  "<uri-pattern>"
],
"PropertyRequirements": {
  "<property-name>": {
    "<property-requirements>": "<property-requirements-value>"
  },
  "<property-name>": {
    "<property-requirements>": "<property-requirements-value>"
  }
},
"ActionRequirements": {
  "<action-name>": {
    "<action-requirements>": "<action-requirements-value>"
  }
},
"ConditionalRequirements": [
  {
    "<conditional-requirement>": "<conditional-requirements-value>"
  },
  {
    "<conditional-requirement>": "<conditional-requirements-value>"
  }
]
},
"<additional-schemas>": {}
}

```

9.4.1 Schema-level functions

The following options are available at the schema level:

Property	Type	Description
Repository	string	A URI providing the location of the repository that contains the JSON files to be included. The filenames of the JSON files contained in the repository are expected to follow the Redfish schema filename conventions. If absent, the repository location shall be the Redfish schema repository (http://redfish.dmtf.org/schemas).
MinVersion	string	The minimum version required by this Redfish profile. The version shall be represented using a <code><major>.<minor>.<errata></code> format, including an optional errata version. If this property is absent, the minimum value shall be <code>1.0.0</code> .
ReadRequirement	string	Resource-level requirement for this schema. See the Read requirement clause.

Property	Type	Description
Purpose	string	A description of the purpose of this requirement. This text can provide justification or reasoning behind the requirement for use in the profile documentation.
ConditionalRequirements	object	Resource-level conditional requirements that apply to instances of this schema. See the Conditional requirements clause.
CreateResource	boolean	Specifies a requirement that a user may create a member of this resource. This normally applies to Redfish resource collections. If this property is absent, there is no requirement to support creation of members of this resource.
DeleteResource	boolean	Specifies a requirement that a user may delete a member of this resource. This normally applies to Redfish resource collections. If this property is absent, there is no requirement to support deletion of members of this resource.
UpdateResource	boolean	Specifies a requirement that a user may update a member of this resource. This normally applies to Redfish resource collections. If this property is absent, there is no requirement to support updating of members of this resource, but individual property-level read-write requirements apply.
URIs	array	An array of URI references to which the <code>ReadRequirement</code> and <code>WriteRequirement</code> are applied. The values shall follow the resource URI pattern definition specified in the <i>Redfish Specification</i> .

9.4.1.0.1 URI patterns

As the *Redfish Specification* version 1.6 or higher defines the set of possible URIs for each resource type, this fact can be used to easily create requirements or conditional requirements for resource types that occur at multiple locations in the resource tree. This method is preferred for any profile that will also desire OpenAPI compatibility, which requires Redfish v1.6 protocol support and therefore the URIs of any conforming implementation will match those listed in the profile.

Profiles which intend to apply to implementations conforming to *Redfish Specification* versions 1.0 through 1.5 cannot use this URI pattern matching in their profile definition. Profiles containing URI pattern requirements shall require a *Redfish Specification* version 1.6 or higher in the profile's `Protocol` object `MinVersion` property.

9.4.1.1 Example

This example shows a simple required schema:

```
{
  "ComputerSystem": {
    "MinVersion": "1.2.0",
    "Purpose": "Every instance must have a logical-view ComputerSystem resource.",
    "PropertyRequirements": {
      "SerialNumber": {},
      "Manufacturer": {},
      "Model": {
```

```

    "ReadRequirement": "Recommended"
  }
}
}
}

```

9.4.2 Property-level functions

Within the `PropertyRequirements` object are additional objects that are named to match the property name in the parent object's schema definition. This object then contains the property-level requirements, which account for the bulk of a profile's definition. One additional level of JSON objects may be embedded, essentially nesting a `PropertyRequirements` object.

The following options are available at the property level:

Property	Type	Description
<code>ReadRequirement</code>	string	Property-level requirement for this property. See the Read requirement clause.
<code>WriteRequirement</code>	string	Property-level write (HTTP <code>PATCH</code> or <code>PUT</code>) requirement for this property. See the Write requirement clause.
<code>ConditionalRequirements</code>	object	Property-level conditional requirements that apply to instances of this property. See the Conditional Requirements clause.
<code>MinCount</code>	integer	For array type properties, the minimum number of non-NULL instances within the array.
<code>MinSupportValues</code>	array	The minimum set of enumerations that must be supported for this writable property.
<code>Comparison</code>	string	The condition used to compare the value of the property to <code>Values</code> . See the Comparison clause.
<code>Purpose</code>	string	A description of the purpose of this requirement. This text can provide justification or reasoning behind the requirement for use in the profile documentation.
<code>Values</code>	array	The values used to perform a <code>Comparison</code> . Multiple values are only allowed for <code>AnyOf</code> or <code>AllOf</code> comparisons. If no <code>Comparison</code> property is present, the comparison is assumed to be an <code>AnyOf</code> comparison.
<code>PropertyRequirements</code>	object	For Redfish object properties, this object contains requirements for the properties contained within the specified object. This specification allows for only one level of nested objects and requirements.

9.4.2.1 Example

This example shows property-level requirements, including one object property containing further requirements on that object's properties. For each `Power` resource, the `PowerSupplies` and `Voltages` array properties are required. `Voltages` has no further requirements. By default, this `Voltages` is mandatory, and as an array type,

must have at least one item in the array. The `PowerSupplies` array must contain at least two items. Within the array, at least one item's `PowerSupplyType` property must have a value of `AC` or `DC`.

```

{
  "Power": {
    "PropertyRequirements": {
      "PowerSupplies": {
        "ReadRequirement": "Mandatory",
        "MinCount": 2,
        "PropertyRequirements": {
          "Status": {},
          "PowerSupplyType": {
            "Comparison": "AnyOf",
            "Purpose": "Need to know AC vs. DC to know expected input.",
            "Values": [
              "AC",
              "DC"
            ]
          },
          "LineinputVoltage": {},
          "PowerCapacityWatts": {},
          "InputRanges": {
            "ReadRequirement": "Recommended"
          }
        }
      }
    },
    "Voltages": {}
  }
}

```

9.4.2.2 Comparison

The `Comparison` function uses the following enumerations to represent the various comparisons available:

Value	Description
Absent	The property is not present in this resource.
AnyOf	At least one instance of the property in this resource must be equal to one of the values listed.
AllOf	At least one instance of the property in this resource must be equal to each of the values listed.
Equal	The value of the property must be equal to the value in the profile.
NotEqual	The value of the property must not be equal to the values listed in the profile.
GreaterThan	The value of the property must be greater than the values listed in the profile. This comparison is only valid for numeric properties.

Value	Description
GreaterThanOrEqualTo	The value of the property must be greater than or equal to the values listed in the profile. This comparison is only valid for numeric properties.
LessThan	The value of the property must be less than the values listed in the profile. This comparison is only valid for numeric properties.
LessThanOrEqualTo	The value of the property must be less than or equal to the values listed in the profile. This comparison is only valid for numeric properties.
Present	The property is present in this resource.
LinkToResource	The object contains a link to a resource with a type equal to one of the schema names listed in the values of the profile. The type is the unversioned schema name, such as <code>Thermal</code> or <code>Memory</code> .

Many of these comparison types are simple arithmetic, boolean, or string value comparisons. In addition, `Absent` and `Present` allow for comparisons concerning the existence or absence of a property. The `LinkToResource` comparison specifies that the object property contains an `@odata.id` property to a resource whose schema name (type) is listed in the `Values` array.

9.4.2.3 Read requirement

The `ReadRequirement` function specifies the level of basic read (HTTP `GET`) requirement applied to the resource or property. The default value, or if no `ReadRequirement` is present, is `Mandatory`. For object properties, requirements of the embedded properties will apply only if the object is present.

Value	Description
Mandatory	This property is required in all instances of this resource. For array properties, the property is required in all non-null array items. If <code>Values</code> is defined, at least one instance of each enumeration value is required among instances of this property.
Supported	This property is required to be supported by the service, but may not appear in all instances of this resource. The requirement is met if the property appears in at least one instance of this resource.
Recommended	It is recommended, but not required, that this property be supported.
IfImplemented	This property is required if the underlying functionality is implemented. For object properties, requirements on embedded properties within the object will only apply if the object is present.
IfPopulated	For property-level requirements, this property is required if the <code>State</code> property within the <code>Status</code> object for the object or resource does not contain <code>Absent</code> . This value is useful for properties within absent resources where empty slots, sockets, or bays are rendered with minimal properties until they are populated by a device. For resource-level requirements, this value indicates that the resource is required, but may not be present (populated) in the service at all times.
Conditional	This property is only required if <code>ConditionalRequirements</code> items apply to this instance of the resource.
None	This property is not required by this profile. It is listed here for clarity.

9.4.2.4 Write requirement

The `WriteRequirement` function specifies the level of write support (HTTP PATCH or PUT) applied to a property. The default value, or if no `WriteRequirement` is present, is `None`. The `WriteRequirement` applies to a property once the `ReadRequirement` is met.

Value	Description
Mandatory	This property is required to be writable in all instances of this resource.
Supported	This property is required to be writable in some instances of this resource. A service meets the requirement if the property is writable in at least one resource instance.
Recommended	It is recommended, but not required, that this property be writable.
None	This property is not required to be writable by this profile. It is listed here for clarity, and is the default value used if <code>WriteRequirement</code> is not present.

9.4.2.5 Conditional requirements

The most flexible aspect of the Redfish profile definition is the ability to make resource or property-level requirements that are dependent on one or more conditional requirements within the resource and the parent resources in the resource tree.

The `ConditionalRequirements` array function specifies these conditional requirements, which add to any requirements also defined for the resource or property. Note that a condition cannot override or weaken a requirement already specified. For example, if a property requirement is marked as `Mandatory`, no conditional requirement could mark the property as `None`. Instead, the property would be specified with a `None` requirement, and with one or more `ConditionalRequirements` that would specify when the property requirement becomes `Mandatory`.

The following options are available for each conditional requirement:

Property	Type	Description
<code>ReadRequirement</code>	string	The requirement to apply to the resource or property if the condition is met.
<code>WriteRequirement</code>	string	Property-level write (HTTP PATCH or PUT) requirement for this property. See the Write requirement clause.
<code>Purpose</code>	string	Text describing the purpose of this conditional requirement.
<code>URIs</code>	array	An array of URI references to which the <code>ReadRequirement</code> and <code>WriteRequirement</code> is applied. The values shall follow the resource URI pattern definition specified in the <i>Redfish Specification</i> .

Property	Type	Description
<code>SubordinateToResource</code>	array	An ordered list, from top of hierarchy to bottom, of resources where this resource is linked as a subordinate resource. The conditional requirements listed for the resource apply only to instances which are subordinate to the listed parent resource list. See the Parent and subordinate resources clause.
<code>Comparison</code>	string	The condition used to compare the value of the property to <code>Values</code> . See the Comparison clause.
<code>Values</code>	array	The values used to perform a comparison. Multiple values are only allowed for <code>AnyOf</code> or <code>AllOf</code> comparisons. If no <code>Comparison</code> property is present, the comparison is assumed to be an <code>AnyOf</code> comparison.
<code>CompareProperty</code>	string	The name of the property in this resource whose value is used to test this condition. The property name will be evaluated at the current object level within the resource. If the property name is not found at the current level, upper levels will be searched until the root level is reached. See the Compare property clause.
<code>CompareValues</code>	array	Values of the <code>CompareProperty</code> used to test this condition. See the Compare property clause.
<code>CompareType</code>	string	The condition used to compare the value of the property named by <code>CompareProperty</code> to the value of <code>CompareValues</code> . If the comparison is true, this conditional requirement applies. See the Compare property clause.

9.4.2.5.1 Parent and subordinate resources

Because there can be several instances of a particular Redfish schema in the resource tree, the requirements placed on those resources may vary depending on their usage. Since the profile is schema-centric, the `SubordinateToResource` function allows a profile to specify requirements based a resource instance's placement in the resource tree.

`SubordinateToResource` allows specifying the schema (resource) path from parent resources to the resource to which the requirements apply. This property contains an array of schema names, in the top-down order that they appear in the path to the required resource.

9.4.2.5.2 Example

For the property `HostName` in the `EthernetInterface` schema, the example shows it as `Recommended` property. But if an instance of `EthernetInterface` is linked from a `ComputerSystem` resource, through the `EthernetInterfaceCollection` resource, the `Condition` is met, which changes the `HostName` property requirement to `Mandatory`.

In the second part of the example, the `IPv6Addresses` array property is required to have at least one item (`MinCount`) in the array. But if, as in the previous example, the instance is subordinate to a `ComputerSystem` (and `EthernetInterfaceCollection`) resource, at least two items are required in the array.

```
{
```

```

    "EthernetInterface": {
      "PropertyRequirements": {
        "HostName": {
          "ReadRequirement": "Recommended",
          "WriteRequirement": "Recommended",
          "ConditionalRequirements": [
            {
              "SubordinateToResource": [
                "ComputerSystem",
                "EthernetInterfaceCollection"
              ],
              "ReadRequirement": "Mandatory",
              "Purpose": "Used to match this instance to other data sources."
            }
          ]
        },
        "IPv6Addresses": {
          "ReadRequirement": "Mandatory",
          "MinCount": 1,
          "ConditionalRequirements": [
            {
              "SubordinateToResource": [
                "ComputerSystem",
                "EthernetInterfaceCollection"
              ],
              "MinCount": 2
            }
          ]
        }
      }
    }
  }
}

```

9.4.2.5.3 Compare property

A typical need for a conditional requirement is a dependency on the value of another property within the resource. This type of dependency can be used when several different product variations share a common schema definition. In that case, Redfish schemas normally define a type-specifying property with enumerations, for a variety of product categories, that can be used to differentiate profile requirements by product category.

To accomplish this, there are three Profile properties related to this function:

Property	Type	Description
CompareProperty	string	The name of the property in this resource whose value is used to test this condition. The property name will be evaluated at the current object level within the resource. If the property name is not found at the current level, upper levels will be searched until the root level is reached.

Property	Type	Description
CompareType	string	The condition used to compare the value of the property named by <code>CompareProperty</code> to the value of <code>Values</code> . If the comparison is true, this conditional requirement applies.
CompareValues	array	Values of the <code>CompareProperty</code> used to test this condition.

9.4.2.5.4 Examples

Simple dependencies can be expressed using the conditional requirement and a comparison. This example shows a `CompareProperty` condition applied to the `Pepperoni` property. If the `PizzaType` property is not equal to `Cheese` , then the `Pepperoni` property becomes both mandatory and must have a value of `true` .

```
{
  "Pepperoni": {
    "ReadRequirement": "Recommended",
    "ConditionalRequirements": [
      {
        "Purpose": "Pepperoni is required on all pizza types except Cheese.",
        "CompareProperty": "PizzaType",
        "CompareType": "NotEqual",
        "CompareValues": [
          "Cheese"
        ],
        "ReadRequirement": "Mandatory",
        "Comparison": "Equal",
        "Values": [
          true
        ]
      }
    ]
  }
}
```

This example shows a `CompareProperty` condition applied to the `IndicatorLED` property, which has a base `Recommended` requirement, but becomes `Mandatory` if the `SystemType` property has a value of `Physical` or `Composed` .

```
{
  "IndicatorLED": {
    "ReadRequirement": "Recommended",
    "ConditionalRequirements": [
      {
        "Purpose": "Physical and composed systems must have a writable LED",
        "CompareProperty": "SystemType",
        "CompareType": "AnyOf",

```



```

        "CompareValues": [
            "Physical",
            "Composed"
        ],
        "ReadRequirement": "Mandatory",
        "WriteRequirement": "Mandatory"
    }
}
]
}
}

```

9.4.3 Action requirements

Because several critical functions of a Redfish service are implemented as `Actions`, the profile may place requirements for support of these Actions. The requirements can specify which parameters must be supported, and may specify allowable values for those parameters.

The following functions are available to specify requirements for an action within a resource requirement:

Property	Type	Description
<code>ReadRequirement</code>	string	The requirement to apply to this action.
<code>Parameters</code>	object	The requirements for any parameter available for this action.
<code>Purpose</code>	string	A description of the purpose of this requirement. This text can provide justification or reasoning behind the requirement for use in the profile documentation.

9.4.3.1 Parameters

The following functions are available to specify requirements for a parameter on a particular action:

Property	Type	Description
<code>ReadRequirement</code>	string	The requirement to apply to this parameter.
<code>ParameterValues</code>	array	The minimum set of enumerations that must be supported for this parameter to meet the Requirement.
<code>RecommendedValues</code>	array	For mandatory parameters, the set of enumerations, in addition to those listed in <code>ParameterValues</code> , that are recommended for this parameter.

9.4.3.2 Example

This example shows the `Reset` action as required for this resource, along with the required parameter `ResetType`, which must support the values of `ForceOff` and `PowerCycle`.

```

{
  "ActionRequirements": {
    "Reset": {
      "ReadRequirement": "Mandatory",
      "Purpose": "Ability to reset the unit is a core requirement of most users.",
      "Parameters": {
        "ResetType": {
          "ParameterValues": [
            "ForceOff",
            "PowerCycle",
            "On"
          ],
          "RecommendedValues": [
            "GracefulShutdown",
            "GracefulRestart",
            "ForceRestart",
            "PushPowerButton"
          ],
          "ReadRequirement": "Mandatory"
        }
      }
    }
  }
}

```

9.5 Registry-level requirements

While not normally part of the JSON resources, the Redfish-defined message registries are important for interoperability, as they indicate what functionality has been implemented for events, and are also a useful method for setting expectations on the use of extended info error messages when interacting with a Redfish service.

The following functions are available to specify registry-level requirements:

Property	Type	Description
Repository	string	A URI providing the location of the repository which contains the JSON files to be included. The filenames of the JSON files contained in the repository are expected to follow the Redfish message registry filename conventions. If absent, the repository location shall be the Redfish registry repository (http://redfish.dmtf.org/registries).
MinVersion	string	The minimum version required by this Redfish profile. The version shall be represented using a <major>.<minor>.<errata> format, including an optional errata version. If this property is absent, the minimum value shall be 1.0.0.
ReadRequirement	string	Resource-level requirement for this registry. See the Read requirement clause.

Property	Type	Description
Purpose	string	A description of the purpose of this requirement. This text can provide justification or reasoning behind the requirement for use in the profile documentation.
Messages	object	The messages in this registry that have support requirements for this Redfish profile. If this property is absent, all messages in this registry follow the registry-level <code>ReadRequirement</code> .
SupportedFeatures	object	The features in this registry that have support requirements for this Redfish profile. If this property is absent, all supported features in this registry follow the registry-level <code>ReadRequirement</code> .

9.5.1 Messages

Within the registry object are additional objects that are named to match the message name in the registry definition. This object then contains the message-level requirements.

The following options are available at the message-level:

Property	Type	Description
ReadRequirement	string	Message-level requirement for this message. See the Read requirement clause.

9.5.2 Example

This example shows requirements for two message registries, including one OEM-defined registry. The `Base` registry is a DMTF standard registry. By default since no `OwningEntity` is listed, and therefore can be retrieved by default from the DMTF repository. The `Base` registry lists only four messages that are required.

In the case of the OEM-defined registry `ContosoPizzaMessages` , the `Mandatory` requirement set at the registry level specifies that all messages defined in that registry are required.

```
{
  "Registries": {
    "Base": {
      "MinVersion": "1.1.0",
      "Messages": {
        "Success": {},
        "GeneralError": {},
        "Created": {},
        "PropertyDuplicate": {}
      }
    },
    "ContosoPizzaMessages": {
      "OwningEntity": "Other",
      "OwningEntityName": "Contoso",
      "Repository": "http://contoso.com/registries",

```

```

    "ReadRequirement": "Mandatory"
  }
}

```

9.5.3 Supported features

Within the registry object are additional objects that are named to match the `SupportedFeatures` name in the registry definition. This object then contains the features-level requirements.

The following options are available at the feature-level:

Property	Type	Description
<code>ReadRequirement</code>	string	Feature-level requirement for this supported feature. See the Read requirement clause.

9.5.4 Example

This example shows requirements for a feature registry. The `SwordfishFeatures` registry is a DMTF-partner defined standard registry, specified as such where the `OwningEntity` is `SNIA`. `SNIA` re-publishes their registries through the DMTF and therefore this registry can be retrieved from the DMTF repository. In this example, the `SwordfishFeatures` registry lists two features that are supported by the service.

```

{
  "Registries": {
    "SwordfishFeatures": {
      "MinVersion": "1.0.2",
      "SupportedFeatures": {
        "SNIA.Swordfish.Discovery": {},
        "SNIA.Swordfish.EventNotification": {}
      }
    }
  }
}

```

10 ANNEX A (informative) Change log

Version	Date	Description
1.4.1	2021-10-06	Corrected descriptions for <code>CreateResource</code> , <code>DeleteResource</code> , and <code>UpdateResource</code> to match terminology and usage in the sample profiles.
1.4.0	2021-09-15	Made many changes for style consistency, grammar, and general clarity. Except for the following additions, no normative changes were made. Any clarifications that inadvertently altered the normative behavior are considered errata, and will be corrected in future revisions to the specification.
		Added <code>License</code> and <code>ContributedBy</code> .
		Added missing table entries for <code>Protocol</code> , <code>Resources</code> , and <code>Registries</code> .
1.3.0	2019-12-06	Added <code>SupportedFeatures</code> to registry-level information, and added an overview and example of <code>SupportedFeatures</code> .
1.2.0	2019-07-03	Added <code>IfPopulated</code> enumeration value to <code>ReadRequirement</code> to indicate to conformance test tools that a required property is not required if the underlying hardware isn't populated, or that a required resource may not be populated under test conditions.
		Added <code>Supported</code> enumeration value to <code>ReadRequirement</code> and <code>WriteRequirement</code> to allow for required properties that are supported by some, but perhaps not all, instances of a resource.
		Added missing <code>pattern</code> term for version properties.
1.1.0	2019-02-26	Added support for new protocol features from <i>Redfish Specification</i> v1.6. Added ability to make requirements based on URI patterns as specified in Redfish schema files. Updated normative references to current versions. Clarified that <code>Repository</code> value may indicate a profile or schema file location, as appropriate. Formatting improvements.
1.0.1	2018-05-15	Errata release. Corrected definition of <code>Comparison</code> for conditional requirements to match the schema usage (and consistent with other usage). Added missing <code>Values</code> property for conditional requirements and added new <code>CompareType</code> property to replace the inconsistent usage of <code>Comparison</code> . Added example for a conditional requirement that uses the <code>Values</code> array.
1.0.0	2018-01-02	Initial release.